

TYPE III AMBULANCE SPECIFICATION

Peach County EM S

INSTRUCTIONS AND GENERAL CONDITIONS TO BIDDERS

NEW 2017-2020 Type III Chevrolet G4500 Cutaway Ambulance or Ford E-450 Gas or Diesel unit

GENERAL INFORMATION

Goods/Services. Peach County is seeking Bids for a NEW Type III Ambulance as described in the attached Technical Specifications and consistent with the terms and conditions of the "Contract Documents," defined below. Each firm responding to this Bid will be referred to as the "Bidder" and the firm selected to provide services to the County Of Peach together with its owners, officers, employees, agents, and/or subcontractors, will be referred to as the "Contractor".

Bid Opening: Award. All bids shall be sealed, delivered no later than, March 18, 2019 at 2:30pm and opened at 2:45pm, Pursuant to the County of Peach Code of Ordinances. The County reserves the right to award this bid as the County's best interests shall dictate, in the light of bid prices/options, the reputation and past performance of the bidder(s), and other factors. The County reserves the right to reject any or all bids, in whole or in part, and is not obligated to accept the lowest bid if that bid is contrary to the best interests of the County, in the sole discretion of the County. A bid may be rejected if it is in any way incomplete or irregular; however the County reserves the right to waive minor irregularities.

Cost of Preparation. Bidder assumes all of its costs of preparing its bid, and of any presentations, correspondence, negotiations, documentation, and any other action undertaken by the Bidder with respect to its bid, and the award of the Contract.

Authority to Bid: Bidder's submission of a signed bid or proposal in response to this solicitation is a representation and certification that Bidder, and its agent submitting the bid, is authorized so to bid and perform all terms and conditions in the event Bidder is awarded the Contract, and further that the Bidder (and any subcontractors) is not currently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from participation in this transaction by any federal or state government or governmental entity, by any court, or by any contract or private obligation of the Bidder. Bidder agrees to notify the County of any change in Bidder's status until such time as an award has been made.

BIDDING REQUIREMENTS

Bid Understanding. Before submittal of a bid, each Bidder must examine the Contract Documents thoroughly. By submitting a bid, the Bidder agrees and represents that these Contract Documents are adequate for the purpose. Bidder shall state any exceptions or deviations in the attached Statement of Compliance /Deviations from Specifications form.

Communication with the County of Peach: It is the responsibility of the Bidder to inquire with the County Of Peach to clarify any requirement of the Request for Bids or the Contract Documents that is unclear to Bidder. The County's responses to such inquiries, if they change or clarify the

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Request for Bids, will be forwarded by addenda to all parties known to the County to have obtained a copy of the Request For Bids for the purpose of submitting a bid. The County will not be bound by oral responses to inquiries or written responses other than addenda. Inquires must be made to: Janet Smith, Purchasing Manager, Peach County Board of Commissioners: 478-825-2535 ~~janet.smith@peachcounty.net~~, Alfonzo Ford EMS Director Peach County EMS, Fort Valley, Georgia 478-447-5757, alfonzo-ford@paachcounty.net.

Submission. Bids are to be sealed and, once received by the County, shall be retained unopened and secure until the time and date of the Bid Opening set forth herein. All bids shall *be* delivered to Janet Smith, 213 Persons Street, Fort Valley, Ga. 31030 no later than 2:30pm on March 18th, 2019.

Faxed or e-mailed bids will not be accepted. Bid documents shall *be* enclosed in an envelope sealed and clearly labeled, ("*New 2017-2020 Type 111 Chevrolet G4500 or Ford E -450 Cutaway Gas or Diesel unit.*") (*Demo units will be considered if specifications are met*)

Bid Opening. At the time fixed for the opening of bids, the material contents of all bids shall not be made public; so that negotiations can be done. Bidders and members of the public are welcome to attend the Bid Opening.

GENERAL TERMS AND CONDITIONS

Assignment. Neither party to the Contract shall assign the Contract or any right or obligation under the Contract, including a right to payment, without the prior, written consent of the other party.

Contract Documents. If a separate contract is not written, the Contract shall consist of the Instructions and General Conditions, the Specifications, including all modifications thereof, and the signed Official Bid Form submitted by the Contractor and counter-signed by the Peach County Board of Commission Chairman, all of which shall be referred to collectively as the Contract Documents.

Contract Modifications and Amendment. The parties may amend a term or condition of the Contract, in a written amendment signed by the parties. Amendments increasing the contract price shall only be made when necessitated by unforeseen circumstances beyond the control of either party.

Cancellation/Termination. Except as otherwise provided herein, Peach County may terminate this Contract by giving 30 days written notice to the Contractor. Such cancellation does not release the County or Contractor from the terms and conditions of the Contract during the notification period. In the event the Contractor defaults on the Contract by failing to furnished the goods or services in conformance with the Contract and to the County's satisfaction, Peach County shall promptly notify the Contractor of such default, and if correction is not made within 48 hours to the County's satisfaction, Peach County may, in its sole discretion, take whatever action it deems necessary to obtain substitute goods/services, and may terminate the Contract without further notice.

TYPE HIAMBULANCE SPECIFICATION

Peach County EMS

Contract Administration; Notice to the County. The Peach County Board of Commissioners shall serve as Peach County Contract Administrator. Any notices required to be provided to the County shall be provided to: Janet Smith, Purchasing Manager, 213 Persons St. Fort Valley, Ga. 31030 – 478-825-2535 janet-smith@peachcounty.net and Alfonzo Ford Peach County EMS Fort Valley, Georgia 31030, 478-447-5757 alfonzo-ford@peachcounty.net 1770 N Hwy 341 Fort Valley, Ga 31030

Indemnification. Contractor is responsible for, and shall hold Peach County harmless from any and all losses, damages, claims, causes, costs, and expenses suffered or sustained by Peach County or for which the County Of Peach may be held or become liable by reason of injury (including death) to persons or property or other causes whatsoever as a result of an actual or alleged act, error, or omission of the Contractor in any way related to this Contract, and Contractor shall indemnify the County for any and all expenses, losses, or payments incurred in the responding to or defending against any claims arising from such act, error, or omission of the Contractor, including attorney's fees and costs.

Independent Contractor. Whether the Contractor is a corporation, partnership, other legal entity, or an individual, the Contractor is an independent contractor, and not an employee or agent of the County. If the Contractor is an individual, the Contractor's duties will be performed with the understanding that the Contractor is a self-employed person; that Contractor has special expertise as to the services which the Contractor is to perform; and that Contractor is customarily engaged in the independent performance of the same or similar services for others. The manner in which the services are performed shall be controlled by the Contractor; however, the nature of the services and the results to be achieved shall be specified by Peach County. The Contractor has no authority to make any binding commitments or obligations on behalf of Peach County except as expressly provided herein.

Contractor's Liability Insurance. During the term of this agreement, the Contractor shall maintain the following insurance:

Commercial General Liability - Aggregate policy limit of one million dollars.

Automotive Liability - Any Hired and Non owned Autos
Combined Single Limits of One million dollars.

Garage Liability - Any Auto
Auto only - Each accident: limit of one million dollars.

Workers Compensation and Employer's Liability –

Each Accident: limit of five hundred thousand dollars.
Disease policy: limit of five hundred thousand dollars.
Disease - Each Employee: limit of five hundred thousand dollars.

Excessive/Umbrella Liability –

Each Occurrence: limit of nine million dollars

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Automotive Damage. Physical Liability Damage

Comprehensive Deductible:

Contractor shall cause the County to be named as an additional insured on each policy of insurance required herein, and the Certificates or other evidence of such policies shall contain a statement of the insurer's obligation to notify the County at least fifteen (15) days prior to the cancellation of such policy. In the event the County is required to defend itself against any claims for which insurance coverage is required by this Contract, Contractor shall Peach County's cost of defense. In any claim which may arise as a result of intentional or negligent acts, or omissions of the Contractor, the comprehensive general liability insurance policy provided by Contractor shall be deemed the primary protection against such claims, and Peach County shall not be called upon to contribute to a loss otherwise payable by the Contractor's insurer(s) due to Contractor's acts, errors, or omissions.

Contract Sum. The total contract price shall include all labor, license fees, costs, equipment guarantees, delivery, transportation, materials and application as described in this Contract

documents. Peach County shall pay the Successful Bidder in current funds the Contract Sum as stated in the Notice of Award for the performance of the Work, subject to additions and deduction by Change Order as provided herein.

Payment. Payment will be upon submittal of an invoice to the Purchasing Department of Peach County by the Successful Bidder on a (C.O.D.) unless discount terms are offered. Invoices must include purchase order number. Requisitions are to be approved by Peach County Purchasing Department.

Sales Tax. This project is exempt from State Sales and Use or Excise Taxes to the extent allowed by law.

Change Orders. Peach County shall have the right to increase or decrease the amount and extent of the work by giving reasonable notice thereof to the Successful Bidder. The value of such Change Orders shall be negotiated between Peach County and the Successful Bidder. Before any change order modifies or becomes a part of the work, the Change Order must be signed by the Successful Bidder and Peach County.

Delivery. The apparatus shall be delivered to Peach County as soon as possible following the Notice to Award, but in no event later than that date which is 120 days from the date of the Notice of Award. The bidder shall state the estimated delivery time on the Official Bid Form in the space provided. The Purchasing Department and EMS Director representative shall be notified at least forty-eight (48) hours in advance of the delivery date and time.

The Contractor shall notify the County in writing of both the tentative shipment date and the actual shipment date of the ambulance from the vehicle manufacturer promptly upon receipt of such dates from the vehicle manufacturer.

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

The unit, to ensure proper break in of all components while still under warranty, shall be delivered under its own power. Rail or Truck freight is not acceptable. A qualified driver representing the bidder shall deliver the unit and remain in Peach County a sufficient length of time to instruct the EMS personnel in the proper operations, care and maintenance of the equipment delivered. The representative shall represent the bidder during the acceptance test and inspection. If the unit is accepted, Peach County will make payment in the amount of the awarded bid.

Date of Acceptance. That date when all Specifications have been satisfactorily met.

Guarantee. The Apparatus and all parts thereof shall be fully operational and free of defect in materials, workmanship, installation and operation for a period of at least one (1) year from the Date of Acceptance. In addition to any other manufacturer's guarantee or warranty, Bidder's proposal shall at minimum include and state, on company letterhead, the following warranty:

We represent and warrant that the Apparatus, and all parts thereof, shall be free from defects in materials, workmanship, installation, and operations under normal use and service (hereinafter, "Defect") for 1 year(s) from the Date of Acceptance. Upon notice of Defect by Peach County, we shall be responsible the prompt repair of the Defect; the cost of transporting the defective part or Apparatus for repair. With or without notice of such Defect, except where such Defect becomes known to Peach County and is not reported to us within a reasonable period of time of such notice, we shall be responsible for and shall defend and hold harmless the County, its officers, employees, volunteers, and agents, from and against any and all claims, costs, damages, and liabilities, including attorney's fees and cost, proximately caused to person or property by such Defect. This warranty shall not apply to (1) normal maintenance service or adjustments; (2) Defects caused by alterations for the Apparatus by Peach County or by a third party without our prior consent during the Warranty Period; (3) damage to the Apparatus caused by improper use, service, or operations of the Apparatus by someone other than the Bidder, and (4) commercial chassis and associated equipment furnished with chassis; signaling devices; generators; batteries; or other trade accessories, unless such equipment is not warranted separately by its manufacturer(s). In the event we fail to repair or replace the defective equipment within a reasonable time of receipt of notice thereof, Peach County may perform the repair or replacement and Bidder shall reimburse Peach County therefore. This Warranty is in lieu of all other warranties expressed or implied, that are for a shorter period of time or that cover fewer repair or replacement costs than are set forth herein. This Warranty does not relieve the Bidder from liability for incidental or consequential damages.

SUBMISSION REQUIREMENTS AND SPECIFICATIONS

Bid Form. The bid shall be in the form of a firm price for the entire contract period. The bid price shall include, and Contractor shall be responsible for all costs and charges other than the bid price, including without limitation storage, transportation / delivery, environmental fees, insurance, bonding, and all other costs. Peach County shall not be responsible for any charges or cost not set forth in Contractor's bid documents.

CONTRACT DOCUMENTS

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

The following documents constitute the Contract Documents;

Instructions to Bidders

Technical Specification – Bidders actual specifications

Official Bid Form and Agreement

Statement of Compliance/Deviation from Specifications

Experience Statement

The following documents must be submitted with the bid in order for such bid to be considered complete. A bid that does not include each and every one of these documents shall constitute cause for rejection of the bid.

1. Executed Official Bid Form and Agreement
2. Executed Statement of Compliance/Proposed Deviations from Specifications
3. Experience Statement
4. Warranty printed on company form per Specifications
5. Proof that Bidder is a Certified Vehicle Modifier for the chassis(s) that are bid.
6. Policy indicating prompt service and ability to furnish replacement parts
7. Bidders Specifications consisting of detailed description of the unit and equipment proposed and to which the unit furnished under contract must conform; computer run-off sheets are not acceptable as a descriptive literature. These specifications shall indicate size, type, model, and make of all component parts and equipment. IT IS AGREED BY THE UNDERSIGNED BIDDER THAT THE SIGNING AND DELIVERY OF THIS BID REPRESENTS THE BIDDER'S ACCEPTANCE OF THE TERMS AND CONDITIONS OF THE FOREGOING SPECIFICATIONS AND PROVISIONS, AND IF AWARDED THE BID BY THIS AGENCY, WILL REPRESENT THE AGREEMENT BETWEEN THE PARTIES.
8. W-9
9. County E-Verify affidavit
10. E-Verify affidavit
11. Liability Insurance

Sign in ink in the space provided below. UNSIGNED bids will be considered incomplete and will be subject to rejection.

Name of Firm:

Signed (in ink):

(Signature of Officer of Company)

Title:

Date Signed:

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Street Address:

Mailing Address:

City: State: Zip Code:

Phone Numbers : Phone: Fax:

Email Address:

Ambulance
Manufacturer:

Model Year: Model Designation: Type III Ambulance G4500 Chevrolet or Ford E450

Delivery will be made within days of receipt of chassis by the Manufacturer

Bid Amount:

TOTAL BID AMOUNT:

TYPE III AMBULANCE SPECIFICATION

SPECIFICATION EVALUATION CHECKLIST

ITEMS INCLUDED

INITIAL

CURRENT KKK-A-1822F CERTIFICATION

CURRENT Q.V.M. CERTIFICATION

PRODUCT LITERATURE

PRODUCT BUILD SPECIFICATIONS

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

ALL APPLICABLE WARRANTY DOCUMENTS	_____
PROPOSAL DRAWINGS	_____
INSURANCE CERTIFICATE	_____
COPY OF DEALER'S LICENSE	_____
COMPLETED BID FORM	_____
COMPLETED NON-COLLUSIVE CERTIFICATE	_____
REFERENCES	_____
LIST OF SERVICE FACILITIES	_____
BID DOCUMENT WITH YES/NO RESPONSES	_____
TOTAL NUMBER OF YES's	_____
TOTAL NUMBER OF NO's	_____

STATEMENT OF COMPLIANCE/DEVIATIONS FROM SPECIFICATIONS.

The Bidder proposes the following deviations from the Specifications and/or Drawings, which the Bidder represents and warrants as being fully equal or superior to the requirements of the Specifications and Drawings, for the reason(s) set forth fully below (attach additional sheets if necessary):

If there are no deviations from the Specifications and/or Drawings, please state same.
NONE

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

I certify that the foregoing fully and completely describes each proposed deviation, if any, and the reason why each deviation is fully equal or superior to those in specified in the Detailed Specifications.

BIDDER:

BY:

IT'S:

TYPE III EMERGENCY VEHICLE

Intent of this Bid

This Request of Bid (RFB) is intended to provide vendors with a common, uniform set of specifications to assist them in the development of their bids and to provide a uniform method for the bidding agency to fairly evaluate

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

bids and subsequently select a vendor from which to purchase these ambulances.

The following specification describes a new ambulance that is expected to be acquired by this purchaser. The specification describes the needs of this purchaser as far as chassis configuration and module body design. A state of the art vehicle is required. However, manufacturers that utilize prototype equipment will not be considered. The builder's manufacturing history shall be supported by documentation where applicable, and by the reference section within this specification. The benchmark for the initial configuration of this ambulance shall be the current KKK Federal Specification for Ambulances, Ambulance Manufacturers Division Standards, Federal D.O.T specifications and/or regulations, applicable NFPA Standards, all State of Georgia Emergency Medical Services and Georgia Bureau of Labor Standards rules, laws and standards. However, most requirements in this specification exceed the federal specifications because of the specific needs of this purchaser. Please note that the following specifications represent minimum general terms or requirements. While it is not the intent of this purchaser to preclude any qualified bidder from submitting a proposal, it must be clear that any bidder deviating in any substantial manner from these specifications will be rejected as being non-compliant.

In responding to this RFB, vendors should follow the prescribed format and use the forms included, thus providing the County with data that is easily compared with data submitted by other vendors in order to fairly and objectively evaluate the proposal.

Each bid shall be accompanied by a set of "Contractor's Specifications" consisting of a detailed description of the unit and equipment proposed and to which the unit furnished under contract must conform. These specifications shall indicate size, type, model, and make of all components parts and equipment. Drawings including dimensions showing the unit as proposed in the bid shall be submitted with the bid documents.

NOTE: Bidders that simply check each box is not enough, each bidder will be required to submit with their bid proposal, "ACTUAL" detailed specification and drawings describing what they are providing. This way Peach County will be able to compare each bidder's package to this bid specifications. If a bidder does not comply with this section there bid will be deemed no-responsive and incomplete and will not be accepted. NO EXCEPTIONS.

The Bidding Agency assumes no responsibility for conclusion or interpretations derived from the information presented in this RFB, or otherwise distributed or made available during this procurement process. In addition, the Bidding Agency will not be bound by or be responsible for any explanation, interpretation or conclusions of the RFB or any documents provided by the Bidding Agency other than those given in writing by the Bidding Agency through the issuance of addenda. In no event may a vendor rely on any oral statement by the Bidding Agency or its agents, advisors or consultants. It is the full responsibility of the vendor to thoroughly investigate the needs, requirements of the Bidding Agency not necessarily assumed in this RFB and to submit a bid for:

INSTRUCTIONS FOR BIDDERS

This specification establishes standards for the design, construction and performance of a Type III Modular ambulance. The completed vehicle and components must comply with the current version of Federal Specification KKK-A-1822 unless specifically requested otherwise in the following document. As the criteria for compliance with KKK-A-1822 are well established, this document

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

will not contain redundant references to their content.

Bids will only be considered from companies that have an established reputation in the field of ambulance construction. Preference shall be given to ambulance manufacturers who employ Ambulance Manufacturers Division (AMD) standards in the construction of their ambulances.

Bids will not be accepted after the date and time stated in the invitation to bid.

Payment shall be made in accordance with these specifications and the Bid Proposal submitted by the Bidder. Payment will be made upon acceptance of the vehicle(s) and equipment specified in this document.

Bids received shall be evaluated by the Purchaser. This evaluation will be based on, but not limited to, completeness of proposal, exceptions, price, and delivery schedule.

Bid Proposals taking total exception to these specifications will not be accepted.

Any exception to the provisions in these specifications must be marked in the body of this document and itemized on a separate attached page(s) titled EXCEPTIONS. Referenced by section number and paragraph, a detailed explanation of the exception shall be provided along with by the bidder's alternative proposal.

Bids not following this format shall not be considered. NO EXCEPTIONS TO THIS SECTION.

The Contractor shall indemnify and save the Purchaser harmless from any and all claims, liability, losses, and causes of actions which may arise out of the fulfillment of this agreement. The Bidder shall pay all claims and losses of any nature whatsoever in connection therewith, and shall defend all suits, in the name of the Purchaser when applicable, and shall pay all costs and judgments which may ensue thereafter.

Failure to deliver any part of the order to the terms required may be considered by the Purchaser as a breach of contract. In such case the vehicle(s) and equipment may be rejected and the purchaser shall retain the right to require forfeiture of the full amount of the Performance Bond (if required) as liquidated damages.

When submitting their Bid Proposal, Bidders must return all pages of these specifications as part of the Bid Proposal as it will form the Contract between the Contractor and the Purchaser. Caution should be taken by the Bidder that all questions are answered in the spaces provided and that all information requested is provided.

It is the Bidder's responsibility to be familiar with all federal, state, and local laws, ordinances, codes, and regulations concerning the submission of this bid and the work it effects. Ignorance of said enactments shall not relieve the Bidder of responsibility to comply or complete the bid work.

In the event a clarification is requested on the contents of this specification, the question shall be addressed in writing to:

When a Bidder requests clarification, a copy of the request and this Agency's reply will be forwarded

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

to all Bidders.

The vehicle(s) shall, at the time of delivery, conform to the minimum requirements of the latest standards covering vehicles of this type. This shall include federal, state and local requirements.

In the event the bidder represents more than one ambulance manufacturer meeting the manufacturer requirements outline herein, then the bidder shall "only" bid the highest quality vehicle that the bidder represents. Under no circumstances will multiple bids from the same bidder on different manufacturers be accepted. Should a bidder submit two or more bids representing more than one manufacturer, then all bids submitted by that bidder will be rejected as being non-complaint with the requirements of this specification. This purchaser is seeking quality equipment. Bidders are asked to bid only the product of the highest level of quality represented by that bidder.

Is this requirement understood and met? Yes ___ No ___ Bidder's initials: _____

By signing this document, the Bidder agrees that this Bid is made without any understanding, agreement or connection with any other person, firm or corporations making a bid for the same purpose, and that this bid is in all respects fair and without collusion or fraud.

PIGGY BACK CONTRACT

It is the intent of this agency to enter into a contract with the successful bidder to allow that contract to be extended for 2 years, in order to add additional units to the contract. This contract shall allow for chassis model year increases, only if and when the successful bidder provides documentation from its chassis supplier on their letterhead indicating an increase to the chassis.

This contract shall allow any other agency within the State of this contract, or any other State outside of this state to purchase off of contract. However, prospective purchasers shall enter into separate agreements for product being offered. The Bidding Agency does not control this contract outside of what it is intended on.

Latest literature and detailed specifications on the unit proposed shall be included with the proposal submittal.

TYPE OF BIDS TO BE SUBMITTED

The information requested within the bid must be furnished in full. Any bidder not completing this proposal or not furnishing any required information will not be considered. If a bidder will not furnish a material or fabrication process exactly as described in this specification, then that differences must be designated in the list of exceptions. If a substitution is being proposed, then the bidder must note the section to which the alternative is being proposed and provide technical data, supported by an engineer, supporting the fact that the substitute is equal to or better than the item as specified. If this data is not submitted with the bid, then the bid shall be rejected as being non-compliant. Bidder added narrative describing a substitution as being clarification, exceeding, being equal to, etc. will not be

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

accepted. Statements such as these, with or without the technical data described in this section, will cause the bid to be rejected as being non-compliant

This purchaser reserves the right to require samples of any deviating material to be provided for evaluation.

Does the bidder comply with these requirements? Yes ___ No ___

GENERAL REQUIREMENTS

Payment shall be made on delivery of the purchased item, or upon completion of all work contracted for (whichever occurs later) and to performed to the satisfaction of the purchaser.

Does the bidder comply with this requirement? Yes _____ No _____

All bid prices shall quote F.O.B. destination basis, at the Purchaser's specified location. Bid prices shall be complete and include all warranties and equipment specified. After bid allowances will not be made for incorrect or incomplete bids proposals.

All prices, terms and conditions must be specified on the Bid Proposal Form.

Does the bidder comply with this requirement? Yes ___ No ___

INSPECTION TRIPS

PRE CONSTRUCTION CONFERENCE

There shall be a required pre-construction conference at the successful bidder's manufacturer's facility before any construction can begin.

NOTE: The pre-construction conference meeting shall be conducted at the "primary builder", of the apparatus. No meeting shall take place at the dealerships place of business. This is the only method that will be the only acceptable way to conduct the pre-construction meeting. NO EXCEPTIONS.

Two (2) department personnel along with a representative or dealer of the successful bidder shall attend.

At this meeting both parties shall again go over the specifications to insure that the apparatus is built to meet or exceed all requirements.

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

After this meeting the representative of the successful bidder shall present the department with detailed drawings and work order to be used in the production of the apparatus being bid.

Do you comply to all inspection trips? Yes ____ No ____

MID POINT INSPECTION

There shall be a midpoint inspection trip at the factory of the successful bidder. The inspection trip shall consist of three (2) members from the Department who shall inspect the progress of the apparatus to insure compliance to all specifications.

Do you comply to all inspection trips? Yes ____ No ____

PRE DELIVERY INSPECTION (FINAL)

There shall be a pre delivery inspection trip at the factory of the successful bidder. The inspection trip shall consist of two (2) members from the department along with the representative of the successful bidder, to insure compliance to all specifications.

NOTE: All expenses relating to the Pre-Construction, Mid Point and Final inspection trips shall be at the cost of the successful bidder and be at no cost to the Department. This is to include all meals and lodging while at the inspection along with travel allowances (round trip coach air flight), for up to 1 representatives for any factory that is over (190 miles) from (Peach County EMS) facility.

Do you comply? Yes ____ No ____

Under no circumstances shall the completed ambulance leave the manufacturer's facility unless everything is completed at the factory. Bidders that make allowances for units to be completed at their service facility or office shall not be acceptable to this bidding agency.
NO EXCEPTIONS.

Do you comply? Yes ____ No ____

ONE MONTH SERVICE CALL

After the vehicle has been in service for approximately one month, the successful vendor shall perform a follow up inspection or interview with the Peach County EMS, for a service and warranty review.

TYPE HI AMBULANCE SPECIFICATION

Peach County EMS

The Factory technician shall check all operating systems and repair or replace any items found defective or in need of re-work.

However should a problem occur before the one month service call. Peach County EMS will require immediate service from the FACTORY technician. at the Departments location. NO EXCEPTIONS

Do you comply? Yes _____ No _____

Bid prices shall be valid for at least forty-five (45) days from the date of the Bid Opening, or as otherwise specified on the Bid Proposal Form.

Does your proposal comply? Yes _____ No _____

Peach County shall seek the highest level of quality assurance and liability protection to insure that these standards are met. Bidders must submit documentation that they are a current member of the QVM (Qualified Vehicle Modifier) program.

They must be able to show that they have been factory trained. Proposals not meeting this requirement will be considered non-responsive and shall be rejected.

Do you comply with the requirements? Yes _____ No _____

WARRANTY

The proposal shall include all warranties that are required in the following detailed specifications. The minimum acceptable warranty periods are noted below. In the blank lines the bidder shall note the terms of the warranty that apply to the manufacturer being proposed. **Each bidder will be required to submit their own warranty coverage's, simply checking and filling in the blanks below will not be tolerated and will be grounds for rejection.**

Bidding Agency shall provide a minimum 12 month/12,000 mile Limited Warranty on the vehicle conversion, which covers defective parts and/or components, improper choice of materials, parts and/or components, improper design or engineering and poor or improper workmanship or quality control techniques. This warranty shall cover the complete vehicle, exclusive of the chassis, and shall include any and all costs for labor and parts or materials required to correct deficiencies. It is not the intent of this requirement that items such as light bulbs, or equipment installed in or on the vehicles which are covered by their own separate and specific warranty statements, be included in this warranty.

State the General warranty terms you are bidding: 12 Months

Number of year's _____ Mileage _____

Since it is the purpose of these specifications to provide for a modular body that will offer many years of service, the Manufacturer of the vehicle(s) bid shall warranty the structural modular body for the life of the unit. This warranty shall be in writing and shall be included with the Bid Proposal. Bidders who fail to meet this

TYPE III AMBULANCE SPECIFICATION

requirement shall not be considered responsive.

State the Structural warranty terms you are bidding:

Number of year's _____ Mileage limitations (if applicable) _____

There shall be an electrical warranty provided on the ambulance conversion electrical system. The warranty shall cover all conversion circuit boards, harnesses, switches, circuit breakers, and relays. This county will not accept bids that have a Lifetime Electrical unless that entire electrical system is covered under the original ambulance manufacturer. Warranties that cover wiring harness only will not be acceptable and will cause the bidder's bid to be no-responsive and unacceptable to this bidding agency.

State the Electrical warranty terms you are bidding:

Number of year's _____ Mileage limitations _____

A seven (7) year paint warranty shall be provided on the paint and its application. A copy of the painter's warranty statement shall be included with this Bid Proposal. All warranties shall begin at the acceptance of the vehicle(s) by the Purchaser. NOTE: Manufacturers must be PPG Certified or show that their paint process is totally certified by the paint manufacturer's representatives.

State the Paint warranty terms you are bidding:

Number of year's _____ NO MILEAGE ACCEPTED; Yes _____ or No _____

For verification of the completed warranty terms stated above the bidder must include printed manufacturer's warranty certificates that meet or exceed the minimum required periods stated below.

Are the manufacturers warranties included? Yes _____ No _____

All warranties shall be from the manufacturer as opposed to a distributor or service center. This is necessary for the protection of the purchaser, and to guarantee a certain known level of service and warranty. If, however, the bidder feels that it is necessary to modify the manufacturer's warranties, then the bidder shall state why this modification is necessary. In addition, the bidder shall provide a full descriptive warranty certificate describing the warranty modification and the fact that it takes specific precedence over the warranty offered by the manufacturer. If no such certificate is provided, then the modified warranty shall be considered invalid and the manufacturer's warranty shall remain in force. If the manufacturer states that no party is permitted to modify its warranty, then any warranty modification provided by the bidder, despite being in writing, shall automatically be rejected.

Does the bidder conform to the above-written section? Yes _____ No _____

In order to simplify the evaluation process the following questions must be answered and this section must be initialed by the bidder.

Are the warranties pro-rated in any manner? Yes _____ No _____

If yes explain:

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Are the warranties transferable? Yes ____ No ____
If yes explain:

Has the bidder modified the manufacturer's warranties? Yes ____ No ____
If yes explain:

If yes was chosen above, has the bidder included modified written warranties? Yes ____ No ____
If no explain:

If 'yes' was chosen above, has the bidder included financial statements, for the last five (5) years, of the warranty modifier? Yes ____ No ____

If no explain:

Bidder shall initial that this section is understood and has been answered truthfully. Initials: ____

Note: Bidders, who are found to be untruthful in this, or in any other section of this bid, will have their bid automatically rejected.

PRODUCT LIABILITY INSURANCE

Proof of current liability insurance shall be supplied. The proof of insurance shall bear the insurance carrier's name, address and phone number. The proof shall also bear the name and address of the insured. This document shall contain the coverage schedule, explaining the type of insurance, the policy number, the effective date of coverage, the policy expiration date and the minimum amount of coverage shall be as follows.

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Commercial General Liability - Aggregate policy limit of one million dollars.

Automotive Liability - Any Hired and Non owned Autos
Combined Single Limits of One million dollars.

Garage Liability - Any Auto
Auto only - Each accident: limit of one million dollars.

Workers Compensation and Employer's Liability —

Each Accident: limit of five hundred thousand dollars.
Disease policy: limit of five hundred thousand dollars.
Disease - Each Employee: limit of five hundred thousand dollars.

Excessive/Umbrella Liability —

Each Occurrence: limit of nine million dollars

Automotive Damage. Physical Liability Damage
Comprehensive Deductible:

Since these specifications describe an emergency vehicle that may be used under adverse conditions, this agency seeks to reduce its future liability exposure. Therefore, all bidders responding to these specifications shall submit a proper and verifiable Certificate of Insurance. This shall certify that the Manufacturer of the bid vehicle has in force, Product Liability insurance in the *minimum* amount of ten million dollars (\$10,000,000.00). This insurance shall have been issued by a Company rated "A+" as reported in the current edition of Best's Key Rating Guide, published by Alfred M. Best Company, Inc.

The amount of Product Liability must be adhered to by both manufacturer and dealer, who will be providing the bid. Utilizing the ambulance manufacturer's insurance will be acceptable if the bidder is an authorized dealer, they also must have coverage.

Bidders failing to submit proof of the above requirement cannot be accepted and their Bid Proposal will be rejected.

Does the bidder comply with this requirement? Yes ___ No___

The bidding agency has concerns with bidders not having the completed unit built by the manufacturer. With that said, the bidding agency will not accept units that are not built and completed at the manufacturer's facility. This will eliminate split responsibility into service, warranty repairs. Add-on equipment shall be furnished by the manufacturer and not their Representatives, to avoid warranty issues

If the bidder makes any claim to adding equipment at the dealership, then your bid will be considered non-responsive and rejected. NO EXCEPTION.

TYPE HI AMBULANCE SPECIFICATION

Peach County EMS

Does the bidder comply with this requirement? Yes ____ No ____

It is the intent of this agency to have the vehicle completed and ready for service once it leaves the ambulance manufacturer's facility. NO EXCEPTIONS.

Does the bidder comply with this requirement? Yes ____ No ____

All equipment furnished shall be guaranteed to be new and of current manufacture: meet all requirements of this specification: and be in proper operating condition at the time of delivery. All parts shall be of high quality workmanship and construction.

No part or attachment shall be substituted or applied contrary to the manufacturer's recommendations and standard practices.

Does the bidder comply with this requirement? Yes ____ No ____

ANTI-COLLUSION STATEMENT

By signing this proposal, the offeror agrees that his bid is made without any understanding, agreement, or connection with any other person, firm or corporation making a bid for the same purpose and that his bid is in all respect fair and without collusion or fraud.

Company Name: _____

Offeror Signature: _____

Date Signed: _____

Offeror Complies Yes No____

SERVICE FACILITY

Service will be a major factor in the award of this proposal. Convenience and experience will be determining factors in defining acceptable service. A service facility within a radius as described below will be required. Personnel performing the service shall be trained by the manufacturer with emphasis

TYPE HI AMBULANCE SPECIFICATION

Peach County EMS

in the area of electrical service. In order to evaluate the proposed service facility the following information shall be provided on the appropriate lines.

Radius from Purchaser: Not more than _____ miles.

Facility Name (If not the manufacturer):

Address:

City: _____ State: _____ Zip Code: _____

Contact:

Phone: Toll Free Preferably:

Training Description:

Bidders shall include with the Bid Proposal: literature, photographs or similar documents which describe or depict the manufacturer's type and model proposed; a complete set of the manufacturer's specifications for the type and model proposed; and one (1) set of drawings. These drawings shall consist of: four (4) exterior views: front, rear, curbside and street side and four (4) interior views: front, rear, curbside and street side, showing the location of all requested features attached thereto.

NOTE: the drawings submitted by the Bidder must show the design, layout, and features specified in this document. Submitting a manufacturer's "generic" or "standard feature" drawings, or photocopies of the reference drawings provided with this document, shall NOT be acceptable. Bidder's not including the required drawings will be considered non-responsive and will, therefore, be rejected.

Are the required drawings included with this bid? Yes _____ No _____

LICENSING REQUIREMENT

Bidder must be a registered and/or licensed automobile dealer within the state of the purchaser. (Georgia): This will insure the purchaser full protection under the laws governing the sale and service of automobiles within the purchaser's state. A copy of the dealer's license must be submitted with the bid.

Are the required drawings included with this bid? Yes _____ No _____

The **bidder shall utilize these specifications** and **return their proposal in the same format as the specifications** are provided. Failure to submit the bid specifications in alternate format will be grounds for rejection. **NO EXCEPTIONS.**

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Are your specifications in the same format? Yes _____ No _____

QUALITY CONTROL ASSURANCE

To ensure the Purchaser that proper engineering and production control guidelines have been implemented the ambulance manufacturing shall employ an integrated quality and process control program including specific process controls for facets of the manufacturing process deemed to be "critical". These critical elements of the process shall be documented and that documentation shall be available not only to manufacturing personnel but also customers who visit the manufacturing facilities. The critical elements shall be denoted on the vehicle control document, which accompanies the vehicle through the manufacturing process. A sample of this document shall be available to the purchaser upon request. A continuous series of inspections shall be performed and signed off on the vehicle control document and shall include but not be limited to the following:

Visual inspection of the body, welds, and exterior attachments.

Visual and mechanical inspection of the heater/air conditioning lines, cables, grommets, valve connections, clamps, mounting brackets, belts, etc.

Visual inspection of cabinets, sliding/hinged cabinet doors, moldings, flooring, walls, headliner, and cushions.

Visual inspection of exterior paint, decals, and lettering.

Operational inspection of all electrical systems, This must consist of tests of battery voltage, electrical load test, alternator output, beacons, flashers, siren, interior lighting, compartment lighting, power exhaust vent, scene lights, chassis lights, silent signal lights/buzzer, heat/cool units, and any optional electrical devices as furnished by the manufacturer. The current requirements of each device tested must be noted on an inspection sheet together with the total current requirements.

The oxygen and vacuum systems shall be tested both prior to and after installation to meet the requirements as listed in those individual sections of this specification. Test data indicating temperature, pressure, timing, flow, etc., shall be recorded.

All chassis fluid levels shall be checked and filled to capacity. All doors, locks, windows, tires, etc., shall be inspected for proper operations and/or condition.

The completed vehicle must be test driven a minimum of twenty (20) miles on paved highways and on rough terrain to check handling, brakes, acceleration, and noises. A water spray test and visual inspection shall be performed after the road test.

Does the bidder comply with this requirement? Yes _____ No _____

GENERAL VEHICLE DESIGN, TYPE, AND FLOORPLAN

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

The ambulance and the allied equipment furnished under this specification shall be the manufacturer's current commercial vehicle of the type and class specified. The ambulance shall be complete with the operating accessories as specified herein and furnished with such modifications and attachments as may be necessary or specified to enable the vehicle to function reliably and efficiently in sustained operation. The design of the vehicle and the specified equipment shall permit accessibility for servicing, replacement, and adjustment of components parts and accessories with minimum disturbance to other components and systems. The term "HEAVY DUTY" as used to describe an item shall mean in excess of the components.

Does the bidder comply with this requirement? Yes ____ No ____

CURB WEIGHT

The curb weight is the total weight of the complete ambulance and is defined as the chassis, cab, body, and minimum required equipment as required by KKK-A-1822F, and includes a full complement of fuel, lubricants and coolant shall meet Federal Requirements.

Does the bidder comply with this requirement? Yes ____ No ____

PAYLOAD ALLOWANCE

A minimum of 1,750 pounds will be allowed over and above the curb weight for personnel, patient, and miscellaneous support equipment

Does the bidder comply with this requirement? Yes ____ N ____

INTERIOR HEADROOM

There shall be 72" inch of interior headroom provided inside the patient area of the module. It shall be free of obstructions for the occupant's safety and shall meet or exceed all transportation and regulatory requirements.

TECHNICAL REQUIREMENTS CAB/CHASSIS

The ambulance shall be a Type III, Class I, and shall have a chassis furnished with two-door cutaway cab/chassis, 4x2. The cab/chassis shall be suitable for subsequent mounting of a modular (containerized) transferable equipped ambulance body conforming to the requirements specified herein.

Does the bidder comply with this requirement? Yes ____ No ____

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

STAR-OF-LIFE CERTIFIED AMBULANCE

The Emergency Medical Vehicle described in this specification is designed to meet or exceed the requirements of Federal Ambulance Specification KKK-A-1822 Revision F, and AMD Standards 001-009

NOTE: Throughout the written Federal Ambulance Specification KKK-A-1822, there are frequent references to item to be included WHEN SPECIFIED item, but such items may not be included in the attached specifications.

INSTRUCTIONS TO OFFERORS

The Specifications calls for the following type of vehicle. It is in accordance with paragraph 1.2.1 of KKK-A-1822F.

Type III: Specialty (cutaway cab/chassis) with integral or containerized Modular body.

Class 1: Two wheel driven (4x2)

Configuration B: Elevating cot and squad bench for ALS (see 3.1.5.1/3.15.3 of KKK-A-1822F).

The emergency medical care vehicle, chassis, ambulance body, equipment, devices, medical accessories, and electronic equipment to be delivered under this contract shall be standard commercial products that meet or exceed the requirements of these specifications. The ambulance shall comply with all Federal Motor Vehicle Safety Standards (FMVSS) and Federal regulations applicable or specified for the year of the manufacture. The chassis, components, and optional items shall be represented in the manufacturer's current technical data. Materials used in the construction shall be new and not less than the quality conforming to current engineering and manufacturing practices. Materials shall be free of defects and shall be suitable for the intended use.

SECTION 1.0 – CHASSIS AND COMPONENTS

O.E.M.: The acronym O.E.M. is Original Equipment Manufacturer. The O.E.M. is the chassis manufacturer and the vehicles Make Origin.

CHASSIS MAKE: The apparatus shall be mounted on a commercially available cab and chassis manufactured by General Motors or Ford Motor Company. The chassis manufacturer shall be the vehicle's point of origin. The chassis shall be supplied by (Chevrolet or Ford) as an incomplete vehicle to the successful ambulance manufacturer. The chassis supplied shall conform to all applicable Federal Motor Vehicle Safety Standards in force at time of manufacture. A statement of conformity shall be supplied with the chassis in an "Incomplete Vehicle Manual".

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

CHASSIS MODEL: The ambulance module shall be mounted on a (2017- 2020 Chevrolet G4500) (4x2), Cab/Chassis, or Ford E-450 Cutaway, 159 inch wheel base, dual rear wheel, chassis equipped as follows below)

WHEEL BASE: The wheel base shall be 159 inches or appropriate for chassis size with a cab to axle of 100 inches or appropriate. The wheel base shall be factory supplied by the O.E.M. Modified wheel bases made from chassis with shorter or longer wheel bases in not acceptable.

ENGINE: A 6.0 V-8 Vortec engine or Ford 6.8L Triton V8. The engine performance shall comply with or exceed the most current revision of KKK-A-1822F. (Demo units submissions shall include engine offered)

TRANSMISSION: Automatic 6-speed, automatic with overdrive transmission shall be provided

GROSS VEHICLE WEIGHT RATING (GVWR): The GVWR of the chassis supplied shall be at least 14,200 pounds.

FRONT AXLE WEIGHT RATING (FAWR): The FAWR shall be rated at no less than 4,600 pounds.

REAR AXLE WEIGHT RATING (RAWR): The RAWR shall be rated no less than 9,600 pounds.

HEAVY DUTY FRONT AND REAR SWAY BARS Roadmaster Heavy Duty Front and Rear axle

CAB INTERIOR COLOR: The color of the cab interior shall be black. All conversion manufacturer's added consoles and device shall be pleasing in color with the interior color provided by the O.E.M.

CAB SEATS: O.E.M. High back, velour covered bucket type seats shall be provided in the cab. The seats adjust forward and aft as well as recline. Seat base must be O.E.M., per QVM guidelines..

OCCUPANT RESTRAINT SYSTEM: The front, forward facing cab seats shall be equipped with O.E.M. installed three point seat belts. The seat belts shall have pre tensioners built in to the seatbelt assembly to take up belt slack during a violent frontal collision. The seat belts assemblies shall meet or exceed F.M.V.S.S. 208 and 209. The inside conversion panels shall not interfere with the swivel arc of the shoulder ring.

SUPPLEMENTAL RESTRAINT SYSTEM: An O.E.M. air bag shall be installed on the driver and passenger side.

TRIM PACKAGE: The highest level trim package shall be supplied from the O.E.M. The package shall include high quality chrome like bright work on the grille face. Chrome plated steel bumper(s) shall also be supplied by the O.E.M. Argent or painted bumpers are not acceptable. The O.E.M. grill work shall remain the same O.E.M. After market vacuum formed, proprietary grille work made by the ambulance manufacturer is not acceptable due to replacement part cost and lack of immediate availability.

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

CAB FLOOR COVERING: The cab floor shall be covered with an O.E.M. black rubber mat.

BRAKES: 4-Wheel anti-lock, power hydraulic brakes shall be supplied by the O.E.M. The brakes shall be 4-wheel Disc type with Dual piston calipers and front and rear vented discs.

TILT STEERING WHEEL: The steering wheel shall be tilt adjustable. An easy to operate, column mounted pull to adjust lever shall lock the steering wheel angle position.

INTERIOR UPGRADE PACKET; Interior upgrade package shall be ordered and supplied on the chassis.

This package shall include:

Cloth Headliner

High trim door panels

High back bucket seats with arm rests.

Cloth sun visors

Front Rubber Floor matting

Power Door locks

Power Windows

Insulation package.

DOOR LOCKS: The chassis shall have O.E.M. power door locks. There shall be a remote O.E.M. key fob included with the package.

DAYTIME RUNNING LIGHTS: Daytime running lights option No 942 shall be supplied and installed by the O.E.M. Both headlights shall come on with the ignition switch.

WHEEL/RIM APPEARANCE: All four outside chassis wheels shall be covered in polished stainless steel wheel simulators. The wheel simulator design shall not affect tire and wheel balance when the vehicle is driven between zero and eighty miles per hour. The lugs shall be capped off with bright stainless steel, snap on caps designed to cover wrench marks, normally left on the lug nuts.

SHOCK ABSORBERS: The chassis shall be equipped with one shock absorber for each side of each axle. An O.E.M. selected one and three eighths (1-3/8") inch gas type shock shall control vehicle spring oscillation and dampen road related jounce and harshness. Ambulance related shields, floor members or other devices shall not interfere with shock replacement.

FUEL TANK: The fuel capacity shall be at least 57 US gallons. The fuel range shall be at least 250 miles per current KKK-A-12822F.

REAR AXLE TYPE AND RATIO: The axle type shall be a Limited Slip Differential with a 3.73 gear ratio.

SPARE TIRE STOWARD LOCATION: The spare tire and wheel assembly will not be carried on the units. The spare tire and the related tools, if supplied by the O.E., shall be shipped loose with the completed vehicle.

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

TIRES: All tires shall be identical make, thread type, size and load range. The tires shall be LT225/75R16E AS front and rear (Includes Spare).

TIRE VALVE EXTENDERS: One pair of tire valve extenders shall be supplied and installed for each inside rear wheel. The tire valve extenders shall permit the user to check tire pressure and fill the inside rear tires without removing the outer tire. The extenders shall have a braided stainless steel outer jacket to resist abrasions and cuts. The filler end shall be supported by a valve bracket.

AMBULANCE PREPARATION PACKAGE: The chassis provided shall be equipped with an 47A ambulance preparations package designed and installed by O.E.M. The package shall be designed to hold up to the demands and duty cycles inherent with Emergency Medical Vehicles.

ALTERNATOR — CHARGING SYSTEM: Dual 145 AMP.

THROTTLE HIGH IDLE: The O.E.M. high idle shall be installed by OEM.

CAB STEREO: An O.E.M. AM/FM/CD in dash radio and two cab door speakers shall be included with the chassis.

SIDE REAR VIEW MIRRORS: Dual O.E.M. Mirrors. and manually telescoping mirror heads shall be mounted to the forward, lower corner of the cab door window. Both mirrors shall feature a bi-directional break-away function to permit folding the mirror heads against body in close quarters. The mirrors shall provide 63.3 sq. inch flat glass position over a 30.1 sq. inch convex glass within a common head.

CHASSIS WARRANTY

The chassis manufacturer's standard vehicle warranty polices shall apply.

BASIC	3 Years / 36,000 miles
Engine	5 Years / 100,000 miles
Transmission	5 Years / 100,000 miles

Does the bidder comply with this requirement? Yes _____ No _____

RUNNING BOARDS- NFPA -ADP - ADD GRIP STRUTS

- Bright finish aluminum diamond plate running board shall be Of the body, as required, and include nonmetallic spacers to Prevent trapping of dirt and water between the running board and the cab body.

- All running boards shall be gusseted and provide brackets to Prevent flexing, sagging, and damage.

- Design of the running boards shall incorporate a splash shield to

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Protect the front of the modular body from wheel wash.

The running boards shall reinforce and be braced to handle a minimum of 250 pounds without flexing. Running board installation to conform to chassis manufacturer's recommendation.

Does the bidder comply with this requirement? Yes ___ No ___

PHOENIX SIMS WITH VALVE EXTENDERS

- Chevrolet G4500 or Ford E450 Cutaway
- A set of Phoenix stainless steel wheel inserts shall be provided for the front and rear wheels
- The wheel inserts shall be approved and shall not be held in place by the wheel lug nuts.

- Braided stainless steel air stem extensions shall be furnished for the inside dual rear wheels to allow these wheels to be easily checked and filled with air. Deluxe type Air Max AML-1 Valve Extensions.

Does the bidder comply with this requirement? Yes ___ No ___

SIREN SPEAKERS, RECESSED FRONT BUMPER CAST

(2) 100 Watt Speakers

Does the bidder comply with this requirement? Yes ___ No ___

WIRE ENGINE BLOCK HEATER - SHORLINE SUPPLIED & SWITCHED

- NOTE: Add label indicating "On/Off" on switch box.

- An engine block heater shall be electrically tied to the vehicle shoreline. There shall be a summer/winter switch consisting of a 15 amp (toggle) circuit breaker, located behind the front driver seat, unless otherwise requested, to disable the block heater in warm weather conditions.

Does the bidder comply with this requirement? Yes ___ No ___

HEAT SHIELDS

- There shall be protective heat shields installed above the exhaust system as recommended by the chassis manufacturer.

- The heat shields must be a minimum of 16-gauge material for additional strength to prevent rattling.

Does the bidder comply with this requirement? Yes ___ No ___

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

SECTION - 2.0 MODULE CONVERSION

14' TYPE III WALK THRU

** 169" L X 96" W X 72" HEADROOM**

Does the bidder comply with this requirement? Yes ____ No ____

MODULE RECESSED FRONT WALL

Note: 6 TO 8 inch extension will be for Cutaway module.

FRONT WALL WALK-THROUGH

- There will be a walk through between the driver's and patient compartment.
- The modular body will be attached by bolting through the .125" aluminum body skin and the steel flange in the chassis cab wall.
- The body shall be attached to the cab using a minimum of twenty-four (24) .250" x 20 bolts.
- The front wall structure of the module shall be the .125" aluminum skin reinforced with 1" x 2" x .125" extruded aluminum tubing to provide a rigid connection between the cab-chassis and the module.
- Between the cab and body will be installed a one-piece automotive style closed cell bulb seal to completely seal the cab to the modular body.
- The walk-thru opening shall be closed with a hinged wood door with sliding Plexiglas window and positive latches to hold the door in the open or closed position or appropriate design.

Does the bidder comply with this requirement? Yes ____ No ____

BODY CONSTRUCTION OVERVIEW

The dimensions of the patient module shall be in accordance with manufacturer's specifications with minimum dimensions of 169" in length, 96" in width, and 72" headroom.

There shall be a bulkhead separating the cab and patient compartment that allows for a pass through area.

The ambulance body shall be constructed of custom designed aluminum extrusions and aluminum plate. The ambulance body shall be designed and engineered specifically as an Emergency vehicle and shall be built to meet the heavy duty requirements of emergency service.

The body shall be of welded construction for maximum strength and integrity for the entire life of the ambulance. The aluminum extrusions shall be custom designed structural shapes that are an alloy of 6061 and heated to a temper of T6 hardness.

The aluminum shapes shall be designed with a force fit interlocking system that shall eliminate any vibration to the welded structural members. The interior structural members, sides and roof shall be spaced a minimum of 12 inches on center. The floor structure shall be a minimum 12 inches on

TYPE HIAMBULANCE SPECIFICATION

Peach County EMS

center. The floor, roof and sides shall be of a cage-type construction that is built to form an independent structure.

The exterior walls shall be constructed of a minimum of .125 inch thick aluminum plate 3003 alloy with a heat treated plate that is stretch leveled to a tolerance of +1- 0.003 inches. The exterior walls shall interlock into place.

All exterior compartments shall be separate and individual components and no two compartments shall share a common wall.

Does the bidder comply with this requirement? Yes___ No___

ROOF RADIUS

The roof radius shall be an extruded aluminum shape with an alloy and temper of 6061-T6 with an ultimate strength of 42,000 PSI.

The shape shall be a four inch radius with a built-in inner structural connector to form a one piece side and roof structure.

The roof radius shall incorporate a built-in drip molding to aid in the channeling of water.

Does the bidder comply with this requirement? Yes___ No___

ROOF CONSTRUCTION

The roof shall be constructed of 0.125" thick aluminum plate. The roof structure shall consist of 2" x 3" 6063-T5 aluminum tubing that shall span the full width of the body and have a bow effect to facilitate water runoff from the roof.

The roof tubes shall be welded to the roof and to the inner structural connector of the radius. The aluminum plate sheet roof shall be completely welded to the roof radii.

Does the bidder comply with this requirement? Yes___ No___

CORNER RADIUS

The corner radius shall be of the same heavy duty construction as the roof radius, except there shall be a built-in drip molding. The corner radius shall be a three inch radius.

All corners shall be a semi-hollow shape for structural strength and shall give a smooth exterior appearance without the need for bending or forming sheet metal.

Does the bidder comply with this requirement? Yes___ No___

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

SIDE STRUCTURE

The sides shall be constructed with four corner radii. The radii shall be a three inch arc shape with interlocking edges on both sides. The extrusions shall be of an alloy of 6061 with a heat treated temper of T6.

The corner and roof shall be designed to work as a system that has a double gusset connector in each corner joint.

The roof, corner and sides shall be welded so as no bolts or rivets are required or permitted.

The sides shall be of a lig-locked' style construction. The jig shall hold the corners and body side panels in place while an inner 6063-T5 structure is welded into place. The members shall be located 12 inches on center and welded to the roof rail and inner structure connector that shall be the roof members.

The exterior aluminum panels .125" shall interlock with the roof, corner and specially designed extruded aluminum compartment door frames and shall be constructed of a 6063-T5 material. The door frame extrusion shall be designed to match fit the exterior compartment doors. The frame shall be a full 1/4" thick to allow for taping for door hinges.

The door frame shall have an exterior trim edge that shall channel any water away from the compartment openings.

Does the bidder comply with this requirement? Yes____ No____

MOUNT MODULE DOWN

*Ten Point mount down system

- Bolted to chassis frame with (10) 5/8" -11 grade 8 bolts

Through OEM rubber insulating spacers installed on Outriggers at ten (10) separate locations.

This will provide noise insulation and easy removal for chassis replacement.

-Frame mounting bolts to be torqued and secured with Loctite.

Does the bidder comply with this requirement? Yes No ____

EXTERIOR COMPARTMENT VENTING

-A minimum of nine (9) square inches of venting shall be

Provided inside the exterior compartments doors to provide for easier closure of the compartment doors.

Does the bidder comply with this requirement? Yes No ____

OXYGEN COMPARTMENT DOOR VENTING

- There shall be a stamped louvered provided in the exterior "A" Oxygen Compartment to dissipate any leaking oxygen

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

gas.

Does the bidder comply with this requirement? Yes ___ No ___

EXTERIOR COMPARTMENTS -SWEEP-OUT DESIGN

- Exterior compartment floors, with the exception of the front ALS compartment shall be constructed to be flush with the bottom door frame.

Does the bidder comply with this requirement? Yes ___ No ___

SHELVING EXTERIOR COMPARTMENTS

- All Shelving to have a 2" lip all the way around
- All Shelving to be Scorpion Coated ILO Brushed Aluminum.

Does the bidder comply with this requirement? Yes ___ No ___

STREETSIDE COMPARTMENTS: (3)

"A" Exterior Compartment

Forward compartment Main 02 Compartment

Vent thru Door - machine stamped vent and ability to block dust entry into the department.

Single hinged door

- Interior of Compartment (22" Depth)
- One (1) Vertical Aluminum Divider

Does the bidder comply with this requirement? Yes ___ No ___

"B" Exterior Compartment forward of rear wheels.

Double hinged doors.

(1) Adjustable Shelf. Include the ability of the compartment to block dust.

Does the bidder comply with this requirement? Yes ___ No ___

"C" Exterior Compartment - FULL HEIGHT

- DIMENSIONS: 80" H X 40" W X 20" D

Rear compartment behind rear wheels.

- One (1) Aluminum Adjustable Shelf. With inside compartment having dust blocking means
- (2) Hinged double doors.

Does the bidder comply with this requirement? Yes ___ No ___

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

CURBSIDE COMPARTMENTS: (3)

"D" Exterior Compartment

Forward compartment of curbside entry door, ALS
Single hinged door.

(2) Adjustable Shelves, Aluminum Painted White

Inside/Outside Access *Must indicate anything different.

Does the bidder comply with this requirement?

Yes _____

No _____

"E" Exterior Battery Compartment.

- Battery Door to be a Drawer.

Slide out tray for (2) Batteries

Does the bidder comply with this requirement? Yes _____ No _____

"F" Exterior Compartment - Lower Special Compartment

Intermediate Compartment directly behind rear wheels

Double hinged door.

- 40" wide x 29" tall x 20" deep

- One (1) adjustable shelf

Does the bidder comply with this requirement? Yes _____ No _____

(G) COMPARTMENT - Upper Special Compartment

- DIMENSIONS: 48" H X 15" W X 20" D

- Upper compartment over (F) compartment at right rear of module
Compartment.

- Three (3) adjustable shelves

- Compartment shall have inside/outside access (solid door)

Does the bidder comply with this requirement? - Curbside patient door to have Cleveland Style Door hold
opener installed-DIMENSIONS: 78" high x 32" wide.

- Two (2) Red Flashing OS lights mounted on the inside face of doors.

Lights to activate upon opening of door

-Emergency door release handles to be installed at top and bottom of door

Does the bidder comply with this requirement? Yes _____ No _____

STEPWELL (SIDE DOOR)

- The curbside door step well shall be automatically lit when the side or rear doors are opened.

- The step-well shall be finished with highly polished aluminum diamond plate.

TYPE HIAMBULANCE SPECIFICATION

Peach County EMS

Single hinged door.

Does the bidder comply with this requirement? Yes ___ No ___

REAR, PASSAGE DOORS

- DIMENSIONS: 47.50" wide x 60" high
- The right rear passage door shall have a lockable chrome Exterior handle
- The hinge shall be full length stainless steel with 3/16" stainless Steel hinge pin and shall be two-way adjustable.
- Each rear door shall have a two point slam action automotive type rotary latching system to the Body
- The right rear door shall latch to the body at the top and bottom, Not to the left rear door.
- The doors shall have .213" steel door latch activator rods with Turn buckle adjusters.
- The doors shall be lockable from either inside or outside.
- Two (2) Red Flashing OS lights mounted on the inside face of doors. Lights to activate upon opening of door
- Emergency door release handles to be installed at top and bottom of door
- All doors shall shut on molded, air-core automotive type Door seals to prevent any water from leaking into the Vehicle interior
- Each door shall have an access port adjacent to the rotary locks.

HAZARDOUS WARNING/SAFETY TAPE ON THRESHOLD PER MASS OEM REQUIREMENTS

- Black/Yellow Hazardous Safety Tape to be applied ILOS Grip tape on threshold.

Does the bidder comply with this requirement? Yes ___ No ___

EXTRUDED COMPARTMENT DOORS -ALL MODULE DOORS

Does the bidder comply with this requirement? Yes ___ No ___

EXTERIOR COMPARTMENT DOORS IN ADP PANEL TO BE SCORPION SPRAYED (Gray) ILO Standard ADP.

Does the bidder comply with this requirement? Yes ___ No ___

DRIP RAIL -STAINLESS STEEL

- NOTE: Install Drip Rail on the top extrusion, in line with the upper edge.

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

NOT ON THE MODULE WALLS

Does the bidder comply with this requirement? Yes___ No___

INSULATION PKG - EXTREME WEATHER

- The entire ambulance body, sides, ends, and roof of the patient's Compartment shall be insulated to meet or enhance the Environmental criteria specified in Federal Specifications KKK-A-1822F.
- Insulation shall have a minimum "R" factor of eleven (11).
- There shall be Poly Fiber insulation in the sidewalls, floor and roof. The doors shall be insulated with at least 1.875" of Poly Fiber
- NOTE: This insulation shall not interfere with the working of the door latching hardware.

Does the bidder comply with this requirement? Yes___ No___

PATIENT COMPARTMENT SOUND LEVEL

- Sound levels within the patient compartment shall not exceed Eighty (80) decibels in accordance with AMD Standard 006.

Does the bidder comply with this requirement? Yes___ No___

PATIENT COMPARTMENT CARBON MONOXIDE LEVEL

- The ambulance modular body shall be constructed in such a manner as to provide a safe environment for patients and crew as pertains to the presence of carbon monoxide (CO).
- A CO level of not more than ten (10) PPM shall be attained in accordance with AMD Standard 007.

Does the bidder comply with this requirement? Yes___ No___

MUD FLAPS- DRW - NO LOGO

- Heavy duty, anti-sail style mud flaps, at least as wide as the rear tires, shall be provided per SAE J682 behind the rear wheels and shall be reinforced at the point of attachment to the vehicle.

Does the bidder comply with this requirement? Yes___ No___

REAR STEP: ALUMINUM FLIP UP

- *Center to be hinged and flip up. Also grip strut
- The rear bumper shall be affixed to the chassis frame.
- Bumper to be constructed with a hinged center section of aluminum grip strut material.
- Outer pods to be covered with .125" thick aluminum diamond plate.
- Rear Frame of Bumper to be Scorpion Coated

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Does the bidder comply with this requirement? Yes ___ No ___

WINDOW REAR ENTRY: FIXED-DARK TINT

- There shall be two (2) fixed rear passage door windows installed on the two rear doors. Size to be 19" x 18

Does the bidder comply with this requirement? Yes ___ No ___

CURBSIDE ENTRY DOOR: "FIXED"-DARK TINT

- The curbside passenger door shall have a 19" x 18" window.

Does the bidder comply with this requirement? Yes ___ No ___

RUB RAIL 'C' CHANNEL 3 INCH POLISHED ALUMINUM WITH RED / WHITE REFLECTIVE IN THE MIDDLE.

- Bright dip anodized aluminum "C" Channel (rub-rails) shall be installed on the lower sides of the body below outside compartment sill areas.
- The rub rails shall be offset 3/16" from the body to facilitate wash down of road debris and the rub rail incorporate two (2) Reflective Striping Scotchlite safety accent stripes.
- Reflective stripe to be RED/WHITE ILOS

Does the bidder comply with this requirement? Yes ___ No ___

FRONT STONE GUARDS, MODULE FRONT - ADP

- Aluminum diamond plate stone guards will be installed on the lower 24" of the module front. These stone guards shall be 14" Wide and silicone sealed at the top.
- SPECIAL: ALL DIAMOND PLATE TO BE RIVETED ILO SCREWED.

Does the bidder comply with this requirement? Yes ___ No ___

STAINLESS STEEL THRESHOLDS, REAR DOORWAY KICKPLATE

- Aluminum diamond plate rear kick plate shall be installed at the rear lower door area, providing a kick / scuff plate at the rear of the vehicle above the rear step.
- SPECIAL: ALL DIAMOND PLATE TO BE RIVETED ILO SCREWED.

Does the bidder comply with this requirement? Yes ___ No ___

FENDERETTES: POLISHED ALUMINUM

- Bright Finish polished aluminum fenderettes will be installed around the rear wheel well openings.

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Does the bidder comply with this requirement? Yes ____ No ____

(2) CAST GRABBERS REAR DOORS

- The Cast Grabbers will be located on the rear of the module to hold the rear doors in the open position.

Does the bidder comply with this requirement? Yes ____ No ____

SPLASH FILL GUARD: POLISHED ALUMINUM

- Both Fuel Fill and Urea Area's

Does the bidder comply with this requirement? Yes ____ No ____

EXTERIOR DOOR HANDLES: "EASY GRABBER" EBERHARD

- Series 2100

Does the bidder comply with this requirement? Yes ____ No ____

SCORPION LINER EXTERIOR COMPARTMENTS

Includes: Vertical Dividers, and Adjustable Shelving

- SPECIAL: EXTERIOR COMPARTMENTS INNER DOOR PANELS TO BE SPRAYED ALSO. No diamond plate in the exterior compartments.

- Color: Gray

Does the bidder comply with this requirement? Yes ____ No ____

SECTION - 3.0

PATIENT COMPARTMENT / INTERIOR

INTERIOR SURFACES

- The interior of the patient compartment shall be free of all sharp projections. Exposed edges and corners shall be broken with a radius or chamfer. All hinges or supports for equipment and devices shall be mounted as flush as possible with the surrounding surface when not in use.

- Padding shall be placed at all head area obstructions, which may prove dangerous to persons moving about in the patient compartment.

- The finish of the entire patient compartment, including storage cabinets and equipment shall be impervious to soap and water, disinfectants, mildew and shall be fire resistant as per FMVSS 302.

- The color of the interior shall be chosen by this Agency from samples provided by the successful bidder.

Does the bidder comply with this requirement? Yes ____ No ____

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

SOFT EDGE TRIM SYSTEM

- Antimicrobial Integral Skin System which gives it superior infection prevention.
- Antimicrobial Surface -Kills or inhibits the growth of microorganisms, such as bacteria, fungi, or protozoans.
- Soft Edge Trim System offers:
 - * Protects attendant from sharp edges and corners
 - * Antimicrobial outer surface
 - * Durable I-Skin foam Construction
 - * Latex, PVC and BPA Free
- Meets FMVSS 302, MVSS203, Cal 117, FAR25.853a(ii)
- Color Choices: Cobalt, Desert Rose, Ash, Gun Metal.

Does the bidder comply with this requirement? Yes _____ No _____

CABINETS (14') MODULE 3/4 INCH MAPLE PLYWOOD

Does the bidder comply with this requirement? Yes _____ No _____

INTERIOR CABINET SHELVES: PAINTED ALUMINUM

Does the bidder comply with this requirement? Yes _____ No _____

CEILING GRAB RAIL: (2) 72" STAINLESS STEEL

One on each side of the A/C Duct

ALS CABINET LAYOUT

*Upper: (2) Plexiglas Insert Doors with Southco non locking latches.

Dimensions: 16" High x 33.50" Wide x 23.75" Depth (ID)

Note - Close Upper section for inside access only.

*Center Section: 12" inch sliding drug drawer with Southco locking latch.

Dimensions: 12" High x 33.50" Wide x 23.75" Depth (ID)

*Lower: (2) Plexiglas Insert Doors with Southco locking latches,

Dimensions: 22" High x 33.50" Wide x 23.75" Depth (ID)

Inside/Outside Access lower area only.

Does the bidder comply with this requirement? Yes _____ No _____

STREET SIDE - CABINET LAYOUT

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

'A 1' Cabinet above the forward action area.

- (1) Aluminum Painted Adjustable Shelf
- NOTE: Shelving to have Rubber matting installed - BLACK
- Sliding Plexiglas doors with center tab hole for inventory lock
- Clear Plexiglas

Does the bidder comply with this requirement? Yes No

'A2' Cabinet rearward of 'A1'

- (1) Aluminum Painted Adjustable Shelf
- NOTE: Shelving to have Rubber matting installed - BLACK
- Sliding Plexiglas doors with center tab hole for inventory lock
- Clear Plexiglas

Does the bidder comply with this requirement? Yes No

CPR seat with Flip up bottom couching and storage underneath the CPR seat Back rest to be hard mounted.

The back of the seat is to flip down and create a countertop the Counter top shall be sterion hard surface material.

Does the bidder comply with this requirement? Yes No

'B3' Roll out drawer in area just aft of 'A3' drawer the roll out drawer to have divider for IV storage 3 compartments.

Does the bidder comply with this requirement? Yes No

'131' Cabinet above Second Action Area Countertop.

- (1) Aluminum Painted Adjustable Shelf
- NOTE: Shelving to have Rubber matting installed - BLACK
- Sliding Plexiglas doors with center tab hole for inventory lock
- Clear Plexiglas

Does the bidder comply with this requirement? Yes No

'B3' Cabinet below 2nd Action Area Countertop.

TYPE HIAMBULANCE SPECIFICATION

Peach County EMS

- (1) Aluminum Painted Adjustable Shelf
- NOTE: Shelving to have Rubber matting installed - BLACK
- Sliding Plexiglas doors with center tab hole for inventory lock
- Clear Plexiglas

Does the bidder comply with this requirement? Yes ___ No ___

'C2' Cabinet Center Rear Street side

- (1) Aluminum Painted Adjustable Shelf
- (1) Aluminum Painted Adjustable Shelf
- Sliding Plexiglas doors with center tab hole for inventory lock
- Clear Plexiglas

Does the bidder comply with this requirement? Yes ___ No ___

CURBSIDE CABINET OVER SQUAD - CABINET LAYOUT

- (2) Cabinets above squad bench.
- 10.25" High x 31.00" Wide x 8.00" Depth (ID)
- Sliding Plexiglas doors with center tab hole for inventory lock
- Clear Plexiglas

Does the bidder comply with this requirement? Yes ___ No ___

SQUAD BENCH WITH STORAGE UNDERNEATH

- Full width cushions
- (2) Gas Struts to hold open, Bolted on.
- (3) Seatbelt positions separate back rests with 3 point harness setup to secure medics

Does the bidder comply with this requirement? Yes ___ No ___

SHARPS/WASTE HEAD OF SQUAD BENCH

Note: Compartment to be flip up compartment install a locking/Keyed Different latch to eliminate access.

Sharps to the front and Trash to the rear, different Plexiglas lid color. Red for Sharps and Black for trash.

Does the bidder comply with this requirement? Yes ___ No ___

SAFETY NETTING- HEAD OF SQUAD BENCH

Note: Intertek Model ZRS-NET130-29 (mod) -Angle —Black

Does the bidder comply with this requirement? Yes ___ No ___

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

GLOVE BOX COMPT OVER CURBSIDE ENTRY DOOR

Note: 3/8 inch LEXAN with Southco latch (no Velcro)

Does the bidder comply with this requirement? Yes___ No___

CEILING HEADLINER

- The headliner shall have an access panel full length to facilitate repairs and maintenance of the main electrical wiring loom in the patient compartment and be of non-permeable material.

-The ceiling will be finished with 1/8" Luan backed glossy white commercial grade plastic laminate panels. Any seams shall be trimmed to prevent sagging and provide a clean attractive appearance. The ceiling panel shall be mechanically attached to the roof structure but all fasteners shall be hidden.

- Headliners with padded vinyl or un-backed fiberglass materials will not be acceptable due to their potential for contamination, tears, cracking and sapling, thus involving costly repairs.

- Along the longitudinal center of the ceiling, a padded cover shall be installed to close-off the electrical wiring chase. It must be covered with vinyl to match the upholstery.

Does the bidder comply with this requirement? Yes___ No___

FORMICA COLOR: "GLOSSY GRAY / WHITE"

Does the bidder comply with this requirement? Yes___ No___

STARON COUNTERTOPS or Equivalent: (2) SOLID SURFACE (EBONY GRAY)

Note: Forward Action Area and 2nd Action Area

Does the bidder comply with this requirement? Yes___ No___

DRY ERASE MARKER BOARD, SQUAD BENCH, ACTION AREA WALL

Does the bidder comply with this requirement? Yes___ No___

02 VIEWING WINDOW LOCATION FRONT STREETSIDE

- View window to be flat surface instead of wrap around.

Does the bidder comply with this requirement? Yes___ No___

INTERIOR UPHOLSTERY: BLUE VACUUM FORMED

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Does the bidder comply with this requirement? Yes___ No___

FLOOR

-The sub floor of the module shall be .063" 5052-H32 alloy rated aluminum securely welded to the wall structures and exterior compartment and completely sealed from the outside element minimum

- Over the aluminum sub-floor there shall be a COOSA COMPOSITE SUB FLOORING ILO WOOD

Does the bidder comply with this requirement? Yes___ No___

- This agency is concerned with ambulances built utilizing plywood in the interior flooring, so for that reason the purchasing agency is requesting that all bidders provide the following type of flooring material. Due to the industries standard plywood and the fact that this agency may elect to remount the modular body as some time in the future, it is our concern that plywood flooring has the tendencies of rotting and mildew thus we have elected to go with the following floor composite material. This material is readily available to all ambulance manufacturers. NO EXCEPTION

- The sub flooring shall be Coosa Composite "Bluewater Series 26" boards that consist of polyurethane foam filled throughout with layers of continuous strand glass and woven roving fiberglass.

Does the bidder comply with this requirement? Yes___ No___

- The flooring density shall be 26 lbs pcf. - (ASTM C271).

- BENEFITS:

- * 30% to 40% lighter than plywood
- * NO water rot or insect infestation
- * Less than 1% water absorption
- * Dimensionally stable.
- * Mold, mildew and algae resistant.

- Bidder's must provide third party laboratory testing for equal to the proposed sub-floor material, set forth by the National Highway Traffic Safety Administration. In addition the composite material must meet the guidelines set forth by the SAE standard J369a. NO EXCEPTIONS.

Does the bidder comply with this requirement? Yes___ No___

FLOORING: LONPLATE II - GRAY- ROLLED 3"

Color: Standard is Gray Lonplate II

-There shall be provided a heavy duty commercial grade vinyl floor covering the interior patient compartment. The floor covering shall be Lonseal II heavy-duty safety vinyl. The floor covering shall be constructed of multiple layers composed of polyvinyl chloride (PVC) resin, plasticizers, fillers and pigments. The co-calendar war layer shall be formulated to provide maximum resistance to foot traffic

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

and most commercial and healthcare chemical. The middle layer shall provide dimensional stability, sound-absorbing properties and resiliency under foot.

- The floor shall be heavy duty insulated and sound proofing. The flooring shall extend the full length and width of the patient compartment consisting of a minimum of 1/2 inch composite exterior grade. The flooring shall be covered with a no wax commercial heavy duty vinyl covering diamond shape Lon plate or similar product (Gunpowder Gray #424TX). The framing system and framing welding techniques shall be in accordance with manufacturer's specifications. Aluminum sub floor shall be 1/8 inch between the frame and composite floor shall be installed. The vinyl flooring is to be extended up the sidewall a minimum of three inches (3").

-Flooring shall meet or exceed all ASTM and / or NFPA Standards as pertains to friction, flame spread, smoke density, abrasion resistance, flexibility and chemical resistance.

-The sub flooring shall be made of 3/4 " COOSA Composite.

Does the bidder comply with this requirement? Yes ___ No ___

INTERIOR DOOR PANELS

*Upper - Matching Vinyl

*Center - Matching Formica on a slide

*Lower: Smooth Aluminum Plate covered in Reflective Chevron - Color - Red/Yellow. TBD

HANDICAP ENTRY DOOR HANDLES "V" STYLE - SAFETY YELLOW

Both curbside and rear two entry doors.

Does the bidder comply with this requirement? Yes ___ No ___

WISE ATTENDANT SEAT W/ CHILD INTEGRATED SAFETY

Note: Mount on SWIVEL BASE with underneath storage.

Does the bidder comply with this requirement? Yes ___ No ___

SECTION 4.0

COT EQUIPMENT / MOUNTS

COT FASTENER SYSTEM - 'STRYKER' Powerload system.

(* Drop ship from Stryker with installation performed by ambulance builder)

NOTE- POSITION - Center mount.

Does the bidder comply with this requirement? Yes ___ No ___

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

INSTALL SAFETY HOOK if Powerload system is not approved by purchasing agency.

Does the bidder comply with this requirement? Yes ___ No ___

SECTION - 5.0 MEDICAL EQUIPMENT / COMPONENTS

TWO (2) IV HANGERS RECESSED

Does the bidder comply with this requirement? Yes ___ No ___

RICO SUCTION / SUCTION ASPIRATOR

-The ambulance shall be equipped with an on board vacuum aspirator. The unit shall be mounted on the action area wall above the action area tray to collect any bio fluids that may be spilled. The unit shall be impact resistant with an auto clavicle collection jar. The discharge side of the of the vacuum pump shall be vented to the outside of the vehicle through sealed tubing. The clear formed collection jar shall have a dual sealing lid assembly. The removable lid shall incorporate a variable position adjustment valve and gauge calibrated in mm/hgs. The vacuum pump shall be installed via a twelve volt direct current system. The on/off switch shall be located in the attendant's console.

- The Performance of the Aspirator System shall provide a free airflow of at least 30 lpm and achieve a minimum of 300 mm (11.8") Hg vacuum within four seconds after the suction tube is close.

Does the bidder comply with this requirement? Yes ___ No ___

THOMAS VACUUM PUMP OR *EQUIVALENT*

- Model # 107CD020

-The vacuum pump shall be installed via a twelve volt direct current system. The on/off switch shall be located in the attendant's console.

- Vacuum Pump shall show the level of vacuum with a diameter of 3" (+/- 0.5") with numerical markers at least every 100mm Hg and a total of range of 0-760 MM Hg.

Does the bidder comply with this requirement? Yes ___ No ___

ONE (1) VACUUM OUTLET

Does the bidder comply with this requirement? Yes ___ No ___

Note: Bracket for "M" Cylinder set up.

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Location: Front "A" Exterior Compartment

Does the bidder comply with this requirement? Yes ____ No ____

02 WRENCH MOUNTED

Note: Mount on the rear wall of Ext. Compartment "A" with tethered line.

Does the bidder comply with this requirement? Yes ____ No ____

THREE (3) OXYGEN OUTLETS (LOCATION TBD)

Location: One (1) Action Area wall forward.

One (1) Action area rear

One (1) Squad bench forward

Does the bidder comply with this requirement? Yes ____ No ____

SECTION - 7.0

ENVIRONMENTAL SYSTEM / COMPONENTS

AC/HEAT: HOSELINE "DUCTED" SYSTEM 12VDC

Location: Mount over walk through at center of patent compartment

- Auxiliary AC Condenser (standard)

- Digital Thermostat (standard)

-NC ducting shall run through the center of patent compartment

-There shall be six (6) adjustable vents three each side

- Patient compartment heater 12V shoreline activated in Squad bench area forward

Does the bidder comply with this requirement? Yes ____ No ____

EXHAUST FAN/ VENT

Does the bidder comply with this requirement? Yes ____ No ____

SECTION - 8.0

ELECTRICAL COMPONENTS

12V ELECTRICAL SYSTEM- ELECTRICAL CABINET ABOVE WALK THRU- STANDARD

- The emergency medical vehicle's electrical system must meet most current KKK-A-1822F.

Does the bidder comply with this requirement? Yes ____ No ____

ELECTRICAL SYSTEM

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

- The following medical vehicle's electrical system shall be equipped with, but not limited: dual 12 volt batteries, ignition, starting, generating, lighting, visual and audible warning systems; specified electronics equipment and devices to include control consoles located in the cab and patient compartment and other specified accessory wiring.

- The electrical system and equipment shall comply with all applicable FMVSS including Federal Motor Carrier Safety Regulations (FMCSR), and shall conform to all the applicable SAE recommended standards and practices whether or not specifically referenced in this document.

- Additionally, the electrical system shall meet the requirements of AMD Standard 005.

- All electrical and electronic components shall be selected to minimize electrical load and levels of heat generated by those electrical components thereby not exceeding the vehicle's generating system capacity or diminish its ability to provide the required levels of electrical power.

- Electrical system utilizing switching of "hot load" circuits for emergency and warning lights shall not be accepted by the purchasing agency.

- All electrical systems components and wiring shall be readily accessible through access panels for checking and maintenance.

- The cab and patient compartment consoles shall also be constructed in such a way that the switches and gauges are easily serviced. These panels will be secured in the closed position in a positive manner, yet can be easily opened for servicing.

Does the bidder comply with this requirement? Yes ____ No ____

WIRING INSTALLATION

- The ambulance body and accessory electrical equipment shall be served by circuit(s) separate and distinct from the vehicle chassis circuits.

- All wiring provided by the ambulance manufacturer shall be copper and conform to all the SAE J1292 requirements and shall have type GXL "cross linked" high temperature polyethylene or better insulation rated to 300 degrees Fahrenheit and conforming to SAE J1127 and J1128.

- Insulation on the low-voltage computer type control cables shall have a minimum temperature rating of 80 degrees centigrade.

- Wiring shall be permanently color coded to identify wires. Wires shall be permanently heat ink embossed with both number and function codes. The function codes shall be the "descriptive" name of the circuit served. The number code shall be the exact purpose of that circuit.

WIRING LOOM

- There shall be engine wiring routed in conduit or high temperature looms with a rating of 300 degrees Fahrenheit.

- All added wiring shall be in a protective loom, located in accessible, enclosed and protected locations, and kept at least six inches (6") away from the exhaust system components.

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

- There shall be no electrical wiring or components that will terminate in the oxygen storage compartment except for the compartment light and door switch.
- All apertures on the vehicle will have properly installed grommets for passing wiring and conform to SAE 1292.
- All items used for protecting or securing the wiring shall be appropriate for the specific application and be standard automotive, aircraft, marine or electronic hardware.
- All wiring devices, switches, outlets, etc., except circuit breakers shall be rated to carry at least 125% of the maximum ampere load for which the circuit is protected.
- There shall be a master electrical component panel located in the ambulance.
- It will be located on or near the bulkhead of the patient compartment, unless otherwise noted.

Does the bidder comply with this requirement? Yes ___ No ___

CIRCUIT CONNECTIONS

- Circuit connection shall be made on high current terminal block; brass bolts, or approved electronic connectors. Connection components selected to minimize heat generation under circuit load. All terminals shall fasten directly to the terminal block or be machine crimped to plastic enclosed spade terminals or open ring connections.
- The use of "Scotch-Lock" fasteners will not be acceptable.
- To insure minimal voltage drop and secure connections, NO splices shall be allowed in the wiring harness.
- Standard circuit breakers, relays, and diodes shall be mounted on a printed circuit panel and shall be easily accessible through a door.
- All components on the circuit boards shall be permanently labeled as to their function.
- No splices shall be permitted except for connection of "OEM" pigtail-type" devices. All connectors shall be UL approved. The uses of "Scotch-Locks" type fasteners are NOT ACCEPTABLE.

Does the bidder comply with this requirement? Yes ___ No ___

ELECTRICAL LOAD WARNING

- The electrical warning lights shall not go beyond those required by this specifications. Additional lighting will utilize reserve alternator capacity and could result in overloaded electrical systems, which may result in electrical system failure and cause the ambulance to fail in the field.

Does the bidder comply with this requirement? Yes ___ No ___

BATTERY SYSTEM

- The vehicle shall be supplied with a dual OEM 12-Volt battery system.

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

- The Batteries will have a combined minimum cold cranking ampere capacity of 1500 CCA.
- Both batteries shall be located in a separate compartment, mounted on a slide out tray located below the ALS Cabinet in the lower right front corner of the module.

Does the bidder comply with this requirement? Yes ___ No ___

ENGINE HIGH-IDLE SPEED CONTROL, AUTOMATIC

- The vehicle shall be equipped with an engine high idle control.
- The device shall operate only when the transmission is in "Neutral" or "Park", and the parking brake has been engaged.
- The device shall disengage when the operator depresses the service brake pedal, the transmission is placed in gear, or parking brake is disengaged and automatically re-engage when the service brake is released, when the transmission is placed in neutral or park, and the parking brake is re-engaged.

Does the bidder comply with this requirement? Yes ___ No ___

EXTERIOR LAMPS

- All exterior lamps, electrical devices and fixtures shall be corrosion resistant and weatherproofed. Electrical fixtures attached to the sides of the ambulance below the 75" level shall be near flush mounted, not to protrude more than two (2) inches.

Does the bidder comply with this requirement? Yes ___ No ___

RADIO INTERFERENCE PROTECTION

- All electronic devices and equipment installed in this ambulance will have proper, filters, suppressor or shielding to contain electromagnetic radiation and prevent radio frequency interference (RFI).

ICC MARKER LIGHTS-LED (Minimum)

- (7) Front Amber LED
- (7) Rear Red LED

Does the bidder comply with this requirement? Yes ___ No ___

COMPARTMENT LIGHT- SIX (8) LED STRIP LIGHT

- Location: (1) Ext. compartment "A", (1) Ext. Compartment "B",
(1) Ext. compartment "C", (1) Ext. Compartment "D"
(1) Ext. Compartment "F", (1) Ext. Compartment "G"

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Does the bidder comply with this requirement? Yes ___ No ___

SHORELINE: 20 AMP AUTO EJECT

Location: Mount shoreline plug at right rear wall of module

Does the bidder comply with this requirement? Yes ___ No ___

FRONT CONSOLE- SCORPION COATED GRAY

- Front console shall be scorpion coated to match upholstery.
- The control console shall not be integrated into the OEM Dash, but will be mounted between the driver and passenger seat in the cab.
- Console to accommodate two (2) Cup Holders, Map Book Slot and switch panel, siren and radio's.

Does the bidder comply with this requirement? Yes ___ No ___

FRONT CONTROL SWITCH PANEL

- The Front Console Switch Panel shall incorporate low-voltage full size easy-to-use rocker switches.
- The switches are for ambulance equipment operation, including, but not limited to the following, siren, all warning and emergency lights, battery indicator light, horn/siren cut-off switch, side and rear flood lights, compartment and entry door ajar warning light, patient compartment master switch, and Emergency lights master switch.

Does the bidder comply with this requirement? Yes ___ No ___

SPOTLIGHT: HANDHELD

*Hardwired spotlight to electrical system

Does the bidder comply with this requirement? Yes ___ No ___

INTERIOR LIGHTS: EIGHT (8) HI/LOW LED DOME LIGHTS

- Note: Incandescent Lights
- (4) Street side Ceiling area
 - (4) Curbside Ceiling area.

TYPE HIAMBULANCE SPECIFICATION

Peach County EMS

Does the bidder comply with this requirement? Yes___ No___

15 MINUTE TIMER/CHECKOUT

Location: Mount on squad bench wall.

Wire curbside dome lights (4) to timer switch in low intensity.

Does the bidder comply with this requirement? Yes___ No___

PRE-WIRE FOR INVERTER

INVERTER, DIMENSION UNLIMITED 1000 WATT

- Automatic transfer switch to prevent power interruptions. 50 amp battery conditioner

Does the bidder comply with this requirement? Yes___ No___

CLOCK: INTELITEC DIGITAL

Location: Action Area wall.

Does the bidder comply with this requirement? Yes___ No___

BATTERY CUTOFF SWITCH RECESSED

- There shall be a 12 volt battery switch located in a recessed housing on the front console. The switch will disengage the batteries or engaged them.

Does the bidder comply with this requirement? Yes___ No___

EMERGENCY LIGHTS MASTER SWITCH

- The emergency lights "master" switch shall be padded type switch having a translucent label with a RED "on" indicator.

- The remainder of the function switches shall be low voltage switches.

- These switches shall be connected to the electronic control module through a computer cable.

- All switches labels shall be back lighted, permanently identifying it as to function and have an L.E.D. indicator to show that.

Does the bidder comply with this requirement? Yes___ No___

BACK-LIGHTING

TYPE HI AMBULANCE SPECIFICATION

Peach County EMS

- Back lighting for the front console switch panel shall turn on with the headlights and be controlled by the headlight switch rheostat function.

Does the bidder comply with this requirement? Yes ___ No ___

MODULE DISCONNECT SWITCH

- There shall be a module disconnect switch located on the front console switch panel and shall disconnect all patient compartment conversion circuits.

- The switch shall be connected to the electronic control module through a computer cable.

- The switch label shall be back lighted, permanently identifying it as to function and have an L.E.D. indicator to show that function is activated.

Does the bidder comply with this requirement? Yes ___ No ___

TWO (2) 12V OUTLETS

Location: (1) Action Area

(2) TBD for radio usage etc

Does the bidder comply with this requirement? Yes ___ No ___

Three (3) 110V GFI DUPLEX OUTLETS LIGHTED

Location: (2) Action Area

(1) In ALS Compartment

(1) Captain chair area front side

(1) Left action area

(1) Monitor area left rear

Does the bidder comply with this requirement? Yes ___ No ___

TWO (2) LED LIGHT-ACTION AREAS

Does the bidder comply with this requirement? Yes ___ No ___

RECESSED LICENSE TAG W/LED LIGHT

Does the bidder comply with this requirement? Yes ___ No ___

BACK UP ALARM

- An (OSHA approved) back up alarm shall be installed with disable switch for silent backing.

- The disable switch shall be located on the front console.

- The backup alarm system shall automatically reset to the "on" mode when the transmission is taken out of reverse.

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

Does the bidder comply with this requirement? Yes___ No___

STEPWELL LIGHT LED

Note: To come on with either curbside entry or rear doors are opened.

Does the bidder comply with this requirement? Yes___ No___

SECTION - 9.0 EMERGENCY LIGHTING PACKAGE

SPECIAL- Please indicate Lens colors as (CLEAR)

Does the bidder comply with this requirement? Yes___ No___

(5) 900 SERIES SUPER LED W/CHROME FLANGES- *
RLED/CLED/RLED/CLED/RLED/CLED/RLED*
Bulkhead with Clear Lens

Does the bidder comply with this requirement? Yes___ No___

GRILLE LIGHTS: WHELEN IONS SERIES RED LED W/BEZELS

- Four (4) lights stagger Red/Clear
- Whelen # WIONSMCR & @WIONSMCW

Does the bidder comply with this requirement? Yes___ No___

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

INTERSECTORS: WHELEN 700 SERIES RED/CLEAR LED W/BEZELS
- Whelen # 7ORC6FCR

Does the bidder comply with this requirement? Yes ___ No ___

BRAKE/TURN ARROW/BACK UP: WHELEN 600 SERIES LED
Note: Whelen w/individual chrome housings

Does the bidder comply with this requirement? Yes ___ No ___

FOUR (4) WHELEN 900 SERIES RED LED W/CHROME FLANGES- (2) ON EACH SIDE OF MODULE

Does the bidder comply with this requirement? Yes ___ No ___

WIG-WAG Headlights

Does the bidder comply with this requirement? Yes ___ No ___

TWO (2) REAR OUTER 900 SERIES RED LED W/FLANGE
- NOTE: Wire to Brake Flasher and cancel in Emergency Operation.

Does the bidder comply with this requirement? Yes ___ No ___

ONE (1) CENTER REAR 900 SERIES AMBER LED W/FLANGE

Does the bidder comply with this requirement? Yes ___ No ___

TWO (2) REAR THRU WINDOW WHELEN 900 SERIES RED LED W/FLANGES

Does the bidder comply with this requirement? Yes ___ No ___

SCENE LIGHTS: SIX (6) 900 SERIES Halogen CLEAR SCENELIGHT W/FLANGES
Location: (2) per side of module

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

(2) on Rear tied into reverse

Does the bidder comply with this requirement? Yes ___ No ___

SECTION - 10.0 COMMUNICATION / COMPONENTS

TWO (2) ANTENNA COAX

Location: (front cab/ front top of patient compartment box)

Does the bidder comply with this requirement? Yes ___ No ___

PRE-WIRE 12V RADIO (2)

Does the bidder comply with this requirement? Yes ___ No ___

SIREN: WHELEN 295SLSA7

- 200 Watt Self Contained.

- Full Function Hands-Free siren plus radio repeat and public address. Operates up to two 100 watt speakers. 17-Scan-Lock Siren Tones. Self-contained unit.

Does the bidder comply with this requirement? Yes ___ No ___

SECTION - 11.0 LETTERING, STRIPING/DECALS

MODULE PAINT: White

Does the bidder comply with this requirement? Yes ___ No ___

LETTERING: ALLOWANCE or Wrap around Back side rear to rear of compartment

Does the bidder comply with this requirement? Yes ___ No ___

MAIN STRIPE: ALLOWANCE

Note:

Color- Reflective:

Does the bidder comply with this requirement? Yes ___ No ___

TYPE III AMBULANCE SPECIFICATION

Peach County EMS

PIN STRIPING: TBD

Note: Size:

Color:

Does the bidder comply with this requirement? Yes ___ No ___

UNDERCOATING

Does the bidder comply with this requirement? Yes ___ No ___

SOL DECALS

Standard: Reflective Blue with White Reflective Boarder.

- NOTE: Install 32" Star of Life on Roof

Does the bidder comply with this requirement? Yes___ No___

SECTION - 12.00 MISCELLANEOUS

FIRE EXTINGUISHER 5#

Note: Shipped Loose

(1) 20 LBS ABC DRYCHEM FIRE EXTINGUISHER

Fire extinguisher to be mounted in exterior compartment passenger side rear

Does the bidder comply with this requirement? Yes___ No___

WARRANTY

There shall be provided a manufacturer's warranty for the ambulance vehicle conversion, which coverage shall, at a minimum include:

A. A Limited Warranty on the ambulance conversions: Forty-eight (48) months or 48,000 miles from date of original purchase.

A. Paint: Seven (7) years from date of original purchase

Does the bidder comply with this requirement? Yes___ No___

B. Electrical: Six (6) years or 72,000 miles from date of original purchase.

TYPE III AMBULANCE SPECIFICATION
Peach County EMS

Does the bidder comply with this requirement? Yes ____ No ____

C. Modular Body Structural Integrity: Lifetime from date of original purchase.

Does the bidder comply with this requirement? Yes ____ No ____

E. Chassis: Warranty on the chassis portion of the completed ambulance shall be the responsibility of the chassis manufacturer.

Does the bidder comply with this requirement? Yes ____ No ____

BOARD OF COMMISSIONERS
Meetings Second Tuesday

MARTIN H. MOSELEY, JR.
Chairman

WALTER SMITH
Vice-Chairman

BETTY C. HILL

ROY LEWIS

WADE YODER

MARCIA W. JOHNSON
County Administrator

Peach County

213 Persons Street,
Fort Valley, Georgia 31030
Phone 478-825-2535
Fax 478-825-2678
www.peachcounty.net

COUNTY OFFICIALS

KIM WILSON
Probate Judge

JOE WILDER
Clerk of Superior Court

TERRY DEESE
Sheriff

W. L. BROWN
Tax Commissioner

KERRY ROOKS
Coroner

LAURENS C. LEE
Magistrate

Greetings Prospective Vendor,

Georgia law has made it mandatory that all private employers enroll in and use the federal E-Verify system, not only for public contractors (including subcontractors and sub-subcontractors) providing labor to public projects, but also those companies providing services of any kind over \$2,499.99 in value, regardless of the number of employees a contractor has. This expands the E-Verify requirement to lots of small businesses that have contracts to perform labor or services with our county. A contractor or subcontractor may be exempt from this requirement if the contractor or sub-contractor has NO employees and does not hire nor intend to hire employees for the purpose of completing any part of the public contract.

E-Verify is a federal database that can be used to verify that an employee is authorized to work in the United States. The SAVE (Systematic Alien Verification for Entitlements Affidavit) program determines the immigration status of any person that receives a public benefit. The State of Georgia has determined that a public benefit is any contract, business license, occupational tax certificate, alcohol license, taxi permit, pawnbroker's license, billiard room license, precious metals/gems dealer's license, flea market license or insurance company license.

In keeping with compliance, we ask that you provide the following forms to do business with our agency:

- New Vendor Information sheet (ALL CONTRACTORS MUST SUBMIT THIS FORM)
- Form W-9 (Taxpayer Identification Number) (ALL CONTRACTORS MUST SUBMIT THIS FORM)
- E-Verify Affidavit (ANY CONTRACTOR PROVIDING GOODS AND LABOR/SERVICE)
- SAVE Affidavit (ANY CONTRACTOR RECEIVING PUBLIC BENEFIT OR THAT PROVIDES GOODS)
- Subcontractor Affidavit (ANY SUBCONTRACTOR PROVIDING GOODS AND LABOR/SERVICES)
- Certificate of Liability Insurance (ANY CONTRACTOR WHO DOES WORK ON OUR PROPERTY)
 - o *Minimum Liability Insurance: \$2,000,000 aggregate, \$1,000,000 per occurrence*
 - o *Minimum Automobile Liability Insurance: \$2,000,000 aggregate, \$1,000,000 per occurrence*
 - o *Minimum Workers Compensation Insurance: \$500,000*
- Sole Proprietor Contractor Affidavit (ONLY USE IF YOU HAVE NO EMPLOYEES)
- Photo Identification (PROVIDE ONLY IF A SOLE PROPRIETOR. SEE ATTACHED LIST OF ACCEPTABLE DOCUMENTS)
- PRIVATE EMPLOYER EXEMPTION (USE ONLY IF SOLE PROPRIETOR)

Please note that some of the forms require notarization and will be considered incomplete and not processed. You may return the forms properly completed by fax, e-mail, US Postal Service or drop it off at our office: Peach County Board of Commissioners, Purchasing Department, 213 Persons Street, Fort Valley, GA 31030. If you need to register for the E-Verify program, go to www.uscis.gov and follow the instructions. If you have any questions about E-Verify or any of these forms, please call the office.

Sincerely,

Peach County Accounting Department

NEW VENDOR INFORMATION

COMPANY NAME: _____

CONTACT PERSON: _____ TITLE: _____

BUSINESS ADDRESS: _____

PHONE: _____ FAX: _____

EMAIL: _____

TYPE OF BUSINESS: (CIRCLE ONE) CORPORATION PARTNERSHIP SOLE PROPRIETOR

Have you done business with Peach County in the past? (circle one) YES NO

Do you participate in the E-Verify Program? (circle one) YES NO

Do you have a Federal Tax ID number? (circle one) YES NO

The information contained in this document is true to the best of my knowledge and I understand that giving false, misleading or deceptive information is considered unlawful and may be punishable by penalties of prosecution based on Georgia law.

Signature

Date

Request for Taxpayer Identification Number and Certification

**Give Form to the
 requester. Do not
 send to the IRS.**

Print or type See Specific Instructions on page 2.	Name (as shown on your income tax return)	
	Business name/disregarded entity name, if different from above	
	Check appropriate box for federal tax classification: <input type="checkbox"/> Individual/sole proprietor <input type="checkbox"/> C Corporation <input type="checkbox"/> S Corporation <input type="checkbox"/> Partnership <input type="checkbox"/> Trust/estate <input type="checkbox"/> Limited liability company. Enter the tax classification (C=C corporation, S=S corporation, P=partnership) ▶ _____ <input type="checkbox"/> Other (see instructions) ▶ _____	Exemptions (see instructions): Exempt payee code (if any) _____ Exemption from FATCA reporting code (if any) _____
	Address (number, street, and apt. or suite no.)	Requester's name and address (optional)
	City, state, and ZIP code	
List account number(s) here (optional)		

Part I Taxpayer Identification Number (TIN) Enter your TIN in the appropriate box. The TIN provided must match the name given on the "Name" line to avoid backup withholding. For individuals, this is your social security number (SSN). However, for a resident alien, sole proprietor, or disregarded entity, see the Part I instructions on page 3. For other entities, it is your employer identification number (EIN). If you do not have a number, see <i>How to get a TIN</i> on page 3. Note. If the account is in more than one name, see the chart on page 4 for guidelines on whose number to enter.	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td colspan="2" style="text-align: center;">Social security number</td> </tr> <tr> <td style="text-align: center;">[] [] [] - [] [] - [] [] [] []</td> <td></td> </tr> <tr> <td colspan="2" style="text-align: center;">Employer identification number</td> </tr> <tr> <td style="text-align: center;">[] [] [] [] - [] [] [] [] [] [] [] []</td> <td></td> </tr> </table>	Social security number		[] [] [] - [] [] - [] [] [] []		Employer identification number		[] [] [] [] - [] [] [] [] [] [] [] []	
Social security number									
[] [] [] - [] [] - [] [] [] []									
Employer identification number									
[] [] [] [] - [] [] [] [] [] [] [] []									

Part II Certification Under penalties of perjury, I certify that:	
1. The number shown on this form is my correct taxpayer identification number (or I am waiting for a number to be issued to me), and 2. I am not subject to backup withholding because: (a) I am exempt from backup withholding, or (b) I have not been notified by the Internal Revenue Service (IRS) that I am subject to backup withholding as a result of a failure to report all interest or dividends, or (c) the IRS has notified me that I am no longer subject to backup withholding, and 3. I am a U.S. citizen or other U.S. person (defined below), and 4. The FATCA code(s) entered on this form (if any) indicating that I am exempt from FATCA reporting is correct.	
Certification instructions. You must cross out item 2 above if you have been notified by the IRS that you are currently subject to backup withholding because you have failed to report all interest and dividends on your tax return. For real estate transactions, item 2 does not apply. For mortgage interest paid, acquisition or abandonment of secured property, cancellation of debt, contributions to an individual retirement arrangement (IRA), and generally, payments other than interest and dividends, you are not required to sign the certification, but you must provide your correct TIN. See the instructions on page 3.	

Sign Here	Signature of U.S. person ▶	Date ▶
------------------	----------------------------	--------

General Instructions

Section references are to the Internal Revenue Code unless otherwise noted.

Future developments. The IRS has created a page on IRS.gov for information about Form W-9, at www.irs.gov/w9. Information about any future developments affecting Form W-9 (such as legislation enacted after we release it) will be posted on that page.

Purpose of Form

A person who is required to file an information return with the IRS must obtain your correct taxpayer identification number (TIN) to report, for example, income paid to you, payments made to you in settlement of payment card and third party network transactions, real estate transactions, mortgage interest you paid, acquisition or abandonment of secured property, cancellation of debt, or contributions you made to an IRA.

Use Form W-9 only if you are a U.S. person (including a resident alien), to provide your correct TIN to the person requesting it (the requester) and, when applicable, to:

- Certify that the TIN you are giving is correct (or you are waiting for a number to be issued),
- Certify that you are not subject to backup withholding, or
- Claim exemption from backup withholding if you are a U.S. exempt payee. If applicable, you are also certifying that as a U.S. person, your allocable share of any partnership income from a U.S. trade or business is not subject to the withholding tax on foreign partners' share of effectively connected income, and

4. Certify that FATCA code(s) entered on this form (if any) indicating that you are exempt from the FATCA reporting, is correct.

Note. If you are a U.S. person and a requester gives you a form other than Form W-9 to request your TIN, you must use the requester's form if it is substantially similar to this Form W-9.

Definition of a U.S. person. For federal tax purposes, you are considered a U.S. person if you are:

- An individual who is a U.S. citizen or U.S. resident alien,
- A partnership, corporation, company, or association created or organized in the United States or under the laws of the United States,
- An estate (other than a foreign estate), or
- A domestic trust (as defined in Regulations section 301.7701-7).

Special rules for partnerships. Partnerships that conduct a trade or business in the United States are generally required to pay a withholding tax under section 1446 on any foreign partners' share of effectively connected taxable income from such business. Further, in certain cases where a Form W-9 has not been received, the rules under section 1446 require a partnership to presume that a partner is a foreign person, and pay the section 1446 withholding tax. Therefore, if you are a U.S. person that is a partner in a partnership conducting a trade or business in the United States, provide Form W-9 to the partnership to establish your U.S. status and avoid section 1446 withholding on your share of partnership income.

GEORGIA SECURITY AND IMMIGRATION COMPLIANCE ACT (OCGA 13-10-91)

CONTRACTOR E-VERIFY AFFIDAVIT

By executing this affidavit, the undersigned contractor verifies its compliance with O.C.G.A § 13-10-91, stating affirmatively that the individual, firm or corporation which is engaged in the physical performance of services on behalf of PEACH COUNTY BOARD OF COMMISSIONERS has registered with, is authorized to use and uses the federal work authorization program commonly known as E-Verify, or any subsequent replacement program, in accordance with the applicable provisions and deadlines established in OCGA § 13-10-91. Furthermore, the undersigned contractor will continue to use E-Verify throughout the contract period and the undersigned contractor will contract for the physical performance of services in satisfaction of such contract only with subcontractors who present an affidavit to the contractor with the information required by OCGA § 13-10-91(b). Contractor hereby attests that its federal work authorization user identification number and date of authorization are as follows:

Federal Work Authorization User Identification Number
(4-6 digit number can be found on MOU)

Date of Authorization

Name of Contractor

Name of Project

I hereby declare under penalty of perjury that the foregoing is true and correct.
Executed on _____, _____, 201__ in _____ (city), _____ (state).

Signature of Authorized Officer or Agent

Printed Name and Title of Authorized Officer or Agent

SUBSCRIBED AND SWORN BEFORE ME
ON THIS THE ____ DAY OF _____, 201__.

NOTARY PUBLIC
My Commission Expires:

SAVE (SYSTEMATIC ALIEN VERIFICATION FOR ENTITLEMENTS) PROGRAM AFFIDAVIT
(O.C.G.A §50-36-1(E)(2))

AFFIDAVIT VERIFYING STATUS FOR PUBLIC BENEFIT APPLICATION CONTRACTS

Peach County, Georgia is authorized to enter into contracts pursuant to GA. Const. Art. IX, § III Par I; OCGA § 36-10-1 through §36-10-2.2; OCGA § 36-60-14; OCGA § 36-91-1. Prior to entering into a contract with the PEACH COUNTY BOARD OF COMMISSIONERS, by executing this affidavit under oath, I, _____, on behalf of _____,

Am Stating that:

1.) _____ I am a United States citizen.

OR

2.) _____ I am a legal permanent resident of the United States.

OR

3.) _____ I am an otherwise qualified alien or non-immigrant under the Federal Immigration and Nationality Act and lawfully present in the United States.

The undersigned applicant also hereby verifies that he or she is 18 years of age or older and has provided at least one (1) secure and verifiable document as verification, as required by OCGA § 50-30-1(e)(1), with this affidavit. In making the above representation under oath, I understand that any person who knowingly and willfully makes a false, fictitious or fraudulent statement or representation in an affidavit shall be guilty of a violation of Code Section 16-10-20 of the Official Code of Georgia.

Signature of Employee Date

Printed Name

Alien Registration Number (for non-citizens)

Type of secure and verifiable document provided
(i.e., driver's license, passport, etc.)

SUBSCRIBED AND SWORN BEFORE ME
ON THIS THE ____ DAY OF _____, 201__.

NOTARY PUBLIC

My Commission Expires:

GEORGIA SECURITY AND IMMIGRATION COMPLIANCE ACT (OCGA 13-10-91)

SUBCONTRACTOR E-VERIFY AFFIDAVIT

SUBCONTRACTOR'S NAME: _____

CONTRACTOR'S NAME: _____

By executing this affidavit, the undersigned Subcontractor verifies its compliance with OCGA § 13-10-91, stating affirmatively that the Subcontractor which is engaged in the physical performance of services under a contract with the Contractor identified above on behalf of PEACH COUNTY BOARD OF COMMISSIONERS has registered with and is participating in the E-Verify program in accordance with the applicability provisions and deadlines established in OCGA 13-10-91.

Federal Work Authorization User Identification Number

(4-6 digit number can be found on MOU)

Date of Authorization

Name of Project

I hereby declare under penalty of perjury that the foregoing is true and correct.

Executed on _____, _____, 201__ in _____ (city), _____ (state).

Signature of Authorized Officer or Agent

Printed Name and Title of Authorized Officer or Agent

SUBSCRIBED AND SWORN BEFORE ME

ON THIS THE ____ DAY OF _____, 201__.

NOTARY PUBLIC

My Commission Expires:

SOLE PROPRIETOR EXEMPTION AFFIDAVIT

The undersigned sole proprietor of _____ verifies that they are exempt from compliance with O.C.G.A. § 36-60-6, stating affirmatively that the individual, firm, or corporation has **no employees** other than themselves and is not required to register with and/or utilize the federal work authorization program commonly known as E-Verify, or any subsequent replacement program, in accordance with the applicable provisions.

In making this representation under oath, I understand that any person who knowingly and willfully makes a false, fictitious or fraudulent statement or representation in an affidavit shall be guilty of a violation of Code Section 16-10-20 of the Official Code of Georgia.

I hereby declare under penalty of perjury that the foregoing is true and correct.

Executed on _____, _____, 201__ in _____ (city), _____ (state).

Signature of Authorized Officer or Agent

Printed Name and Title of Authorized Officer or Agent

Type of secure and verifiable document provided
(Attach copy i.e., driver's license, passport, etc.)

SUBSCRIBED AND SWORN BEFORE ME
ON THIS THE _____ DAY OF _____, 201__.

NOTARY PUBLIC
My Commission Expires:

Private Employer Exemption Affidavit Pursuant To O.C.G.A. § 36-60-6(d)

By executing this affidavit, the undersigned private employer verifies that it is exempt from compliance with O.C.G.A. § 36-60-6, stating affirmatively that the individual, firm, or corporation has NO employees that you are the sole proprietor of _____ and are not required to register with and/or utilize the federal work authorization program commonly known as E-Verify, or any subsequent replacement program, in accordance with the applicable provisions and deadlines established in O.C.G.A. § 36-60-6.

I hereby declare under penalty of perjury that the foregoing is true and correct.
Executed on _____, ____, 201__ in _____ (city), _____ (state).

Printed Name of Exempt Private Employer

Signature of Exempt Private Employer or
Authorized Officer or Agent

Printed Name and Title of Person Executing Affidavit

SUBSCRIBED AND SWORN BEFORE ME
ON THIS THE _____ DAY OF _____, 201__.

NOTARY PUBLIC
My Commission Expires:

* This affidavit is for submissions made on or after to July 1, 2013.

Secure and Verifiable Documents Under O.C.G.A. § 50-36-2

Issued August 1, 2012 by the Office of the Attorney General, Georgia

The Illegal Immigration Reform and Enforcement Act of 2011 (“IIREA”) provides that “[n]ot later than August 1, 2011, the Attorney General shall provide and make public on the Department of Law’s website a list of acceptable secure and verifiable documents. The list shall be reviewed and updated annually by the Attorney General.” O.C.G.A. § 50-36-2(f). The Attorney General may modify this list on a more frequent basis, if necessary.

Any secure and verifiable document presented must not be expired. If expiration occurs during contract/benefit period, a current document must be presented to maintain compliance.

The following list of secure and verifiable documents, published under the authority of O.C.G.A. § 50-36-2, contains documents that are verifiable for identification purposes, and documents on this list may not necessarily be indicative of residency or immigration status.

- A United States passport or passport card [O.C.G.A. § 50-36-2(b)(3); 8 CFR § 274a.2]
- A United States military identification card [O.C.G.A. § 50-36-2(b)(3); 8 CFR § 274a.2]
- A driver’s license issued by one of the United States, the District of Columbia, the Commonwealth of Puerto Rico, Guam, the Commonwealth of the Northern Marianas Islands, the United States Virgin Island, American Samoa, or the Swain Islands, provided that it contains a photograph of the bearer or lists sufficient identifying information regarding the bearer, such as name, date of birth, gender, height, eye color, and address to enable the identification of the bearer [O.C.G.A. § 50-36-2(b)(3); 8 CFR § 274a.2]
- An identification card issued by one of the United States, the District of Columbia, the Commonwealth of Puerto Rico, Guam, the Commonwealth of the Northern Marianas Islands, the United States Virgin Island, American Samoa, or the Swain Islands, provided that it contains a photograph of the bearer or lists sufficient identifying information regarding the bearer, such as name, date of birth, gender, height, eye color, and address to enable the identification of the bearer [O.C.G.A. § 50-36-2(b)(3); 8 CFR § 274a.2]
- A tribal identification card of a federally recognized Native American tribe, provided that it contains a photograph of the bearer or lists sufficient identifying information regarding the bearer, such as name, date of birth, gender, height, eye color, and address to enable the identification of the bearer. A listing of federally recognized Native American tribes may be found at: http://www.bia.gov/WhoWeAre/BIA_OIS_TribalGovernmentServices_TribalDirectory/index.htm [O.C.G.A. § 50-36-2(b)(3); 8 CFR § 274a.2]
- A United States Permanent Resident Card or Alien Registration Receipt Card [O.C.G.A. § 50-36-2(b)(3); 8 CFR § 274a.2]
- An Employment Authorization Document that contains a photograph of the bearer [O.C.G.A. § 50-36-2(b)(3); 8 CFR § 274a.2]
- A passport issued by a foreign government [O.C.G.A. § 50-36-2(b)(3); 8 CFR § 274a.2]
- A Merchant Mariner Document or Merchant Mariner Credential issued by the United States Coast Guard [O.C.G.A. § 50-36-2(b)(3); 8 CFR § 274a.2]
- A Free and Secure Trade (FAST) card [O.C.G.A. § 50-36-2(b)(3); 22 CFR § 41.2]
- A NEXUS card [O.C.G.A. § 50-36-2(b)(3); 22 CFR § 41.2]
- A Secure Electronic Network for Travelers Rapid Inspection (SENTRI) card [O.C.G.A. § 50-36-2(b)(3); 22 CFR § 41.2]
- A driver’s license issued by a Canadian government authority [O.C.G.A. § 50-36-2(b)(3); 8 CFR § 274a.2]
- A Certificate of Citizenship issued by the United States Department of Citizenship and Immigration Services (USCIS) (Form N-560 or Form N-561) [O.C.G.A. § 50-36-2(b)(3); 6 CFR § 37.11]
- A Certificate of Naturalization issued by the United States Department of Citizenship and Immigration Services (USCIS) (Form N-550 or Form N-570) [O.C.G.A. § 50-36-2(b)(3); 6 CFR § 37.11]
- Certification of Report of Birth issued by the United States Department of State (Form DS-1350) [O.C.G.A. § 50-36-2(b)(3); 6 CFR § 37.11]
- Certification of Birth Abroad issued by the United States Department of State (Form FS-545) [O.C.G.A. § 50-36-2(b)(3); 6 CFR § 37.11]
- Consular Report of Birth Abroad issued by the United States Department of State (Form FS-240) [O.C.G.A. § 50-36-2(b)(3); 6 CFR § 37.11]
- An original or certified copy of a birth certificate issued by a State, county, municipal authority, or territory of the United States bearing an official seal [O.C.G.A. § 50-36-2(b)(3); 6 CFR § 37.11]

In addition to the documents listed herein, if, in administering a public benefit or program, an agency is required by federal law to accept a document or other form of identification for proof of or documentation of identity, that document or other form of identification will be deemed a secure and verifiable document solely for that particular program or administration of that particular public benefit. [O.C.G.A. § 50-36-2(c)]