



shaw hard surface®

[resilient](#) [porcelain](#) [carpet](#) [technical](#) [environmental](#) [project gallery](#) [about](#)

[design is...theblog](#)

Home » Resilient Products » Rexcourt™ 6.5



01451 Golden Cherry 01452 Indian Cherry 01811 Noble Zelkova 01821 Tiger Oak 01822 Windsor Oak 01823 Antique Oak 02001 Grand Maple 06200 Red 06301 Beige

Rexcourt™ 6.5

Heterogeneous Sheet

[» Contact a Sales Rep](#)

- Absorbs shock and impact, reduces vibration to lessen leg stress, and offers optimum traction and slip resistance for the prevention of injuries.
- Creates subtle spring-like effect to reduce fatigue and allow for more efficient running and jumping.
- Meets NCAA and EN standards for ball bounce-back percentage and has softer acoustics for a quieter gym.
- Polyurethane coating seals out dirt and eliminates the need for polishes or finishes. Simple maintenance involves daily dry mopping and wet mopping as needed.
- 6.5 mm thickness is more forgiving over uneven subfloors.
- FloorScore® certified for low VOCs
- 10 year wear warranty

[» Installation & Maintenance](#) [» Warranty](#)

Products rendered in these room scenes may not be an exact representation of actual flooring. Color of swatches and rendered images may vary according to monitor settings. To confirm color, call 800-241-2073 to order a sample.

Specs

Construction

Style Name/Number	Rexcourt™ 6.5 / 0004V
Construction	Heterogeneous Sheet
Overall Thickness	6.5 mm
Backing Class	Cell foam
Roll Size	Length: 15 m or 49.2' Width: 180 cm or 70.86"
Weight	113 kg/roll or 249.12 lbs/roll
Installation	Glue Down
Warranty	10 year limited commercial wear warranty

[» Complete Spec](#) [» Tear Sheet](#)

Product Specifications

Style Name / Number	Rexcourt / 0004V
Construction / EN 649 / ASTM-1303-04	Heterogeneous PVC
Overall Thickness / EN 428	6.5 mm
Wearlayer Thickness / EN 429	0.95 mm or 37 mils (Wood) 1.45 mm or 57 mils (Solid)
Backing	Cell foam
Surface Treatment	Polyurethane
Pattern	Uni, wood

Packaging

Roll Size / EN 426, Width	180 cm or 70.86" wide
Roll Size / EN 426, Length	15 m or 49.2' long
Weight / EN 430	4300 g/m2 or 250 lbs/roll
Installation	Glue down

Testing

Coefficient of Friction / EN 13036-A	Ø 70.6
Specular Gloss / EN ISO 2813	20-25%
Color Fastness / ISO 105 B02	Passes
Resistance to Wear / EN ISO 5470-1	200 mg
Vertical Deformation / EN 14809	0.8 mm
Indentation Resistance / EN 1516	0.13 mm
Resistance to Impact / EN 1517	No damage
Behavior Under a Rolling Load / EN 1569	No damage
Shock Absorption / EN 14808	≥ 25%
Ball Reflection / EN 12235	Ø 97 %
Chemical Product Resistance / F 925	Mostly unchanged

Fire Test Data

Behavior to Fire / EN 13501-1	Class 2 / >450
-------------------------------	----------------

Warranty

10 year limited commercial wear warranty.
Please visit www.shawhardsurface.com for the most current warranty information.

Environmental

Indoor Air Quality	FloorScore® certified
--------------------	-----------------------



Specifications are subject to nominal manufacturing variance.
Material supply and/or manufacturing processes may necessitate changes without notice.