

FAÇADE RESTORATION AND IMPROVEMENTS TO 711-713 N MAIN STREET COLUMBIA

HARDWARE SET NO. 01

FOR USE ON DOOR #(S):

01 5-3 X 10-3 PAIR

EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
10	EA	HW HINGE	5BB1HW 4.5" X 4.5"	643	IVE
2	EA	POWER TRANSFER	EPT-10	695	VON
1	EA	ELECTRIFIED EXIT DEVICE	RX-QEL9850EO	643E	VON
1	EA	ELECTRIFIED EXIT DEVICE	RX-QEL9850L 996L	643E	VON
1	EA	SURF. AUTO OPERATOR	9553 STD2 MS	ANDKB	LCN
2	EA	ACTUATOR, WALL MOUNT	8310-856T	630	LCN
2	EA	FLUSH MOUNTBBOX	8310-868F		LCN
2	EA	ESCUTCHEON	8310-874	630	LCN
2	EA	KICK PLATE	8400 18" X 1" LDW B-CS	613	IVE
1	EA	MEETING STILE	557D/56D	DKB	ZER
1	EA	GASKETING	8800S-BK	S-BK	ZER
1	EA	DOOR BOTTOM	3546A	AL	ZER
1	EA	THRESHOLD	545D	DKB	ZER
2	EA	DOOR CONTACT	679-05	630	SCE
1	EA	POWER SUPPLY	PS904	GRY	VON

OPERATIONAL DESCRIPTION

SPECIFIED HARDWARE TO BE INSTALLED WITHOUT POWER WITH THE EXCEPTION OF THE ACTUATORS WHICH WILL BECOME OWNER STOCK TO BE INSTALLED ONCE POWER HAS BEEN PROVIDED.. POWER TO BE PROVIDED BY OWNER AND ALL CONNECTIONS TERMINATED AT A LATER DATE. ONCE POWER HAS BEEN PROVIDED REFER TO THIS OPERATIONAL DESCRIPTION FOR OPERATION OF THE OPENING. LATCH BOLTS TO REMAIN RETRACTED DURING BUSINESS HOURS. PRESSING EITHER ACTUATOR ENGAGES AUTOMATIC OPERATOR. DOORS CLOSE AFTER PRESET INTERVAL. WHEN LATCH BOLTS ARE LATCHED INTERIOR ACTUATOR RETRACTS LATCHBOLTS AND ENGAGES AUTOMATIC OPERATOR. RX SWITCHES IN PANIC BARS SHUNT DOOR POSITION SWITCHES. FREE EGRESS AT ALL TIMES BY EITHER OR BOTH LEAFS

HARDWARE SET NO. 02

FOR USE ON DOOR #(S):

01 5-4 X 8-11 PAIR

EACH TO HAVE:

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
8	EA	HW HINGE	5BB1HW 4.5" X 4.5"	643	IVE
2	EA	POWER TRANSFER	EPT-10	695	VON
1	EA	ELECTRIFIED EXIT DEVICE	RX-QEL9850EO	643E	VON
1	EA	ELECTRIFIED EXIT DEVICE	RX-QEL9850L 996L	643E	VON
1	EA	SURF. AUTO OPERATOR	9553 STD2 MS	ANDKB	LCN
2	EA	ACTUATOR, WALL MOUNT	8310-856T	630	LCN
2	EA	FLUSH MOUNTBBOX	8310-868F		LCN
2	EA	ESCUTCHEON	8310-874	630	LCN
2	EA	KICK PLATE	8400 18" X 1" LDW B-CS	613	IVE
1	EA	MEETING STILE	557D/56D	DKB	ZER
1	EA	GASKETING	8800S-BK	S-BK	ZER

1	EA	DOOR BOTTOM	3546A	AL	ZER
1	EA	THRESHOLD	545D	DKB	ZER
2	EA	DOOR CONTACT	679-05	630	SCE
1	EA	POWER SUPPLY	PS904	GRY	VON

OPERATIONAL DESCRIPTION

SPECIFIED HARDWARE TO BE INSTALLED WITHOUT POWER WITH THE EXCEPTION OF THE ACTUATORS WHICH WILL BECOME OWNER STOCK TO BE INSTALLED ONCE POWER HAS BEEN PROVIDED. POWER TO BE PROVIDED BY OWNER AND ALL CONNECTIONS TERMINATED AT A LATER DATE. ONCE POWER HAS BEEN PROVIDED REFER TO THIS OPERATIONAL DESCRIPTION FOR OPERATION OF THE OPENING. LATCH BOLTS TO REMAIN RETRACTED DURING BUSINESS HOURS. PRESSING EITHER ACTUATOR ENGAGES AUTOMATIC OPERATOR. DOORS CLOSE AFTER PRESET INTERVAL. WHEN LATCH BOLTS ARE LATCHED INTERIOR ACTUATOR RETRACTS LATCHBOLTS AND ENGAGES AUTOMATIC OPERATOR. RX SWITCHES IN PANIC BARS SHUNT DOOR POSITION SWITCHES. FREE EGRESS AT ALL TIMES BY EITHER OR BOTH LEAFS