



PURCHASING DIVISION

901 Broadway, N.E. • Knoxville, TN 37917-6699
 865.403.1133 • Fax 865.594.8858
 800.848.0298 (Tennessee Relay Center)
 Email: purchasing@kcdc.org
<http://www.kcdc.org/en/DoingBusiness.aspx>

Addendum

SOLICITATION NAME	LED Lights at Nature’s Cove Q1510	ADDENDUM NUMBER	1	DATE	08-13-14
--------------------------	-----------------------------------	------------------------	---	-------------	----------

KCDC is providing this addendum to answer questions that have been raised about this solicitation. To aid in readability, the questions are in black and the answers are in **bold** and the answers follow immediately below.

Q1	May I submit multiple quotes?
	Vendors may submit up to two quotes. Note that “or equals” have to be approved by KCDC as specified in the solicitation document.
Q2	Are all of the model numbers typed correctly?
	We have discovered some discrepancies. Please see the revised pages that follow this sheet and use these to submit your quote.

REVISED

j. The desired items are:

Room	Item	Model	Quantity
Dining Room	Light Fixture LED light source Housing: Die-form cold rolled steel Finish: Stain Nickel Shade: Acrylic Certifications: UL/cUL listed, Energy Star Listed Input Power: 21 watts Lamp Type: LEDs Lamp Lumen: 1,600 Color Render Index: 80 Color Temperature: 4100K Diameter: 14 inch Height: 4.0 inch Input Voltage: 120V-277V	DM-DC014D	95
Kitchen	Light Fixture LED light source Housing: Die-form cold rolled steel Finish: Stain Nickel Shade: Acrylic Certifications: UL/cUL listed, Energy Star Listed Input Power: 21 watts Lamp Type: LEDs Lamp Lumen: 1,600 Color Render Index: 80 Color Temperature: 4100K Diameter: 14 inch Height: 4.0 inch Input Voltage: 120V-277V	DM-DC014D	95
Bathroom	Light Fixture (Vanity) Size: 24.5L x 6.0W x 5.9D Safety: UL/cUL Listed Finish: Satin Nickel Plated Trim (metal) Shade: Diffused Acrylic System Watts: 22W Light Source: LEDs Lumens: 1350 Color Temperature: 4000K Operating Temperature: -10C to 45C LED Voltage: 120V-277V Operating Life: 50,000 hours	DM-FL2103D-LED	162

Bedroom	<p>Light Fixture LED light source Housing: Die-form cold rolled steel Finish: Stain Nickel Shade: Acrylic Certifications: UL/cUL listed, Energy Star Listed Input Power: 21 watts Lamp Type: LEDs Lamp Lumen: 1,600 Color Render Index: 80 Color Temperature: 4100K Diameter: 14 inch Height: 4.0 inch Input Voltage: 120V-277V</p>	DM-DC014D	182
Hallway	<p>Light Fixture (Ceiling) Application: Indoor or Outdoor Ceiling or Wall Mount Size: 11.0 OD x 3.7 H Safety: UL/cUL Listed Base: White Polycarbonate Shade: Opal White Polycarbonate Input Wattage: 16W nominal Input Voltage: 120V 60HZ Light Source: LEDs Lumens: 1300 Color Temperature: 4100K Operating Temperature: -20C to 40C Operating Life: 50,000 hours Wire Mold Access: Surface Mount Fixture: Sealed</p>	DM-BH-2D	284
Porch	<p>Light Fixture Application: Indoor or Outdoor Ceiling or Wall Mount Size: 9.25 x 5.0 x 4.3 Safety: UL/cUL Listed Base: White Polycarbonate Shade: Opal Input Wattage: 12W Input Voltage: 120V Light Source: LEDs Lumens: 950 Color Temperature: 4100K Operating Temperature: -20C to 40C Operating Life: 50,000 hours Fixture: Sealed Photo Cell: Yes</p>	DM-BH-1D-PC	95

Community Building	<p>Wall Packs (Option) Application: Outdoor Wall Mount Size: 10.0 L x 15.0W x 11.0H Safety: UL/cUL listed Shade: Heat and impact resistance glass diffuser/lens Input Voltage: 120V-277V 60 Hz Input Wattage: 55W nominal Light Source: LEDs Color Temperature: 5000K Lumen: 4,400 Operating Temperature: -40F/+125F LED Operating Life: 70,000 hours Gasket: Continuous</p>	DM-LED-21055FLD	4
Community Building	<p>Porch Light (Option) Application: Indoor or Outdoor Ceiling or Wall Mount Size: 9.25 x 5.0 x 4.3 Safety: UL/cUL Listed Base: White Polycarbonate Shade: Opal Input Wattage: 12W Input Voltage: 120V Light Source: LEDs Lumens: 950 Color Temperature: 4100K Operating Temperature: -20C to 40C Operating Life: 50,000 hours Fixture: Sealed Photo Cell: Yes</p>	DM-BH-1D-PC	7
Community Building	<p>Light Tube (Option) Size: 4 foot T8 LED tub for F32T8, 32W/28W/25W Replacement for existing T12 Fluorescent lamp Driver: Built in Lens: Diffused High CRO LEDs >80 Color Temperature: 4000K Safety: UL and DLC listed Warranty: Five Years AC Voltage: 100-277V Frequency: 50-60 Hz Power Consumption: 22W Power Factor: 0.62 Driving Current to LED:" 45mA Color Temperature: 4000K Luminous Flux: 2350 lm Tube Length with pin: 47.72 View Angle: 120 degree</p>	LED-DM-T8-LED-48-840	126

	Lamp Holders Required: Un-shunted		
Community Building	Light Tube Kit (Option) Bi-Pin Rapid Start Lamp Holder (Tombstone)	NA	252

REVISED LED Lights and Fixtures for Nature' Cove Q1510**Solicitation Document B Cost Section****Vendor:****Cost**

Room	Item	Model	Quantity	Cost Each	Total Cost
Dining Room	Light Fixture	DM-DC014D	95	\$	\$
Kitchen	Light Fixture	DM-DC014D	95	\$	\$
Bathroom	Light Fixture (Vanity)	DM-FL2103D-LED	162	\$	\$
Bedroom	Light Fixture	DM-DC014D	182	\$	\$
Hallway	Light Fixture (Ceiling)	DM-BH-2D	284	\$	\$
Porch	Light Fixture	DM-BH-1D-PC	95	\$	\$
				TOTAL COST	\$

Options

Community Building	Wall Packs	DM-LED-21055FLD	4	\$	\$
Community Building	Porch Light	DM-BH-1D-PC	7	\$	\$
Community Building	Light Tube	LED-DM-T8-LED-48-840	126	\$	\$
Community Building	Light Tube Kit Bi-Pin Rapid Start Lamp Holder	NA	252	\$	\$

Vendor:					
REVISED Information about the products quoted					
Room	Item	Model Specified	Brand Quoted	Model Quoted	Notes
Dining Room	Light Fixture	DM-DC014D			
Kitchen	Light Fixture	DM-DC014D			
Bathroom	Light Fixture (Vanity)	DM-FL2103D-LED			
Bedroom	Light Fixture	DM-DC014D			
Hallway	Light Fixture (Ceiling)	DM-BH-2D			
Porch	Light Fixture	DM-BH-1D-PC			
Community Building	Wall Packs	DM-LED-21055FLD			
Community Building	Porch Light	DM-BH-1D-PC			
Community Building	Light Tube	LED-DM-T8-LED-48-840			
Community Building	Light Tube Kit Bi-Pin Rapid Start Lamp Holder	NA			