

ADDENDUM NO. 2

BENJAMIN HILL LINEAR PARK

CITY OF LAGRAGE LAGRANGE, GEORGIA

SPECIFICATIONS

Specification 32 90 00; Subsection 3.5

Replace Items A- I with the following:

- A. Loosen the grade of lawn areas to a minimum depth of ~~six (6)~~ four (4) inches. Remove stones over one-half ($\frac{1}{2}$) inches in any dimension and sticks, roots, rubbish and other extraneous matter using a Harley Rock Machine or equivalent. All debris shall be legally removed from the Site. Limit preparation to areas which will be planted promptly after preparation.
- B. Place approximately one-half (1/2) of total amount of ~~topsoil~~ on-site soil as required. Work into top of loosened subgrade to create a transition layer and then place remainder of ~~topsoil mixture~~ on-site soil to minimum depth required to meet lines, grades and elevations shown, after light rolling and natural settlement. Grades shall be within +/- one-half (1/2") of designated slopes and elevation.
- C. Allow for sod thickness in areas to be sodded.
- D. Grade lawn areas to be smooth, even surface with loose, uniformly fine texture. Roll and rake, remove ridges and fill depressions as required to meet finish grades. Limit fine grading to areas which can be planted immediately after grading.
- E. The depths and grades indicated on the Plans are the final grades after settlement and shrinkage of the organic material. The Contractor shall install the planting soil mix at a higher level to compensate for this anticipated reduction of planting soil volume.
- F. Fertilize and lime prior to start of grassing operation. Apply ground limestone at the rate recommended by soil test analysis and work into top ~~six (6)~~ four (4) inches of soil. Apply fertilizer at the recommended rate; work into top two (2) inches of soil. The fertilizer application shall not precede the placement of sod by more than three (3) days.
- G. Moisten prepared lawn areas before planting if soil is dry. Water thoroughly and allow surface moisture to dry before planting lawns. Do not create a muddy soil condition.
- H. Restore lawn areas to specified condition if eroded or otherwise disturbed after fine grading and prior to planting.
- I. Preparation of Unchanged Grades: Where lawns are to be planted in areas that have not been altered or disturbed by excavating, grading, or stripping operations, prepare soil for lawn planting as follows: Till to a depth of not less than ~~six (6)~~ four (4) inches; apply soil amendments and initial fertilizers as specified; remove high areas and fill in depressions; till soil to a homogenous mixture of fine texture, free of lumps, clots, stones,

roots and other extraneous matter. Prior to preparation of unchanged areas, remove existing grass, vegetation and turf. Dispose of such material outside of Owner's property; do not turn over into soil being prepared for lawns.

Bidder Must Acknowledge Receipt of this Addendum on Bid Form

May 21, 2021
Barge Design Solutions, Inc.
1201 Front Ave, Suite F
Columbus, Georgia 31901
706-321-4590