



PURCHASING DIVISION

901 Broadway, N.E. • Knoxville, TN 37917-6699
 865.403.1133 • Fax 865.594.8858
 800.848.0298 (Tennessee Relay Center)
 Email: purchasing@kcdc.org
<http://www.kcdc.org/en/DoingBusiness.aspx>

Addendum

SOLICITATION NAME	LED Lights at Autumn Landing Q1509	ADDENDUM NUMBER	1	DATE	08-13-14
--------------------------	------------------------------------	------------------------	---	-------------	----------

KCDC is providing this addendum to answer questions that have been raised about this solicitation. To aid in readability, the questions are in black and the answers are in **bold** and the answers follow immediately below.

Q1	May I submit multiple quotes?
	Vendors may submit up to two quotes. Note that “or equals” have to be approved by KCDC as specified in the solicitation document.
Q2	Are all of the model numbers typed correctly?
	We have discovered some discrepancies. Please see the revised pages that follow this sheet and use these to submit your quote.

REVISED

1 k. The desired items are:

Room	Item	Model	Quantity
Living Room	<p>Light Fixture LED light source Housing: Die-form cold rolled steel Finish: Stain Nickel Shade: Acrylic Certifications: UL/cUL listed, Energy Star Listed Input Power: 21 watts Lamp Type: LEDs Lamp Lumen: 1,600 Color Render Index: 80 Color Temperature: 4100K Diameter: 14 inch Height: 4.0 inch Input Voltage: 120V-277V</p>	DM-DC014D	102
Kitchen	<p>LED 4 Foot Tube with Internal Driver Size: 4 foot T8 LED tub for F32T8, 32W/28W/25W Replacement for existing T8 Fluorescent lamp Mercury: No Lens: Diffused Certifications: UL & DLC listed, Warranty: Five Years AC Voltage: 100-2770V Frequency: 50-60Hz Power Consumption: 22W Power Factor: >0.95 Driving Current to LED: 210mA Color Temperature: 4000K CRI: 83 Luminous Flux: 2200 lm Tube Length with pin: 48 View Angle: 240 degree</p>	DM-L48T8/840/22W-EB	102
Bathroom	<p>Light Fixture (Vanity) Size: 24.5L x 6.0W x5.9D Safety: UL/cUL Listed Finish: Satin Nickel Plated Trim (metal) Shade: Diffused Acrylic System Watts: 22W Light Source: LEDs Lumens: 1350 Color Temperature: 4000K Operating Temperature: -10C to 45C LED Voltage: 120V-277V Operating Life: 50,000 hours</p>	DM-FL2103D-LED	128

Bathroom	<p>Light Fixture (Ceiling) Application: Indoor/Outdoor and Ceiling/Wall Mount Size: 11.0 OD x 3.7 H Safety: UL/cUL Listed Base: White Polycarbonate Shade: Opal White Polycarbonate Input Wattage: 16W nominal Input Voltage: 120V 60HZ Light Source: LEDs Lumens: 1300 Color Temperature: 4100K Operating Temperature: -20C to 40C Operating Life: 50,000 hours Wire Mold Access: Surface Mount Fixture: Sealed</p>	DM-BH-2D	110
Bedroom	<p>Light Fixture LED light source Housing: Die-form cold rolled steel Finish: Stain Nickel Shade: Acrylic Certifications: UL/cUL listed, Energy Star Listed Input Power: 21 watts Lamp Type: LEDs Lamp Lumen: 1,600 Color Render Index: 80 Color Temperature: 4100K Diameter: 14 inch Height: 4.0 inch Input Voltage: 120V-277V</p>	DM-DC014D	208
Hallway	<p>Light Fixture (Ceiling) Application: Indoor or Outdoor Ceiling or Wall Mount Size: 11.0 OD x 3.7 H Safety: UL/cUL Listed Base: White Polycarbonate Shade: Opal White Polycarbonate Input Wattage: 16W nominal Input Voltage: 120V 60HZ Light Source: LEDs Lumens: 1300 Color Temperature: 4100K Operating Temperature: -20C to 40C Operating Life: 50,000 hours Wire Mold Access: Surface Mount Fixture: Sealed</p>	DM-BH-2D	128

Porch	<p>Light Fixture Application: Indoor or Outdoor Ceiling or Wall Mount Size: 9.25 x 5.0 x 4.3 Safety: UL/cUL Listed Base: White Polycarbonate Shade: Opal Input Wattage: 12W Input Voltage: 120V Light Source: LEDs Lumens: 950 Color Temperature: 4100K Operating Temperature: -20C to 40C Operating Life: 50,000 hours Fixture: Sealed Photo Cell: Yes</p>	DM-BH-1D-LED-PC	102
Exterior	<p>Wall Packs (Option) Application: Outdoor Wall Mount Size: 10.0 L x 15.0W x 11.0H Safety: UL/cUL listed Shade: Heat and impact resistance glass diffuser/lens Input Voltage: 120V-277V 60 Hz Input Wattage: 55W nominal Light Source: LEDs Color Temperature: 5000K Lumen: 4,400 Operating Temperature: -40F/+125F LED Operating Life: 70,000 hours Gasket: Continuous</p>	DM-LED-21055FLD	14
Office	<p>Wall Packs (Option) Application: Outdoor Wall Mount Size: 10.0 L x 15.0W x 11.0H Safety: UL/cUL listed Shade: Heat and impact resistance glass diffuser/lens Input Voltage: 120V-277V 60 Hz Input Wattage: 55W nominal Light Source: LEDs Color Temperature: 5000K Lumen: 4,400 Operating Temperature: -40F/+125F LED Operating Life: 70,000 hours Gasket: Continuous</p>	DM-LED-21055FLD	4

Office	<p>Recessed Cans (Option) Application: 5" and 6" recess can light LED retrofit Size: 7.5" OD (Trim) x 3.78H Lumens: 860 Color Temperature: 3000K CRI: >80 Rated Life Hours: 50,000 Input Voltage: 120V Input Wattage: 13.2W Connection: Editor or GU24 base Pig Tail supplied Recessed Can Light: Not supplied Safety: UL/cUL Listed Wet Listed: Yes Dimmable: Yes</p>	DM-RT6-3000K-LED	16
Office	<p>Porch Light, Exterior (Option) Application: Indoor or Outdoor Ceiling or Wall Mount Size: 9.25 x 5.0 x 4.3 Safety: UL/cUL Listed Base: White Polycarbonate Shade: Opal Input Wattage: 12W Input Voltage: 120V Light Source: LEDs Lumens: 950 Color Temperature: 4100K Operating Temperature: -20C to 40C Operating Life: 50,000 hours Fixture: Sealed Photo Cell: Yes</p>	DM-BH-1D-PC	2
Office	<p>LED 4 Foot Tube with Internal Driver (Option) Size: 4 foot T8 LED tub for F32T8, 32W/28W/25W Replacement for existing T8 Fluorescent lamp Mercury: No Lens: Diffused Certifications: UL & DLC listed, Warranty: Five Years AC Voltage: 100-2770V Frequency: 50-60Hz Power Consumption: 22W Power Factor: >0.95 Driving Current to LED: 210 mA Color Temperature: 4000K CRI: 83 Luminous Flux: 2200 lm Tube Length with pin: 48 View Angle: 240 degree</p>	DM-L48T8/840/22W-EB	126

Office	<p>Light Tubes (Option) Size: 4 foot T8 LED tub for F32T8, 32W/28W/25W Replacement for existing T12 Fluorescent lamp Driver: Built in Lens: Diffused High CRO LEDs >80 Color Temperature: 4000K Safety: UL and DLC listed Warranty: Five Years AC Voltage: 100-277V Frequency: 50-60 Hz Power Consumption: 22W Power Factor: 0.62 Driving Current to LED:” 45mA Color Temperature: 4000K Luminous Flux: 2350 lm Tube Length with pin: 47.72 View Angle: 120 degree Lamp Holders Required: Un-shunted</p>	LED-DM-T8-LED 48-840	81
Office	<p>Light Tube Kit (Option) Bi-Pin Rapid Start Lamp Holder (Tombstone)</p>	NA	42
Office	<p>Light Fixture (Vanity) (Option) Size: 24.5L x 6.0W x5.9D Safety: UL/cUL Listed Finish: Satin Nickel Plated Trim (metal) Shade: Diffused Acrylic System Watts: 22W Light Source: LEDs Lumens: 1350 Color Temperature: 4000K Operating Temperature: -10C to 45C LED Voltage: 120V-277V Operating Life: 50,000 hours</p>	DM-FL2103D	5
Office	<p>Light Fixture (Ceiling) Option Application: Indoor or Outdoor/Ceiling or Wall Mount Size: 11.0 OD x 3.7 H Safety: UL/cUL Listed Base: White Polycarbonate Shade: Opal White Polycarbonate Input Wattage: 16W nominal Input Voltage: 120V 60HZ Light Source: LEDs Lumens: 1300 Color Temperature: 4100K Operating Temperature: -20C to 40C Operating Life: 50,000 hours Wire Mold Access: Surface Mount Fixture: Sealed</p>	DM-BH-2D	5

REVISED LED Lights and Fixtures for Autumn Landing Q1509**Solicitation Document B Cost Section****Vendor:**

Cost					
Room	Item	Model	Quantity	Cost Each	Total Cost
Living Room	Light Fixture	DM-DC014D	102	\$	\$
Kitchen	LED 4 Foot Tube Internal Driver	DM-L48T8/840/22W-EB	102	\$	\$
Bathroom	Light Fixture (Vanity)	DM-FL2103D-LED	128	\$	\$
Bathroom	Light Fixture (Ceiling)	DM-BH-2D	110	\$	\$
Bedroom	Light Fixture	DM-DC014D	208	\$	\$
Hallway	Light Fixture (Ceiling)	DM-BH-2D	128	\$	\$
Porch	Light Fixture	DM-BH-1D-LED-PC	102	\$	\$
				TOTAL COST	\$
Options					
Exterior	Wall Packs	DM-LED-21055FLD	14	\$	\$
Office	Wall Packs	DM-LED-21055FLD	4	\$	\$
Office	Recessed Cans	DM-RT6-3000K-LED	16	\$	\$
Office	Porch Light, Exterior	DM-BH-1D-PC	2	\$	\$
Office	LED 4 Foot Tube with Internal Driver	DM-L48T8/840/22W-EB	126	\$	\$
Office	Light Tubes	LED-DM-T8-LED 48-840	81	\$	\$
Office	Light Tube Kit Bi-Pin Rapid Start Lamp Holder (Tombstone)	NA	42	\$	\$
Office	Light Fixture (Vanity)	DM-FL2103D	5	\$	\$
Office	Light Fixture Ceiling	DM-BH-2D	5	\$	\$

Vendor:					
REVISED Item Information					
Room	Item	Model Specified	Brand Quoted	Model Quotes	Notes
Living Room	Light Fixture	DM-DC014D			
Kitchen	LED 4 Foot Tube Internal Driver	DM- L48T8/840/22W- EB			
Bathroom	Light Fixture (Vanity)	DM-FL2103D- LED			
Bathroom	Light Fixture (Ceiling)	DM-BH-2D			
Bedroom	Light Fixture	DM-DC014D			
Hallway	Light Fixture (Ceiling)	DM-BH-2D			
Porch	Light Fixture	DM-BH-1D-LED- PC			
Exterior	Wall Packs	DM-LED- 21055FLD			
Office	Wall Packs	DM-LED- 21055FLD			
Office	Recessed Cans	DM-RT6-3000K- LED			
Office	Porch Light, Exterior	DM-BH-1D-PC			
Office	LED 4 Foot Tube with Internal Driver	DM- L48T8/840/22W- EB			
Office	Light Tubes	LED-DM-T8-LED 48-840			
Office	Light Tube Kit Bi-Pin Rapid Start Lamp Holder (Tombstone)	NA			
Office	Light Fixture (Vanity)	DM-FL2103D			