

Scan. Order. Done.
Details on page A1.



PLUMBING

Electric Tankless Water Heaters & Elements



No. 2E768



Electric Water Heater Elements

All models include a gasket.

| Watts | Style | Voltage* | Insert Length (in.) | Item No. | Watts | Style | Voltage* | Insert Length (in.) | Item No. |
|--------------------------|----------|----------|---------------------|----------|-------------------------------------|----------|----------|---------------------|----------|
| High-Watt Density | | | | | Nickel-Based Alloy Sheath | | | | |
| GA, Copper Sheath | | | | | GA, Nickel Base Alloy Sheath | | | | |
| 1500 | Bolt On | 120 | 7 3/4 | 2E491 | 2000 | Screw In | 240 | 9 3/4 | 2E765 |
| 1500 | Screw In | 120 | 7 3/4 | 2E457 | 3500 | Screw In | 240 | 13 3/4 | 2E766 |
| 1500 | Screw In | 240 | 7 3/4 | 2E460 | 4500 | Screw In | 240 | 16 3/4 | 2E673 |
| 2000 | Screw In | 240 | 7 3/4 | 2E756 | 5000 | Screw In | 240 | 19 1/4 | 2E767 |
| 2500 | Screw In | 240 | 9 3/4 | 2E757 | 6000 | Screw In | 240 | 22 3/4 | 2E768 |
| 3000 | Screw In | 240 | 10 3/4 | 2E758 | Threaded | | | | |
| 3500 | Screw In | 240 | 12 3/4 | 2E759 | RHEEM, Copper Sheath | | | | |
| 4500 | Screw In | 240 | 13 3/4 | 2E760 | 2000 | Straight | 120 | 7 3/4 | 15A528 |
| Low-Watt Density | | | | | Threaded, 1 1/2" | | | | |
| GA, Copper Sheath | | | | | VANGUARD, Copper Sheath | | | | |
| 750 | Screw In | 240 | 7 3/4 | 2E458 | 4500 | Foldback | 240 | 13 3/4 | 15A531 |
| 1000 | Screw In | 240 | 7 3/4 | 2E459 | RHEEM, Titanium Sheath | | | | |
| 1500 | Bolt On | 120 | 7 1/4 | 2E102 | 4500 | Foldback | 240 | 16 1/2 | 15A533 |
| 1500 | Screw In | 120 | 7 3/4 | 2E295 | Item No. | | | | |
| 1500 | Screw In | 240 | 7 3/4 | 2E298 | Element, 6000W, 480V, 19.2"L | | | | |
| 1650 | Screw In | 120 | 9 3/4 | 2E754 | 2XE69 | | | | |
| 2000 | Screw In | 240 | 10 3/4 | 2E299 | | | | | |
| 2500 | Screw In | 240 | 7 1/4 | 2E300 | | | | | |
| 3000 | Screw In | 240 | 9 | 2E301 | | | | | |
| 3500 | Screw In | 240 | 9 3/4 | 2E302 | | | | | |
| 4500 | Screw In | 240 | 11 3/4 | 2E303 | | | | | |

* 240V elements can be used to replace 208V elements, resulting in a 25% lower recovery rate.



Electric Mini-Tank Water Heaters

Factory-installed T&P valve
Simply plug into a standard wall outlet and set thermostat control, except Nos. 21EW70 and 5AE45 are hardwired. All have glass-lined tank with titanium inside, stainless steel heating element, and 30" grounded 16/3 cord. 120V. Eemax MiniTank™ models have a 5-yr. limited manufacturer's warranty. Bosch heaters have up to 98% thermal efficiency and a 6-yr. limited manufacturer's warranty. UL Listed and UPC Certified; except Eemax models are ETL Listed, CSA and UL Certified.



No. 14U450



No. 4JY90

| Tank Cap. | Water Connc. | Total Watts | Voltage | Amps AC | Temp. Range | Overall Height | Overall Width | Overall Length | Mr. Brand | Item Model | Item No. |
|--------------------------------|--------------|-------------|---------|---------|--------------|----------------|---------------|----------------|-----------|------------|----------|
| Mini-Tank Water Heaters | | | | | | | | | | | |
| 1.5 gal. | 1/2" NPT | 1440 | 120 | 12 | 50° to 140°F | 15 1/4" | 9 3/4" | 10" | Eemax | EMT1 | 14U450 |
| 2.5 gal. | 1/2" NPT | 1440 | 120 | 12 | 50° to 140°F | 17" | 11" | 11 1/4" | Eemax | EMT2.5 | 21EW68 |
| 2.7 gal. | 1/2" NPT | 1440 | 120 | 12 | 65° to 145°F | 13 3/4" | 13 3/4" | 10 3/4" | Bosch | ES2.5 | 4JY89 |
| 4 gal. | 1/2" NPT | 1440 | 120 | 12 | 50° to 140°F | 18 3/4" | 12 1/2" | 13" | Eemax | EM14 | 21EW69 |
| 4 gal. | 1/2" NPT | 1440 | 120 | 12 | 65° to 145°F | 13 3/4" | 13 3/4" | 13 3/4" | Bosch | ES4 | 4JY90 |
| 6 gal. | 3/4" NPT | 1440 | 120 | 12 | 50° to 140°F | 21" | 14" | 14 1/4" | Eemax | EM16 | 21EW70 |
| 7 gal. | 3/4" NPT | 1440 | 120 | 12 | 65° to 145°F | 17 1/2" | 17 1/2" | 14 1/2" | Bosch | ES8 | 5AE45 |

Chronomite® Electric Tankless Water Heaters

Up to 99% efficient and provide unlimited hot water on demand. Feature vandal-resistant aluminum housing and include compression fittings and faucet controls. Nos. 54EL15 to 54EL18 have user adjustable temperature and water flow (0.35 to 5.0 gpm). Nos. 10G720, 6DXT1, and 6DXT2 are designed for low-flow, handwashing applications and are cold water feed only. All models are certified for use in potable water applications. ADA compliant; UL and IAPMO Listed; HUD.



| Water Connc. | Watts | Voltage | Amps AC | Min. Flow Activation | Temp. Range | H | W | D | Temp. Rise @ 0.5 gpm | Temp. Rise @ 1.5 gpm | Mr. Model | Item No. |
|------------------|--------|---------|----------|------------------------|------------------------|-------------|--------|--------|----------------------|----------------------|------------------|----------|
| 3/4" Compression | 1800 | 120VAC | 15 | 0.35 gpm | 80° to 120°F | 6 1/4" | 9 3/4" | 2 3/4" | 25°F | — | SR-15L/120 HTR-I | 10G720 |
| | 2400 | 120VAC | 20 | 0.35 gpm | 90° to 120°F | 6 1/4" | 9 3/4" | 2 3/4" | 33°F | — | SR-20L/120 HTR-I | 6DXT1 |
| | 3600 | 120VAC | 30 | 0.35 gpm | 90° to 120°F | 6 1/4" | 9 3/4" | 2 3/4" | 49°F | — | SR-30L/120 HTR-I | 6DXT2 |
| | 4150 | 277VAC | 15 | 0.35 gpm | 80° to 120°F | 6 1/4" | 9 3/4" | 2 3/4" | 57°F | — | SR-15L/277 HTR-I | 19C803 |
| | 4160 | 208VAC | 20 | 0.35 gpm | 80° to 120°F | 6 1/4" | 9 3/4" | 2 3/4" | 57°F | — | SR-20L/208 HTR-I | 10G722 |
| | 5540 | 277VAC | 20 | 0.35 gpm | 80° to 120°F | 6 1/4" | 9 3/4" | 2 3/4" | 76°F | — | SR-20L/277 HTR-I | 10G723 |
| | 6240 | 208VAC | 30 | 0.65 gpm | 80° to 120°F | 6 1/4" | 9 3/4" | 2 3/4" | — | 28°F | SR-30/208 HTR-I | 10G725 |
| | 8310 | 277VAC | 30 | 0.65 gpm | 80° to 120°F | 6 1/4" | 9 3/4" | 2 3/4" | — | 38°F | SR-30/277 HTR-I | 10G724 |
| | 8320 | 208VAC | 40 | 0.65 gpm | 80° to 120°F | 6 1/4" | 9 3/4" | 2 3/4" | — | 38°F | SR-40/208 HTR-I | 19C804 |
| | 11,520 | 240VAC | 48 | 0.35 gpm | Ambient Plus Temp Rise | 93° to 101° | 4 1/4" | — | — | 52°F | R-48L/240 | 54EL15 |
| 13,920 | 240VAC | 58 | 0.35 gpm | Ambient Plus Temp Rise | 93° to 101° | 4 1/4" | — | — | 63°F | R-58L/240 | 54EL17 | |
| 18,000 | 240VAC | 75 | 0.35 gpm | Ambient Plus Temp Rise | 93° to 101° | 4 1/4" | — | — | 82°F | R-75L/240 | 54EL18 | |



No. 6DXT1

Bosch Electric Tankless Water Heaters

Mount under sinks in any direction. Meet National Appliance Energy Conservation Act. UL and C-UL Listed, are low lead, and certified for use in potable water applications.

Note: Pay careful attention to unit selection. Temperature and volume of water are dependent on the kilowatt rating of heater. The higher the kilowatt rating, the greater the volume of hot water. Max. outlet temp.: 135°F. These heaters are not designed to be used as boosters or preheaters. Install without a temperature/pressure relief valve (refer to local codes) close to the faucet or tap to eliminate long pipe runs. 1/2" NPT inlet and outlet.

| Water Connc. | Watts | Voltage | Amps AC | Min. Flow Activation | Temp. Range | H | W | D | Temp. Rise @ 0.5 gpm* | Temp. Rise @ 1.5 gpm* | Temp. Rise @ 2.5 gpm* | Mr. Model | Item No. |
|--------------|--------|------------|----------|----------------------|---------------|---------|---------|--------|-----------------------|-----------------------|-----------------------|-----------|----------|
| 1/2" NPT | 3400 | 110/120VAC | 29 | 0.50 gpm | 135°F | 6 1/2" | 12 3/4" | 3" | 46°F | 14°F | 9°F | US3 | 4JY93 † |
| | 6000 | 277VAC | 22 | 0.50 gpm | 135°F | 6 1/2" | 12 3/4" | 3" | 82°F | 27°F | 16°F | US6 | 4JY92 |
| | 7200 | 220/240VAC | 30 | 0.75 gpm | 135°F | 6 1/2" | 12 3/4" | 3" | 95°F | 32°F | 26°F | US7 | 4JY94 |
| | 9500 | 208/240VAC | 40 | 0.75 gpm | 135°F | 6 1/2" | 12 3/4" | 3" | 126°F | 33°F | 26°F | US9 | 4JY91 |
| | 12,000 | 240VAC | 50 | 0.80 gpm | 135°F | 6 1/2" | 12 3/4" | 3" | 159°F | 55°F | 33°F | US12 | 2KJH5 |
| 3/4" NPT | 17,000 | 220VAC | 60 | 0.80 gpm | 100° to 140°F | 12 1/2" | 15 1/2" | 4 1/2" | 140°F | 75°F | 45°F | WH17 | 53XL95 |
| | 27,000 | 220VAC | 120 | 0.80 gpm | 100° to 140°F | 12 1/2" | 15 1/2" | 4 1/2" | 140°F | 119°F | 71°F | WH27 | 53XL96 |
| 36,000 | 240VAC | 180 | 0.60 gpm | 95° to 131°F | 15 1/4" | 20" | 4 1/2" | — | — | 95°F | Ironic 5000C WH36 | 48NU39 | |

* °F at gpm. Gal. per min./minimum water pressure 15 psi/max. water pressure 150 psi. † Recommended where ground water temperatures exceed 60°F and flow rates are less than 1 gpm.



No. 2KJH5



No. 53XL95

Sanitizing Commercial Water Heaters

- ASME T&P valve included
- Max. temp: 190°F
- Water connections have 1/4" NPT dielectric nipples

These 240V, 3-phase electric units provide 180°F sanitizing rinse water to comply with NSF and all federal, state, county, and local department sanitation codes. Screw-in type heating elements. LED diagnostic panel signals any nonoperating element. Glass-lined storage tank. 6" stainless steel legs. 150 psi working pressure. Fused 120V control circuit. 3-yr. manufacturer's warranty on tank.



No. 6E769

| Tank Cap. | Total Watts | Overall Height | Overall Width | Overall Length | Recovery @ 100°F (gph) | Mr. Model | Item No. |
|-----------|-------------|----------------|---------------|----------------|------------------------|-----------|----------|
| 10 gal. | 12,000 | 23" | 21 3/4" | 21 1/2" | 50 | E10-12-G | 6E769 |
| 10 gal. | 18,000 | 23" | 21 3/4" | 21 1/2" | 74 | E10-18-G | 6E770 |

1-800-GRAINGER (472-4643)

Sign in to **Grainger.com®** to see **YOUR Pricing and MORE**

2713