



LIVING AREA = 1349 S.F.
 TOTAL UNDER ROOF = 1625 S.F.
 GARAGE = 276 S.F.
FLOOR PLAN 1/4"=1'-0"

DOOR SCHEDULE					
MARK	SIZE	TYPE	FINISH	REMARKS	AMOUNT
1	30X68	SWING	S.C.	ENTRY	1
2	30X68	SWING	STL.	ENTRY	4
3	30X68	SWING	H.C.	INTERIOR	4
4	30X68	BIFOLD	H.C.	INTERIOR	3
5	40X68	BIFOLD	H.C.	INTERIOR	1
6	100X70	OVERHEAD	STL.	GARAGE	1
7					

NOTE:
 * EXACT ROUGH OPENING SIZES FOR DOORS & WINDOWS TO BE PROVIDED BY DOOR & WINDOW MANUFACTURER.
 * VERIFY THESE DIMENSIONS BEFORE PROCEEDING WITH THE WORK.

WINDOW SCHEDULE					
MARK	SIZE	TYPE	FINISH	REMARKS	AMOUNT
A	8'-2 1/2" X 3'-4"	MI-3540-VINTL	SGL. HANG	INSUL. LOWE	3
B	8'-2 1/2" X 3'-4"	MI-3540-VINTL	SGL. HANG	INSUL. LOWE	2
C	8'-2 1/2" X 3'-4"	MI-3540-VINTL	SGL. HANG	INSUL. LOWE	2
D	8'-2 1/2" X 3'-4"	MI-3540-VINTL	SGL. HANG	INSUL. LOWE	2
E					
F					

- ALL LINTELS CAST-CONCRETE
- ▲ 8F14 - 1B / IT X 3'-4"
 - ▲ 8F16 - 1B / IT X 4'-4"
 - ▲ 8F16 - 1B / IT X 7'-4"
 - ▲ 8F14 - 1B / IT X 4'-6"
 - ▲ 8F16 - 1B / IT X 11'-8"

INDEX:
 A-1 FLOOR & SITE PLANS
 A-2 ELEVATIONS
 E-1 ELECTRICAL PLAN
 S-1 FOUNDATIONAL PLAN
 S-2 ROOF FRAMING PLAN

THESE PLANS MEET THE REQUIREMENTS OF SECTION 904.2 OF THE 2017 FLORIDA RESIDENTIAL BUILDING CODE FOR A BASE WIND SPEED OF 139.5 MPH, RISK CATEGORY II EXPOSURE B, ENCLOSED BUILDING, INTERNAL PRESSURE COEFFICIENT 0.18.

INTERIOR ROOF ZONE
 3' ROOF EAVE ZONE & RIDGES
 3' X 3' CORNER ROOF ZONE
 INTERIOR WALL ZONE
 3' END WALL ZONE
 GARAGE DOOR

161.1 - 30.2
 161.1 - 45.7
 20.3 - 53.1
 30.0 - 33.0
 33.7 - 44.0
 18.5 - 20.2

Sheet No A-1	DUHART ULYSSES & ETHEL 332 ELLSWORTH ST. DAYTONA BEACH, FL. 32114	CERTIFIED BY: DAVID C. LEETE AR000731	HANDY HELPER DRAFTING 386-846-2450	DATE	COMM NUMBER
				REVISED	