



CITY OF BATTLE CREEK

ADDENDUM 1

IFB# 2017-077B

TITLE: 2017 Water Main Project

ADDENDUM ISSUED: March 27, 2017

The following changes, additions and deletions have been provided:

ADD the attached Hot Mix Asphalt Special Provision:

HOT MIX ASPHALT (HMA) APPLICATION ESTIMATE

DESCRIPTION

This work shall be done in accordance with the requirements of Division 5 of the MDOT 2012 Standard Specifications for Construction except as herein specified.

MATERIALS

The HMA BASE, **13A** shall have a yield of **165 pounds** per square yard and placed in lifts with a maximum thickness of 1.5-inches.

The HMA TOP, **13A** shall have a yield of **165 pounds** per square yard and placed in lifts with a maximum thickness of 1.5-inches.

Hand Patching shall be HMA, **13A**, shall have a yield of **165 pounds per square yard**, and placed in lifts with a maximum thickness of 1.5-inches.

The Performance Grade asphalt binder range shall be 58-28 for the HMA, LVSP.

The Hot Mix Asphalt Bond Coat material shall be per Section 501.03. The uniform rate of application shall be 0.05 to 0.15 gallons per square yard.

The minimum Average Wear Index (AWI) shall be 260 for top course only.

For this project the 13A HMA mixture the target air voids shall be reduced to 3.0%.

MEASUREMENT AND PAYMENT

Measurement and Payment shall be at the contract unit price per ton.