

CONSTRUCTION DOCUMENTS LUMINAIRE SCHEDULE										
TYPE	LUMINAIRE		LAMP TYPE	DESCRIPTION	MOUNTING	MANUFACTURER	CATALOG NUMBER	CONTROL PROTOCOL	ALTERNATE	REMARKS
	WATTS	VOLTS								
A	TBD	TBD BY EE	INTEGRAL 4000K LED	NOSTALGIC FLUTED 16' SINGLE LUMINAIRE STREET LIGHT WITH LED, FLOWER POT ARMS, BANNER ARMS & FLAG HOLDER - LANCASTER STYLE BASE.	POLE	UNION METAL	N1775-53/54-B21	TBD	N/A	
A1	TBD	TBD BY EE	INTEGRAL 4000K LED	NOSTALGIC FLUTED 18' TWIN LUMINAIRE STREET LIGHT WITH LED, FLOWER POT ARMS, BANNER ARMS & FLAG HOLDER - LANCASTER STYLE BASE.	POLE	UNION METAL	B2473-54-B14-Y1GF	TBD	N/A	
B	50	120	INTEGRAL RGBW LED, 2000+ LUMENS	POLE MOUNTED RGBW SPOTLIGHT LUMINAIRE WITH 8 X 60 DEGREE BEAM SPREAD, DIE-CAST ALUMINUM HOUSING WITH TEMEPRED GLASS LENS, INTEGRAL POWER SUPPLY, IP67 RATED. 12 LBS. SEE POLE DETAIL FOR QUANTITY .PROVIDE 20' TALL 6" SQUARE SMART POLE AND UNIVERSAL YOKES FOR FIXTURES: LUMENPULSE PL-T-6-S-20-COLOR-SB, PLTU	POLE	LUMENPULSE	LBL-100-RGBW-VN-LSLV-BK-DMX/RDM-UL, SNW	DMX	COLOR KINETICS, INSIGHT	COLOR TO BE CONFIRMED
B1	28	120	INTEGRAL 4000K LED, 1400 LUMENS	POLE MOUNTED WHITE SPOTLIGHT LUMINAIRE WITH 40 DEGREE FLOOD OPTIC, DIE-CAST ALUMINUM HOUSING, TEMPERED GLASS LENS, INTEGRAL POWER SUPPLY/DMX MODULE, IP67 RATED. 6 LBS. PROVIDE 20' TALL 6" SQUARE SMART POLE AND UNIVERSAL YOKES FOR FIXTURES: LUMENPULSE PL-T-6-S-20-COLOR-SB, PLTU	POLE	LUMENPULSE	LBM-X-40K-FL-WHTX-7-LBMVS-WH	DMX	INSIGHT, COLOR KINETCS	COLOR TO BE CONFIRMED.
B2	28	120	INTEGRAL 4000K LED, 1400 LUMENS	SAME AS TYPE "B1" EXCEPT WITH VISOR AND ADJUSTABLE SPREAD LENS	POLE	LUMENPULSE	LBM-X-40K-NFL-WHTX-7, LBMVSSLA-WH	DMX	INSIGHT, COLOR KINETCS	COLOR TO BE CONFIRMED
F	8	120	INTEGRAL 4000K LED, 400+ LUMENS	SUSPENDED LOW VOLTAGE CATANARY SYSTEM WITH 12' TALL ROUND TAPERED STEEL POLE AND LOW VOLTAGE LUMINAIRE WITH 4.25" DIAMETER APERTURE, 4" TALL ALUMINUM HOUSING AND DROP FROSTED ACRYLIC DECORATIVE LENS. PROVIDE REMOTE POWER SUPPLY.	CATENARY	LUMIERE	CAMBRIA PDR53209-213-10LEDXXX-12-XX-ACRYLIC HOOD	0-10V	SUBMIT FOR CONSIDERATION	POLE BY UNION METAL, SEE CUT SHEETS FOR DETAILS
H	4.6 W/FT	120	INTEGRAL 4000K LED, 200+ LUMENS/ FT	INTEGRATED ILLUMINATED STAINLESS STEEL HANDRAIL WITH EMBEDDED LINEAR LED WITH LENS, ASYMETRIC DISTRIBUTION AND LUTRON A-SERIES POWER SUPPLY IN POST. COORDINATE HEIGHT WITH ARCHITECT.	HANDRAIL	INTENSE LIGHTING	IVR15-SPI-ST-PXX-HO-40-30AS	FORWARD PHASE	COLE LIGHTING, WAGNER ARCHITECT-URAL	
J	19	120	INTEGRAL 4000K LED, 92 CRI	SURFACE MOUNTED LED CYLINDER WITH 6" DIAMETER APERTURE, 9" TALL HOUSING INTEGRAL DIMMABLE DRIVER, WIDE DISTRIBUTION AND IP 65 RATING. (PAVILION)	SURFACE	ERCO	84528-WH-92CRI	REVERSE PHASE	WE-EF	

K	100	120	INTEGRAL LED	PIPE MOUNTED LED STAGE WASH LUMINAIRE WITH NARROW AND MEDIUM LENS. WET LOCATION LISTED. PROVIDE SAFETY CABLE. (STAGE LIGHTING)	PIPE	ETC	SELD40LO-1	DMX	N/A	PROCURED BY INTEGRATOR
L	17 W/ FT	120	INTEGRAL RGBW LED, 400+ LUMENS/ FT	RECESSED INGRADE LED LINEAR LUMINAIRE WITH 10X60 OPTIC, RGBW COLOR MIXING, INTEGRAL DRIVER AND SLIP RESISTANT LENS AND IP68 RATING.	INGRADE	LUMENPULSE	LOI-120/277-48-RGBW-10X60-TS2.5-DMX/RDM-ASL	DMX	INSIGHT, COLOR KINETCS,	
L1	8.5 W/FT	120	INTEGRAL 4000K LED	SAME AS TYPE "L" EXCEPT WHITE LIGHT, ASYMETRIC WALLWASH OPTIC AND ANTI-SLIP LENS REQUIREMENT	INGRADE	LUMENPULSE	LOI-RO-120-48-40K-WW-DMX/RDM-ASL	DMX	INSIGHT, COLOR KINETICS	
L2	17 W/FT	120	INTEGRAL RGBW	SAME AS TYPE "L" EXCEPT WITH 10X10 OPTIC WITH A PRESET 5 DEGREE TILT.	INGRADE	LUMENPULSE	LOI-120/277-48-RGBW-10X60-TS5-DMX/RDM-	DMX	INSIGHT, COLOR KINETICS	
M	6	120	INTEGRAL LED	FLAGPOLE MOUNTED LED BEACON WITH INTEGRAL POWER SUPPLY.	POLE	AMERICAN BEACON	95866-006X	N/A	TBD	
P	17 W/FT	TBD BY EE	INTEGRAL LED, RGBW	SURFACE MOUNTED LINEAR LED LUMINIARE WITH 30 DEGREE OPTIC, INTEGRAL DRIVER AND POWER SUPPLIES, AND QUAD-CHROMATIC CHIP. PROVIDE DMX MODULES AS REQUIRED (32 PER MODULE)	SURFACE	INSIGHT LIGHTING	MVWII-17-RGBWq-30-SMSS-48"-120-DMXFX-TW, CDS-A	DMX	TRAXON, HYDREL	MUST MATCH "P1"
P1	17 W/FT	TBD BY EE	INTEGRAL LED RGBW	SAME AS TYPE "P" EXCEPT WITH 15 DEGREE GRAZING OPTIC.	SURFACE	INSIGHT LIGHTING	MVWII-17-RGBWq-30-SMSS-48"-120-DMXFX-TW, CDS-A	DMX	TRAXON, HYDREL	MUST MATCH "P"
R	6	24/120	INTEGRAL 4300 K LED	SPIKE MOUNTED LED LANDSCAPE SPOTLIGHT LUMINAIRE WITH 25 DEGREE OPTIC, IP65 RATING AND REMOTE DIRECT BURIAL POWER SUPPLY.	SPIKE	LUMASCAPE	LS782LED-6W4-NM-13DIM-CB, LSTDB1-300	0-10V	SUBMIT FOR CONSIDERATION	