

RUNWAY SAFETY AREA 

ROFZ RUNWAY OBSTACLE FREE ZONE

WORK AREA A (PHASE II)

WORK AREA A1 (PHASE II)

WORK AREA B (PHASE III)


200 200 100 0 400 SCALE IN FEET 1"= 200'

- 2. INSTALL TEMPORARY SEDIMENTATION EROSION CONTROL ITEMS AS REQUIRED.
- 3. INSTALL LIGHTED BARRICADES ACROSS TAXIWAYS, APRON CONNECTOR TAXIWAY AND ACROSS RUNWAY 5-23 AS SHOWN
- 4. COMPLETE PROFILE MILLING OF RUNWAY 5-23 IN PHASE I AREA. CONTRACTOR MAY COMPLETE MILLING OPERATIONS WITHIN AREA B CONCURRENTLY WITH WORK IN PHASE I AREA. ACCESS TO RUNWAY 11-29 USING CROSSING AT TAXIWAY 'B' SHALL REMAIN OPEN AT AT ALL TIMES. SEE NOTE A.
- 5. COMPLETE CRACK CLEANING AND SEALING AS REQUIRED PER SPECIFICATION P-101. CONTRACTOR MAY COMPLETE CRACK CLEANING AND SEALING WITHIN AREA B CONCURRENTLY WITH WORK IN PHASE I AREA. ACCESS TO RUNWAY 11-29 USING CROSSING AT TAXIWAY 'B' SHALL REMAIN OPEN AT ALL TIMES. SEE NOTE A.
- 6. APPLY TACK COAT AND PAVE FIRST 2" LIFT OF P-401. CONTRACTOR MAY COMPLETE PAVING OF FIRST 2" LIFT OF P-401 WITHIN AREA B CONCURRENTLY WITH WORK IN PHASE I AREA. ACCESS TO RUNWAY 11-29 USING CROSSING AT TAXIWAY 'B' SHALL REMAIN OPEN AT ALL TIMES. SEE NOTE A.

CLOSED THE CROSSING AT TAXIWAY 'C' SHALL BE OPEN TO AIRCRAFT TRAFFIC. CONTRACTOR SHALL BE REQUIRED TO COMPLETE TEMPORARY PAVEMENT TRANSITIONS TO MAINTAIN TRAFFIC, CONTRACTOR SHALL BE REQUIRED TO COMPLETE SAFETY INSPECTION AND PLACE BARRICADES AS SHOWN PRIOR TO OPENING TAXIWAY 'C' CROSSING.


- 1. ONCE FIRST LIFT OF PAVING IS COMPLETE IN PHASE II, CONTRACTOR SHALL WORK TO COMPLETE PAVING OF FIRST 2" LIFT OF PAVEMENT IN PHASE III AREA.
- 2. COMPLETE PROFILE MILLING AND CRACK CLEANING AND SEALING IN WORK AREA B.
- 3. APPLY TACK COAT AND PAVE FIRST 2" LIFT OF P-401 WITHIN WORK AREA
- 4. BY MAINTAINING THE TAXIWAY 'B' CROSSING OPEN, THE CONTRACTOR MAY CONCURRENTLY BEGIN OPERATIONS TO PAVE SECOND 2" LIFT OF P-401 STARTING AT THE RUNWAY 5 END. PAVING OPERATIONS SHALL BE PLANNED TO MINIMIZE THE NUMBER OF TRANSVERSE JOINTS IN THE FINAL LIFT OF PAVEMENT.
- 5. ONCE THE TAXIWAY 'B' CROSSING IS CLOSED, AIRCRAFT TRAFFIC TO RUNWAY 11-29 SHALL UTILIZE THE TAXIWAY 'C' CROSSING. TRANSITIONS SHALL BE COMPLETED AS REQUIRED AND BARRICADES INSTALLED IN ACCORDANCE WITH DETAILS SHOWN.
- 6. CONTRACTOR SHALL COMPLETE PROFILE MILLING OPERATIONS, CLEANING AND CRACK FILLING AND PLACEMENT OF FIRST 2" LIFT OF P-401 WITHIN WORK AREA C.
- 7. COMPLETE PAVING OF FINAL 2" LIFT OF P-401 AND ALL PAVEMENT TRANSITIONS. CONTRACTOR SHALL BEGIN FINAL LIFT OF PAVEMENT ON THE RUNWAY 5 END AND PROCEED TO THE RUNWAY 23 END MINIMIZING THE NUMBER OF JOINTS IN THE FINAL LIFT OF P-401, MAINTAINING ACCESS TO RUNWAY 11-29 AT ALL TIMES.
- 8. COMPLETE SHOULDER GRADING OPERATIONS.


- 12. AFTER CONSTRUCTION AND FINAL PUNCH LIST ITEMS ARE COMPLETED, A FINAL SAFETY INSPECTION FOR RUNWAY 5-23 AND TAXIWAYS SHALL BE COMPLETED PRIOR TO REOPENING. REMOVE BARRICADES AND CLOSURE CROSSES AND REOPEN RUNWAY 5-23 AND TAXIWAYS TO AIR OPERATIONS.
- 13. AFTER RUNWAY 5-23 IS REOPENED, RUNWAY 11-29 SHALL BE CLOSED PLACING BARRICADES AND CLOSURE CROSSES AS REQUIRED. THE TEMPORARY RELOCATED THRESHOLD SHALL BE REMOVED AND NEW MARKING WITH BEADS SHALL BE COMPLETED ON ORIGINAL RUNWAY 11 THRESHOLD MARKINGS. REMOVE BARRICADES AND CLOSURE CROSSES AND REOPEN RUNWAY 11-29 TO AIR OPERATIONS.
- 14. REMOVE ANY TEMPORARY SILT FENCE AND SEDIMENTATION CONTROL MEASURES WITHIN THE PROJECT AREA AS DIRECTED BY THE ENGINEER. RESTORE DISTURBED AREAS AND SEED AND MULCH
- 15. CONTRACTOR SHALL REMOVE ALL EQUIPMENT, MATERIALS, AND DEBRIS. REMOVE STAGING AREA. REGRADE AND RESTORE DISTURBED AREAS AND SEED AND MULCH.
- 16. AFTER SPECIFIED CURING PERIOD, CONTRACTOR SHALL COMPLETE GROOVING OPERATIONS AND APPLY FINAL APPLICATION OF MARKING WITHIN PROJECT WITH REFLECTIVE BEADS AS REQUIRED. SEE PHASE IV PHASING PLAN ON SHEET A1.9.



S

Date	DECEMBER 202
Scale	1" = 200'
Drawn	PCC
Checked	AMS
Project No.	2601-2001
Sheet No.	





200 100 0 200 600


SCALE IN FEET

1"= 200'

4. EACH MORNING COMPLETE SAFETY INSPECTION, REMOVE CLOSURE CROSSES AND BARRICADES, AND REOPEN RUNWAY 5-23 TO AIR OPERATIONS.

AFTER GROOVING AND THOROUGH CLEANING, THE CONTRACTOR SHALL HAVE ONE CALENDAR DAY FOR A TWELVE HOUR PERIOD TO COMPLETE THE FINAL MARKING INCLUDING REFLECTIVE BEADS AS REQUIRED ON RUNWAY 5-23. THE ONE DAY CLOSURE SHALL OCCUR ON EITHER A TUESDAY OR WEDNESDAY AS COORDINATED WITH THE AIRPORT MANAGEMENT. CONTRACTOR SHALL CLOSE THE RUNWAY AND TAXIWAYS BY PLACING BARRICADES AND CLOSURE CROSSES AS SHOWN ON THIS SHEET.

- 1. CLOSE RUNWAY 5-23 AND RUNWAY 11-29 BY PLACING LIGHTED CLOSURE CROSSES ON EACH END. INSTALL LIGHTED BARRICADES AS SHOWN TO CLOSE TAXIWAYS AND KEEP AIRCRAFT FROM TAXIING ON TO CLOSED RUNWAYS.
- 2. COMPLETE FINAL MARKING AND BEAD APPLICATION AS REQUIRED.
- 3. COMPLETE SAFETY INSPECTION, REMOVE CLOSURE CROSSES AND BARRICADES, AND REOPEN RUNWAY 5-23 TO AIR OPERATIONS.



Date	DECEMBER 2020
Scale	1" = 200'
Drawn	PCC
Checked	AMS
Project No.	2601-2001
Sheet No.	