
William Prokop CITY MANAGER 843-525-7070 FAX 843-525-7013



COUNCIL MEMBERS: Billy Keyserling, Mayor Mike McFee, Mayor Pro Tem Stephen Murray Philip Cromer Nan B. Sutton

BEAUFORT, SOUTH CAROLINA 29902

## City of Beaufort IFB 2020 - 115 Waterfront Park Replacement Swings Addendum 3 Updated Scope Work Specifications of Materials and Installation

This Addendum No. 3 to IFB 2020 - 115 Waterfront Park Replacements Swings is issued by the City of Beaufort Finance Department. Except as modified by this Addendum No. 3, all areas of the IFB not specifically mentioned in or affected by this Addendum shall remain unchanged.

## **Specifications of the Materials and Installation:**

- 1. Width of bench swing should be 6 ft and commercial grade construction with bolts and reinforcement hardware that must resist rust and corrosion. Any eyebolts mush closed loop.
- 2. Swing should be made of solid wood or composite that mimics wood (grain, texture, color, etc.) and is resistant to rot and insects and will withstand harsh elements such as direct sunlight, heavy rains, snow, wind and extreme temperatures. Examples of wood such wood would be cypress; cedar; white oak; ipe; teak; acacia; mahogany; redwood; shorea; Brazilian walnut; eucalyptus black locust, etc. Stainless steel screws and hardware are preferred.
- 3. Minimal maintenance requirements.
- 4. Swing hanger brackets (aka ductile swingers) must be galvanized steel.
- 5. Chains gauge must be between 3/8 to 5/16 and made of top-grade galvanized steel. Chain attachments to swing hangers must be galvanized steel Quick Link. Current swing hanger brackets on steel support beam are 6ft apart and cannot be moved.
- 6. Installation by vendor is preferred and shall be priced separately.
- 7. Delivery and installation must be completed by August 30, 2020