ADDENDUM NO. 2 TO THE CONTRACT DOCUMENTS FOR WHIRLIGIG STATION PARKING LOT IMPROVEMENTS CITY OF WILSON, NORTH CAROLINA APRIL 9, 2020

To All Bidders:

This addendum is issued to modify or clarify the previously issued bid documents and/or given for informational purposes, and is herein made a part of the bid documents. This addendum <u>must be acknowledged on the appropriate page</u> of the contract Bid Form. Failure to acknowledge this addendum may subject the bidder to disqualification of his bid. It is the responsibility of all bidders and all individual subcontractors to adhere to the following modifications, clarifications and/or information:

- Bidders to utilize Revised Bid Form dated 04/09/2020, now including unit price line items for concrete sidewalk and concrete drive apron, in the event they need to be replaced along Tarboro Street. Any damage to the existing drive aprons or sidewalks along Goldsboro Street shall be replaced to match the existing at the contractor's expense.
- 2. Bidders to refer to attached exhibit for Proposed Retaining Wall spot elevations.

END OF ADDENDUM NO. 2

Robert S. Bartlett, PE Bartlett Engineering & Surveying, PC

REVISED BID FORM - 04/09/2020 WHIRLIGIG STATION PARKING LOT IMPROVEMENTS WILSON, NC						
MOBILIZATION, BOND, INSURANCE	1	LS				
DEMO & REMOVALS, INCLUDING OFFSITE DISPOSAL	1	LS				
SAWCUT, REMOVE & REPLACE 30" CONCRETE CURB	270	LF				
GOLDSBORO STREET (PIPE TRENCH) SAWCUT, REMOVE & REPLACE EXISTING ASPHALT W/ PAVEMENT PATCH (8" CABC, 3" I19.0B, 2" SF9.5B)	240	SY				
CONNECT TO EXISTING DRAINAGE INLET	1	EA				
CONNECT TO EXISTING STORM DRAIN	2	EA				
CATCH BASIN (STANDARD)	3	EA				
OVERSIZED-DOUBLE CATCH BASIN	1	EA				
SPLITTER BOX	1	EA				
STORM DRAIN MANHOLE (5')	4	EA				
DROP INLET	1	EA				
15" RCP (O-RING)	48	LF				
18" RCP	24	LF				
18" RCP (O-RING)	180	LF				
24" RCP	210	LF				
24" RCP (O-RING)	150	LF				
30" RCP (O-RING)	16	LF				
36" RCP (O-RING)	180	LF				
REMOVE UNSUITABLE TRENCH MATERIAL	500	CY				
ADDITIONAL PIPE TRENCH STABILIZATION STONE	100	ΤN				
SELECT TRENCH BACKFILL	500	CY				
UNLOAD & INSTALL STORMTRAP PRECAST CONCRETE CHAMBER SYSTEM INCLUDING EXCAVATION, STONE BEDDING & BACKFILL (STORMTRAP SYSTEM SUPPLIED BY OWNER)	1	LS				
SAND FILTER MEDIA & UNDER DRAIN PIPING	1	LS				
ACCESS OPENINGS FRAMES AND COVERS	1	LS				
INSTALL BTL 40 REINFORCED POLYETHYLENE 8 OZ GEOTEXTILE (MATERIAL SUPPLIED BY OWNER)	1	LS				
FINE GRADING	1	LS				
3" SF9.5B ASPHALT PAVING (2-LIFTS)	1,360	ΤN				
8" CABC STONE BASE	2,480	ΤN				
GEOGRID STABILIZATION	300	SY				
30" CONCRETE CURB & GUTTER	1,140	LF				
CONCRETE WHEEL STOPS	40	EA				

REVISED BID FORM - 04/09/2020 WHIRLIGIG STATION PARKING LOT IMPROVEMENTS WILSON, NC						
6" THICK CONCRETE DUMPSTER PAD	55	SY				
4" THICK CONCRETE SIDEWALK	70	SY				
6" THICK CONCRETE DRIVE APRON	100	SY				
4" WHITE THERMOPLASTIC 90 MIL STRIPING	4,800	LF				
ADJUST EXISTING DRAINAGE LIDS/FRAMES TO FINISH GRADE	7	EA				
VALVE BOX ADJUSTMENTS TO FINISHED GRADE	1	LS				
CONCRETE RETAINING WALL W/ SAFETY RAILING	103	LF				
SIGNAGE	1	LS				
TRAFFIC CONTROL	1	LS				
TEMPORARY 20' X50' CONSTRUCTION ENTRANCE	2	EA				
TEMPORARY CONCRETE WASHOUT	1	EA				
TEMPORARY DEWATERING SILT BAG & PUMP	1	EA				
COMPOST SOX	325	LF				
SILT FENCE	300	LF				
DRAINAGE INLET PROTECTION	15	EA				
ONLY BIDS SUBMITTED ON THIS FORM WILL BE CONSIDER	TOTAL					

ONLY BIDS SUBMITTED ON THIS FORM WILL BE CONSIDERED BY THE CITY OF WILSON.

CONTRACTOR: _____

ADDRESS: _____

SIGNATURE: _____

TITLE: _____ DATE: _____

ADDENDUM NUMBERS ACKOWLEDGED: _____

