



City of Alamogordo

Engineering Department 1376 E. Ninth Street, Alamogordo, New Mexico 88310 Ph. 575 . 439 . 4220 Fax 575 . 439 . 4343

ENG-010-2018

June 4, 2018

Via: e-mail

To: All Bidders/Plan Holders

Re: **Addendum No. 2**
WASHINGTON PARK BASKETBALL COURTS RECONSTRUCTION
Public Works Bid No. 2018-005, NB1804

Addendum Number 2 is issued to provide changes and/or clarifications to the above referenced Bid as per the following:

General Items:

1. The bid opening date has changed. The bid new bid opening date will be **June 14, 2018**. Bids will be received not later than **2:00 p.m.** at which time the Bid Opening and reading of the Bids received will be in the Commission Chambers at 1376 E. Ninth Street, Alamogordo, NM.

Product Substitutions:

General Acrylics Model No. G-100-A as manufactured by Gameco, 22222 N. 22nd Avenue, Phoenix, AZ 85027, has been approved as a substitutions.

Questions Received:

- Q:** Will the general contractor need to submit proof of meeting the below requirements (in Bid Package) Technical Spec, Section 03 03 65?
- A:** The contractor performing the work shall comply with, Technical Specification, Section 03 03 65, 1.1 Quality Assurance.
- Q:** Is there a spec for the basketball goal?
- A:** Yes, see attached.

All other provisions of the Contract Documents shall remain unchanged. This addendum is hereby made part of the Contract Documents to the same extent as though contained in the original documents and itemized listings thereof.

Each bidder is required to acknowledge receipt of each addendum in Section 3 of the Bid Proposal, failure to do so could render the bid non-responsive.

Sincerely,

Project Manager

Enclosure

cc: File

FIXED HEIGHT, IN-GROUND BASKETBALL SYSTEM

1. VERTICAL POLE - Vertical pole shall be 6" square 3/16" wall steel tubing and allow for burying 48" in concrete. Pole shall have a welded watertight steel cap to seal out moisture.
2. EXTENSION ARM - Main 45 degree extension arm tube shall be 6" square 3/16" wall steel tubing and provide for a 66" extension from front of pole to face of backboard. Arm shall be designed to allow backboard to be mounted at four places top and bottom to eliminate rust streaks from forming on face of board. Structures designed to bolt through face of backboard are not considered equal.
3. EXTENSION ARM FACEPLATE - The backboard mounting plate on the pole shall be 1/4" thick and extend the full height of the backboard. A 4" square, 1/8" wall secondary arm tube shall further support the backboard mounting plate.
4. MOUNTING - Arm shall be attached to the pole by means of two 1/2" thick steel plates sandwiched around the 6" pole. One plate shall be welded to the arm, the other used as a crimp plate on the backside of the pole. Six 5/8" high strength bolts shall pass through the two plates and when tightened shall bolt the arm at the desired height. Rim height shall be adjustable from 6' to 10'.
5. CONSTRUCTION - All steel pole components shall be welded using maximum penetration, continuous weld, MIG procedure.
6. FINISH - Pole components shall have a polyester powder-coated black finish.
7. BACKBOARD - Backboard shall be 42"x 72" rectangular steel. Skin shall be 10 gauge steel with 1/4" thick vertical struts. Backboard shall have a white powdercoat finish, a 2" orange border, and have an official orange shooters square.
8. RIM - Standard rim shall be fabricated from 3/16" backplates and sideplates fully welded. Rim shall be double 5/8" diameter, high strength steel welded together at a minimum of six places. Nets shall be attached by means of a netlocking system that facilitates the use of either nylon or chain nets (nylon net included). The entire rim shall be powdercoated orange. Other rims including outdoor breakaway rims shall be available.
9. DIRECT RIM MOUNT - Rim and backboard shall be attached to the pole by passing four high strength steel bolts through the rim, backboard, and pole so that weight suspended from the rim is transferred directly to the pole structure. The backboard shall also be mounted to the pole at four places along the top and bottom, eliminating common rust streaks found on units where backboard is bolted through face.
10. WARRANTY - Pole, backboard, and standard rim shall carry a Lifetime Unconditional Warranty. Entire system weight shall be approximately 530#, minimum.
11. APPROVED BASKETBALL SYSTEMS:
 - a. Bison, 603 L Street, Lincoln, NE 68508
 - b. Mega Slam Hoops, LLC, 1141 N. Loop 1604 E., #105-117, San Antonio, TX 78232
 - c. Hercules, Pro Dunk Hoops, 22047 Lutheran Church Rd., Suite 1, Tomball, TX 77377