# Compact Track Loaders / T76 Compact Track Loader **T76 Loader Specifications & Options**

Review the T76 compact track loader specs and compare with other models.

Units US
----------

	Bobcat T76
Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	74 hp
Turbocharged Engine	

#### Performance

Rated Operating Capacity (ISO)	2,900 lb
Operating Capacity (50% of Tip)	4143 lb
Tipping Load	8285 lb
Operating Weight	10250 lb
Travel Speed	6.8 mph
Travel Speed (2-speed option)	9.2 mph
Ground Pressure (Rubber)	6.2 psi

## Capacities

Fuel Tank	31.7 gal

## Hydraulic System

System Relief @ Quick Couplers	3,500 psi
Auxiliary Std Flow	23.3 gal/min
Auxiliary High Flow	30.3 gal/min

### Dimension

Length	147.1 in
Length without Attachment	113.9 in
Length with Standard Bucket	147.1 in
Width	72.9 in
Width (with bucket)	74 in
Height	81.8 in
Height with Operator Cab	81.8 in
Height to Bucket Hinge Pin	128.3 in
Reach @ Maximum Height	39.9 in
Turning Radius	89.3 in
Length of track on ground	59.2 in
Track Width	12.6 in
Track Width - Optional	17.7 in

#### **Features**

Joystick Control	-
Air Conditioning	
Backup Alarm	• • • • • • • • • • • • • • • • • • •
BICS System (Interlock)	
Cab Heater	$\checkmark$
Operating Lights	
Suspension Seat	<ul> <li>•</li> </ul>
Two Speed Travel	$\checkmark$
Deluxe Instrumentation	$\checkmark$
Engine Shutdown	N/A
Hydraulic Bucket Positioning	$\checkmark$
High Flow Option	$\checkmark$
Auxiliary Hydraulics	-
Bob-Tach Attachment System	-
Power Bob-Tach	
ACS (Switchable Controls)	N/A
Ride Control	
Horn	• • • • • • • • • • • • • • • • • • •

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.