


# LAKELAND ATHLETIC COMPLEX PHASE ONE

9661 MEMPHIS ARLINGTON ROAD, LAKELAND, TN 38002

**CITY OF LAKELAND**  
10001 HIGHWAY 70, LAKELAND, TN

## INDEX OF DRAWINGS

SHEET NO.	DESCRIPTION
G0.01	COVER SHEET
G0.02	GENERAL NOTES
C0.41	EXISTING CONDITIONS AND DEMO PLAN
C0.42	TREE REMOVAL AND PROTECTION PLAN
C1.00	OVERALL SITE PLAN
C1.01	SITE LAYOUT PLAN
C1.02	SITE LAYOUT PLAN
C2.00	OVERALL GRADING PLAN
C2.01	GRADING PLAN
C2.02	GRADING PLAN
C2.31	INITIAL EROSION CONTROL PLAN
C2.32	INITIAL EROSION CONTROL PLAN
C2.41	INTERMEDIATE EROSION CONTROL PLAN
C2.42	INTERMEDIATE EROSION CONTROL PLAN
C2.51	FINAL EROSION CONTROL PLAN
C2.52	FINAL EROSION CONTROL PLAN
C5.01	MAINTENANCE ROAD PLAN & PROFILE
C5.02	MAINTENANCE ROAD PLAN & PROFILE
C7.01	SITE DETAILS
C7.02	SITE DETAILS
C7.03	SITE DETAILS
C7.04	SITE DETAILS
C7.21	EROSION CONTROL DETAILS
C7.22	EROSION CONTROL DETAILS
L0.01	LANDSCAPE NOTES
L1.01	LANDSCAPE PLAN
L1.02	LANDSCAPE PLAN
L7.01	LANDSCAPE DETAILS
IR1.01	IRRIGATION PLAN
IR1.02	IRRIGATION PLAN
IR1.03	IRRIGATION PLAN
IR1.04	IRRIGATION PLAN
E1.00	ELECTRICAL - LEGEND, GEN. NOTES, SCHEDULES
E1.01	ELECTRICAL - PHOTOMETRICS PLAN
E1.02	ELECTRICAL - SITE PLAN
P1.01	PLUMBING - SITE PLAN, LEGEND, GEN. NOTES



**LOCATION MAP**

NOT TO SCALE

### CITY MANAGER

SHANE HORN

### MAYOR & COMMISSIONERS

MIKE CUNNINGHAM, MAYOR

MICHELE DIAL, VICE-MAYOR

JIM ATKINSON, COMMISSIONER

RICHARD GONZALES, JR., COMMISSIONER

WESLEY WRIGHT, COMMISSIONER

THIS PROJECT IS FUNDED IN PART BY A LOCAL PARKS AND RECREATION FUND  
GRANT ADMINISTERED BY THE TENNESSEE DEPARTMENT OF ENVIRONMENT  
AND CONSERVATION RECREATION EDUCATIONAL SERVICES DIVISION



60 Germantown Court // Suite 100 // Memphis, Tennessee 38018  
PHONE (901) 755-7166 // FAX (901) 755-7844

*Eisly Howell*  
CITY ENGINEER

04-20-21  
DATE

**G0.01**  
PROJECT No.  
36953-00

COVER SHEET  
LAKELAND ATHLETIC COMPLEX  
PHASE ONE



USER:MADONLEY  
 FILE:F:\3695300\CAD\CIVIL\LOT\3695300\_C041\_EXISTING.dwg  
 SAVE:02/22/2021  
 PLOT:02/24/2021



**EXISTING LEGEND**


- PROPERTY LINE
- - - 280 EXISTING MAJOR CONTOUR
- - - 283 EXISTING MINOR CONTOUR
- SS SANITARY SEWER
- (SM) SANITARY SEWER MANHOLE
- - - VEGETATION LIMITS
- LIMITS OF DISTURBANCE
- [Hatched Box] EXISTING WETLAND
- EXISTING FENCE LINE
- [Cross-hatched Box] AREA TO BE CLEARED

**NOTES**

1. UTILITY DISCLAIMER - LOCATION OF EXISTING UTILITIES AND STRUCTURES INDICATED ARE APPROXIMATE ONLY, AND THOSE INDICATED ARE NOT NECESSARILY ALL WHICH MAY EXIST ON THE PROJECT SITE. CONTRACTOR SHALL DETERMINE ACTUAL LOCATIONS OF ALL UTILITIES AND STRUCTURES ON THE PROJECT SITE, WHETHER THEY ARE INDICATED OR NOT. CONTRACTOR SHALL ASSUME THE RESPONSIBILITY FOR ANY DAMAGE TO THE UTILITY LINES, WHETHER SHOWN ON THE CONSTRUCTION PLANS OR NOT, DURING WORK ON THE PROJECT.
2. FOR UNDERGROUND UTILITY LOCATIONS CALL 811 OR 1-800-351-1111.
3. FILED VERIFY EXISTING GRADES AND COMPARE WITH PLAN ON THIS SHEET. REPORT ALL DISCREPANCIES TO THE ENGINEER PRIOR TO STARTING CONSTRUCTION OPERATIONS.
4. SEE SHEET C1.01 FOR ASPHALT REMOVAL LIMITS.
5. ALL DEMOLITION LINES BETWEEN PROPOSED AND REMAINING PAVEMENTS SHALL BE CUT STRAIGHT AND SMOOTH.
6. SEE TREE REMOVAL AND PROTECTION PLAN SHEET C0.42.

**BARGE**  
 DESIGN SOLUTIONS

60 GERMANTOWN COURT // SUITE 100 // MEMPHIS // TENNESSEE // 38018




**EXISTING CONDITIONS & DEMO PLAN**

**LAKELAND ATHLETIC COMPLEX**

**PHASE 1**

MEMPHIS-ARLINGTON ROAD  
 LAKELAND, TENNESSEE



60' 30' 0' 60' 120'  
 SCALE: 1 INCH = 60 FEET




**Know what's below.**  
**Call before you dig.**

REVISION INFORMATION		
REV.	CHK.	DESCRIPTION
	DR.	DATE
	MD	WD
	WD	ISSUE FOR BID
	WD	04-21-21

**C0.41**

FILE NO. 3695300




TREE REMOVAL AND PROTECTION PLAN

LAKELAND ATHLETIC COMPLEX

PHASE 1

MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE



**EXISTING LEGEND**

- PROPERTY LINE
- - - 280 EXISTING MAJOR CONTOUR
- - - 283 EXISTING MINOR CONTOUR
- SS SANITARY SEWER
- ⊙ SANITARY SEWER MANHOLE
- ~ VEGETATION LIMITS
- - - LIMITS OF CLEARING
- ▨ EXISTING WETLAND
- - - EXISTING FENCE LINE
- - - TREE PROTECTION FENCE
- AREA TO BE CLEARED (BASE BID)

**PHASE 1 TREE DENSITY**

PHASE 1 AREA: 15.00 ACRES

**EXISTING PHASE 1 AREA TREES**

1,074 TREES  
34,942 DENSITY UNITS

**PHASE 1 AREA TREE REMOVAL**


606 TREES REMOVED  
18,846 DENSITY UNITS REMOVED

**REMAINING TREE COVER**


468 TREES  
16096 DENSITY UNITS

**TREE PROTECTION NOTES:**

1. ALL TREE PROTECTION FENCING SHALL BE INSTALLED PRIOR TO AND MAINTAINED THROUGHOUT THE LAND DISTURBING AND CONSTRUCTION PROCESS, AND NOT BE REMOVED UNTIL FINAL LANDSCAPING IS INSTALLED.
2. THE TREE PROTECTION AREA SHALL INCLUDE NO LESS THAN THE TOTAL AREA BENEATH THE TREE CANOPY AS DEFINED BY THE DRIPLINE OF THE TREE OR GROUP OF TREES, UNLESS PRIOR APPROVAL IS RECEIVED FROM THE CITY.
3. PROHIBITED ACTIVITIES WITHIN A TREE PROTECTION AREA INCLUDE, BUT ARE NOT LIMITED TO, PARKING, MATERIALS STORAGE, CONCRETE WASHOUT, BURN-HOLE PLACEMENT, SOIL COMPACTION AND PLACING OF WASTE MATERIAL.
4. ROOT DISTURBANCE DUE TO CUTS OR FILL SHALL NOT BE ALLOWED WITHIN A TREE PROTECTION AREA. ALL EXPOSED ROOTS ONE INCH AND GREATER IN DIAMETER AT THE EDGE OF THE TREE PROTECTION AREA SHALL BE PRUNED WITH A CLEAN CUT FLUSH TO SOIL EDGE.
5. EROSION AND SEDIMENTATION CONTROL MEASURES SHALL BE INSTALLED IN A MANNER DESIGNED TO PREVENT THE ACCUMULATION OF SEDIMENT WITHIN A TREE PROTECTION AREA.
6. ALL CLEARED TREES ARE TO BE FULLY REMOVED INCLUSIVE OF BELOW GRADE ROOT MASS.
7. ALL AREAS DESIGNATED TO BE CLEARED BY CONTRACTOR OR SELECTIVELY CLEARED ARE TO BE FLAGGED IN THE FIELD PRIOR TO CLEARING. NOTED FLAGGING LIMITS ARE TO BE APPROVED BY L.A. PRIOR TO COMMENCING CLEARING.
8. IF SO INDICATED ON THE SITE PLAN TO REMAIN, THE CONTRACTOR SHALL PROTECT ANY PLANT MATERIAL FROM DAMAGE OR ANY SCARRING. A MINIMUM AREA SHALL BE THE DRIP LINE OF THE TREE UNLESS OTHERWISE NOTED.




**1 TREE PROTECTION FENCING**  
C0.42 NTS



REV.	CHK.	DATE	DESCRIPTION

**C0.42**

FILE NO. 3695300



**SITE LEGEND**



	CONCRETE
	GRAVEL PAVEMENT
	ASPHALT PAVEMENT
	NUMBER OF PARKING SPACE

**PARKING PROVIDED**  
 PROPOSED PARKING SPACES: 89  
 PROPOSED ADA PARKING SPACES: 4  
 TOTAL PROPOSED PARKING SPACES: 93

- SITE NOTES**
- THE SITE LAYOUT SHALL BE BASED ON THE DIMENSIONS AND OTHER INFORMATION SHOWN. MINOR ADJUSTMENTS TO THE LAYOUT APPROVED BY THE ENGINEER MAY BE NEEDED IN THE FIELD TO ACHIEVE THE DESIRED ALIGNMENT WITH THE EXISTING FEATURES TO REMAIN. CONTRACTOR SHALL BE FAMILIAR WITH THE SITE AND CHECK ALL FINAL DIMENSIONS ON THE GROUND PRIOR TO CONSTRUCTION ACTIVITIES. NOTIFY THE ENGINEER IMMEDIATELY OF DISCREPANCIES FROM THE PLANS.
  - THE EXACT LOCATION OF ALL EXISTING UTILITIES SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR. CARE SHALL BE TAKEN CARE TO PROTECT ANY UTILITIES THAT ARE TO REMAIN AND ALL CONSTRUCTION SHALL BE COORDINATED WITH THE APPROPRIATE UTILITY COMPANY/AGENCY. ANY DAMAGED UTILITY SHALL BE REPAIRED/RELOCATED TO MEET LOCAL STANDARDS AT THE CONTRACTOR'S EXPENSE. CONTRACTOR SHALL HAVE ALL UTILITIES LOCATED PRIOR TO ANY CONSTRUCTION ACTIVITIES TAKING PLACE.
  - THE CONTRACTOR SHALL CUT CLEAN EDGES ON EXISTING PAVEMENT AND PROVIDE SMOOTH TRANSITION INTO PROPOSED PAVEMENT.
  - PROPOSED ACCESSIBLE PARKING SPACES SHALL NOT EXCEED 2% SLOPE IN ANY DIRECTION. CONTRACTOR SHALL NOTIFY THE ENGINEER IF THE INFORMATION ON THESE PLANS EXCEEDS THE MAXIMUM ALLOWABLE SLOPE OR THE IMPROVEMENTS CAN NOT BE CONSTRUCTED WITHIN THE MAXIMUM ALLOWABLE SLOPE LIMIT.
  - PROPOSED CONCRETE SIDEWALK ROUTES INDICATED ON THESE PLANS SHALL NOT EXCEED A LONGITUDINAL SLOPE OF 5% OR A CROSS SLOPE OF 2%. CONTRACTOR SHALL NOTIFY THE ENGINEER IF THE INFORMATION ON THESE PLANS EXCEEDS THE MAXIMUM ALLOWABLE SLOPE OR THE IMPROVEMENTS CAN NOT BE CONSTRUCTED WITHIN THE MAXIMUM ALLOWABLE SLOPE LIMIT.
  - PROPERTY LINES SHALL BE FIELD VERIFIED PRIOR TO CONSTRUCTION. GRADING AND CLEARING ALONG PROPERTY LINES SHALL BE FULLY COORDINATED WITH ADJACENT PROPERTY OWNERS.
  - IRRIGATION SOLAR POWER EQUIPMENT PAD SHALL BE 5'x6'x4" THICK, WIRE REINFORCED CONCRETE. MINOR ADJUSTMENTS TO THE FINAL LOCATION AND ORIENTATION MAY BE REQUIRED TO FIT WITH OTHER IRRIGATION EQUIPMENT AND SITE ELEMENTS. NOTIFY LANDSCAPE ARCHITECT IF LOCATION DEVIATES FROM WHAT IS SHOWN ON THESE PLANS.

**KEYNOTES**

1	3' CONCRETE SWALE	7	CONCRETE BLEACHER PAD
2	GRAVEL PARKING/ENTRY ROAD	8	24' GRAVEL ENTRY ROAD
3	CONCRETE PAVED ADA PARKING	9	14' GRAVEL MAINTENANCE ROAD
4	WOODEN SPLIT RAIL FENCE	10	12' BAR GATE
5	28' BAR GATE	11	16' BAR GATE
6	CONCRETE SIDEWALK	12	VERTICAL CURB
7	CONCRETE BLEACHER PAD	13	ASPHALT PAVEMENT
8	24' GRAVEL ENTRY ROAD	14	CONCRETE WHEEL STOPS
9	14' GRAVEL MAINTENANCE ROAD	15	CURB WIPEDOWN
10	12' BAR GATE	16	STOP SIGN
11	16' BAR GATE	17	PAVEMENT CONNECTION
12	VERTICAL CURB	18	PAVEMENT CONNECTION TO GRAVEL



**OVERALL SITE PLAN  
 LAKELAND ATHLETIC COMPLEX  
 PHASE 1  
 MEMPHIS-ARLINGTON ROAD  
 LAKELAND, TENNESSEE**




**REVISION INFORMATION**

REV.	CHK.	DATE	DESCRIPTION





USER:MADONLEY  
 FILE:F:\3695300\36953000\004\_CADD\CIVIL\PL\LOT103695300\_C100 OVERALL SITE PLAN.dwg  
 SAVE: 02/16/2021  
 PLOT: 02/16/2021

**SITE LEGEND**


-  CONCRETE
-  GRAVEL PAVEMENT
-  ASPHALT PAVEMENT

**SITE NOTES**

1. THE SITE LAYOUT SHALL BE BASED ON THE DIMENSIONS AND OTHER INFORMATION SHOWN. MINOR ADJUSTMENTS TO THE LAYOUT APPROVED BY THE ENGINEER MAY BE NEEDED IN THE FIELD TO ACHIEVE THE DESIRED ALIGNMENT WITH THE EXISTING FEATURES TO REMAIN.
2. CONTRACTOR SHALL BE FAMILIAR WITH THE SITE AND CHECK ALL FINAL DIMENSIONS ON THE GROUND PRIOR TO CONSTRUCTION ACTIVITIES. NOTIFY THE ENGINEER IMMEDIATELY OF DISCREPANCIES FROM THE PLANS.
3. THE EXACT LOCATION OF ALL EXISTING UTILITIES SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR. CARE SHALL BE TAKEN TO PROTECT ANY UTILITIES THAT ARE TO REMAIN AND ALL CONSTRUCTION SHALL BE COORDINATED WITH THE APPROPRIATE UTILITY COMPANY/AGENCY. ANY DAMAGED UTILITY SHALL BE REPAIRED/RELOCATED TO MEET LOCAL STANDARDS AT THE CONTRACTOR'S EXPENSE. CONTRACTOR SHALL HAVE ALL UTILITIES LOCATED PRIOR TO ANY CONSTRUCTION ACTIVITIES TAKING PLACE.
4. THE CONTRACTOR SHALL CUT CLEAN EDGES ON EXISTING PAVEMENT AND PROVIDE SMOOTH TRANSITION INTO PROPOSED PAVEMENT.
5. PROPOSED ACCESSIBLE PARKING SPACES SHALL NOT EXCEED 2% SLOPE IN ANY DIRECTION. CONTRACTOR SHALL NOTIFY THE ENGINEER IF THE INFORMATION ON THESE PLANS EXCEEDS THE MAXIMUM ALLOWABLE SLOPE OR THE IMPROVEMENTS CAN NOT BE CONSTRUCTED WITHIN THE MAXIMUM ALLOWABLE SLOPE LIMIT.
5. PROPOSED CONCRETE SIDEWALK ROUTES INDICATED ON THESE PLANS SHALL NOT EXCEED A LONGITUDINAL SLOPE OF 5% OR A CROSS SLOPE OF 2%. CONTRACTOR SHALL NOTIFY THE ENGINEER IF THE INFORMATION ON THESE PLANS EXCEEDS THE MAXIMUM ALLOWABLE SLOPE OR THE IMPROVEMENTS CAN NOT BE CONSTRUCTED WITHIN THE MAXIMUM ALLOWABLE SLOPE LIMIT.
6. PROPERTY LINES SHALL BE FIELD VERIFIED PRIOR TO CONSTRUCTION. GRADING AND CLEARING ALONG PROPERTY LINES SHALL BE FULLY COORDINATED WITH ADJACENT PROPERTY OWNERS.
7. ALL RADI AND DIMENSIONS ARE MEASURED TO THE FACE OF CURB WHERE PRESENT OR EDGE OF PAVEMENT OR GRAVEL WHERE CURB IS NOT PRESENT.
8. ALL RADII SHALL BE 5' UNLESS OTHERWISE NOTED.



**SITE LAYOUT PLAN  
LAKELAND ATHLETIC COMPLEX  
PHASE 1  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE**




Know what's below.  
Call before you dig.

**C1.01**  
FILE NO. 3695300




USER:MDONLEY  
FILE:F:\3695300\36953000\_CAD\CIVIL\LOT3695300\_C1.01 SITE LAYOUT PLAN.dwg  
SAVED: 02/19/2021  
PLOT: 02/19/2021

REV.	DR.	CHK.	DATE	DESCRIPTION

MATCH LINE SHEET C1.01



SITE LEGEND


-  CONCRETE
-  GRAVEL PAVEMENT
-  ASPHALT PAVEMENT

SITE NOTES

1. THE SITE LAYOUT SHALL BE BASED ON THE DIMENSIONS AND OTHER INFORMATION SHOWN. MINOR ADJUSTMENTS TO THE LAYOUT APPROVED BY THE ENGINEER MAY BE NEEDED IN THE FIELD TO ACHIEVE THE DESIRED ALIGNMENT WITH THE EXISTING FEATURES TO REMAIN.
2. CONTRACTOR SHALL BE FAMILIAR WITH THE SITE AND CHECK ALL FINAL DIMENSIONS ON THE GROUND PRIOR TO CONSTRUCTION ACTIVITIES. NOTIFY THE ENGINEER IMMEDIATELY OF DISCREPANCIES FROM THE PLANS.
3. THE EXACT LOCATION OF ALL EXISTING UTILITIES SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR. CARE SHALL BE TAKEN CARE TO PROTECT ANY UTILITIES THAT ARE TO REMAIN AND ALL CONSTRUCTION SHALL BE COORDINATED WITH THE APPROPRIATE UTILITY COMPANY/AGENCY. ANY DAMAGED UTILITY SHALL BE REPAIRED/RELOCATED TO MEET LOCAL STANDARDS AT THE CONTRACTOR'S EXPENSE. CONTRACTOR SHALL HAVE ALL UTILITIES LOCATED PRIOR TO ANY CONSTRUCTION ACTIVITIES TAKING PLACE.
4. THE CONTRACTOR SHALL CUT CLEAN EDGES ON EXISTING PAVEMENT AND PROVIDE SMOOTH TRANSITION INTO PROPOSED PAVEMENT.
5. PROPOSED ACCESSIBLE PARKING SPACES SHALL NOT EXCEED 2% SLOPE IN ANY DIRECTION. CONTRACTOR SHALL NOTIFY THE ENGINEER IF THE INFORMATION ON THESE PLANS EXCEED THE MAXIMUM ALLOWABLE SLOPE OR THE IMPROVEMENTS CAN NOT BE CONSTRUCTED WITHIN THE MAXIMUM ALLOWABLE SLOPE LIMIT.
6. PROPOSED CONCRETE SIDEWALK ROUTES INDICATED ON THESE PLANS SHALL NOT EXCEED A LONGITUDINAL SLOPE OF 5% OR A CROSS SLOPE OF 2%. CONTRACTOR SHALL NOTIFY THE ENGINEER IF THE INFORMATION ON THESE PLANS EXCEED THE MAXIMUM ALLOWABLE SLOPE OR THE IMPROVEMENTS CAN NOT BE CONSTRUCTED WITHIN THE MAXIMUM ALLOWABLE SLOPE LIMIT.
7. PROPERTY LINES SHALL BE FIELD VERIFIED PRIOR TO CONSTRUCTION. GRADING AND CLEARING ALONG PROPERTY LINES SHALL BE FULLY COORDINATED WITH ADJACENT PROPERTY OWNERS.
8. ALL RADII AND DIMENSIONS ARE MEASURED TO THE FACE OF CURB WHERE PRESENT OR EDGE OF PAVEMENT OR GRAVEL WHERE CURB IS NOT PRESENT.
9. ALL RADII SHALL BE 5' UNLESS OTHERWISE NOTED.

**BARGE**  
DESIGN SOLUTIONS

60 GERMAN TOWN COURT // SUITE 100 // MEMPHIS // TENNESSEE // 38018



SITE LAYOUT PLAN

LAKELAND ATHLETIC COMPLEX

PHASE 1

MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE


REV.	DR.	DATE	DESCRIPTION

**C1.02**  
FILE NO. 3695300

SCALE: 1 INCH = 30 FEET



Know what's below.  
Call before you dig.





**GRADING NOTES:**

1. THE EXACT LOCATION OF ALL EXISTING UTILITIES SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR. CARE SHALL BE TAKEN TO PROTECT ANY UTILITIES THAT ARE TO REMAIN AND ALL CONSTRUCTION SHALL BE COORDINATED WITH THE APPROPRIATE UTILITY COMPANY/AGENCY. ANY DAMAGED UTILITY SHALL BE REPAIRED/RELOCATED TO MEET LOCAL STANDARDS AT THE CONTRACTOR'S EXPENSE. CONTRACTOR SHALL HAVE ALL UTILITIES LOCATED PRIOR TO ANY CONSTRUCTION ACTIVITIES TAKING PLACE.
2. SOLID SOD PLAYING FIELD AREAS AND SEED ALL OTHER EARTHEN AREAS DISTURBED DURING CONSTRUCTION UNLESS OTHERWISE NOTED.
3. CONTRACTOR SHALL VERIFY SITE CONDITIONS PRIOR TO CONSTRUCTION. NOTIFY THE OWNER OF ANY VARIATIONS PRIOR TO COMMENCEMENT OF WORK.
4. PROPERTY LINES SHALL BE FIELD VERIFIED PRIOR TO CONSTRUCTION. GRADING AND CLEARING ALONG PROPERTY LINES SHALL BE FULLY COORDINATED WITH ADJACENT PROPERTY OWNERS.
5. PROPOSED ACCESSIBLE PARKING SPACES SHALL NOT EXCEED 2% SLOPE IN ANY DIRECTION. CONTRACTOR SHALL NOTIFY THE OWNER IF THE INFORMATION ON THESE PLANS EXCEEDS THE MAXIMUM ALLOWABLE SLOPE OR THE IMPROVEMENTS CAN NOT BE CONSTRUCTED WITHIN THE MAXIMUM ALLOWABLE SLOPE LIMIT.
6. PROPOSED CONCRETE SIDEWALK ROUTES INDICATED ON THESE PLANS SHALL NOT EXCEED A LONGITUDINAL SLOPE OF 5% OR A CROSS SLOPE OF 2%. CONTRACTOR SHALL NOTIFY THE ENGINEER IF THE INFORMATION ON THESE PLANS EXCEEDS THE MAXIMUM ALLOWABLE SLOPE OR THE IMPROVEMENTS CAN NOT BE CONSTRUCTED WITHIN THE MAXIMUM ALLOWABLE SLOPE LIMIT.
7. THE CONTRACTOR SHALL CUT CLEAN EDGES ON EXISTING PAVEMENT AND PROVIDE SMOOTH TRANSITION INTO PROPOSED PAVEMENT.
8. SEE SHEETS C2.31 TO C2.52 FOR EROSION CONTROL INFORMATION.
9. THE CONTRACTOR MUST IMPLEMENT ALL PROPER EROSION AND SEDIMENT CONTROL MEASURES FOR THE PROJECT AND MEET ALL LOCAL, STATE, AND FEDERAL REQUIREMENTS.

**GRADING & DRAINAGE LEGEND**


- STORM DRAIN
- 1020 EXISTING CONTOUR
- 1021 PROPOSED CONTOUR
- DRAIN INLET
- TYPE D HEADWALL
- RIP-RAP OUTLET PROTECTION
- SPOT ELEVATION
- BC BOTTOM OF CURB (GUTTER)
- TC TOP OF CURB
- FL SWALE FLOWLINE



**OVERALL GRADING PLAN**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
 MEMPHIS-ARLINGTON ROAD  
 LAKELAND, TENNESSEE

REV.	DR.	CHK.	DATE	DESCRIPTION
			04-21-21	ISSUE FOR BID






- GRADING NOTES:**
- THE EXACT LOCATION OF ALL EXISTING UTILITIES SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR. CARE SHALL BE TAKEN TO PROTECT ANY UTILITIES THAT ARE TO REMAIN AND ALL CONSTRUCTION SHALL BE COORDINATED WITH THE APPROPRIATE UTILITY COMPANY/AGENCY. ANY DAMAGED UTILITY SHALL BE REPAIRED/RELOCATED TO MEET LOCAL STANDARDS AT THE CONTRACTOR'S EXPENSE. CONTRACTOR SHALL HAVE ALL UTILITIES LOCATED PRIOR TO ANY CONSTRUCTION ACTIVITIES TAKING PLACE.
  - SOLID SOD PLAYING FIELD AREAS AND SEED ALL EARTHEN AREAS DISTURBED DURING CONSTRUCTION UNLESS OTHERWISE NOTED.
  - CONTRACTOR SHALL VERIFY SITE CONDITIONS PRIOR TO CONSTRUCTION. NOTIFY THE OWNER OF ANY VARIATIONS PRIOR TO COMMENCEMENT OF WORK.
  - PROPERTY LINES SHALL BE FIELD VERIFIED PRIOR TO CONSTRUCTION. GRADING AND CLEARING ALONG PROPERTY LINES SHALL BE FULLY COORDINATED WITH ADJACENT PROPERTY OWNERS.
  - PROPOSED ACCESSIBLE PARKING SPACES SHALL NOT EXCEED 2% SLOPE IN ANY DIRECTION. CONTRACTOR SHALL NOTIFY THE OWNER IF THE INFORMATION ON THESE PLANS EXCEEDS THE MAXIMUM ALLOWABLE SLOPE OR THE IMPROVEMENTS CAN NOT BE CONSTRUCTED WITHIN THE MAXIMUM ALLOWABLE SLOPE LIMIT.
  - PROPOSED CONCRETE SIDEWALK ROUTES INDICATED ON THESE PLANS SHALL NOT EXCEED A LONGITUDINAL SLOPE OF 5% OR A CROSS SLOPE OF 2%. CONTRACTOR SHALL NOTIFY THE ENGINEER IF THE INFORMATION ON THESE PLANS EXCEEDS THE MAXIMUM ALLOWABLE SLOPE OR THE IMPROVEMENTS CAN NOT BE CONSTRUCTED WITHIN THE MAXIMUM ALLOWABLE SLOPE LIMIT.
  - THE CONTRACTOR SHALL CUT CLEAN EDGES ON EXISTING PAVEMENT AND PROVIDE SMOOTH TRANSITION INTO PROPOSED PAVEMENT.
  - SEE SHEETS C2.31 TO C2.52 FOR EROSION CONTROL INFORMATION.
  - 3070 INLETS SHALL HAVE A CONCRETE APRON SURROUND. SEE DETAIL 2, SHEET C7.04.
  - THE CONTRACTOR MUST IMPLEMENT ALL PROPER EROSION AND SEDIMENT CONTROL MEASURES FOR THE PROJECT AND MEET ALL LOCAL, STATE, AND FEDERAL REQUIREMENTS.

**GRADING & DRAINAGE LEGEND**

1020	STORM DRAIN
1021	EXISTING CONTOUR
---	PROPOSED CONTOUR
■	DRAIN INLET
□	TYPE D HEADWALL
▤	RIP-RAP OUTLET PROTECTION
✕ 282.50	SPOT ELEVATION
BC	BOTTOM OF CURB (GUTTER)
TC	TOP OF CURB
FL	SWALE FLOWLINE

**BARGE**  
DESIGN SOLUTIONS

60 GERMANTOWN COURT // SUITE 100 // MEMPHIS // TENNESSEE // 38018



**GRADING PLAN**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE


MATCH LINE SHEET C2.02

**Structure Table**

Node	Description	Rim Elevation (ft)	Sump Elevation (ft)	Area (Ac.)	Q Design (cfs)
A1	3070 Inlet	281.18	278.18	0.75	1.30
A2	3070 Inlet	280.22	277.17	0.63	1.10
A3	3070 Inlet	280.27	276.48	0.18	0.40
A4	3070 Inlet	279.41	275.59	2.56	6.10
A5	Type 'D' HW	277.44	275.00	-	-
B1	Type 'D' HW	285.68	283.72	0.41	2.50
B2	Type 'D' HW	284.71	282.75	-	-
C1	Type 'D' HW	282.75	279.50	26.99	63.90
C2	Type 'D' HW	281.85	278.60	-	-
D1	Type 'D' HW	287.05	282.80	25.09	60.50
D2	Type 'D' HW	286.95	282.70	-	-
E1	Type 'D' HW	285.10	283.14	1.39	2.30
E2	Type 'D' HW	284.77	282.81	-	-

**Pipe Table**

Pipe Label	Upstream Node	Upstream Invert (ft)	Downstream Node	Downstream Invert (ft)	Length (ft)	Slope (ft/ft)	Size (in)	Area in Pipe	Q Design (cfs)	Q Capacity (cfs)	Pipe Type
P-1	A1	278.18	A2	277.17	202	0.0050	15	0.75	1.30	4.58	HDPE
P-2	A2	277.17	A3	276.48	138	0.0050	15	1.38	2.40	4.57	HDPE
P-3	A3	276.48	A4	275.84	127	0.0050	15	1.56	2.80	4.59	HDPE
P-4	A4	275.59	A5	275.00	53	0.0112	18	4.12	8.90	11.14	HDPE
P-5	B1	283.72	B2	282.75	49	0.0200	15	0.41	2.50	9.16	HDPE
P-6	C1	279.50	C2	278.60	24	0.0380	30	26.99	63.90	80.21	RCP
P-7	D1	282.80	D2	282.70	20	0.0050	34x53	25.09	60.50	40.60	RCP
P-8	E1	283.14	E2	282.81	33	0.0100	15	1.39	2.30	6.48	RCP



**REVISION INFORMATION**

REV.	DR.	CHK.	DATE	DESCRIPTION
1	MD	WD	04-21-21	ISSUE FOR BID

**C2.01**  
FILE NO. 3695300

USER:MDONLEY  
FILE:F:\3695300\3695300\04\_CAD\CIVIL\LOT3695300\_C201 GRADING & DRAINAGE.dwg  
SAVED:2/25/2021  
PLOT:2/24/2021


MATCH LINE SHEET C2.01

GRADING NOTES:

1. THE EXACT LOCATION OF ALL EXISTING UTILITIES SHALL BE VERIFIED IN THE FIELD BY THE CONTRACTOR. CARE SHALL BE TAKEN TO PROTECT ANY UTILITIES THAT ARE TO REMAIN AND ALL CONSTRUCTION SHALL BE COORDINATED WITH THE APPROPRIATE UTILITY COMPANY/AGENCY. ANY DAMAGED UTILITY SHALL BE REPAIRED/RELOCATED TO MEET LOCAL STANDARDS AT THE CONTRACTOR'S EXPENSE. CONTRACTOR SHALL HAVE ALL UTILITIES LOCATED PRIOR TO ANY CONSTRUCTION ACTIVITIES TAKING PLACE.
2. SOLID SOOD PLAYING FIELD AREAS AND SEED ALL EARTHEN AREAS DISTURBED DURING CONSTRUCTION UNLESS OTHERWISE NOTED.
3. CONTRACTOR SHALL VERIFY SITE CONDITIONS PRIOR TO CONSTRUCTION. NOTIFY THE OWNER OF ANY VARIATIONS PRIOR TO COMMENCEMENT OF WORK.
4. PROPERTY LINES SHALL BE FIELD VERIFIED PRIOR TO CONSTRUCTION. GRADING AND CLEARING ALONG PROPERTY LINES SHALL BE FULLY COORDINATED WITH ADJACENT PROPERTY OWNERS.
5. PROPOSED ACCESSIBLE PARKING SPACES SHALL NOT EXCEED 2% SLOPE IN ANY DIRECTION. CONTRACTOR SHALL NOTIFY THE OWNER IF THE INFORMATION ON THESE PLANS EXCEEDS THE MAXIMUM ALLOWABLE SLOPE OR THE IMPROVEMENTS CAN NOT BE CONSTRUCTED WITHIN THE MAXIMUM ALLOWABLE SLOPE LIMIT.
6. PROPOSED CONCRETE SIDEWALK ROUTES INDICATED ON THESE PLANS SHALL NOT EXCEED A LONGITUDINAL SLOPE OF 5% OR A CROSS SLOPE OF 2%. CONTRACTOR SHALL NOTIFY THE ENGINEER IF THE INFORMATION ON THESE PLANS EXCEEDS THE MAXIMUM ALLOWABLE SLOPE OR THE IMPROVEMENTS CAN NOT BE CONSTRUCTED WITHIN THE MAXIMUM ALLOWABLE SLOPE LIMIT.
7. THE CONTRACTOR SHALL CUT CLEAN EDGES ON EXISTING PAVEMENT AND PROVIDE SMOOTH TRANSITION INTO PROPOSED PAVEMENT.
8. SEE SHEETS C2.31 TO C2.52 FOR EROSION CONTROL INFORMATION.
9. 3070 INLETS SHALL HAVE A CONCRETE APRON SURROUND. SEE DETAIL 2, SHEET C7.04.
10. THE CONTRACTOR MUST IMPLEMENT ALL PROPER EROSION AND SEDIMENT CONTROL MEASURES FOR THE PROJECT AND MEET ALL LOCAL, STATE, AND FEDERAL REQUIREMENTS.


GRADING & DRAINAGE LEGEND

- 1020 STORM DRAIN
- 1021 EXISTING CONTOUR
- 1021 PROPOSED CONTOUR
- DRAIN INLET
- TYPE D HEADWALL
- RIP-RAP OUTLET PROTECTION
- 282.50 SPOT ELEVATION
- BC BOTTOM OF CURB (GUTTER)
- TC TOP OF CURB
- FL SWALE FLOWLINE



**BARGE**  
DESIGN SOLUTIONS

60 GERMANTOWN COURT // SUITE 100 // MEMPHIS // TENNESSEE // 38018




GRADING PLAN  
LAKELAND ATHLETIC COMPLEX  
PHASE 1  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE

REVISION INFORMATION			
REV.	DR.	DATE	DESCRIPTION



**C2.02**  
FILE NO. 3695300

USER:MDONLEY  
FILE:F:\3695300\3695300\CAD\CIVIL\LOT3695300\_C2.01 GRADING & DRAINAGE.dwg  
SAVED:2/25/2021  
PLOTTED:4/19/2021



## INITIAL EROSION CONTROL PLAN

### LAKELAND ATHLETIC COMPLEX

#### PHASE 1

MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE

REVISION INFORMATION		CHK.	DATE	DESCRIPTION
REV.	DR.	WD	04-21-21	ISSUE FOR BID

# C2.31

FILE NO. 3695300

### LEGEND

LIMITS OF DISTURBANCE	LOD
SILT FENCE	SF
CONCRETE WASHOUT	CW
OUTLET PROTECTION	OP
CONSTRUCTION EXIT	CO
STONE FILTER RING	FR
INLET PROTECTION	IP
DIVERSION BERM	TD
TREE PROTECTION FENCE (HIGH VISIBILITY ORANGE PLASTIC PROTECTION FENCING)	X



OFFSITE BYPASS DRAINAGE AREA = 25.1 ACRES

EXISTING WETLANDS

EXISTING WETLANDS


LIMITS OF DISTURBANCE

STREAM BUFFER

TOP OF BANK

SCOTTS CREEK


MATCH LINE SHEET C2.32



Know what's below.  
Call before you dig.


USER:MADONLEY  
FILE:F:\3695300\CAD\CIVIL\LOT3695300\_C2.31 INITIAL EROSION.dwg  
SAVED: 27/09/2021  
PLOTTED: 4/19/2021

MATCH LINE SHEET C2.31




LEGEND

- LIMITS OF DISTURBANCE
- SILT FENCE
- CONCRETE WASHOUT
- OUTLET PROTECTION
- STONE FILTER RING
- INLET PROTECTION
- DIVERSION BERM
- TREE PROTECTION FENCE (HIGH VISIBILITY ORANGE PLASTIC PROTECTION FENCING)



**INITIAL EROSION CONTROL PLAN**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
 MEMPHIS-ARLINGTON ROAD  
 LAKELAND, TENNESSEE




Know what's below.  
 Call before you dig.

REVISION INFORMATION	
REV.	DESCRIPTION

**C2.32**  
 FILE NO. 3695300

USER:MDONLEY  
 FILE:F:\3695300\3695300\04\_CAD\CIVIL\LOT\3695300\_C231 INITIAL EROSION.dwg  
 SAVED: 2/19/2021  
 PLOTTED: 4/19/2021

USER:MDONLEY  
 FILE:F:\383965\383965300\CAD\CIVIL\LOT\383965300\_C2.41 INTERMEDIATE EROSION.dwg  
 SAVED: 27/10/2021  
 PLOTTED: 4/10/2021



**LEGEND**

- LIMITS OF DISTURBANCE: L.O.D.
- SILT FENCE: SF
- CONCRETE WASHOUT: CW
- OUTLET PROTECTION: OP
- CONSTRUCTION EXIT: CO
- STONE FILTER RING: FR
- INLET PROTECTION: IP
- DIVERSION BERM: DB
- BASIN LIMITS: [Symbol]
- TREE PROTECTION FENCE (HIGH VISIBILITY ORANGE PLASTIC PROTECTION FENCING): T.P.F.


**BARGE**  
 DESIGN SOLUTIONS

60 GERMANTOWN COURT // SUITE 100 // MEMPHIS // TENNESSEE // 38018




INTERMEDIATE EROSION CONTROL PLAN  
 LAKELAND ATHLETIC COMPLEX  
 PHASE 1  
 MEMPHIS-ARLINGTON ROAD  
 LAKELAND, TENNESSEE

REVISION INFORMATION	
REV.	DESCRIPTION



Know what's below.  
 Call before you dig.

**C2.41**  
 FILE NO. 3695300



INTERMEDIATE EROSION CONTROL PLAN


LAKELAND ATHLETIC COMPLEX

PHASE 1  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE

REV.	DR.	CHK.	DATE	DESCRIPTION
			04-21-21	ISSUE FOR BID


**C2.42**  
FILE NO. 3695300

MATCH LINE SHEET C2.41




**LEGEND**

- LIMITS OF DISTURBANCE: LOD (dashed line)
- SILT FENCE: SF (dashed line with 'SF' label)
- CONCRETE WASHOUT: CW (rectangle with 'CONCRETE WASHOUT' text)
- OUTLET PROTECTION: OP (rectangle with 'OP' text)
- CONSTRUCTION EXIT: CO (rectangle with 'CONSTRUCTION EXIT' text)
- STONE FILTER RING: FRI (rectangle with 'STONE FILTER RING' text)
- INLET PROTECTION: IP (rectangle with 'INLET PROTECTION' text)
- DIVERSION BERM: TD (dashed line with 'TD' label)
- BASIN LIMITS: (dashed line)
- TREE PROTECTION FENCE (HIGH VISIBILITY ORANGE PLASTIC PROTECTION FENCING): (line with 'X' markers)



Know what's below.  
Call before you dig.

USER: MADONLEY  
 FILE: F:\38\3895300\CAD\CIVIL\LOT\3895300\_C251\_FINAL\_EROSION.dwg  
 SAVED: 27/09/2021  
 PLOTTED: 4/10/2021



**LEGEND**


- LIMITS OF DISTURBANCE ——— LOD
- SILT FENCE [SF] ———
- CONCRETE WASHOUT [CW] CONCRETE WASHOUT
- OUTLET PROTECTION [OP] OUTLET PROTECTION
- CONSTRUCTION EXIT [CO] CONSTRUCTION EXIT
- STONE FILTER RING [FR] STONE FILTER RING
- INLET PROTECTION [IP] INLET PROTECTION
- PERMANENT SEEDING [++] PERMANENT SEEDING
- PERMANENT SOD [x] PERMANENT SOD
- TURF REINFORCEMENT MAT [grid] TURF REINFORCEMENT MAT
- ASPHALT PAVING [solid grey] ASPHALT PAVING
- CONCRETE PAVING [dotted] CONCRETE PAVING
- GRAVEL DRIVE/PARKING [stippled] GRAVEL DRIVE/PARKING
- TREE PROTECTION FENCE (HIGH VISIBILITY ORANGE PLASTIC PROTECTION FENCING) [x-x-x-x] TREE PROTECTION FENCE (HIGH VISIBILITY ORANGE PLASTIC PROTECTION FENCING)



FINAL EROSION CONTROL PLAN  
 LAKELAND ATHLETIC COMPLEX  
 PHASE 1  
 MEMPHIS-ARLINGTON ROAD  
 LAKELAND, TENNESSEE


REV.	DR.	CHK.	DATE	DESCRIPTION

MATCH LINE SHEET C2.52




Know what's below.  
 Call before you dig.

**C2.51**  
 FILE NO. 3695300



LEGEND

LIMITS OF DISTURBANCE	LOD
SILT FENCE	SF
CONCRETE WASHOUT	CW
OUTLET PROTECTION	OP
CONSTRUCTION EXIT	CE
STONE FILTER RING	SF
INLET PROTECTION	IP
PERMANENT SEEDING	+
PERMANENT SOD	+
TURF REINFORCEMENT MAT	+
ASPHALT PAVEMENT	+
CONCRETE PAVING	+
GRAVEL DRIVE/PARKING	+
TREE PROTECTION FENCE (HIGH VISIBILITY ORANGE PLASTIC PROTECTION FENCING)	+




Know what's below.  
Call before you dig.





FINAL EROSION CONTROL PLAN  
LAKELAND ATHLETIC COMPLEX  
PHASE 1  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE

REVISION INFORMATION	
REV.	DESCRIPTION

C2.52  
FILE NO. 3695300










**MAINTENANCE ROAD PLAN & PROFILE**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
 MEMPHIS-ARLINGTON ROAD  
 LAKELAND, TENNESSEE

REV.	DR.	CHK.	DATE	DESCRIPTION
		WD	04-21-21	ISSUE FOR BID



Know what's below.  
 Call before you dig.

**C5.01**  
 FILE NO. 3695300




Know what's below.  
 Call before you dig.

REVISION INFORMATION			
REV.	DR.	CHK.	DATE
		WD	04-21-21
			ISSUE FOR BID


**MAINTENANCE ROAD PLAN & PROFILE**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
 MEMPHIS-ARLINGTON ROAD  
 LAKELAND, TENNESSEE

**C5.02**  
 FILE NO. 3695300



**BARGE**  
 DESIGN SOLUTIONS

60 GERMANTOWN COURT // SUITE 100 // MEMPHIS // TENNESSEE // 38018




**SITE DETAILS**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE

REVISION INFORMATION			
REV.	DR.	DATE	DESCRIPTION




Know what's below.  
Call before you dig.




- NOTES:
- EXPANSION JOINTS SHALL BE SPACED AT 50' O.C. SEE TYPICAL EXPANSION JOINT DETAILS.
  - PROVIDE 3/4" - 3/4" CONTRACTION JOINTS AT 10' ON CENTER. JOINTS ADJACENT TO CONCRETE PAVEMENT (E.G. SIDEWALK) TO MATCH PAVEMENT JOINTS.
  - EXACT CURB DIMENSIONS MAY BE ALTERED SLIGHTLY TO FIT STANDARD EXTRUDED CURB MACHINES, BUT SUCH VARIANCES MUST BE APPROVED BY THE ENGINEER. SUBMIT PROPOSED CURB TEMPLATE FOR APPROVAL.
  - SEE TYPICAL CONCRETE PAVEMENT DETAIL FOR PAVEMENT INFORMATION.
  - PROVIDE EXPANSION JOINT BETWEEN CURB AND CONCRETE PAVEMENT PER TYPICAL DETAILS.
  - CONCRETE AND CONSTRUCTION TO CONFORM TO REQUIREMENTS OF THE TDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, CURRENT EDITION.

**12 VERTICAL CURB**  
C7.01 SCALE: NTS




NOTE: STOP SIGN PER MUTCD STANDARD R1-1. FOLLOW CITY OF LAKELAND STANDARDS FOR SIGN INSTALLATION.

**13 STOP SIGN & STOP BAR**  
C7.01 SCALE: NTS




- NOTES:
- FOR PREPARATION OF PAVEMENT SUBGRADE, FILL PLACED WITHIN 8 INCHES OF FINISHED SUBGRADE ELEVATION IN AREAS TO BE PAVED SHOULD BE COMPACTED TO AT LEAST 98% OF MATERIAL'S MAXIMUM STANDARD PROCTOR DRY DENSITY (ASTM D698). FILL PLACED BELOW THIS LEVEL SHOULD BE COMPACTED TO AT LEAST 95% OF MATERIAL'S MAXIMUM DRY DENSITY.
  - AFTER PROOFROLLING WITH A LOADED TANDEM AXLE DUMP TRUCK AND REPAIRING DEEP SUBGRADE DEFICIENCIES, ENTIRE SUBGRADE SHOULD BE SCARIFIED TO DEPTH OF 8 INCHES AND UNIFORMLY COMPACTED TO AT LEAST 98% OF STANDARD PROCTOR.
  - GRAVEL BASE COURSE MIXTURES SHOULD CONFORM TO REQUIREMENTS OF SECTION 303 OF TDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.
  - PORTLAND CEMENT CONCRETE PAVEMENT MIXTURE SHALL BE IN ACCORDANCE WITH SECTION 501 OF TDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.
  - CONTRACTOR MAY NEED TO INCREASE CONCRETE AND BASE DEPTHS TO MATCH EXISTING CONDITIONS. CONTRACTOR TO FIELD VERIFY EXISTING PAVEMENT SECTION PRIOR TO CONSTRUCTION AND REPORT TO ENGINEER.

**8 CONCRTE PAVEMENT**  
C7.01 SCALE: NTS




- NOTES:
- SEE DETAIL 10 THIS SHEET FOR EXPANSION & CONTROL JOINT DETAILS.
  - LONGITUDINAL SLOPES ALONG SIDEWALK SHALL NOT EXCEED 5%. NOTIFY ENGINEER IF THE INFORMATION ON THESE PLANS DO NOT MEET THIS REQUIREMENT OR IF IMPROVEMENTS CAN NOT BE CONSTRUCTED TO THIS REQUIREMENT.
  - SIDEWALK CROSS SLOPE SHALL NOT EXCEED 2%. NOTIFY ENGINEER IF THE INFORMATION ON THESE PLANS DO NOT MEET THIS REQUIREMENT OR IF IMPROVEMENTS CAN NOT BE CONSTRUCTED TO THIS REQUIREMENT.

**9 CONCRETE SIDEWALK**  
C7.01 SCALE: NTS




NOTE: LOCATE EXP. JOINTS @ 24' (TYP.) OR AS INDICATED ON PLAN  
NOTE: LOCATE CONTRACTION JOINTS @ A DISTANCE EQUAL TO WIDTH OF WALK, OR AS INDICATED ON PLAN.

**10 SIDEWALK EXPANSION AND CONTROL JOINT DETAILS**  
C7.01 SCALE: NTS




**11 CURB WIPEDOWN**  
C7.01 SCALE: NTS




- NOTES:
- FOR PREPARATION OF SUBGRADE, SEE GEOTECHNICAL ENGINEER'S RECOMMENDATIONS.
  - MINERAL AGGREGATE BASE TYPE "A" GRADE "D" IN ACCORDANCE WITH TDOT STANDARDS.
  - DENSITY REQUIREMENTS FOR COMPACTION PER TDOT STANDARDS.

**4 GRAVEL MAINTENANCE ROAD**  
C7.01 SCALE: NTS




- NOTES:
- FOR PREPARATION OF PAVEMENT SUBGRADE, FILL PLACED WITHIN 8 INCHES OF FINISHED SUBGRADE ELEVATION IN AREAS TO BE PAVED SHOULD BE COMPACTED TO AT LEAST 98% OF MATERIAL'S MAXIMUM STANDARD PROCTOR DRY DENSITY (ASTM D698). FILL PLACED BELOW THIS LEVEL SHOULD BE COMPACTED TO AT LEAST 95% OF MATERIAL'S MAXIMUM DRY DENSITY.
  - AFTER PROOFROLLING WITH A LOADED TANDEM AXLE DUMP TRUCK AND REPAIRING DEEP SUBGRADE DEFICIENCIES, ENTIRE SUBGRADE SHOULD BE SCARIFIED TO DEPTH OF 8 INCHES AND UNIFORMLY COMPACTED TO AT LEAST 98% OF STANDARD PROCTOR.
  - GRAVEL BASE COURSE MIXTURES SHOULD CONFORM TO REQUIREMENTS OF SECTION 903.5 OF TDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.
  - DEPTH OF GRAVEL MAY INCREASE AND SUBGRADE PREPARATION SUBJECT TO CHANGE PER GEOTECHNICAL ENGINEER'S REPORT.


**5 ENTRY ROAD & PARKING SECTION**  
C7.01 SCALE: NTS



**6 CONCRETE WHEELSTOP**  
C7.01 SCALE: NTS




**7 CONCRETE SWALE**  
C7.01 SCALE: NTS




PAVEMENT LAYER	PAVEMENT THICKNESS
ASPHALTIC CONCRETE SURFACE	1.5"
BINDER COURSE	2"
COMPACTED MINERAL AGGREGATE BASE	8"

- NOTES:
- FOR PREPARATION OF PAVEMENT SUBGRADE, SEE GEOTECHNICAL ENGINEER'S RECOMMENDATIONS.
  - ASPHALTIC CONCRETE SURFACE GRADE "E" (PG64-22) LIMESTONE, MATERIAL AND INSTALLATION IN ACCORDANCE WITH TDOT STANDARDS.
  - MINERAL AGGREGATE BASE TYPE "A" GRADE "D" IN ACCORDANCE WITH TDOT STANDARDS.
  - DENSITY REQUIREMENTS FOR COMPACTION PER TDOT STANDARDS.
  - BINDER COURSE GRADE "B-M".
  - FOR PREPARATION OF PAVEMENT SUBGRADE, FILL PLACED WITHIN 8 INCHES OF FINISHED SUBGRADE ELEVATION IN AREAS TO BE PAVED SHOULD BE COMPACTED TO AT LEAST 98% OF MATERIAL'S MAXIMUM STANDARD PROCTOR DRY DENSITY (ASTM D698). FILL PLACED BELOW THIS LEVEL SHOULD BE COMPACTED TO AT LEAST 95% OF MATERIAL'S MAXIMUM DRY DENSITY.
  - AFTER PROOFROLLING WITH A LOADED TANDEM AXLE DUMP TRUCK AND REPAIRING DEEP SUBGRADE DEFICIENCIES, ENTIRE SUBGRADE SHOULD BE SCARIFIED TO DEPTH OF 8 INCHES AND UNIFORMLY COMPACTED TO AT LEAST 98% OF STANDARD PROCTOR.
  - GRAVEL BASE COURSE MIXTURES SHOULD CONFORM TO REQUIREMENTS OF SECTION 303 OF TDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.
  - ASPHALTIC BINDER COURSE MIXTURES SHALL BE IN ACCORDANCE WITH TYPE REFERENCED IN SECTION 307 OF TDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.
  - ASPHALTIC SURFACE COURSE MIXTURES SHALL BE IN ACCORDANCE WITH TYPE REFERENCED IN SECTION 411 OF TDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.
  - PROVIDE PRIME COAT AND TACK COAT TO FACE OF CURB WHERE CURB CONTACTS ASPHALT.

**1 ASPHALT PAVEMENT**  
C7.01 SCALE: NTS




**2 PAVEMENT CONNECTION**  
C7.01 SCALE: NTS




**3 PAVEMENT CONNECTION TO GRAVEL DRIVEWAY**  
C7.01 SCALE: NTS




**SITE DETAILS**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE




**1 PIPE BOLLARD DETAIL**  
C7.02 SCALE: NTS




**2 BIKE HOOP DETAIL**  
C7.02 SCALE: NTS




**3 TRASH RECEPTACLE DETAIL**  
C7.02 SCALE: NTS



**4 ADA PARKING SIGN DETAIL**  
C7.02 SCALE: NTS



**5 ENLARGED PLAN**  
C7.02



NOTE:  
1. TO BE INSTALLED PER MANUFACTURER'S SPECIFICATIONS  
2. SEE CIVIL SITE PLAN FOR LOCATION INFORMATION


NOTE:  
1. ALL ACCESSIBLE SPACES SHALL BE SIGNED WITH STANDARD ADA PARKING.  
2. SIGNS SHALL BE PER CITY OF LAKELAND STANDARD SIGNS AND REQUIREMENT.  
3. ACCESSIBLE PARKING SPACE AND ACCESS AISLE DIMENSIONS SHALL BE AS INDICATED ON THESE PLANS. STRIPING SHALL BE PROVIDED PER LOCAL CODE REQUIREMENTS. SLOPES SHALL NOT EXCEED 2% IN ANY DIRECTION ACROSS THE PARKING SPACE & ACCESS AISLE.

NOTES CONTINUED:


- DIMENSIONS ARE TO THE CENTERLINE OF WHITE MARKINGS, UNLESS OTHERWISE SHOWN.
- INTERIOR BLUE MARKINGS ARE SUPPLEMENTAL AND SHALL BE TINTED TO MATCH SHADE 15180 OF FEDERAL STANDARDS 595A.
- AN ACCESS AISLE IS REQUIRED FOR EACH ACCESSIBLE SPACE THAT IS NOT A PARALLEL PARKING SPACE.
- ACCESSIBLE AISLE TO BE LOCATED PASSENGER SIDE FOR SOLITARY ADA PARKING SPACES AND ALL VAN PARKING SPACES.
- PAVEMENT SYMBOL SHALL BE 3" HIGH AND WHITE IN COLOR.
- IF NO CURBING IS SPECIFIED IN THE PLANS, WHEEL STOPS SHALL BE USED TO DELINEATE PARKING SPACES. SEE LAYOUT.
- STALL DEPTH IS TO ACCOUNT FOR 2' VEHICLE OVERHANG AS MEASURED FROM FACE OF CURB OR FACE OF WHEEL STOP.



Know what's below.  
Call before you dig.




**SITE DETAILS**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE




- NOTES:**
1. CONTRACTOR TO SUBMIT SHOP DRAWINGS FOR ENTIRE GATE SYSTEM TO A/E FOR APPROVAL PRIOR TO INSTALLATION.
  2. CONTRACTOR SHALL FIELD VERIFY GATE LOCATION CONDITIONS PRIOR TO SUBMITTING SHOP DRAWINGS.
  3. ALL COMPONENTS TO BE PREFABRICATED TO EXTENT POSSIBLE.
  4. ALL WELDS TO BE FULL CIRCUMFERENCE WELDS.
  5. GRIND ALL EXPOSED EDGES TO A RADIUS.
  6. ALL EXPOSED METAL SHALL SHOP PRIME AND FIELD PAINTED W/ MINIMUM 2 COATS OF PAINT. COLOR SHALL BE SAFETY YELLOW.
  7. INSTALL KEEPER POSTS TO SECURE GATES IN OPEN POSITION.

**1** DOUBLE SWING BAR GATE  
C7.03 SCALE: NTS




- NOTES:**
1. CONTRACTOR TO SUBMIT SHOP DRAWINGS FOR ENTIRE GATE SYSTEM TO A/E FOR APPROVAL PRIOR TO INSTALLATION.
  2. CONTRACTOR SHALL FIELD VERIFY GATE LOCATION CONDITIONS PRIOR TO SUBMITTING SHOP DRAWINGS.
  3. ALL COMPONENTS TO BE PREFABRICATED TO EXTENT POSSIBLE.
  4. ALL WELDS TO BE FULL CIRCUMFERENCE WELDS.
  5. GRIND ALL EXPOSED EDGES TO A RADIUS.
  6. ALL EXPOSED METAL SHALL SHOP PRIME AND FIELD PAINTED W/ MINIMUM 2 COATS OF PAINT. COLOR SHALL BE SAFETY YELLOW.

**3** BAR GATE HINGE POST DETAIL  
C7.03 SCALE: NTS



- NOTES:**
1. CONTRACTOR TO SUBMIT SHOP DRAWINGS FOR ENTIRE GATE SYSTEM TO A/E FOR APPROVAL PRIOR TO INSTALLATION.
  2. CONTRACTOR SHALL FIELD VERIFY GATE LOCATION CONDITIONS PRIOR TO SUBMITTING SHOP DRAWINGS.
  3. ALL COMPONENTS TO BE PREFABRICATED TO EXTENT POSSIBLE.
  4. ALL WELDS TO BE FULL CIRCUMFERENCE WELDS.
  5. GRIND ALL EXPOSED EDGES TO A RADIUS.
  6. ALL EXPOSED METAL SHALL SHOP PRIME AND FIELD PAINTED W/ MINIMUM 2 COATS OF PAINT. COLOR SHALL BE SAFETY YELLOW.
  7. INSTALL KEEPER POSTS TO SECURE GATES IN OPEN POSITION.

**2** SINGLE SWING BAR GATE  
C7.03 SCALE: NTS



- NOTES:**
1. ALL FENCE MATERIALS SHALL BE PRESSURE TREATED LUMBER. COLOR TO BE NATURAL.
  2. FENCE CONSTRUCTION SHALL BE DOWELED POST AND RAIL.
  3. CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR APPROVAL.



**4** WOODEN SPLIT RAIL FENCE  
C7.03 SCALE: NTS



Know what's below.  
Call before you dig.


REV.	DR.	CHK.	DATE	DESCRIPTION
		WD	04-21-21	ISSUE FOR BID

**C7.03**  
FILE NO. 3695300




1 3070 INLET  
C7.04 N.T.S.

NOTES:  
1. 3070 INLET STRUCTURE IS THE SAME AS THE STANDARD CITY OF MEMPHIS NO. 10 INLET  
2. SEE DETAIL 2 THIS SHEET FOR INLET APRONS REQUIRED AROUND 3070 INLETS.




GRATE TOP DETAIL  
N.T.S.

ESTIMATED WEIGHTS  
FRAME: 170 LBS.  
GRATE: 156 LBS.  
TOTAL: 326 LBS.




PLAN VIEW  
N.T.S.


NOTE: EACH CORNER OF THE FRAME AND GRATE IS TO BE GROPPED AT A DEGREE ANGLE ONE-INCH ON A DIAGONAL.




SECTION A-A  
N.T.S.



FRAME EDGE DETAIL  
N.T.S.



GRATE EDGE DETAIL  
N.T.S.




NOTES:

- FOR INLET STRUCTURE CONSTRUCTION SEE THE CITY OF MEMPHIS DESIGN STANDARD FOR A NO. 10 INLET
- INLET CAPACITY (WITH 50% TRASH BLOCKAGE)  

H (FT.)	Q (C.F.S.)
1.0	6.6
0.8	0.6
0.6	5.6
	4.4
- MAXIMUM TRIBUTARY DRAINAGE AREA ALLOWED IN INLET = 2 AREAS
- NO TWIN 3070 INLETS ALLOWED.

3 3070 INLET GRATE  
C7.04 N.T.S.



2 INLET APRON  
C7.04 N.T.S.






TABLE OF DIMENSION AND DIAMETERS

DIA.	18"	21"	24"	30"	36"	42"	48"	54"	60"	66"	72"
B	11-11 1/2"	2-8 1/4"	2-5 1/4"	2-8 1/2"	3-2"	2-9 1/2"	4-4"	4-10 1/2"	5-0"	6-0"	6-8 1/2"
D	1-1 1/2"	1-10 1/2"	2-1 1/2"	2-5"	3-2"	3-7"	4-2"	4-8"	5-4"	6-0"	7-2"
E	1-8 1/2"	2-0 1/2"	2-3 1/2"	2-7"	3-2"	3-9"	4-4"	4-10"	5-0"	6-2"	7-4"
H	3-1 1/2"	3-4 1/2"	3-7 1/2"	3-11"	4-0"	5-1"	6-3"	6-10"	7-0"	8-1"	8-8"
J	2-2 1/2"	2-10 1/2"	3-1 1/2"	3-5 1/2"	4-0 1/2"	4-10 1/2"	5-2 1/2"	5-9 1/2"	6-4 1/2"	7-0 1/2"	8-2 1/2"
K	4-10 1/2"	5-6 1/2"	6-0 1/2"	6-8 1/2"	7-11 1/2"	8-2 1/2"	10-5 1/2"	11-8 1/2"	12-11 1/2"	14-3 1/2"	15-6 1/2"
N	7-11 1/2"	8-9 1/2"	9-7 1/2"	10-4 1/2"	12-4 1/2"	14-2 1/2"	16-0 1/2"	17-10 1/2"	19-4 1/2"	21-8 1/2"	23-5 1/2"
W	5-3 1/2"	5-11"	6-5 1/2"	7-1 1/2"	8-4 1/2"	9-7 1/2"	10-10 1/2"	12-1 1/2"	13-4 1/2"	14-8 1/2"	17-2 1/2"
X	3-10 1/4"	4-4 1/2"	4-10 1/2"	5-6"	6-4"	7-2"	8-0"	9-0"	10-10"	12-0"	14-2"
Y	3-2 1/4"	7-1 1/2"	7-1 1/2"	8-10 1/2"	8-10 1/2"	12-4 1/2"	14-4 1/2"	16-2 1/2"	18-4 1/2"	20-2 1/2"	22-8 1/2"



4 TYPE 'D' HEADWALL  
C7.04 N.T.S.




**SITE DETAILS**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE


REV.	CHK.	DATE	DESCRIPTION
1	WD	04-21-21	ISSUE FOR BID



Know what's below.  
Call before you dig.



**EROSION CONTROL DETAILS**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE




- NOTES:**
- STONE FOR A STABILIZED CONSTRUCTION EXIT SHALL BE 2 TO 4 INCH STONE, RECLAIMED STONE, OR RECYCLED CONCRETE EQUIVALENT.
  - THE LENGTH OF THE STABILIZED ENTRANCE SHALL NOT BE LESS THAN 50 FEET.
  - THE THICKNESS OF THE STONE FOR THE STABILIZED ENTRANCE SHALL NOT BE LESS THAN 6 INCHES.
  - THE WIDTH OF THE ENTRANCE SHALL NOT BE LESS THAN THE FULL WIDTH OF THE ENTRANCE WHERE INGRESS OR EGRESS OCCURS OR 20 FEET, WHICH EVER IS GREATER.
  - GEOTEXTILE FILTER CLOTH SHALL BE PLACED OVER THE ENTIRE AREA PRIOR TO PLACING THE STONE. FABRIC SHALL BE 12 OZ./S.Y. NON-WOVEN.
  - ALL SURFACE WATER THAT IS FLOWING TO OR DIVERTED TOWARD THE CONSTRUCTION ENTRANCE SHALL BE PIPED BENEATH THE ENTRANCE. IF PIPING IS IMPRACTICAL, A BERM WITH 5:1 SLOPES THAT CAN BE CROSSED BY VEHICLES MAY BE SUBSTITUTED FOR THE PIPE.
  - THE ENTRANCE SHALL BE MAINTAINED IN A CONDITION THAT WILL PREVENT TRACKING OR FLOWING OF SEDIMENT ONTO PUBLIC RIGHTS-OF-WAY. THIS MAY REQUIRE PERIODIC TOPDRESSING WITH ADDITIONAL STONE AS CONDITIONS DEMAND AND REPAIR AND/OR CLEANOUT OF ANY MEASURES USED TO TRAP SEDIMENT. ALL SEDIMENT SPILLED, WASHED, OR TRACKED ONTO PUBLIC RIGHT-OF-WAY MUST BE REMOVED PROMPTLY.
  - IF APPLICABLE, DIVERSION DITCH AND SEDIMENT TRAP SHALL BE LOCATED AS SHOWN IN PLANS. REPRESENTATION IN THE ABOVE DETAIL IS FOR GENERAL REFERENCE.

**1** CONSTRUCTION EXIT  
C7.21 SCALE: NTS

CO

BSI-ECR-7008


- NOTES:**
- FILTER CLOTH SHALL MEET THE REQUIREMENTS OF THE STANDARD SPECIFICATION FOR GEOTEXTILES AASHTO DESIGNATION: M288, SEDIMENT CONTROL, SELF SUPPORTED.
  - THE FILTER MATERIAL SHALL BE STAPLED TO THE STAKES. HEAVY DUTY WIRE STAPLES WITH 1/2 INCH WIDTH SHALL BE USED AND EVENLY SPACED WITH AT LEAST FOUR PER POST FOR SILT FENCES AND THREE (3) PER POST FOR FILTER BARRIERS. FILTER MATERIAL SHALL NOT BE STAPLED TO EXISTING TREES.
  - MINIMUM (2" NOMINAL X 2" NOMINAL) - (1.5" ACTUAL X 1.5" ACTUAL) (2.25 SQ. IN.) HARDWOOD POST (OAK OR HICKORY) - LENGTH 48" OR MINIMUM 1.33 LB./FT. STEEL POST (STD. OR U SECTION).
  - WHEN STEEL POSTS ARE USED THEY SHALL HAVE A PROTECTION FOR FASTENING WIRE TO THEM. THE WIRE FASTENERS SHOULD BE EVENLY SPACED WITH AT LEAST FIVE PER POST.
  - ACCUMULATED SEDIMENT SHALL BE REMOVED WHEN 12" DEEP. INSTALL FENCE ALONG CONTOUR (NEVER UP AND DOWN SLOPE).
  - SILT FENCE SHALL BE MAINTAINED UNTIL CONTRIBUTING AREA IS STABILIZED WITH PAVEMENT OR VEGETATION. ALL FENCING SHALL BE REMOVED AFTER STABILIZATION AND DISPOSED OF IN AN APPROVED LANDFILL.



**2** SILT FENCE  
C7.21 SCALE: NTS

SF


BSI-ECR-7014



**3** CONCRETE WASHOUT  
C7.21 SCALE: NTS


CW

BSI-ECR-7005



**4** INLET PROTECTION  
C7.21 SCALE: NTS


IP



**5** STONE FILTER RING  
C7.21 SCALE: NTS

FR

BSI-ECR-7015




- NOTES:**
- $d_{50} = 12"$  (NSA NO. R-6).
  - MIN. DEPTH OF RIP-RAP = 18".
  - 10 OZ./SQ. YD. (MIN.) NON-WOVEN GEOTEXTILE OR FILTER STONE BLANKET (NSA FS-3) SHALL BE INSTALLED BENEATH RIP-RAP.

**6** RIP-RAP OUTFALL APRON  
C7.21 SCALE: NTS

OP




REVISION INFORMATION		CHK.	DATE	DESCRIPTION
REV.	DR.	MD	WD	ISSUE FOR BID
			04-21-21	



NOTES:  
 1. CONSTRUCT DIVERSION TO PROVIDE POSITIVE DRAINAGE WITH A MINIMUM RUNNING SLOPE OF 1% IN THE DIRECTION INDICATED ON PLANS.

1 DIVERSION BERM  
 C7.22 SCALE: NTS

TD



**EROSION CONTROL DETAILS**

**LAKELAND ATHLETIC COMPLEX**

**PHASE 1**

MEMPHIS-ARLINGTON ROAD  
 LAKELAND, TENNESSEE



Know what's below.  
 Call before you dig.

**C7.22**  
 FILE NO. 3695300

REV.		DR.		CHK.		DATE		DESCRIPTION
							04-21-21	ISSUE FOR BID



GENERAL NOTES

- 1. CONTRACTOR IS RESPONSIBLE FOR CONDUCTING SITE INSPECTION PRIOR TO BIDDING WORK... 2. PRIOR TO THE START OF WORK, THE LANDSCAPE CONTRACTOR SHALL ASCERTAIN THE LOCATION OF ALL SURFACE AND UNDERGROUND UTILITIES, ETC., AND SHALL TAKE PROPER PRECAUTIONS TO PREVENT DAMAGE TO SUCH IMPROVEMENTS... 3. EXAMINE SUBGRADE UPON WHICH WORK IS TO BE PERFORMED. VERIFY SUBGRADE ELEVATIONS, OBSERVE CONDITIONS UNDER WHICH WORK IS TO BE PERFORMED, AND PROVIDE PERCOLATION TESTS AND ALL OTHER TESTS NECESSARY TO ASCERTAIN THAT ADEQUATE GROWING CONDITIONS WILL BE PROVIDED FOR PLANTS... 4. ACTUAL AS-BUILT SITE CONDITIONS MAY VARY FROM THIS PLAN. PLANT AND MATERIAL QUANTITIES AS SHOWN ON THE PLAN ARE FOR UNIFORM COMPARISON AND ESTIMATE PURPOSES ONLY... 5. THE QUANTITIES INDICATED ON THE DRAWINGS ARE PROVIDED FOR THE BENEFIT OF THE LANDSCAPE CONTRACTOR, BUT SHOULD NOT BE ASSUMED TO ALWAYS BE CORRECT... 6. PRIOR TO PLANTING, THE CONTRACTOR IS TO OBTAIN SOIL TESTS FOR ALL PLANTING AREAS TO DETERMINE IF THE PROPER SOIL PH IS PRESENT... 7. PROTECT EXISTING GRASS AREAS, TREES, AND OTHER VEGETATION TO REMAIN... 8. DURING LANDSCAPE INSTALLATION KEEP PAVEMENTS CLEAN AND WORK AREA IN ORDERLY CONDITION... 9. CONTRACTOR TO REPAIR ANY PAVEMENTS, CURBS, AND OTHER IMPROVEMENTS DAMAGED AS A RESULT OF LANDSCAPE INSTALLATION ACTIVITIES... 10. DAMAGE BY CONTRACTOR TO UNDISTURBED AREAS OUTSIDE THE LIMITS OF CONSTRUCTION SHALL BE REPAIRED BY CONTRACTOR TO THE SATISFACTION OF THE OWNER AT THE CONTRACTOR'S EXPENSE... 11. SUBSTANTIAL COMPLETION: WILL BE PROVIDED AFTER THE CONTRACTOR HAS SATISFACTORILY COMPLETED WORK REQUIREMENTS AS SPECIFIED... 12. FINAL ACCEPTANCE: THE A/E WILL PROVIDE THE FINAL INSPECTION AFTER THE CONTRACTOR HAS SATISFACTORILY CORRECTED THE DEFICIENCIES ON THE PUNCH LIST... 13. IF THE SUBSTANTIAL COMPLETION OR FINAL INSPECTION REQUIRE REINSPECTION BY A/E DUE TO FAILURE OF WORK TO COMPLY WITH CONTRACTOR'S CLAIMS ON INITIAL INSPECTION... 14. AFTER FINAL ACCEPTANCE AND PRIOR TO END OF WARRANTY PERIOD, CONTRACTOR SHALL REPLACE ALL PLANT MATERIAL THAT HAS DIED OR HAS DEFECTS, INCLUDING UNSATISFACTORY GROWTH, IN THE OPINION OF THE A/E.

LANDSCAPE NOTES

- 1. DIMENSIONS FOR HEIGHTS, SPREAD, AND TRUNK SPECIFIED ON THE MATERIAL SCHEDULE IS A GUIDE FOR THE MINIMUM DESIRED SIZE OF EACH PLANT... 2. THE LOCATION OF ALL TREES, SHRUBS, AND GROUND COVER AREAS SHOWN ON THE PLAN SHALL BE STAKED/FLAGGED BY THE CONTRACTOR AND APPROVED BY THE A/E... 3. PROVIDE ONLY PLANTS THAT ARE FREE FROM DISEASES AND PESTS, AND THAT COMPLY WITH THE LATEST EDITION OF PUBLICATION ANSI Z60.1, AMERICAN STANDARDS FOR NURSERY STOCK... 4. DO NOT MAKE SUBSTITUTIONS REGARDING PLANT SIZES OR SPECIES WITHOUT WRITTEN PERMISSION FROM THE A/E... 5. NO PLANT SHALL BE BOUND WITH ROPE OR WIRE IN A MANNER THAT DAMAGES THE BARK, BREAKS BRANCHES, OR DESTROYS ITS NATURAL SHAPE... 6. PLANTS DESIGNATED "B&B" IN THE PLANT LIST SHALL BE BALLED AND BURLAPPED... 7. ONLY "HEMP" BURLAP AND TWINE SHALL BE USED... 8. MINIMIZE DAMAGE TO THE ROOT BALL WHEN INSTALLING ALL PLANT MATERIAL... 9. REMOVE ALL STRINGS AND OTHER TIES FROM TREES... 10. THE BALLS OF "B&B" PLANTS WHICH CANNOT BE PLANTED IMMEDIATELY ON DELIVERY SHALL BE COVERED WITH MOIST SOIL OR MULCH... 11. ALL PLANTS SHALL BE HANDLED SO THAT ROOTS ARE ADEQUATELY PROTECTED AT ALL TIMES... 12. PLANT BED PREPARATION: THOROUGHLY DISC, SCARIFY, & LOOSEN SUBGRADE OF PLANTING BEDS TO A MINIMUM DEPTH OF 12 INCHES... 13. ALL PLANT BEDS SHALL BE SPRAYED WITH PRE-EMERGENT HERBICIDE (TRIFLORALIN OR EQUIVALENT)... 14. ALL PLANTING BEDS AND TREE PLANTINGS SHALL RECEIVE A MINIMUM 3" DEEP SHREDDED HARDWOOD MULCH LAYER... 15. ANY SERIES OF TREES OR SHRUBS TO BE PLACED IN A PARTICULAR ARRANGEMENT WILL BE FIELD CHECKED FOR ACCURACY... 16. GROUND COVER SPACING PATTERN SHALL BE AS INDICATED ON TYPICAL SPACING PATTERN USING SPACING DIMENSION AS SHOWN ON PLANS AND SCHEDULE... 17. LANDSCAPE CONTRACTOR IS RESPONSIBLE FOR STAKING, GUYING, FERTILIZING, APPLICATION OF INSECTICIDES/HERBICIDES... 18. ALL PLANT MATERIAL IS TO BE GUARANTEED FOR ONE (1) YEAR... 19. THE A/E MAY INSPECT TREES AND SHRUBS EITHER AT PLACE OF GROWTH OR AT SITE BEFORE PLANTING... 20. REPLACEMENT PLANT MATERIAL SHALL CLOSELY MATCH ADJACENT SPECIMENS OF THE SAME SPECIES AND SHALL CONFORM TO THE STANDARDS FOR PLANT MATERIALS SPECIFIED... 21. NO PLANT MATERIAL REQUIRED TO BE BALLED AND BURLAPPED SHALL BE ACCEPTED IF THE BALL IS CRACKED OR BROKEN EITHER BEFORE OR DURING THE PROCESS OF PLANTING...

SODDING NOTES


- 1. SOD IS TO BE CYNODON DACTYLON 'TIFWAY 419' (T-419 BERMUDA GRASS). SOD ALL AREAS AS INDICATED ON THE PLANS... 2. 4" OF IMPORTED TOPSOIL SHALL BE PROVIDED ON ALL AREAS TO BE SODDED... 3. SOD BED PREPARATION: LOOSEN SUBGRADE OF LAWN AREAS TO A MINIMUM DEPTH OF 8 INCHES... 4. THE SOIL SHALL BE THOROUGHLY TILLED TO DEPTH OF FOUR (4) INCHES AND FERTILIZER ADDED... 5. FINE GRADE LAWN AREAS TO SMOOTH, EVEN SURFACE WITH LOOSE, UNIFORMLY FINE TEXTURE... 6. FERTILIZER: CONTRACTOR SHALL PERFORM A SOIL TEST PRIOR SODDING AND APPLICATION OF ANY SOIL AMENDMENTS... 7. SOD IS TO BE ROLLED AND WATERED WITHIN TWO WEEKS OF INSTALLATION... 8. ENDS OF SOD PANELS ARE TO BE OFFSET... 9. SOD IS TO BE LAID AS SOON AS IT IS DELIVERED TO PLANTING AREAS... 10. REPAIR AND RESOD ALL ERODED OR DISTURBED SOD AREAS WHERE DESIRED VEGETATIVE COVER HAS NOT BEEN ESTABLISHED... 11. CONTRACTOR IS RESPONSIBLE FOR WATERING AND MAINTENANCE OF SODDED AREAS UNTIL AREAS EXHIBIT HEALTHY AND VIGOROUS GROWTH AS DETERMINED BY A/E... 12. SOD IS TO BE TOP DRESSED WITHIN ONE MONTH OF INSTALLATION.

SEEDING NOTES

- 1. 4" OF TOPSOIL SHALL BE PROVIDED ON ALL AREAS TO BE SEEDED UNLESS NOTED OTHERWISE... 2. SEED BED PREPARATION: THOROUGHLY DISC, SCARIFY, & LOOSEN SUBGRADE OF LAWN AREAS TO A MINIMUM DEPTH OF 4 INCHES... 3. FERTILIZER: CONTRACTOR SHALL PERFORM A SOIL TEST PRIOR TO SEEDING AND APPLICATION OF ANY SOIL AMENDMENTS... 4. PERMANENT VEGETATIVE COVER OF AT LEAST 90% IS REQUIRED... 5. AREAS WILL BE REPLANTED IF PERMANENT VEGETATION IS DISTURBED OR NOT ESTABLISHED... 6. REPAIR AND RE SEED ALL ERODED OR DISTURBED SEEDED AREAS WHERE VEGETATIVE COVER HAS NOT BEEN ESTABLISHED... 7. THE CONTRACTOR IS RESPONSIBLE FOR MAINTENANCE OF SEEDED AREAS UNTIL 95% PERMANENT GRASS COVER IS ESTABLISHED... 8. APPLY A 1/2" TO 3/4" LAYER OF THRASHED RYE, OAT, OR WHEAT STRAW... 9. GRASS SEED TO BE CYNODON DACTYLON 'SAHARA' (SAHARA BERMUDA GRASS)... 10. FINE GRADE LAWN AREAS TO SMOOTH, EVEN SURFACE WITH LOOSE, UNIFORMLY FINE TEXTURE... 11. PROTECT ALL SLOPES 3:1 OR STEEPER AGAINST EROSION... 12. UNLESS OTHERWISE APPROVED IN WRITING BY THE A/E, SEEDING OPERATIONS SHALL BE LIMITED TO THE FOLLOWING PLANTING PERIOD... 13. WHEN REQUIRED, SEEDING DURING NOVEMBER 15 THROUGH FEBRUARY 28... 14. SEEDING IS TO BE DONE AS AREAS ARE READY... 15. CONTRACTOR IS RESPONSIBLE FOR PROVIDING ADEQUATE WATER TO SEEDED AREAS TO ESTABLISH ACCEPTABLE GRASS COVERAGE.



60 GERMANTOWN COURT // SUITE 100 // MEMPHIS // TENNESSEE // 38018



Date: 2021.04.21

07:13:27-05'00"

LANDSCAPE NOTES

LAKELAND ATHLETIC COMPLEX

PHASE 1

MEMPHIS-ARLINGTON ROAD LAKELAND, TENNESSEE

Table with 4 columns: REV., DR., CHK., DATE and 4 rows: REVISION INFORMATION, DESCRIPTION, ISSUE FOR BID, DATE




Know what's below. Call before you dig.

L0.01


FILE NO. 3695300

PLANT SCHEDULE							
TREES	QTY	BOTANICAL NAME	COMMON NAME	CONDITION	SIZE	HEIGHT	REMARKS
AR	12	Acer rubrum 'October Glory'	October Glory Red Maple	B & B	2"-2 1/2" Cal.	8'-10' Ht.	Strong Central Leader, Full Canopy, Well Rooted
QR	19	Quercus rubra	Red Oak	B & B	2"-2 1/2" Cal.	8'-10' Ht.	Strong Central Leader, Full Canopy, Well Rooted
TD	6	Taxodium distichum 'Autumn Gold'	Autumn Gold Bald Cypress	B & B	2"-2 1/2" Cal.	8'-10' Ht.	Strong Central Leader, Well formed and Fully Branched, Well Rooted
SHRUBS	QTY	BOTANICAL NAME	COMMON NAME	CONDITION	SIZE	SPACING	REMARKS
IGS	30	Ilex glabra 'Shamrock'	Shamrock Inkberry	3 gal	--	48" O.C.	Full in pot, Well rooted, Matched
IVL	11	Itea virginica 'Little Henry' TM	Virginia Sweetpire	3 gal	--	36" O.C.	Full in pot, Well rooted, Matched
SBG	23	Spiraea x bumalda 'Goldflame'	Goldflame Spirea	3 gal	--	42" O.C.	Full in pot, Well rooted, Matched
VBC	4	Viburnum x burkwoodii 'Chenaultii'	Chenault Viburnum	5 gal	--	48" O.C.	Full in pot, Well rooted, Matched
GROUND COVERS	QTY	BOTANICAL NAME	COMMON NAME	CONDITION	SIZE	SPACING	REMARKS
LMB	262	Liriope muscari 'Big Blue'	Big Blue Lilyturf	1 gal	--	18" o.c.	Full in pot, Well rooted, Matched



MATCH LINE SHEET L1.02

**LEGEND**  
 AREAS TO BE SEEDDED  
 AREAS TO RECEIVE SOD  
 (SEE DETAIL 6/L7.01)



**BARGE**  
DESIGN SOLUTIONS

60 GERMANTOWN COURT // SUITE 100 // MEMPHIS // TENNESSEE // 38018



**LANDSCAPE PLAN**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
 MEMPHIS-ARLINGTON ROAD  
 LAKELAND, TENNESSEE


REVISION INFORMATION	
REV.	DESCRIPTION
DR.	DATE
MD	04-21-21
MD	ISSUE FOR BID

**L1.01**



FILE NO. 3695300



MATCH LINE SEE SHEET L1.01

NOTE: SEE SHEET L1.01 FOR PLANT SCHEDULE.



LEGEND

- AREAS TO BE SEEDED 
- AREAS TO RECEIVE SOD (SEE DETAIL 6/L7.01) 



Know what's below.  
Call before you dig.

**BARGE**  
DESIGN SOLUTIONS

60 GERMANTOWN COURT // SUITE 100 // MEMPHIS // TENNESSEE // 38018




LANDSCAPE PLAN  
 LAKELAND ATHLETIC COMPLEX  
 PHASE 1  
 MEMPHIS-ARLINGTON ROAD  
 LAKELAND, TENNESSEE


REVISION INFORMATION	
REV.	DESCRIPTION
DR.	DATE
MD	04-21-21
MD	ISSUE FOR BID

L1.02


FILE NO. 3695300



**1** TYPICAL SHRUB PLANTING DETAIL  
L7.01 1/2" = 1'-0"




**2** TYPICAL GROUNDCOVER PLANTING DETAIL  
L7.01 1/2" = 1'-0"




**3** TYPICAL TRENCH EDGING DETAIL  
L7.01 NTS  
NOTE: USE TRENCH EDGING ON ALL LANDSCAPE BEDS THAT ARE NEXT TO GRASSED AREAS.

NOTE: SPACING VARIES SEE PLANT LIST

PLANT SPACING (D)	ROW SPACING (A)	SPACING OFF OF PAVEMENT
6" O.C.	5"	6"
8" O.C.	7"	8"
10" O.C.	9"	8"
12" O.C.	10"	12"
15" O.C.	13"	18"
18" O.C.	16"	18"
24" O.C.	21"	30"
30" O.C.	26"	36"
36" O.C.	30"	42"
48" O.C.	42"	48"




**4** TYPICAL SHRUB SPACING DETAIL  
L7.01 NTS



- NOTE:
1. ONLY STAKE TREES AS NEEDED TO ENSURE VERTICAL GROWTH.
  2. THE TRUNK OF ALL TREES IS REQUIRED TO BE PLUMB WITH THE GROUND PLANE. IT WILL BE THE CONTRACTOR'S RESPONSIBILITY TO STRAIGHTEN ANY TREE THAT DOES NOT HAVE A VERTICAL TRUNK. STAKING TREES DIFFERENTLY THAN THIS DETAIL WITHOUT OBTAINING APPROVAL PRIOR TO STAKING WILL RESULT IN ALL TREES BEING RESTAKED.
  3. TOP OF ROOT BALL TO BE EQUAL OR SLIGHTLY HIGHER THAN EXISTING GRADE.
  4. DO NOT PIERCE ROOT BALL WITH STAKES.
  5. PRUNE TREE UNDER DIRECTION OF LANDSCAPE ARCHITECT.

**5** TYPICAL TREE PLANTING/ TRANSPLANTING DETAIL  
L7.01 NTS



- NOTE:
1. FIELD SOD SHALL BE TIFWAY 419 BERMUDA.
  2. SOD PIECES ARE TO BE BUTTED UP AGAINST EACH OTHER WITH NO GAPS. IF THERE ARE GAPS THEY SHOULD BE FILLED WITH SOD OR SAND (AS SPECIFIED ABOVE).

**6** MULTIPURPOSE FIELD SOD  
L7.01 NTS



LANDSCAPE DETAILS  
LAKELAND ATHLETIC COMPLEX  
PHASE 1  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE


REVISION INFORMATION		DATE	DESCRIPTION
CHK.	DATE		
MD	04-21-21		ISSUE FOR BID
DR.			
REV.			



Know what's below.  
Call before you dig.



**IRRIGATION PLAN**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE



**IRRIGATION SCHEDULE**

SYMBOL	MANUFACTURER/MODEL/DESCRIPTION
Ⓢ	Rain Bird 8005-SS Turf Rotor, 5.0" Pop-Up, Stainless Steel Riser, Standard Nozzle. With Seal-A-Matic Check Valve, Adjustable 50-330 arc, and 360 Non-Reversing Full-Circle. 1" (26/34) NPT Female Threaded Inlet. Extended Radius is Ideal for Large Turf Applications.
Ⓢ	Rain Bird PEB 1", 1-1/2", 2" Plastic Industrial Valves. Low Flow Operating Capability, Globe Configuration.
Ⓢ	Rain Bird 44-LRC 1" Brass Quick-Coupling Valve, with Corrosion-Resistant Stainless Steel Spring, Locking Thermoplastic Rubber Cover, and 2-Piece Body.
Ⓢ	Matox-Norco 10RT 2" to 8" cast iron gate isolation valve. Ring-Tite Gasket Ends. Resilient wedge with epoxy coating and optional nut. For IPS pipe. Same size as mainline pipe.
BF	Febco 825Y 2" Reduced Pressure Backflow Preventer
C	Rain Bird ESP-LXD-LXMM Flow sensing Two-Wire Decoder Commercial Controller. 50 Stations. UV-Resistant, Outdoor-Rated, Powder-Coated Metal Cabinet. Available in the US market, International, European, or Australian Markets.
R	Rain Bird WR2-RFS Wireless Rain/Freeze Sensor.
G	2-Wire Grounding Point Install as per plan detail and manufacturers instructions.
SP	Solar Power Equipment Site One Greentech Model Solar 250Temp See plan detail.
M	Water Meter 2"
---	Irrigation Lateral Line: PVC Class 200 SDR 21
---	Irrigation Mainline: PVC Class 200 SDR 21
---	Pipe Sleeve: PVC Schedule 40
---	Valve Callout
Ⓢ	Valve Number
Ⓢ	Valve Flow
Ⓢ	Valve Size

**REFERENCE NOTES SCHEDULE**

SYMBOL	DESCRIPTION
1	Irrigation system water source to be a 3" service line to a 2" water meter. System requirements are 51 gpm at a static pressure of 80 psi. Verify available flow and pressure prior to construction.
2	Install 2" RPZ backflow preventer with HDPE insulated enclosure on a concrete pad as per plan detail.
3	Coordinate exact location of the solar panel, irrigation controller and rain sensor with the owners representative. See plan detail for approximate layout of solar panel, controller and rain sensor

**CRITICAL ANALYSIS**



Generated: 2020-07-24 14:17  
 P.O.C. NUMBER: 01  
 Water Source Information:  
 FLOW AVAILABLE  
 Water Meter Size: 2"  
 Flow Available: 120.00 gpm  
 PRESSURE AVAILABLE  
 Static Pressure at POC: 80.00 psi  
 Elevation Change: 5.00 ft  
 Service Line Size: 3"  
 Length of Service Line: 20.00 ft  
 Pressure Available: 77.00 psi  
 DESIGN ANALYSIS  
 Maximum Station Flow: 50.40 gpm  
 Flow Available at POC: 120.00 gpm  
 Residual Flow Available: 69.60 gpm  
 Critical Station: C11  
 Design Pressure: 50.00 psi  
 Friction Loss: 2.87 psi  
 Fittings Loss: 0.29 psi  
 Elevation Loss: 0.00 psi  
 Loss through Valve: 3.63 psi  
 Pressure Req. at Critical Station: 56.79 psi  
 Loss for Fittings: 0.21 psi  
 Loss for Main Line: 2.09 psi  
 Loss for POC to Valve Elevation: 0.00 psi  
 Loss for Backflow: 12.04 psi  
 Loss for Water Meter: 1.53 psi  
 Critical Station Pressure at POC: 73.06 psi  
 Pressure Available: 77.00 psi  
 Residual Pressure Available: 3.94 psi

**EXAMPLE WATERING SCHEDULE**

NUMBER	MODEL	TYPE	PRECIP	IN/WEEK	MIN/WEEK	GAL/WEEK	GAL/DAY
C1	Rain Bird PEB	Turf Rotor	0.69 in/h	1	88	4,435	
C2	Rain Bird PEB	Turf Rotor	0.35 in/h	1	173	8,719	
C3	Rain Bird PEB	Turf Rotor	0.36 in/h	1	169	8,518	
C4	Rain Bird PEB	Turf Rotor	0.35 in/h	1	170	8,568	
C5	Rain Bird PEB	Turf Rotor	0.70 in/h	1	87	4,385	
C6	Rain Bird PEB	Turf Rotor	1.35 in/h	1	45	1,134	
C7	Rain Bird PEB	Turf Rotor	0.72 in/h	1	84	4,234	
C8	Rain Bird PEB	Turf Rotor	0.69 in/h	1	88	4,435	
C9	Rain Bird PEB	Turf Rotor	1.35 in/h	1	45	1,134	
C10	Rain Bird PEB	Turf Rotor	0.71 in/h	1	85	4,284	
C11	Rain Bird PEB	Turf Rotor	0.34 in/h	1	178	8,971	
C12	Rain Bird PEB	Turf Rotor	0.34 in/h	1	178	8,971	
C13	Rain Bird PEB	Turf Rotor	0.36 in/h	1	169	8,518	
C14	Rain Bird PEB	Turf Rotor	0.69 in/h	1	87	4,385	
C15	Rain Bird PEB	Turf Rotor	1.30 in/h	1	47	1,184	
C16	Rain Bird PEB	Turf Rotor	0.71 in/h	1	85	4,284	
C17	Rain Bird PEB	Turf Rotor	0.70 in/h	1	86	4,334	
C18	Rain Bird PEB	Turf Rotor	1.36 in/h	1	45	1,134	
TOTALS:						1,909	91,627


**VALVE SCHEDULE**

NUMBER	MODEL	SIZE	TYPE	GPM	PSI	PSI @ POC	PRECIP
C1	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.37	70.89	0.69 in/h
C2	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.93	71.48	0.35 in/h
C3	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.95	71.93	0.36 in/h
C4	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.94	72.19	0.35 in/h
C5	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.27	71.58	0.70 in/h
C6	Rain Bird PEB	1-1/2"	Turf Rotor	25.20	58.02	70.36	1.35 in/h
C7	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.33	71.64	0.72 in/h
C8	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.36	71.56	0.69 in/h
C9	Rain Bird PEB	1-1/2"	Turf Rotor	25.20	58.18	70.21	1.35 in/h
C10	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.14	72.42	0.71 in/h
C11	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.79	73.06	0.34 in/h
C12	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.79	72.64	0.34 in/h
C13	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.84	72.61	0.36 in/h
C14	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.25	72.15	0.69 in/h
C15	Rain Bird PEB	1-1/2"	Turf Rotor	25.20	57.85	70.40	1.30 in/h
C16	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.27	72.71	0.71 in/h
C17	Rain Bird PEB	1-1/2"	Turf Rotor	50.40	56.25	72.89	0.70 in/h
C18	Rain Bird PEB	1-1/2"	Turf Rotor	25.20	57.76	70.38	1.36 in/h





Know what's below.  
Call before you dig.

**IR1.01**  
FILE NO. 3695300



### IRRIGATION SCHEDULE

SYMBOL	MANUFACTURER/MODEL/DESCRIPTION
	Rain Bird 8005-SS Turf Rotor, 5.0" Pop-Up, Stainless Steel Riser, Standard Nozzle. With Seal-A-Matic Check Valve, Adjustable 50-330 arc, and 360 Non-Reversing Full-Circle. 1" (26/34) NPT Female Threaded Inlet. Extended Radius is Ideal for Large Turf Applications.
	Rain Bird PEB 1", 1-1/2", 2" Plastic Industrial Valves. Low Flow Operating Capability, Globe Configuration.
	Rain Bird 44-LRC 1" Brass Quick-Coupling Valve, with Corrosion-Resistant Stainless Steel Spring, Locking Thermoplastic Rubber Cover, and 2-Piece Body.
	Matco-Norco 10RT 2" to 8" cast iron gate isolation valve. Ring-Tite Gasket Ends. Resilient wedge with epoxy coating and optional nut. For IPS pipe. Same size as mainline pipe.
	Febco 825Y 2" Reduced Pressure Backflow Preventer
	Rain Bird ESP-LXD-LXMM Flow sensing Two-Wire Decoder Commercial Controller. 50 Stations. UV-Resistant, Outdoor-Rated, Powder-Coated Metal Cabinet. Available in the US market, International, European, or Australian Markets.
	Rain Bird WR2-RFS Wireless Rain/Freeze Sensor.
	2-Wire Grounding Point Install as per plan detail and manufacturers instructions.
	Solar Power Equipment Site One Greentech Model Solar 250Temp See plan detail.
	Water Meter 2"
	Irrigation Lateral Line: PVC Class 200 SDR 21
	Irrigation Mainline: PVC Class 200 SDR 21
	Pipe Sleeve: PVC Schedule 40 Valve Callout
	Valve Number
	Valve Flow
	Valve Size




Know what's below.  
 Call before you dig.




**IRRIGATION PLAN**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
 MEMPHIS-ARLINGTON ROAD  
 LAKELAND, TENNESSEE


REVISION INFORMATION		DATE	DESCRIPTION
REV.	DR.	04-21-2021	ISSUED FOR BID




1 1" INLET ROTOR  
NTS




2 ELECTRIC CONTROL VALVE  
NTS




3 WIRE CONNECTION 3M-DBY-6  
NTS




4 QUICK COUPLER VALVE  
NTS




5 PEDESTAL MOUNT CONTROLLER  
NTS




6 WIRELESS RAIN SENSOR  
NTS




7 ISOLATION VALVE DETAIL 2 1/2" AND LARGER  
NTS



8 TWO WIRE GROUNDING POINT DETAIL  
NTS



9 RPZ BACKFLOW PREVENTER WITH ENCLOSURE  
NTS



10 CONTROLLER GROUNDING DETAIL  
NTS

**GENERAL NOTES**

1. ALL TRENCHING TO BE OUTSIDE OF TREE DRIP LINE
2. MAINLINE TO HAVE MINIMUM OF 18" OF COVER AND A MINIMUM OF 18" OFF OF THE HARDSCAPE
3. LATERALS TO HAVE MINIMUM OF 12" OF COVER AND A MINIMUM OF 12" OFF OF THE HARDSCAPE
4. NO ROCKS, BOULDERS OR SHARP OBJECTS TO BE IN TRENCH BACKFILL
5. ALL PIPE TO BE INSTALLED AS PER MANUFACTURES SPECIFICATIONS
6. SPRINKLERS AND RELATED EQUIPMENT TO BE INSTALLED AS PER DETAILS
7. TWO WIRE CONTROL WIRE TO BE 14 GA UL 2 CONDUCTOR, JACKETED AND APPROVED BY 2-WIRE CONTROLLER MANUFACTURER
8. ALL 2-WIRE CONTROL WIRE TO HAVE 14GA "BLUE" TRACER WIRE FROM THE CONTROLLER TO ALL CONTROL VALVES. TRACER WIRE TO HAVE A 24" LOOP LOCATED IN EACH CONTROL VALVE AND ISOLATION VALVE BOXES.
9. WIRE SPLICES TO BE DONE AS PER DETAILS
10. ALL WIRE SPLICES OUTSIDE OF CONTROL VALVE BOX TO BE IN 10" VALVE BOX
11. TWO WIRE CONDUCTORS TO BE COLOR CODED
12. CONTRACTOR SHALL INSTALL MANUFACTURES GROUNDING EQUIPMENT ON BOTH THE POWER AND OUTPUT SIDES OF CONTROLLER. ALL GROUNDING POINTS TO BE INSTALLED AS PER PLANS AND DETAILS
13. AT EACH VALVE AND CHANGE IN MAINLINE DIRECTION CONTRACTOR TO INSTALL A 30" LOOP OF EXTRA WIRE
14. SPRINKLERS ARE TO BE ADJUSTED TO AVOID OVER-SPRAY INTO NON-IRRIGATED AREAS
15. ELECTRIC CONTROL VALVES ARE TO BE INSTALLED IN VALVE BOXES AS FOLLOWS  
14" RECTANGULAR MINIMUM FOR EACH ELECTRIC CONTROL VALVE JUMBO VALVE BOX FOR DRIP ZONE KITS
16. SPRINKLERS TO BE INSTALLED 12" FROM FOUNDATIONS AND 2" FROM HARDSCAPE
17. CONTRACTOR TO ADD RISER EXTENSIONS TO SPRINKLERS IF REQUIRED TO MAINTAIN PROPER COVERAGE
18. ALL PIPING TO BE FLUSHED PRIOR TO INSTALLATION OF SPRINKLERS
19. ALL VALVES, QUICK COUPLER VALVES, WIRE SPLICES TO BE IN LANDSCAPED BEDS WHEREVER POSSIBLE
20. CONTRACTOR IS RESPONSIBLE FOR OBTAINING PROPER COVERAGE OF AREA TO BE IRRIGATED, MAKE ADJUSTMENTS AS NECESSARY
21. CONTRACTOR SHALL EXERCISE CARE NOT TO DAMAGE EXISTING UTILITIES REPAIRING ANY DAMAGES AT HIS OWN COST
22. PLAN IS DIAGRAMMATIC TO IMPROVE CLARITY ALL IRRIGATION EQUIPMENT TO BE INSTALLED WITHIN PROPERTY LINES AND LANDSCAPED AREAS
23. ANY DISCREPANCIES BETWEEN THE PLAN AND THE SITE TO BE REFERRED TO THE OWNERS REPRESENTATIVE PRIOR TO CONSTRUCTION
24. CONTRACTOR TO PROVIDE 1 YEAR WARRANTY OF ALL PRODUCTS AND WORKMANSHIP TO INCLUDE WINTERIZATION AND SPRING START-UP
25. CONTRACTOR TO PROVIDE OWNER AND OR LANDSCAPE ARCHITECT RECORD DRAWING PRIOR TO SUBSTANTIAL COMPLETION.
26. INSTALLATION OF IRRIGATION SYSTEMS IS THE IRRIGATION CONTRACTORS RESPONSIBILITY. IRRIGATION CONTRACTOR TO COORDINATE WITH GENERAL CONTRACTOR SLEEVE INSTALLATION TO PAVEMENT INSTALLATION
27. CLEANUP AND DISPOSE OF ALL DEBRIS, WASTE AND EXCESS CONSTRUCTION MATERIALS LEAVE AREA NEAT, CLEAN AND READY FOR OWNERS USE. PROVIDE CLEAN PAVEMENT SURFACES INCLUDING AREAS OF PUBLIC R.O.W.

**TWO WIRE CONTROL SYSTEM NOTES**

1. ALL DECODER WIRE SPLICE CONNECTORS TO BE 3M DBY-6 OR BETTER.
2. ALL DECODER TO VALVE SOLENOID SPLICE CONNECTORS TO BE 3M DBY-6 OR BETTER
3. ALL GROUNDING POINTS TO HAVE LSP-01 LIGHTNING ARRESTOR INSTALLED INLINE AS PER MANUFACTURER'S REQUIREMENTS AND INSTALLED AS PER DETAIL.
4. ALL 2-WIRE PRODUCTS TO BE INSTALLED AND OPERATED AS PER THE MANUFACTURER'S RECOMMENDATIONS AND OR REQUIREMENTS.
5. IRRIGATION CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL NECESSARY 2-WIRE INSTALLATION TRAINING PRIOR TO PROJECT START. NOTIFY IRRIGATION CONSULTANT WHEN TRAINING HAS BEEN COMPLETED.
6. IRRIGATION CONTRACTOR IS RESPONSIBLE FOR TRAINING OWNERS STAFF, AS NEEDED, ON THE OPERATION AND MAINTENANCE OF THE CONTROL SYSTEM.
7. IRRIGATION CONTRACTOR IS RESPONSIBLE FOR COMPLETE PROGRAMMING AND OPERATION OF THE CONTROL SYSTEM FOR 6 MONTHS FROM THE DAY THE CONTROLLER BECOMES FUNCTIONAL. CONTRACTOR TO PROVIDE THE OWNERS REPRESENTATIVE A COMPUTER SPREAD SHEET THAT SHOWS EACH PROGRAM, OPERATIONAL DAYS AND RUN TIMES PER ZONE.

**CONTROLLER INSTALLATION NOTES**

1. IRRIGATION CONTRACTOR TO COORDINATE EXACT LOCATION OF CONTROLLER WITH OWNER'S REPRESENTATIVE.
2. PROVIDE 120VAC POWER FROM THE SOLAR PANEL POWER INVERTER TO THE CONTROLLER IN 1-1/4" PVC SCH 40 ELECTRICAL CONDUIT.
3. CONTROLLER TO BE SECURELY ATTACHED TO THE CONCRETE PEDESTAL BASE USING CONCRETE METALLIC WEDGE STYLE ANCHORS.
4. ALL IRRIGATION CONTROL WIRE ABOVE GRADE TO BE ENCASED IN PVC ELECTRICAL CONDUIT.
5. CONTROLLER TO BE GROUNDED AS PER MANUFACTURERS RECOMMENDATIONS AND PLAN DETAIL.



Know what's below.  
Call before you dig.

**BARGE**  
DESIGN SOLUTIONS


60 GERMANTOWN COURT // SUITE 100 // MEMPHIS // TENNESSEE // 38018



**IRRIGATION PLAN**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE

REV.	DR.	CHK.	DATE	DESCRIPTION	ISSUED FOR

**IR1.03**  
FILE NO. 3695300



**INSTALLATION NOTE:**  
SOLAR DETAIL IS TO BE USED FOR ILLUSTRATIVE PURPOSES ONLY. THE CONTRACTOR IS RESPONSIBLE FOR COMPLYING WITH ALL LOCAL CONSTRUCTION AND SAFETY CODES FOR INSTALLATION OF THE SOLAR PANEL.

**SOLAR PANEL LOCATION NOTE:**  
THE DISTANCE FROM SOLAR PANEL POLE TO SOLAR ASSEMBLY ENCLOSURE SHALL BE NO GREATER THAN 12'.

**CABLE AND WIRE NOTE:**  
ALL CABLES AND ELECTRICAL WIRES MUST BE RUN IN CONDUIT.

**GROUNDING NOTE:**  
GROUND ROD SHALL BE LOCATED BETWEEN 8'-12' AWAY FROM ENCLOSURE UNLESS OTHERWISE SPECIFIED. A 10" ROUND VALVE BOX SHALL BE INSTALLED OVER THE GROUND ROD FOR LOCATION AND MAINTENANCE PURPOSES.


- 1 STRONGBOX STAINLESS STEEL NEMA 3R RAINPROOF ENCLOSURE AND SOLAR ASSEMBLY BY SOGT.
- 2 POWER INVERTER.
- 3 CHARGE CONTROLLER.
- 4 \*1 TO 2 PANELS, INSTALL 1 1/2" x 3" GALVANIZED POLE. \*3 TO 4 PANELS, INSTALL 1 1/2" x 4" GALVANIZED POLE.
- 5 FINISHED GRADE.
- 6 ENCLOSURE AND POLE MOUNTING SKID, ALUMINUM 4' X 5'. ANCHOR SKID TO CONCRETE PAD ON ALL 4 CORNERS WITH STAINLESS STEEL ANCHORS.
- 7 1-1/2" ELECTRICAL CONDUIT AND SWEEP ELL FOR 120 VAC POWER LINE TO CONTROLLER.
- 8 1-1/2" PVC CONDUIT AND SWEEP ELL WITH #6 GROUND WIRE TO EXTERNAL GROUND ROD LOCATION.
- 9 UL LISTED 5/8" x 8" GROUND ROD WITH #6 GROUND WIRE AND CLAMP INSTALLED INSIDE 10" ROUND VALVE BOX.
- 10 BATTERIES FOR POWER STORAGE. NUMBER OF BATTERIES BASED ON POWER REQUIREMENT.
- 11 WIRE REINFORCED CONCRETE PAD, 4' GREATER IN SIZE ON ALL SIDE THAN THE ALUMINUM SKID.
- 12 STAINLESS STEEL ANCHOR BOLTS.
- 13 1-1/4" GALVANIZED CONDUIT AND SWEEP ELBOW INTO THE ENCLOSURE.
- 14 POLE ATTACHMENT FLANGE. BOLT TO THE SKID, SIZE PER POLE DIAMETER.
- 15 MOUNT SOLAR PANEL ON GALVANIZED POLE WITH BRACKET PROVIDED BY SOGT. POLE NOT INCLUDED.
- 16 WATER PROOF ELECTRICAL JUNCTION BOX ATTACHED TO POLE FOR SOLAR WIRING.
- 17 GALVANIZED END CAP. SIZE PER POLE DIAMETER.

18"W x 36"H, STRONGBOX: SB-18SS OR SB-18DSS  
FRONT ENTRY ON ALUMINUM SKID

1 SOLAR ASSEMBLY - 250 SERIES, QUOTE #4722853 dated 8-28-2020



10 SOLAR PANEL DETAIL  
NTS



11 SOLAR PANEL AND CONTROLLER LAYOUT  
NTS



**IRRIGATION PLAN**  
**LAKELAND ATHLETIC COMPLEX**  
**PHASE 1**  
MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE

REV.	DR.	CHK.	DATE	DESCRIPTION

**IR1.04**  
FILE NO. 3695300



USER:MICHAEL CLARK  
FILE:D:\0000\Commercial\Projects\BWS\Lakeland Rec Complex\Design Files\3695300\irrigation.dwg  
SAVED: 4/20/2021  
PLOTTED: 4/20/2021



## ELECTRICAL LEGEND

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
<b>LIGHTING</b>		<b>BASIC MATERIALS</b>	
	SOLAR POLE LIGHTING FIXTURE (LED)		BRANCH CIRCUIT WIRE & CONDUIT RUN CONCEALED IN WALL OR ABOVE CEILING, HOME RUN TO PANELBOARD. A NUMERAL, IF PRESENT AT ARROW HEAD, INDICATES CIRCUIT NUMBER. ANY BRANCH CIRCUIT SHOWN WITHOUT SLASH MARKS INDICATES A CONDUIT CONTAINING (3) #12 AWG CONDUCTORS (HOT, NEUTRAL & GROUND). SLASH MARKS, IF PRESENT, INDICATE THE FOLLOWING: HOT (ENERGIZED) CONDUCTOR, NEUTRAL CONDUCTOR, & GROUND CONDUCTOR
<b>SERVICE AND DISTRIBUTION</b>			WIRE & CONDUIT RUN EXPOSED
	SWITCHBOARD		WIRE & CONDUIT RUN IN OR UNDER FLOOR
	DISTRIBUTION PANEL		DISCONNECT SWITCH
	BRANCH CIRCUIT PANEL		JUNCTION BOX
	TRANSFORMER		MANUAL MOTOR STARTER SWITCH
	MOTOR CONNECTION		G.F.I. TYPE DUPLEX RECEPTACLE OUTDOORS (WEATHERPROOF)
	GENERATOR CONNECTION		
	DISCONNECT SWITCH (FUSED AS REQUIRED)		
	MOTOR CONTROLLER (SPECIFIED IN OTHER THAN DIV. 26)		
	COMBINATION MOTOR CONTROLLER & DISCONNECT SWITCH (SPECIFIED IN OTHER THAN DIV. 26)		
	EQUIPMENT NOT FURNISHED UNDER DIV. 26 (SPECIFIED IN OTHER THAN DIV. 26)		
	ELECTRIC METER		
	RELAY		
	CIRCUIT BREAKER		
	LIGHTING CONTACTOR		
	PHOTOCELL		
	THERMOSTAT		

## ELECTRICAL ABBREVIATIONS

SYMBOL	DESCRIPTION
A	AMPERE
AF	ABOVE FINISHED FLOOR
AFS	ABOVE FINISHED GRADE
AIC	AMPERES INTERRUPTING CURRENT
ANN	ANNUNCIATOR
AUX	AUXILIARY
AWG	AMERICAN WIRE GAUGE
C	CONDUIT
CB	CIRCUIT BREAKER
CKT	CIRCUIT
CLP	CURRENT LIMITING PANEL
CT	CURRENT TRANSFORMER
CU	COPPER
DISC	DISCONNECT
EDF	ELECTRIC DRINKING FOUNTAIN
FAAP	FIRE ALARM ANNUNCIATOR PANEL
FACP	FIRE ALARM CONTROL PANEL
FLA	FULL LOAD AMPS
G	GROUND
GFI	GROUND FAULT CURRENT INTERRUPTER
HP	HORSEPOWER
HZ	HERTZ
KCMIL	THOUSAND CIRCULAR MILS
KVA	KILOVOLT-AMPERE
KW	KILOWATT
LED	LIGHT EMITTING DIODE
MCC	MOTOR CONTROL CENTER
MLO	MAIN LUGS ONLY
N	NEUTRAL
NEC	NATIONAL ELECTRIC CODE
PF	POWER FACTOR
SOWB	SPACE ONLY WITH BUS
UGW	UNDERGROUND ELECTRICAL
V	VOLT
VA	VOLT-AMPERE
VFD	VARIABLE FREQUENCY DRIVE
WP	WEATHER PROOF
XFMR	TRANSFORMER
3P	THREE POLE
3PH	THREE PHASE
4W	FOUR WIRE
30/3	30 AMPERE, 3-POLE

### GENERAL PROJECT NOTES:

- ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH DIVISION 26 SPECIFICATIONS, NATIONAL ELECTRICAL CODE, AND ALL OTHER APPLICABLE STANDARDS AND REGULATIONS ENFORCED BY THE AUTHORITY HAVING JURISDICTION.
- ALL ABOVE GROUND EXTERIOR CONDUIT SHALL BE GALVANIZED RIGID STEEL CONDUIT WITH CORROSION RESISTANT FITTINGS, CLAMPS AND SUPPORT. INTERIOR EXPOSED CONDUIT ABOVE GROUND SHALL BE EMT.
- IN THE EVENT OF CONFLICTS BETWEEN THE DRAWINGS, SPECIFICATIONS, CODES AND REGULATIONS, NOTIFY THE ENGINEER IN WRITING FOR ENGINEER OF RECORD'S OPINION PRIOR TO INSTALLATION.
- SHOP DRAWINGS SHALL BE SUBMITTED TO THE ENGINEER FOR APPROVAL AND REVIEW.
- SMACNA SEISMIC RESTRAINT MANUAL, THIRD EDITION 2008, OR LATEST REVISION MAY BE USED AS A GUIDE FOR GENERAL SEISMIC SUPPORT DETAIL AND SUPPORT SPACING RECOMMENDATIONS.
- COORDINATE LOCATION OF ALL LIGHTING FIXTURES WITH OTHER DISCIPLINES PRIOR TO ROUGH-IN.
- ELECTRICAL CONTRACTOR SHALL VERIFY VOLTAGE AND AMP DRAW FOR ALL NEW EQUIPMENT.

### CODE ANALYSIS - INTERNATIONAL BUILDING CODE 2015



CODE COMMENTS	
JURISDICTION	Memphis and Shelby County Construction Code Enforcement
APPLICABLE CODES	2015 International Building Code with Local Amendments 2015 International Existing Building Code with Local Amendments 2015 International Residential Code with Local Amendments 2014 National Electrical Code 2018 Joint Electrical Code 2015 International Mechanical Code with Local Amendments 2015 International Fuel Gas Code with Local Amendments 2015 International Plumbing Code with Local Amendments 2015 International Energy Conservation Code with Local Amendments 2009 ICC A117.1 Accessibility and Useable Buildings and Facilities (by reference) 2013 ASME 17.1 Safety Code for Elevators and Escalators (by reference)

### DRAWING LIST - ELECTRICAL

E1.00	ELECTRICAL - LEGEND, GENERAL NOTES, SCHEDULES, & DETAILS
E1.01	ELECTRICAL - PHOTOMETRICS PLAN
E1.02	ELECTRICAL - SITE PLAN
<b>Grand total: 3</b>	

### LIGHT FIXTURE SCHEDULE

Type Mark	Count	Manufacturer	Description	Model	Wattage	Voltage	Luminous Flux	Total Light Loss Factor	Initial Color Temperature	Comments
A	14	SOL EVERGEN	SOLAR AREA LIGHT & POLE	SOL EVERGEN	20 W		3000 lm	1	4000 K	



**3 SOLAR PARKING LIGHT FIXTURE  
N.T.S.**

**1 IRRIGATION CONTROLLER  
1/2" = 1'-0"**

ELECTRICAL - LEGEND, GENERAL NOTES, SCHEDULES, & DETAILS

LAKELAND ATHLETIC COMPLEX  
PHASE 1

MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE

REV.	DR.	CHK.	DATE	DESCRIPTION
	R/JH	R/JH	04-21-21	ISSUE FOR BID


**IES**  
INNOVATIVE • ENGINEERING  
SERVICES, LLC  
2787 Stage Center Drive, Suite 101  
Bartlett, Tennessee 38134  
www.innovativeies-llc.com 901.379.0500


E1.00

FILE NO. 3695300

**BARGE**  
DESIGN SOLUTIONS

60 GERMANTOWN COURT // SUITE 100 // MEMPHIS // TENNESSEE // 38018





ELECTRICAL - PHOTOMETRICS PLAN

LAKELAND ATHLETIC COMPLEX  
PHASE 1


MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE

REV.	CHK.	DATE	DESCRIPTION
	R/JH	04-21-21	ISSUE FOR BID

E1.01


FILE NO. 3695300

GENERAL DRAWING NOTES  
A. PLEASE REFER TO SHEET E1.00 FOR PROJECT NOTES, LEGEND, SCHEDULES, & DETAILS.



1 ELECTRICAL - PHOTOMETRICS PLAN  
1" = 30'-0"






ELECTRICAL - SITE PLAN

**LAKELAND ATHLETIC COMPLEX  
PHASE 1**

MEMPHIS-ARLINGTON ROAD  
LAKELAND, TENNESSEE

1 ELECTRICAL - SITE PLAN  
1" = 30'-0"



GENERAL DRAWING NOTES

- A. PLEASE REFER TO SHEET E1.00 FOR PROJECT NOTES, LEGEND, SCHEDULES, & DETAILS
- B. IRRIGATION SOLAR ASSEMBLY SHALL BE EQUAL TO SITE ON GREENTECH 250 SOLAR SERIES STRONGBOX, SB-18SS WITH 8W CONTINUOUS POWER, 27 HOURS OF RESERVE POWER, & 36AH OF BATTERY CAPACITY.
- C. COORDINATE WITH SPRINKLER CONTRACTOR TO PROVIDE LATCHING VALVES SO THAT THEY DO NOT NEED CONSTANT POWER.

REVISION INFORMATION	
CHK.	DATE
R/JH	04-21-21
R/JH	04-21-21
R/JH	04-21-21
R/JH	04-21-21
R/JH	04-21-21

DESCRIPTION  
ISSUE FOR BID

**IES**  
INNOVATIVE • ENGINEERING  
SERVICES, LLC  
2787 Stage Center Drive, Suite 101  
Bartlett, Tennessee 38134  
www.innovativees-lic.com 901.379.0500

**E1.02**

FILE NO. 3695300

**GENERAL PROJECT NOTES**

- CONTRACTOR SHALL COORDINATE ALL PLUMBING SYSTEMS WITH ALL OTHER TRADES, SO NOT TO CAUSE INTERFERENCES.
- CONTRACTOR SHALL FIELD VERIFY ALL SITE UTILITY CONNECTIONS OR SIZE LOCATION, AND DEPTH AND INSTALL ALL SYSTEMS IN ACCORDANCE WITH CONDITIONS FOUND (PRIOR TO BEGINNING INSTALLATION). ANY PART OF PLUMBING SYSTEMS INSTALLED INCORRECTLY DUE TO NOT VERIFYING SAME SHALL BE REMOVED AND CORRECTED AT THE EXPENSE OF THE CONTRACTOR.
- CONTRACTOR SHALL GUARANTEE ENTIRE SYSTEM FOR A PERIOD OF ONE YEAR AFTER FINAL DATE OF ACCEPTANCE.
- PROVIDE RATED SEALANT FOR ALL PENETRATIONS THROUGH WALLS, CEILINGS AND ROOFS. PROVIDE FIRE STOP SEALANT AROUND ALL PENETRATIONS THROUGH FIRE RATED WALLS, SO AS TO MAINTAIN FIRE INTEGRITY IN THE EVENT OF A FIRE.
- CONTRACTOR SHALL INSTALL ALL PLUMBING SYSTEMS IN A GOOD WORKMANSHIP MANNER. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH ALL APPLICABLE CODES AND AUTHORITIES.
- CONTRACTOR SHALL REVIEW ENTIRE SET OF DOCUMENTS INCLUDING PLUMBING PLANS AND ADVISE ARCHITECT IN WRITING PRIOR TO BEGINNING CONSTRUCTION IF THERE ARE ANY CODE VIOLATIONS, SPACE CONFLICTS AND/OR OTHER COORDINATION CONFLICTS WITH OTHER TRADES. IT WILL BE THE CONTRACTOR'S RESPONSIBILITY TO INSTALL A COMPLETE PLUMBING SYSTEM IN ACCORDANCE WITH CODES, ETC.
- SEE ARCHITECTURAL DRAWINGS FOR ALL BUILDING DIMENSIONS, DETAILS, ELEVATIONS, AND EXACT LOCATIONS OF ALL FIXTURES.
- THESE DRAWINGS ARE DIAGRAMMATIC AND SHOW GENERAL PLUMBING LAYOUTS AND PIPE ROUTING ONLY. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO PREPARE DETAILED SHOP DRAWINGS WHERE SPACE AND/OR COORDINATION ISSUES ARISE AND TO CONFIRM ALL SPACE ALLOCATIONS.
- CONTRACTOR SHALL PROVIDE TAMPER-PROOF, LOCKABLE ACCESS PANELS FOR ALL CONCEALED VALVES, WATER HAMMER ARRESTORS, ETC.
- CONTRACTOR SHALL COORDINATE ALL ELECTRICAL CHARACTERISTICS OF ELECTRICAL OPERATED EQUIPMENT WITH ELECTRICAL CONTRACTOR PRIOR TO ORDERING SAME. THIS APPLIES TO VOLTAGE, PHASE, RATED CAPACITIES, ETC.
- CONTRACTOR SHALL OFFSET ALL PIPING IN BUILDING AS REQUIRED TO PROPERLY INSTALL PLUMBING SYSTEMS.
- CONTRACTOR SHALL PROVIDE SHUTOFF VALVES ON ALL BRANCH RUNOUTS TO FIXTURES. NO EXCEPTIONS!
- AT COMPLETION OF PROJECT, THE CONTRACTOR SHALL REMOVE ALL AERATORS, FILTERS, ETC. AND FLUSH SYSTEM OUT THOROUGHLY.
- CONTRACTOR SHALL VERIFY ALL CONNECTIONS OF MISC. EQUIPMENT FURNISHED BY OTHERS PRIOR TO INSTALLING THE SAME AND MAKE ALL CONNECTIONS FOR THE SAME.
- SLEEVES SHALL BE INSTALLED WHERE PIPING PASSES THROUGH STRUCTURE. ALL HOLES THROUGH CONCRETE SHALL BE CORE-DRILLED. VERIFY LOCATION WITH ARCHITECT BEFORE COMMENCING WORK.
- ALL PIPING SHALL BE TESTED AND PROVEN TIGHT BEFORE PIPE IS CONCEALED.
- ALL SANITARY PIPING SHALL BE INSTALLED WITH A MINIMUM SLOPE OF 1/8" PER FOOT, UNLESS NOTED OTHERWISE ON THE PLANS.
- PRIOR TO SUBMITTING BID, VISIT THE SITE OF THE PROPOSED CONSTRUCTION AND THOROUGHLY INVESTIGATE EXISTING UTILITIES, WORKING CONDITIONS TO BE ENCOUNTERED ETC. NO ADDITIONAL COMPENSATION SHALL BE ALLOWED FOR CONDITIONS INCREASING COST WHICH WERE NOT KNOWN WHEN SUBMITTING PROPOSAL IF THE CONDITION WAS OBVIOUS AND COULD HAVE BEEN DISCOVERED DURING A SITE VISIT.
- DISCONNECT AND DISMANTLE EXISTING PLUMBING SYSTEMS AND EQUIPMENT TO BE DEMOLISHED AND LEAVE DEBRIS AND DISCONNECTED EQUIPMENT ON THE FLOOR FOR REMOVAL UNDER SECTION 02070 - SELECTIVE DEMOLITION.
- REMOVE EXISTING PLUMBING STACKS, MAINS AND BRANCHES WHEN SERVING FIXTURES TO BE DEMOLISHED. REMOVE PIPING BACK TO WITHIN 24" OF THE ACTIVE MAIN AND PROVIDE CAP OR PLUG TO SUIT SYSTEM. OBTAIN EXISTING RECORD DRAWINGS FROM THE OWNER. MAINTAIN EXISTING PLUMBING RISERS AND STACKS SERVING FIXTURES TO REMAIN.
- AFTER WALLS AND CEILINGS ARE REMOVED AND PIPING IS EXPOSED, VERIFY PIPING SERVES ONLY PLUMBING FIXTURES & EQUIPMENT INDICATED FOR DEMOLITION BEFORE SHUTDOWN FOR DISCONNECTION. IDENTIFY EXISTING PIPING WHICH SERVES FIXTURES & EQUIPMENT TO REMAIN. PROMPTLY NOTIFY ARCHITECT OF ACTIVE PIPING TO BE MAINTAINED WHEN LOCATED IN PARTITIONS TO BE DEMOLISHED.
- REMOVE EXISTING STACKS AND RISERS LOCATED IN EXISTING PARTITIONS TO BE DEMOLISHED AND PROVIDE NEW OFFSET AT CEILING AND DROP THROUGH THE FLOOR AND RECONNECT TO THE EXISTING SERVICES AT THE FLOOR BELOW.

**MISC. CODE NOTES**

- PERMITS SHALL BE APPLIED FOR BY LICENSED CONTRACTOR.
- ANY CONTRACTOR WHO DESIRES TO INSTALL, ENLARGE, ALTER, REPAIR, MOVE OR REPLACE A PLUMBING SYSTEM, WHICH IS TO BE REGULATED BY THE CODE SHALL FIRST MAKE APPLICATION AND OBTAIN THE REQUIRED PERMIT FOR THE WORK.
- PLUMBING PLANS & INSTALLATION SUBJECT TO PLUMBING INSPECTOR'S COMMENTS & FIELD APPROVAL.
- FLOOR DRAINS LOCATED IN SUCH AREAS WHERE TRAPS WILL NOT BE REPLENISHED SHALL HAVE EITHER A MINIMUM 12" DEEP SEAL TRAP, TRAP PRIMER, OR BE ON AN INDIRECT SYSTEM.
- ALL OF PLUMBING SYSTEM SHALL BE INSTALLED IN STRICT ACCORDANCE WITH CURRENT COUNTY PLUMBING CODE AND LOCAL ADMMENDMENTS, PLUMBING INSPECTORS & PLANS EXAMINERS REVIEW.
- PLUMBING CONTRACTOR SHALL PROVIDE INDIRECT WASTE OPENING TO WITHIN 2 FEET OF ALL COOLING COILS & EVAPORATORS FOR CONDENSATE. ROUTE TO HOUSE SIDE OF ACTIVE TRAP & CONNECT TO SAME. VERIFY LOCATIONS IN FIELD WITH HVAC CONTRACTOR PRIOR TO BEGINNING INSTALLATION OF SYSTEMS.
- WATER SUPPLY & SEWER SHALL BE PERMITTED & INSPECTED THROUGH PLUMBING DEPARTMENT.

**CODE ANALYSIS - INTERNATIONAL BUILDING CODE 2015**


CODE COMMENTS	
JURISDICTION Memphis and Shelby County Construction Code Enforcement	
APPLICABLE CODES 2015 International Building Code with Local Amendments 2015 International Existing Building Code with Local Amendments 2015 International Residential Code with Local Amendments 2014 National Electrical Code 2018 Joint Electrical Code 2015 International Mechanical Code with Local Amendments 2015 International Fuel Gas Code with Local Amendments 2015 International Plumbing Code with Local Amendments 2015 International Energy Conservation Code with Local Amendments 2009 ICC A117.1 Accessibility and Useable Buildings and Facilities (by reference) 2013 ASME 17.1 Safety Code for Elevators and Escalators (by reference)	

**PIPING LEGEND**

SYMBOL	DESCRIPTION
—	<b>WATER</b> COLD WATER PIPING
- - - -	<b>DRAINAGE</b> SANITARY OR WASTE PIPING
—	<b>VALVES</b> REDUCED PRESSURE BACKFLOW PREVENTER STRAINER
—	<b>PIPING</b> DROP (OR RISE)


**SYMBOLS LEGEND**

WC-1	X	DRAWING NUMBER
	PXXX	SHEET NUMBER
<b>PLUMBING FIXTURE DESIGNATION</b>		<b>DETAIL DESIGNATION</b>
X/PXXX	A1.2	
<b>ELEVATION DETAIL DESIGNATION</b>		<b>COLUMN LINE DESIGNATION</b>
X XX		
<b>REVISION DESIGNATION</b>		<b>POINT OF CONNECTION/REMOVAL</b>




**NOTES:**

- DRINKING FOUNTAIN TO BE BY MDF FOUNTAINS OR APPROVED EQUAL, COLOR TO BE GREEN. BASE BID INCLUDES AN ADA HELLO MODEL 440 SM FRONT APPROACH. ALL PUSH BUTTON ON FRONT AND REQUIRE LESS THAN 5 LBS. OF PRESSURE TO OPERATE.
  - FOUNTAIN TO INCLUDE HOSE BIB WITH LOCKING COVER ON CENTER POST. SUBMIT SHOP DRAWING TO LANDSCAPE ARCHITECT AND ENGINEER OF RECORD PRIOR TO ORDERING UNIT.
  - CONTRACTOR SHALL PROVIDE ALL PLUMBING REQUIRED.
  - DRINKING FOUNTAIN SHALL MEET ADA GUIDELINES. INSTALLATION SHALL BE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
  - CONTRACTOR SHALL VERIFY FOUNTAIN LOCATIONS FOR APPROVAL OF LANDSCAPE ARCHITECT PRIOR TO INSTALLATION.
- ② DRINKING FOUNTAIN DETAIL  
N.T.S.



① PLUMBING - SITE PLAN  
1" = 50'-0"



③ BACKFLOW PREVENTER ENCLOSURE  
1/16" = 1'-0"



REV.	CHK.	DATE	DESCRIPTION
JEW	JEW	04-21-21	ISSUE FOR BID