

VIRGINIA HOSPITAL CENTER DEMOLITION

PHASE 1 - BID SET - June 18, 2021

ARLINGTON, VA

RRMM ARCHITECTS, PC

ARCHITECTURE / PLANNING / INTERIORS

2900 South Quincy Street, Suite 710
Arlington, VA 22206
(703) 998-0101

115 South 15th Street, Suite 202
Richmond, VA 23219
(804) 277-8987


1317 Executive Boulevard, Suite 200
Chesapeake, VA 23320
(757) 622-2828

28 Church Avenue SW
Roanoke, VA 24011
(540) 344-1212

3737 Glenwood Avenue, Suite 100
Raleigh, NC 27612
(919) 827-0151

1 Research Court, Suite 450
Rockville, MD 20850
(240) 403-4101

VICINITY MAP



CONSULTANTS

AMT ENGINEERING
CIVIL ENGINEERING
800 KING FARM BLVD
ROCKVILLE, MD 20850
(301) 881-2545



GPI ENGINEERING
STRUCTURAL AND MEP ENGINEERING
8001 BRADDOCK ROAD, SUITE 200
SPRINGFIELD, VA 22151
(703) 978-0100

DOWNEY & SCOTT
COST ESTIMATING
6799 KENNEDY ROAD, UNIT F
WARRENTON, VA 20187
(540) 347-5001

OWNER


ARLINGTON COUNTY, FACILITIES
DESIGN & CONSTRUCTION
1400 N UHLE ST.
ARLINGTON, VA 22201
P: 703.228.4509
F: 703.228.3903

LOCATION MAP



SHEET INDEX - PHASE 1	
Sheet Number	Sheet Title
GENERAL	
1-G-001	COVER SHEET
1-G-101	ARCHITECTURAL GENERAL INFORMATION
1-G-102	CODE ANALYSIS
CIVIL	
1-C-100	COVER SHEET
1-C-101	SIGNED TOPOGRAPHIC SURVEY PAGE 1
1-C-102	SIGNED TOPOGRAPHIC SURVEY PAGE 2
1-C-103	EXISTING CONDITIONS PLAN
1-C-104	TREE PRESERVATION PLAN - PHASE 1
1-C-105	NOT USED
1-C-106	TREE PRESERVATION DETAILS
1-C-107	EXISTING TREE TABLE - TREE CONDITION SUMMARY
1-C-108	DEMOLITION PLAN
1-C-109	EROSION AND SEDIMENT CONTROL PLAN - PHASE 1
1-C-110	EROSION AND SEDIMENT CONTROL PLAN - PHASE 2
1-C-111	EROSION AND SEDIMENT CONTROL NOTES
1-C-112	EROSION AND SEDIMENT CONTROL DETAILS
1-C-113	SITE & GRADING AND UTILITY PLAN
1-C-114	UTILITY PLAN
1-C-501	SITE DETAILS
1-C-502	UTILITY DETAILS
1-C-701	PRE-DEVELOPMENT WATER QUALITY MAP
1-C-702	POST-DEVELOPMENT WATER QUALITY MAP
1-C-703	STORMWATER MANAGEMENT NARRATIVES & CALCULATIONS AND POLLUTION PREVENTION PLAN
1-C-704	WATER QUALITY IMPACT ASSESSMENT
1-L-101	LANDSCAPE CONSERVATION PLAN
1-L-501	LANDSCAPE NOTES & DETAILS
ARCHITECTURAL	
1-A-101	FOURTH FLOOR DEMOLITION AND NEW WORK PLANS
1-A-102	FIFTH FLOOR AND ROOF DEMOLITION AND NEW WORK PLANS
1-A-103	REFLECTED CEILING DEMOLITION AND NEW WORK PLANS
1-A-201	EAST AND WEST ELEVATIONS - DEMOLITION AND NEW WORK
1-A-202	NORTH ELEVATION - DEMOLITION AND NEW WORK
1-A-301	WALL SECTIONS
1-A-302	WALL SECTIONS
1-A-303	WALL SECTIONS
1-A-304	WALL SECTIONS AND MISCELLANEOUS DETAILS

SHEET INDEX - PHASE 1	
Sheet Number	Sheet Title
STRUCTURAL	
1-S-001	STRUCTURAL GENERAL NOTES
1-S-101	FOURTH FLOOR FRAMING - DEMOLITION & NEW WORK
1-S-102	FIFTH FLOOR FRAMING - DEMOLITION & NEW WORK
1-S-103	ROOF FRAMING - DEMOLITION & NEW WORK
1-S-301	SECTIONS
MECHANICAL	
1-M-001	COVER SHEET
1-M-102	FOURTH FLOOR DEMOLITION & NEW WORK PLANS
1-M-103	FIFTH FLOOR DEMOLITION & NEW WORK PLANS
PLUMBING	
1-P-001	COVER SHEET
1-P-102	FOURTH FLOOR DEMOLITION PLAN
1-P-103	FIFTH FLOOR DEMOLITION PLAN
ELECTRICAL	
1-E-001	COVER SHEET - ELECTRICAL
1-E-101	SITE PLAN - ELECTRICAL
1-E-102	FOURTH FLOOR DEMOLITION & NEW WORK - ELECTRICAL
1-E-103	FIFTH FLOOR DEMOLITION & NEW WORK - ELECTRICAL
1-E-104	FOURTH & FIFTH FLOOR - NEW WORK - FIRE ALARM
1-E-701	DETAILS & SCHEDULES



DATE	PROJECT	DESIGNED	DRAWN	CHECKED	MARK	DATE	BY	REVISIONS
06.18.2021	13356.28	KDL	DWH	KDL			DES	

DATE	PROJECT	DESIGNED	DRAWN	CHECKED	MARK	DATE	BY	REVISIONS
06.18.2021	13356.28	KDL	DWH	KDL			DES	



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 DRAWING COVER SHEET

SHEET
1-G-001

ABBREVIATIONS

#	NUMBER	DIA	DIAMETER	HWH	HOT WATER HEATER	PTD	PAINTED
&, +	AND	DIAG	DIAGONAL	PTN	PARTITION	QTY	QUANTITY
+/-	PLUS OR MINUS	DIM	DIMENSION	R	RISER, RIDGE	RA	RETURN AIR
@	AT	DIV	DIVISION	RD	RADIUS	RCP	REFLECTED CEILING PLAN
°	DEGREES	DL	DEAD LOAD	REC	RECEPTACLE	REF	REFERENCE
∅	DIAMETER	DN	DOWN	REF	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
Ω	ARC LENGTH	DPG	DAMPPOOFING	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
AB	ANCHOR BOLT	DS	DOWNSPOUT	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
ABV	ABOVE	DWG	DRAWING	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
ACM	ASBESTOS CONTAINING MATERIAL	DWR	DRAWER	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
ADDN	ADDITION	E	EAST	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
ADJ	ADJUSTABLE	EA	EACH	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
AFF	ABOVE FINISH FLOOR	EF	EXHAUST FAN	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
AHU	AIR HANDLING UNIT	EFS	EXTERIOR INSULATION FINISH SYSTEM	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
AL	ALUMINUM	EJ	EXPANSION JOINT	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
ALT	ALTERNATE	ELEC	ELECTRICAL	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
AMP, A	AMPERE	ELEV	ELEVATION, ELEVATOR	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
ANCH	ANCHOR, ANCHORAGE	EMER	EMERGENCY	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
ANOD	ANODIZED	ENCL	ENCLOSE, ENCLOSURE	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
APC	ARCHITECTURAL PRECAST CONCRETE	EPDM	ETHYLENE PROPYLENE DIENE MONOMER	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
APPROX	APPROXIMATE	EQ	EQUAL	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
ARCH	ARCHITECT, ARCHITECTURAL	EQUIP	EQUIPMENT	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
ASB	ASBESTOS	EST	ESTIMATE	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
ASPH	ASPHALT	EWC	ELECTRIC WATER COOLER	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
ATTEN	ATTENUATION	EXH	EXHAUST	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
AUTO	AUTOMATIC	EXIST	EXISTING	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
AVB	AIR VAPOR BARRIER	EXP	EXPOSED / EXPANSION	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
AVG	AVERAGE	EXT	EXTERIOR	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BC	BOTTOM OF CURB	FAB	FABRICATE	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BD	BOARD	FAS	FASTEN, FASTENER	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BEJ	BUILDING EXPANSION JOINT	FD	FLOOR DRAIN, FIRE DAMPER	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BETW	BETWEEN	FDN	FOUNDATION	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BIT	BITUMINOUS	FE	FIRE EXTINGUISHER	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BLDG	BUILDING	FEC	FIRE EXTINGUISHER CABINET	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BLK	BLOCK	FF	FINISH FLOOR	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BLKG	BLOCKING	FGL	FIBERGLASS	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BM	BEAM	FH	FIRE HYDRANT	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BO	BOTTOM OF	FIN	FINISH, FINISHED	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BRG	BEARING	FIX	FIXTURE	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BRK	BRICK	FLEX	FLEXIBLE	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BTWN,	BETWEEN	FLR	FLOOR	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BW	BETWEEN	FOC	FACE OF CONCRETE	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
BUR	BUILT-UP ROOFING	FOM	FACE OF MASONRY	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
C	CARPET	FP	FIREPROOF	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CAB	CABINET	FR	FIRE RATED	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CAP	CAPACITY	FRT	FIRE RETARDANT TREATED	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CEM	CEMENT	FT	FOOT, FEET	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CER	CERAMIC	FTG	FOOTING	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CF	CUBIC FOOT	FUR	FURRED, FURRING	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CFMF	COLD FORMED METAL FRAMING	FURR	FURRING	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CI	CAST IRON	G	GAS	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CIP	CAST IN PLACE	GA	GAUGE	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CJ	CONTROL JOINT	GALV	GALVANIZED	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CLG	CEILING	GC	GENERAL CONTRACT, CONTRACTOR	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CLR	CLEAR	GEN	GENERAL	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CMP	CORRUGATED METAL PIPE	GL	GLASS, GLAZING	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CMU	CONCRETE MASONRY UNIT	GPM	GALLONS PER MINUTE	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CO	CLEAN OUT	GWB	GYPSPUM WALLBOARD	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
COL	COLUMN	GYP	GYPSPUM	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
COMP	COMPOSITE	H	HIGH	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CONC	CONCRETE	H/C	HANDICAPPED	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CONST	CONSTRUCTION	HB	HOSE BIB	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CONT	CONTINUOUS	HC	HOLLOW CORE	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CPT	CARPET	HDWR	HARDWARE	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CRS	COURSE, COURSES	HGT	HEIGHT	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CSMT	CASEMENT	HM	HOLLOW METAL	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CSWK	CASEWORK	HORIZ	HORIZONTAL	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CU FT	CUBIC FEET	HP	HIGH POINT	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CU YD	CUBIC YARD	HR	HOUR	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CUH	CABINET UNIT HEATER	HTG	HEATING	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
CW	COLD WATER	HVAC	HEATING, VENTILATION AND AIR CONDITIONING	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
DBL	DOUBLE	HW	HOT WATER	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
DEMO	DEMOLITION	INSUL	INSULATE, INSULATED, INSULATION	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING
DET/DTL	DETAIL	INT	INTERIOR	REIN	REINFORCE, REINFORCED, REINFORCING	REIN	REINFORCE, REINFORCED, REINFORCING

ARCHITECTURAL MATERIAL LEGEND

	CONTINUOUS WOOD BLOCKING		ALUMINUM
	CONCRETE MASONRY UNIT		FINISHED WOOD
	CAST-IN-PLACE CONCRETE		WOOD BLOCKING
	STEEL		BRICK
	EARTH / COMPACT FILL		GLASS
	BATT INSULATION		ACOUSTICAL TILE
	POROUS FILL / GRAVEL		PLYWOOD
	RIGID INSULATION		CERAMIC TILE - LARGE SCALE
	GYPSPUM BOARD		SAND / MORTAR / PLASTER
	RESILIENT FLOORING / PLASTIC LAMINATE		GRAVEL

GENERAL NOTES

- DO NOT SCALE DRAWINGS. ALL DIMENSIONS ARE TO FINISH FACE OF WALL TO BOTH EXISTING AND NEW CONSTRUCTION. ALL DIMENSIONS NOTED AS "CLEAR" SHALL MAINTAIN THE FULL SPACE INDICATED WITHOUT ENCROACHMENTS, INCLUDING WALL FINISHES. ALL VERTICAL HEIGHTS INDICATED ARE FROM THE FINISH FLOOR ELEVATION AT THE BASE OF THE ITEM INDICATED, UNLESS NOTED OTHERWISE. WHERE WALLS, JAMBS, OR OTHER ITEMS ARE NOTED TO "ALIGN", THE FACE OF ITEMS INDICATED SHALL BE IN LINE WITH EACH OTHER TO FORM A STRAIGHT LINE, FREE OF OFFSETS OR DEVIATIONS. FIELD VERIFY ALL DIMENSIONS.
- EXISTING CONSTRUCTION (PARTITIONS, DOORS, PLUMBING FIXTURES, CASEWORK, EQUIPMENT, ETC.) IS INDICATED ON THE FLOOR PLANS WITH LINES IN A LIGHTER SHADE (SCREENED), WITH EXISTING WALLS TO REMAIN SOLID POCHED. NEW CONSTRUCTION IS INDICATED BY FULL INTENSITY (SOLID) LINES. ITEMS TO BE DEMOLISHED ARE INDICATED IN LIGHT DASHED LINES.
- THE CONTRACTOR SHALL INVESTIGATE AND VERIFY ALL EXISTING CONDITIONS AND TAKE FIELD MEASUREMENTS AND SHALL CAREFULLY COMPARE SUCH FIELD MEASUREMENTS, CONDITIONS, AND OTHER INFORMATION KNOWN TO THE CONTRACTOR WITH THE CONTRACT DOCUMENTS BEFORE PROCEEDING WITH THE WORK. IMMEDIATELY NOTIFY THE ARCHITECT IN WRITING OF ANY DISCREPANCIES.
- THE EXISTING CONDITIONS INFORMATION INDICATED IN THE CONTRACT DOCUMENTS IS BASED ON EXISTING DOCUMENTATION AND FIELD OBSERVATIONS, BUT IS NOT A WARRANTY OF EXISTING CONDITIONS AT THE TIME OF CONSTRUCTION. ALL NEW CONSTRUCTION IS INDICATED RELATIVE TO THE EXISTING BUILDING AND SHALL BE COORDINATED WITH THE ACTUAL FIELD CONDITIONS FOUND. THE CONTRACTOR SHALL ASSUME FULL AND UNDIVIDED RESPONSIBILITY FOR THE ACCURACY, FIT, AND STABILITY OF ALL PARTS OF THE WORK.
- ALL REMOVALS AND SALVAGE, UNLESS SPECIFICALLY NOTED OR REQUESTED BY THE OWNER SHALL BECOME THE PROPERTY OF THE CONTRACTOR.
- THE CONTRACTOR SHALL REPAIR AND RESTORE TO ITS ORIGINAL CONDITION ALL WORK AND ITEMS DAMAGED AS A RESULT OF CONSTRUCTION OPERATIONS. ANY DISTURBANCE OR DAMAGE TO THE EXISTING FACILITY RESULTING EITHER DIRECTLY OR INDIRECTLY FROM THE OPERATION OF THIS CONTRACT SHALL BE PROMPTLY REPAIRED, RESTORED, OR REPLACED AT NO ADDITIONAL COST.
- ALL TRANSITIONS OF NEW WORK TO EXISTING CONSTRUCTION, INCLUDING AT FLOORS, WALL AND CEILINGS, SHALL BE CAREFULLY EXECUTED. EXISTING CONSTRUCTION SHALL BE REPAIRED AND PATCHED AS NEEDED TO PROVIDE A SMOOTH TRANSITION.

GENERAL NOTES

- THE CONTRACTOR SHALL BE RESPONSIBLE FOR CORRECTING DEFECTIVE WORK IN EXISTING CONSTRUCTION WITHIN THE LIMITS OF THE CONSTRUCTION AREA. THIS INCLUDES, BUT IS NOT LIMITED TO, UNEVEN SURFACES AND FINISHES AT PLASTER OR GYPSUM BOARD. THE CONTRACTOR SHALL PATCH AND REPAIR SURFACES TO MATCH NEW ADJACENT SURFACES.
- ALL NEW AND EXISTING TO REMAIN SUBSTRATES SHALL BE PROPERLY PREPARED BEFORE APPLICATION OF FINISHES. CONTRACTOR SHALL ASSUME RESPONSIBILITY FOR SUBSTRATE CONDITIONS WHERE FINISHES ARE APPLIED.
- WHERE ITEMS ARE INDICATED TO BE REMOVED, DEMOLISH IN THEIR ENTIRETY, INCLUDING ALL APPURTENANCES, ANCHORS, AND INTERNAL STRUCTURES. DOORS: REMOVE DOOR PANEL AND ALL HARDWARE. MAINTAIN INTEGRITY OF FRAMES AND ANCHORAGE FOR THE INSTALLATION OF NEW DOOR PANELS AND HARDWARE. REPAIR AS NECESSARY EXISTING DOOR FRAMES TO REMAIN TO LIKE NEW CONDITION. DOORS & FRAMES: REMOVE DOOR PANEL, HARDWARE, FRAMES, ANCHORS, AND ADJACENT SIDELIGHTS AND TRANSOMS WHERE INDICATED. PREPARE WALL OPENING FOR INFILL OF NEW WALL CONSTRUCTION OR PATCH WALLS TO MATCH ADJACENT FINISHES AS INDICATED. WALLS: REMOVE ENTIRE WALL STRUCTURE, FROM FLOOR LINE TO TOP OF WALL TO THE EXTENT SHOWN OR REQUIRED. REMOVE ALL EMBEDDED MECHANICAL AND ELECTRICAL DEVICES, CONDUITS, ETC. WHERE WALLS EXTEND THROUGH THE SLAB ON GRADE, REMOVE WALL TO MINIMUM 4" BELOW SLAB SURFACE. PATCH SLAB AS PER SPECIFICATIONS.
- WHERE EXISTING MASONRY WALLS ARE EXTENDED WITH NEW MASONRY CONSTRUCTION OF SIMILAR MASONRY UNITS, CUT EXISTING WALLS ALONG THE MASONRY JOINTS, REMOVE EXISTING MORTAR BACK TO THE EXISTING UNIT TO REMAIN, AND TOOTH IN NEW MASONRY UNITS TO MAINTAIN THE BOND PATTERN AND INTEGRITY OF THE WALL. WHERE EXISTING MASONRY WALLS ARE EXTENDED WITH NEW MASONRY CONSTRUCTION OF DISSIMILAR MASONRY UNITS, SAW CUT END OF EXISTING WALLS PLUMB AND STRAIGHT. ABUT NEW CONSTRUCTION ALIGNED WITH THE FACE OF THE EXISTING WALL. PROVIDE BACKER ROD & SEALANT IN THE JOINT.
- REFER TO THE PROJECT SPECIFICATIONS SECTION 024119 "SELECTIVE DEMOLITION" FOR ADDITIONAL REQUIREMENTS.

BID ALTERNATES:

THESE DOCUMENTS INCLUDE TWO ALTERNATE EXTERIOR WALL FINISH ASSEMBLIES APPLIED TO THE EXISTING BUILDING SUBSTRATE AS INDICATED. CONTRACTOR'S BID SHALL INCLUDE PRICES FOR EACH ALTERNATE AS A COMPLETE ASSEMBLY. THE ASSEMBLIES ARE IDENTIFIED AS:

ALTERNATE 1: BRICK FAÇADE CONSISTING OF SPRAY APPLIED AIR BARRIER, 2 1/2" (R10.5) RIGID MINERAL WOOL INSULATION, AIR SPACE, AND FACE BRICK INCLUDING STAINLESS STEEL ANGLE SUPPORT AND ALL ANCHORS, TIES AND FLASHINGS.

ALTERNATE 2: FORMED METAL WALL PANEL FAÇADE CONSISTING OF SPRAY APPLIED AIR BARRIER, 2 1/2" Z' FURRING, 2 1/2" (R10.5) RIGID MINERAL WOOL INSULATION, AND EXPOSED FASTENER METAL WALL PANELS INCLUDING ALL SUBGIRTS, ANCHORS AND FLASHINGS.

ARCHITECTURAL GRAPHIC SYMBOLS

	DOOR TAG - BUILDING DIV/DOOR NUMBER LOCATION SUFFIX (IF REQ'D)		BUILDING SECTION REFERENCE
	NEW WORK KEY NOTE		SECTION NUMBER
	DEMOLITION KEY NOTE		DRAWING NUMBER WHERE SECTION IS DRAWN
	EXTERIOR / INTERIOR / INTERIOR CASEWORK ELEVATION IDENTIFICATION NUMBER		SECTION REFERENCE
	SHEET NUMBER WHERE ELEVATION IS LOCATED		DRAWING NUMBER WHERE SECTION IS DRAWN
	ROOM NAME BLDG DIV / CONST NO.		ENLARGED PLAN OR DETAIL REFERENCE
	PARTITION TYPE (SEE PARTITION LEGEND)		PLAN OR DETAIL NUMBER
	ELEVATION REFERENCE		DRAWING NUMBER WHERE ENLARGED PLAN OR DETAIL IS DRAWN
	MATCH LINE SEE 1 / A101		MAIN DRAWING TITLE
	EGRESS LOAD		DRAWING TITLE
	EGRESS CAPACITY		DRAWING SCALE

Amended Permit	DES
05.31.2121	BY
4	MARK DATE
	REVISIONS


DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	KDL	DWH	KDL

RRMM ARCHITECTS, PC
 2900 South Quincy Street, Suite 710
 Arlington, Virginia 22206
 (703)998-0101



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 DRAWING ARCHITECTURAL GENERAL INFORMATION

SHEET
1-G-101



CODE ANALYSIS

A. APPLICABLE CODES:

- 2015 Virginia Uniform Statewide Building Code (VUSBC).
- 2015 Virginia Energy Conservation Code.
- 2010 ADA Standards for Accessible Design.

B. GENERAL INFORMATION:

- The project is submitted under the 2015 Virginia Existing Building Code - VUSBC, Part II, referred to as the "VEBC". The VEBC incorporates by reference Chapters 2 - 16 of the 2015 International Existing Building Code (IEBC) per section 101.2.
- The project is an Alteration as defined by IEBC Section 202.
- The project is submitted under the IEBC WORK AREA compliance method per section 301.1.2.
- Classification of Work: Total WORK AREA does not exceed 50% of the aggregate area of the building. Per VEBC Chapter 5, alterations of the existing building shall meet Level 2 requirements.
- The Work will not require a change of occupancy.
- This project is the first phase of a two-phase project. Phase one includes partial demolition of the structure which connects the building to the existing Virginia Hospital Center. The intent is to provide for egress from the building in preparation for Phase 2 which includes full demolition of the hospital.
- The drawings on this sheet illustrate the occupant load and egress methods that will exist when the separation of the buildings is complete at the end of Phase 1.

C. EXISTING CONDITIONS:

- The existing structure to remain is a medical office building constructed in 1979 and consists of five levels set on a sloping site with the first floor level at grade on the south end and the fourth floor level at grade on the north end.
- Construction consists primarily of steel framing members, steel bar joist floor and roof framing, and 3" thick concrete floors on a 9/16" corrugated metal deck. Exterior walls are brick masonry on metal stud framing.
- The building is partially sprinklered, utility and storage rooms only.

D. ACCESSIBILITY:

- The five building levels are connected by elevator providing an accessible route.

E. USE GROUP CLASSIFICATION:

- The building is a medical office building, Use Group Business B.

F. CONSTRUCTION TYPE:

- Existing documentation indicates the following assembly ratings:

BUILDING ELEMENT	Rating Req'd	Rating Provided
Primary structural frame	1	UL X526 - 1 HR
Bearing walls		
Exterior	1	12" Concrete- 4 HR
Interior	1	NA
Nonbearing walls and partitions		
Exterior		
Interior	0	
Floor construction and associated secondary members	1	UL G229 - 1 HR
Roof construction and associated secondary members	1	UL P214 - 1 HR

- Based on the above the building is submitted as Construction Type 2A in accordance with IBC Table 601.

G. BUILDING HEIGHT:

- Allowable Building Height in Feet = 65 ft.
- Actual building height = 58 ft. from the midpoint of the stair roof to the grade plane calculated at elevation 222.0'.
- Allowable Number of Stories Above Grade per table 504.4 = 5.
- Actual Number of Stories = 5.

H. BUILDING AREA:



- The Allowable Area for Construction Type 2A non-sprinklered, multi-story Use Group B building, per table 506.2 and Equation 5-2 is: 37500 (3) = 112500 sf. (frontage increase is disregarded).
- Actual building area = 64301 sf. - refer to the occupancy schedule for areas by floor.

I. MEANS OF EGRESS:


- Number of Exits:
 - Two exits required from each floor level - two exits provided.
 - Three exits required from the building - six exits provided.
- Egress Capacity:
 - 34" clear width at exit doors at 0.2" per occupant = 170.
 - 46" width of stairs at 0.3" per occupant = 153.
 - Stair width governs egress capacity. See plans for egress load at each exit.
- Egress Length:
 - Exit Access Travel Distance allowed = 200 lf. Maximum travel distance provided = 130 lf.

CONSTRUCTION SEQUENCE:


- Step 1: Separate initial demolition from occupied building. Maintain protected egress path through fourth floor level stair to existing egress door until the new egress door and exit discharge path are complete and operational.
 - Install temporary one-hour rated wall at fourth and fifth floors. Extend tight to floors, wall & roof with perimeter joint firestopping.
 - Install covered pedestrian protection - extend out to a point clear of the construction area and maintain open at all times.
 - Demolish MRI addition as indicated.
- Step 2: Demolition of two story connector.
 - Construct new exterior infill wall and soffit at Fourth Floor.
 - Realign pedestrian egress protection to allow access to the two story connector for demolition.
 - Demolish connecting structure and site paving & steps to the extent shown.
- Step 3: Construct stair vestibule, exit door, and new concrete sidewalk and steps.
 - Maintain egress and pedestrian protection throughout demolition & new construction.
 - Install new end wall to secure the existing to remain building.
 - Construct new vestibule extension, wall cladding and paving.
 - Demolish interior door & refinish opening, and install MEP systems in the existing structure when the building is unoccupied.
 - Construct new concrete steps and connect new egress path to existing steps.
 - Provide a complete exit discharge route before proceeding with step four.
- Step 4: Complete new construction as shown.
 - Remove temporary separation wall after new work is in place.
 - Demolish stair exit door and infill wall opening. Maintain egress path through stair to new exit door and protect building occupants.
 - Demolish existing concrete steps and all temporary construction.
 - Complete new wall cladding.




FIFTH FLOOR
SCALE: 3/64" = 1'-0"




THIRD FLOOR (NO WORK AT THIS LEVEL IN THE PROJECT SCOPE)
SCALE: 3/64" = 1'-0"



FOURTH FLOOR
SCALE: 3/64" = 1'-0"




SECOND FLOOR (NO WORK AT THIS LEVEL IN THE PROJECT SCOPE)
SCALE: 3/64" = 1'-0"




FIRST FLOOR (NO WORK AT THIS LEVEL IN THE PROJECT SCOPE)
SCALE: 3/64" = 1'-0"


OCCUPANCY SCHEDULE				
LEVEL	FUNCTION OF SPACE PER IBC	AREA (SF)	SF/OCC.	OCCUPANT LOAD
FIRST FLOOR	Business Areas	8670 SF	100 SF	87
SECOND FLOOR	Business Areas	11286 SF	100 SF	113
THIRD FLOOR	Business Areas	14286 SF	100 SF	143
FOURTH FLOOR	Business Areas	14608 SF	100 SF	147
FIFTH FLOOR	Business Areas	15451 SF	100 SF	155
TOTAL BUILDING OCCUPANT LOAD		64301 SF		645




SEQUENCING STEP 1
SCALE: 3/64" = 1'-0"



SEQUENCING STEP 2
SCALE: 3/64" = 1'-0"



SEQUENCING STEP 3
SCALE: 3/64" = 1'-0"



SEQUENCING STEP 4
SCALE: 3/64" = 1'-0"



CD Revisions	Permit Revisions	DATE	PROJECT	DESIGNED	DRAWN	CHECKED	MARK	DATE	REVISIONS
		06.18.2021	13356.28	KDL	DWH	KDL			DES
		05.15.2020							BY
		07.30.2020							REVISIONS

RRMM ARCHITECTS, PC
2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
DRAWING CODE ANALYSIS

SHEET
1-G-102

6/15/2021 11:46:04 AM BIN 360/13356-28 Virginia Hospital Center/13356-28 v20 Virginia Hospital Center - Arch.rvt

601 SOUTH CARLIN SPRINGS ROAD

DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1

ARLINGTON COUNTY, VIRGINIA

AMT

A. MORTON THOMAS AND ASSOCIATES, INC.
CONSULTING ENGINEERS
14555 AVION PARKWAY SUITE 150
CHANTILLY, VA 20151
PHONE (703) 817-1373
EMAIL: AMT1@AMTENGINEERING.COM

CONSULTANTS



DATUM NOTES:

HORIZONTAL DATUM: THE SITE SHOWN HEREON IS REFERENCED TO THE VIRGINIA COORDINATE SYSTEM OF 1983 AS COMPUTED FROM A FIELD RUN TOPOGRAPHIC SURVEY.

VERTICAL DATUM: THE SITE SHOWN HEREON IS REFERENCED TO THE NORTH AMERICAN VERTICAL DATUM OF 1988 AS COMPUTED FROM A FIELD RUN VERTICAL CONTROL SURVEY.

OWNER

NAME: THE COUNTY BOARD OF ARLINGTON
ADDRESS: 2100 CLARENDON BLVD, SUITE 300
ARLINGTON, VA 22201
TELEPHONE #: (703) 228-3130

DEVELOPER


NAME: ARLINGTON COUNTY GOVERNMENT - D.E.S.
FACILITIES DESIGN & CONSTRUCTION
ADDRESS: 1400 N UHLE ST., SUITE 403
ARLINGTON, VA 22201
TELEPHONE #: (703) 226-3626
EMAIL: JALMARIO@ARLINGTONVA.US

ENGINEER

NAME: A. MORTON THOMAS & ASSOCIATES, INC.
ADDRESS: 14555 AVION PARKWAY, SUITE 150
CHANTILLY, VA 20151
TELEPHONE #: (703) 817-1373

CONTRACTOR

NAME: TO BE DETERMINED
ADDRESS: TO BE DETERMINED
TELEPHONE #: TO BE DETERMINED



SHEET INDEX

1-C-100	COVER SHEET
1-C-101	SIGNED TOPOGRAPHIC SURVEY PAGE 1
1-C-102	SIGNED TOPOGRAPHIC SURVEY PAGE 2
1-C-103	EXISTING CONDITIONS PLAN
1-C-104	TREE PRESERVATION PLAN
1-C-105	NOT USED
1-C-106	TREE PRESERVATION DETAILS
1-C-107	EXISTING TREE TABLE - TREE CONDITION SUMMARY
1-C-108	DEMOLITION PLAN
1-C-109	EROSION AND SEDIMENT CONTROL PLAN - PHASE 1
1-C-110	EROSION AND SEDIMENT CONTROL PLAN - PHASE 2
1-C-111	EROSION AND SEDIMENT CONTROL NOTES
1-C-112	EROSION AND SEDIMENT CONTROL DETAILS
1-C-113	SITE, GRADING & UTILITY PLAN
1-C-501	SITE DETAILS
1-C-701	PRE-DEVELOPMENT WATER QUALITY MAP
1-C-702	POST-DEVELOPMENT WATER QUALITY MAP
1-C-703	STORMWATER MANAGEMENT NARRATIVES, CALCULATIONS AND POLLUTION PREVENTION PLAN
1-C-704	WATER QUALITY IMPACT ASSESSMENT
1-L-101	LANDSCAPE CONSERVATION PLAN
1-L-501	LANDSCAPE NOTES & DETAILS

DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1

601 SOUTH CARLIN SPRINGS ROAD
ARLINGTON, VA 22204

GENERAL NOTES

- THE CONTRACTOR SHALL FULLY ACQUAINT HIMSELF WITH THE CONDITIONS OF THE SITE. THE CONTRACTOR SHALL THOROUGHLY EXAMINE AND BE FAMILIAR WITH THE DRAWINGS AND SPECIFICATIONS. SHOULD THE CONTRACTOR FIND ANY DISCREPANCIES, OMISSIONS, AMBIGUITIES, OR CONFLICTS IN OR AMONG THE CONTRACT DOCUMENTS OR BE IN DOUBT AS TO THEIR MEANING, HE SHALL BRING THESE ITEMS TO THE ATTENTION OF THE PROJECT OFFICER FOR DIRECTION BEFORE PROCEEDING WITH WORK.
- THE CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AND BE RESPONSIBLE FOR ADHERENCE TO ALL ORDINANCES, REGULATIONS, LAWS AND CODES HAVING JURISDICTION OVER THE PROPERTY.
- THE CONTRACTOR SHALL SUBMIT A REQUIRED "RESPONSIBLE LAND DISTURBER" CERTIFICATION LETTER AS PART OF OBTAINING A BUILDING (OR DISTURBANCE) PERMIT.
- THE CONTRACTOR IS RESPONSIBLE FOR LICENSING AS REQUIRED BY APPLICABLE REGULATORY AGENCIES.
- THE CONTRACTOR IS RESPONSIBLE FOR ALL SALES, USE AND CAPITAL GAINS TAXES.
- UTILITY LOCATIONS SHOWN ON THIS PLAN ARE APPROXIMATE LOCATIONS DETERMINED FROM VISIBLE EVIDENCE AND AVAILABLE RECORDS. ADDITIONAL UNDERGROUND UTILITY LINES MAY BE PRESENT THAT ARE NOT SHOWN. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO LOCATE AND PRESERVE EXISTING UTILITIES.
- CONTRACTOR SHALL NOT SUBSTITUTE PRODUCTS OR MATERIALS WITHOUT PRIOR APPROVAL BY THE PROJECT OFFICER.
- THE CONTRACTOR SHALL IDENTIFY ALL STAGING AREAS AND LIMITS OF WORK FOR APPROVAL BY THE PROJECT OFFICER PRIOR TO THE START OF WORK. AREAS OUTSIDE LIMITS OF WORK SHALL NOT BE USED FOR STORAGE OR MOVEMENT OF MATERIALS, MACHINERY OR DEBRIS.
- THE CONTRACTOR SHALL OBTAIN THE PROJECT OFFICER'S APPROVAL FOR TIMES OF DAY DURING WHICH CONSTRUCTION OPERATIONS MAY OCCUR. ALL CONSTRUCTION OPERATIONS SHALL OCCUR WITHIN TIMES SPECIFIED BY LOCAL ORDINANCES.
- THE CONTRACTOR SHALL BE ON SITE AT TIME OF ALL MATERIALS DELIVERIES.
- THE CONTRACTOR SHALL KEEP THE SITE CLEAN AND FREE OF TRASH AT ALL TIMES DURING CONSTRUCTION. THE CONTRACTOR SHALL PROVIDE A TRASH RECEPTACLE TO BE USED ON SITE DURING CONSTRUCTION AND SHALL REMOVE TRASH FROM THE SITE ON A DAILY BASIS.
- THE CONTRACTOR SHALL KEEP VEHICULAR ACCESS AREAS CLEAN DURING CONSTRUCTION. VEHICULAR AND OTHER PAVED AREAS SHALL BE WASHED FREE OF MUD ON A WEEKLY BASIS DURING CONSTRUCTION.
- THE CONTRACTOR SHALL SECURE THE CONSTRUCTION AREA WITH FENCING AT END OF WORKDAY AND WHEN CONTRACTOR IS NOT ON SITE.
- THE CONTRACTOR SHALL DISTRIBUTE ALL PROJECT MATERIALS AND EQUIPMENT AND DISTRIBUTE ANY STOCKPILES IN SUCH A MANNER AS TO PROTECT EXISTING CONDITIONS, SUCH AS UTILITIES, PAVING, VEGETATION, ETC. THE CONTRACTOR SHALL NOT STOCKPILE SOIL OR CONSTRUCTION MATERIALS, OR DRIVE VEHICLES WITHIN THE CRITICAL ROOT ZONE OF EXISTING TREES TO REMAIN. THE CONTRACTOR SHALL OBTAIN THE PROJECT OFFICER'S APPROVAL FOR ALL CONSTRUCTION ACCESS AREAS, STAGING AND STOCKPILE AREAS PRIOR TO CONSTRUCTION.
- THE CONTRACTOR SHALL NOT BLOCK STREETS, PARKING AREAS, HOUSE OR DRIVEWAY ENTRANCES DURING CONSTRUCTION WITHOUT THE PROJECT OFFICER'S PERMISSION AND APPROVAL OF ANY RIGHT-OF-WAY PERMITS IF REQUIRED.
- THE CONTRACTOR SHALL STAKE THE ALIGNMENT OF ALL PAVEMENT, WALLS, CURBING, SAFETY SURFACING AND SITE FEATURES IN THE FIELD FOR APPROVAL BY THE PROJECT OFFICER PRIOR TO CONSTRUCTION.
- THE CONTRACTOR SHALL PROMPTLY REPAIR ALL DAMAGE TO EXISTING PAVEMENT, DRIVEWAYS, AND ADJACENT FACILITIES CAUSED BY CONSTRUCTION OPERATIONS. COST OF REPAIRS SHALL BE AT CONTRACTOR'S EXPENSE.
- CONTRACTOR SHALL REMOVE ALL EXCESS SOIL, TEMPORARY FENCING, EROSION CONTROL MEASURES, STABILIZATION MATERIALS, AND OTHER DEBRIS AND SHALL DISPOSE LEGALLY UPON COMPLETION OF THE PROJECT. CONTRACTOR SHALL THOROUGHLY WASH AND CLEAN ALL PAVED AREAS, WALLS, SITE FURNISHINGS AND FEATURES, ETC. UPON COMPLETION OF THE PROJECT.
- THE SITE SHOWN HEREON IS REFERENCED TO THE VIRGINIA COORDINATE SYSTEM OF 1983 AS COMPUTED FROM A FIELD RUN TOPOGRAPHIC SURVEY.
- THE SITE SHOWN HEREON IS REFERENCED TO THE NORTH AMERICAN VERTICAL DATUM OF 1988 AS COMPUTED FROM A FIELD RUN VERTICAL CONTROL SURVEY.
- REFER TO INDIVIDUAL DRAWINGS FOR ADDITIONAL NOTES.

06.18.2021	ISSUED FOR BID	
MARK	DATE	DESCRIPTION

PROJECT NO:	19-0679.001
SCALE:	N/A
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS


SHEET TITLE

COVER SHEET

1-C-100

SHEET 01 OF 20


SWM# 20-0148



PROJECT CONTROL POINTS

Point No.	Northing(Y)	Easting(X)	Elev(Z)	Description
1	6999534.3575	11874024.8553	258.05	WAD NAIL
2	6999358.8110	11873648.5154	251.51	MONUMENT
3	6999077.1994	11873973.2243	245.61	PIPE & CAP
4	6999082.0309	11874005.1133	232.45	DRILL HOLE
5	6999139.9413	11874365.1113	224.47	PIPE & CAP
6	6999240.0805	11874380.0199	240.66	PIPE & CAP
7	6999257.5540	11874221.7663	252.71	PIPE & CAP

MATCHLINE SHEET 2 OF 2



ARLINGTON
VIRGINIA

DEPARTMENT OF
ENVIRONMENTAL SERVICES
Engineering Bureau - Survey Section
2100 Clarendon Boulevard, Suite 813
Arlington, VA 22201

THIS TOPOGRAPHIC SURVEY WAS COMPLETED UNDER THE DIRECT AND RESPONSIBLE CHARGE OF STEVEN J. LEARNARD, L.S. FROM AN ACTUAL GROUND SURVEY MADE UNDER MY SUPERVISION; THAT THE IMAGES AND/OR ORIGINAL DATA WAS OBTAINED FROM 9/2019 TO 10/2019; AND THAT THIS PLAN, MAP OR DIGITAL GEOSPATIAL DATA INCLUDING METADATA MEETS MINIMUM ACCURACY STANDARDS, UNLESS OTHERWISE NOTED.


COMMONWEALTH OF VIRGINIA
12-5-2019
STEVEN J. LEARNARD
Lic. No. 2880
LAND SURVEYOR

HORIZONTAL DATUM: VIRGINIA COORDINATE SYSTEM 1983.
VERTICAL DATUM: NORTH AMERICAN VERTICAL DATUM 1988.
CONTOUR INTERVAL: 1'
UNIT OF MEASURE: U.S. SURVEY FOOT
SCALE: 1" = 25'
PREPARED FOR: ARLINGTON COUNTY DEPARTMENT OF ENVIRONMENTAL SERVICES

THE DIMENSIONS OF THE INTERIOR COURTYARDS AND BOILER ROOM ARE APPROXIMATE.
BOUNDARY INFORMATION SHOWN HEREON IS FROM AN EXISTING ALTA/NSPS LAND TITLE SURVEY PREPARED BY ARLINGTON COUNTY DEPARTMENT OF ENVIRONMENTAL SERVICES DATED APRIL 4, 2016.


PARTY CHIEF: SHRADER PROJECT:
SURVEY PM: LEARNARD 7027/CS20

TOPOGRAPHIC SURVEY
OF
PARCEL 'A'
SUBDIVISION OF THE PROPERTIES OF
NORTHERN VIRGINIA DOCTORS HOSPITAL
AND
NVDH CORPORATION
D.B. 2022, PG. 739
ARLINGTON COUNTY, VIRGINIA



1-C-101
SHEET 1 OF 2

MATCHLINE SHEET 1 OF 2




SANITARY TABLE

#11456	TOP = 253.15
	INV = 248.54
#11463	TOP = 255.81
	INV = 249.42
#11471	TOP = 255.26
	INV = 250.57
#11718	TOP = 248.34
	INV = 241.00
#11726	TOP = 237.73
	INV = 229.43
#11745	TOP = 234.64
	INV = 227.49
#11774	TOP = 212.76
	INV = 204.36


STORM TABLE

**REFERENCES INFORMATION FROM EXISTING PLANS

#2075	TOP = 252.54	#16431	TOP = 235.91
	15" RCP IN = 248.12** (16077)		15" RCP IN = 232.63** (16357)
	24" RCP IN = 245.09** (16066)		15" RCP OUT = 232.09 (16560)
	24" RCP OUT = 244.99* (16116)	#16560	TOP = 228.76
#16066	TOP = 252.98		15" RCP IN = 222.96 (16431)
	24" RCP OUT = 245.88 (2075)		15" RCP OUT = 222.86 (16560)
#16077	TOP = 252.17	#16559	TOP = 248.06
	15" RCP OUT = 247.34 (2075)		10" CMP IN = 244.91 (ROOF DRAIN)
#16087	TOP = 254.16		15" RCP IN = 241.18 (28469)
	21" RCP IN = 246.73 (16092)		15" RCP OUT = 241.16 (16639)
	21" RCP OUT = 246.66 (16116)	#16639	TOP = 222.71
#16092	TOP = 254.79		15" RCP IN = 216.64** (16560)
	21" RCP IN = 247.14 (16073)		15" RCP IN = 218.03** (16599)
	21" RCP OUT = 247.04 (16087)		18" RCP OUT = 216.11 (16704)
#16116	TOP = 249.91	#16704	TOP = 218.37
	21" RCP IN = 243.68** (16087)		18" RCP IN = 211.60 (16639)
	24" RCP IN = 242.96** (2075)		18" RCP OUT = 211.03 (16744)
	36" RCP OUT = 241.55** (16128)	#16744	TOP = 211.40
#16128	INV. 36" RCP = 239.44 (16116)		18" RCP OUT = 205.25 (16704)
#16173	TOP = 245.41	#28469	TOP = 245.41
	INV. 10" CMP = 232.04 (16173)		15" RCP OUT = 243.26 (16599)
#16201	TOP = 249.53	#29608	TOP = 252.36 (29609)
	15" RCP IN = 245.03 (EAST)		INV. 18" CMP = 248.93 (29608)
	15" RCP OUT = 244.98 (16357)	#29610	TOP = 257.71
#16337	TOP = 249.12		10" PVC OUT = 254.84 (29611)
	15" RCP OUT = 246.07 (16357)	#29611	INV. 10" PVC = 252.49 (29610)
#16357	TOP = 247.66		
	15" RCP IN = 243.84 (16337)		
	15" RCP IN = 244.16 (16316)		
	15" RCP OUT = 243.31 (16431)		




1-C-102
SHEET 2 OF 2



DEPARTMENT OF ENVIRONMENTAL SERVICES
Engineering Bureau - Survey Section
2100 Clarendon Boulevard, Suite 813
Arlington, VA 22201


THIS TOPOGRAPHIC SURVEY WAS COMPLETED UNDER THE DIRECT AND RESPONSIBLE CHARGE OF STEVEN J. LEARNARD, L.S. FROM AN ACTUAL GROUND SURVEY MADE UNDER MY SUPERVISION. THAT THE IMAGERY AND/OR ORIGINAL DATA WAS OBTAINED FROM 9/2019 TO 10/2019; AND THAT THIS PLAN, MAP OR DIGITAL GEOSPATIAL DATA INCLUDING METADATA MEETS MINIMUM ACCURACY STANDARDS UNLESS OTHERWISE NOTED.



HORIZONTAL DATUM:	VIRGINIA COORDINATE SYSTEM 1983.
VERTICAL DATUM:	NORTH AMERICAN VERTICAL DATUM 1988.
CONTOUR INTERVAL:	1'
UNIT OF MEASURE:	U.S. SURVEY FOOT
SCALE:	1" = 25'
PREPARED FOR:	ARLINGTON COUNTY DEPARTMENT OF ENVIRONMENTAL SERVICES
THE DIMENSIONS OF THE INTERIOR COURTYARDS AND BOILER ROOM ARE APPROXIMATE.	
BOUNDARY INFORMATION SHOWN HEREON IS FROM AN EXISTING ALTA/NSPS LAND TITLE SURVEY PREPARED BY ARLINGTON COUNTY DEPARTMENT OF ENVIRONMENTAL SERVICES DATED APRIL 4, 2016.	

PARTY CHIEF: SHRADER	PROJECT:
SURVEY PM: LEARNARD	7027/CS20

TOPOGRAPHIC SURVEY
OF
PARCEL 'A'
SUBDIVISION OF THE PROPERTIES OF
NORTHERN VIRGINIA DOCTORS HOSPITAL
AND
NVDH CORPORATION
D.B. 2022, PG. 739
ARLINGTON COUNTY, VIRGINIA



A. MORTON THOMAS AND ASSOCIATES, INC.
 CONSULTING ENGINEERS
 14555 AVON PARKWAY SUITE 150
 CHANTILLY, VA 20151
 PHONE (703) 817-1373
 EMAIL: AMT1@AMTENGINEERING.COM

CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1


601 SOUTH CARLIN SPRINGS ROAD
 ARLINGTON, VA 22204

MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID
PROJECT NO: 19-0679.001		
SCALE: 1"=20'		
DESIGNED BY: CMB		
DRAWN BY: JES		
CHECKED BY: JKS		
SHEET TITLE		

EXISTING CONDITIONS PLAN

1-C-103

SHEET 04 OF 20



EXISTING CONDITIONS LEGEND


FEATURE	SYMBOL
BUILDING	[Solid black shape]
CONTOURS MAJOR: MINOR	--- 250 ---
EASEMENT	--- (dashed line) ---
ELECTRIC (UNDERGROUND)	--- UGE ---
FENCE (MATERIAL NOTED)	--- X ---
PROPERTY LINE	--- (dotted line) ---
SANITARY SEWER	--- SAN ---
X" SANITARY SEWER (SIZE INCLUDED IF AVAILABLE)	--- 8" S ---
STORM (SIZE NOTED)	--- STM ---
TELEPHONE (UNDERGROUND)	--- UGT ---
WALL	--- (dashed line) ---
WATER	--- 8" W ---
EDGE OF CONC.	--- (dashed line) ---
CURB	--- (dashed line) ---
RESOURCE PROTECTION AREA	--- RPA ---
STREAM CENTERLINE	--- (dotted line) ---
BUILDING RESTRICTION LIMITS FOR PUBLIC UTILITIES	--- (dashed line) ---
ELECTRIC BOX	[Square symbol]
FIRE HYDRANT	[Circle symbol]
GAS VALVE	[Circle symbol]
GROUND LIGHT	[Triangle symbol]
GUY WIRES	--- Y ---
IRON PIPE OR PIN	[Circle symbol]
LIGHT POLE	[Circle symbol]
SANITARY MANHOLE	[Circle symbol]
STORM BASIN	[Square symbol]
STORM MANHOLE	[Square symbol]
TRAFFIC CONTROL BOX	[Square symbol]
SIGN	[Triangle symbol]
TRAVERSE	[Triangle symbol]
TREES, WOODED AREA	[Circle symbol]
UTILITY MANHOLE TYPE INDICATED ELECTRIC, TELE, ETC	[Circle symbol]
UTILITY POLE	[Square symbol]
WATER MANHOLE	[Circle symbol]
WATER VALVE	[Circle symbol]
DROP INLET	[Circle symbol]
ROOF DRAIN (DATR)	[Circle symbol]

STORM TABLE


#16431	TOP = 235.91	
15" RCP IN = 232.63**	(16357)	
15" RCP OUT = 232.09	(16560)	
#16560	TOP = 228.76	
15" RCP IN = 222.96	(16431)	
15" RCP OUT = 222.86	(16560)	
#16599	TOP = 248.06	
10" CMP IN = 244.91	(ROOF DRAIN)	
15" RCP IN = 241.18	(28469)	
15" RCP OUT = 241.16	(16639)	
#16639	TOP = 222.71	
15" RCP IN = 216.64**	(16560)	
15" RCP IN = 218.03**	(16599)	
18" RCP OUT = 216.11	(16704)	
#16704	TOP = 218.37	
18" RCP IN = 211.60	(16639)	
18" RCP OUT = 211.03	(16744)	
#16744	TOP = 211.40	
18" RCP OUT = 205.25	(16704)	
#28469	TOP = 245.41	
15" RCP OUT = 243.26	(16599)	
#29608	INV. 18" CMP = 252.36	(29609)
#29609	INV. 18" CMP = 248.93	(29608)
#29610	TOP = 257.71	
10" PVC OUT = 254.84	(29611)	
#29611	INV. 10" PVC = 252.49	(29610)
#2075	TOP = 252.54	
15" RCP IN = 248.12**	(16077)	
24" RCP IN = 245.09**	(16066)	
24" RCP OUT = 244.99**	(16116)	
#16092	TOP = 254.79	
21" RCP IN = 247.14	(16073)	
21" RCP OUT = 247.04	(16087)	
#16116	TOP = 249.91	
21" RCP IN = 243.66**	(16087)	
24" RCP IN = 242.96**	(2075)	
36" RCP OUT = 241.55**	(16128)	
#16128	INV. 36" RCP = 239.44	(16116)
#16173	INV. 10" CMP = 238.30	(16201)
#16201	INV. 10" CMP = 232.04	(16173)
#16316	TOP = 249.53	
8" PVC IN = 245.03	(EAST)	
15" RCP OUT = 244.98	(16357)	
#16357	TOP = 247.66	
15" RCP IN = 243.84	(16337)	
15" RCP IN = 244.16	(16316)	
15" RCP IN = 243.31	(16431)	
#16337	TOP = 249.12	
15" RCP OUT = 246.07	(16357)	
#10588	TOP = 247.71	
8" PVC OUT = 245.60	(200120)	
#10797	TOP = 247.58	
4" PVC IN = 246.27	(ROOF DRAIN)	
10" PVC IN = 244.66	(10825)	
8" PVC OUT = 244.03	(WEST)	
#10825	TOP = 246.65	
4" PVC IN = 245.65	(ROOF DRAIN)	
10" PVC OUT = 245.00	(10797)	
#20012	TOP = 247.49	
8" PVC IN = 242.79	(EAST)	
10" PVC IN = 242.94	(10588)	
12" RCP OUT = 242.465	(20023)	
#20023	TOP = 248.10	
12" RCP IN = 237.00	(20012)	
12" RCP OUT = 236.45	(S.W.)	

SANITARY TABLE

#10168	TOP = 248.34	INV = 241.00
#10165	TOP = 237.73	INV = 229.43
#12999	TOP = 234.64	INV = 227.49
#13000	TOP = 212.76	INV = 204.36
#10166	TOP = UNKNOWN	INV = 244.25
#14918	TOP = 257.30	INV = 244.87
#13001	(DATR)	TOP = UNKNOWN
#13002	(DATR)	TOP = UNKNOWN






CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1

601 SOUTH CARLIN SPRINGS ROAD
 ARLINGTON, VA 22204



TREE PROTECTION LEGEND:

- TREE TRUNK AND LIMB PROTECTION WRAP (1-C-106)
- TREE TO BE REMOVED, CONTRACTOR TO GRIND STUMPS
- TPF 6' CHAIN LINK TREE PROTECTION (1-C-106)
- RP ROOT PRUNING (1-C-106)
- CRZ CRITICAL ROOT ZONE

- TREE PRESERVATION NOTES:**
- PRESERVE ALL EXISTING TREES.
 - IF THE TREE PRESERVATION MEASURES PROVIDED ON THE PLANS AND SPECIFICATIONS ARE NOT FOLLOWED DURING ANY PART OF THE CONSTRUCTION PROCESS, THE URBAN FORESTER MAY ASK FOR THE REMOVAL AND REPLACEMENT OF ANY DAMAGED TREES AT THE CONTRACTOR'S EXPENSE. THIS WILL BE COORDINATED WITH THE PROJECT OFFICER AND LANDSCAPE ARCHITECT.
 - CONTRACTOR SHALL COORDINATE TREATMENT (I.E., RADIAL TRENCHING, SUPERSONIC AIR TOOL DECOMPACTION, SOIL COMPOST AMENDMENT, ROOT PRUNING) OF EXISTING TREES WITH COUNTY AS DEEMED NECESSARY.
 - SEE TREE SCHEDULE AND PRESERVATION SUMMARY ON I-C-107 FOR TREE-BY-TREE LIST OF PROPOSED TREE PRESERVATION MEASURES.
 - SEE TREE PROTECTION DETAILS ON I-C-106.
 - SEE DEMOLITION PLAN FOR ADDITIONAL INFORMATION.
 - ARLINGTON COUNTY URBAN FORESTER RESERVES THE RIGHT TO MAKE ADJUSTMENTS TO TREE PROTECTION MEASURES BASED ON CONDITIONS ENCOUNTERED IN THE FIELD.
 - ALL ADJUSTMENTS TO THIS PLAN SHALL BE APPROVED BY URBAN FORESTER PRIOR TO SITE WORK.
 - AN INDEPENDENT ARBORIST, HIRED BY THE GENERAL CONTRACTOR, SHALL BE ON-SITE DURING DEMOLITION OF EXISTING PLAYGROUND TO MONITOR TREE PRESERVATION MEASURES. INDEPENDENT ARBORIST SHALL OVERSEE DEMOLITION WITHIN CRITICAL ROOT ZONES AND REPORT TO DPR FORESTRY STAFF WITH REGULAR COMMUNICATION AND WEEKLY WRITTEN REPORT, INCLUDING PHOTOGRAPHS, NOTES, PRESERVATION UPDATES AND CONSTRUCTION PROGRESS.
 - CONTRACTOR TO NOTIFY URBAN FORESTER 72 HOURS PRIOR TO INSTALLATION OF ANY TREE PRESERVATION MEASURES SHOWN ON PLANS AND URBAN FORESTER SHALL APPROVE THE LAYOUT OF TREE PRESERVATION MEASURES.

- ADDITIONAL TREE PRESERVATION NOTES:**
- GENERALLY, TREE PROTECTION FENCE IS LOCATED AT THE LIMIT OF DISTURBANCE. THEREFORE, THE LAYOUT OF LINES DEPICTING TREE PROTECTION FENCE IS DIAGRAMMATIC, AND FOR REFERENCE ONLY. PLEASE REFER TO THE TREE PRESERVATION DETAILS FOR MORE INFORMATION.
 - BEFORE ANY GRADING, DEMOLITION, SITE IMPROVEMENTS, OR OTHER DISTURBANCE (ASIDE FROM THE INSTALLATION OF TREE PROTECTION AND EROSION/SEDIMENT CONTROL DEVICES) IS PERFORMED, TREE PROTECTION MEASURES SHALL BE INSTALLED PER THE PLAN BY THE CONTRACTOR AND INSPECTED/APPROVED BY AN ARLINGTON COUNTY ARBORIST.
 - THIS PLAN IS FOR TREE PROTECTION/FOREST CONSERVATION PURPOSES ONLY.
 - IF TREE PROTECTION MEASURES PROVIDED ON THE PLANS AND SPECIFICATIONS ARE NOT FOLLOWED DURING ANY PART OF THE CONSTRUCTION PROCESS, THE URBAN FORESTER MAY ASK FOR THE REMOVAL AND REPLACEMENT OF TREES AT THE CONTRACTOR'S EXPENSE. THIS WILL BE COORDINATED WITH THE PROJECT OFFICER.
 - SEE THE FOLLOWING FOR ADDITIONAL TREE PRESERVATION NOTES, INFORMATION AND REQUIREMENTS:
 - E.A. TREE PRESERVATION SPECIFICATION
 - E.B. DEMOLITION PLAN

5 STORY BRICK DOCTORS OFFICE BUILDING
 611 SOUTH CARLIN SPRINGS ROAD
 (NOT INCLUDED)

PARCEL B
 RPC: 21028144
 NORTHERN VIRGINIA DOCTORS
 MEDICAL CENTER CONDOMINIUM


SUBDIVISION OF THE PROPERTY OF
NORTHERN VIRGINIA DOCTORS HOSPITAL CORPORATION & NVDH CORPORATION
 D.B. 2022, PG. 739

MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID

PROJECT NO:	19-0679.001
SCALE:	1"=20'
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS
SHEET TITLE	


TREE PRESERVATION PLAN

1-C-104




- NOTES:**
- MATTING MATERIAL SHALL BE DOUBLE SIDED GEOCOMPOSITE, GEONET CORE WITH NON-WOVEN COVERING (SUCH AS TENAX TENDRAIN 770/2) OR APPROVED EQUIVALENT.
 - RPM SHALL BE INSTALLED BY A CERTIFIED ARBORIST.
 - TO BE USED FOR DESIGNATED TEMPORARY CONSTRUCTION ACCESS AND STOCKPILE AREAS.
 - MATTING SHALL BE PLACED ON 4'-6" WOOD CHIP MULCH UNLESS OTHERWISE DIRECTED.
 - FOR HEAVY TRAFFIC AREAS, MATTING SHALL BE COVERED WITH 6'-8" WELL GRADED CRUSHED AGGREGATE. ADDITIONAL LAYERS OF GEOTEXTILE MAY BE NEEDED.
 - ARLINGTON COUNTY URBAN FORESTER SHALL BE NOTIFIED 72 HOURS PRIOR TO INSTALLATION AND REMOVAL.
- COVER MATTING WITH HEAVY AGGREGATE FOR HEAVY TRAFFIC USE
- ROOT PROTECTION MATTING ANCHORED BY 12" LANDSCAPE NAILS @ 3' AVERAGE SPACING.
- 4'-6" WOOD CHIP MULCH
- ROOT PRUNE PER PLAN (SEE DETAIL)
- EXISTING UNDISTURBED SOIL
- ROOTS TO REMAIN

1 TEMPORARY ROOT PROTECTION MATTING WITHIN CRZ
311300.2INS NOT TO SCALE




- NOTES:**
- TREE PROTECTION FENCE (TPF) SHALL BE INSTALLED PRIOR TO ANY SITE WORK, CLEARING OR DEMOLITION. ARLINGTON COUNTY URBAN FORESTER SHALL BE NOTIFIED 72 HOURS PRIOR TO INSTALLATION OR ANY OTHER TREE PRESERVATION MEASURE SPECIFIED IN PLANS AND SHALL APPROVE LAYOUT.
 - NO PERSONNEL, VEHICLES, EQUIPMENT, CONSTRUCTION MATERIALS OR DEBRIS ALLOWED IN TREE PROTECTION AREAS WITHOUT WRITTEN CONSENT OF ARLINGTON COUNTY URBAN FORESTER.
 - REMOVE TPF ONLY WITH APPROVAL FROM ARLINGTON COUNTY URBAN FORESTER AFTER ALL SITE WORK HAS BEEN COMPLETED.
 - SIGN MATERIAL TO BE WEATHER RESISTANT.

2 6" CHAIN LINK TREE PROTECTION FENCE
311300.1 (2016)





- NOTES:**
- ROOT PRUNING SHALL BE DONE WITH A TRENCHER OR VIBRATORY FLOW TO A DEPTH OF 12". ROOTS OVER 1.5" IN DIAMETER SHALL HAVE A CLEAN CUT MADE BY A CLEAN SAW ON THE SURFACE OF THE ROOT, WHICH IS STILL ATTACHED TO THE TREE. DO NOT BREAK OR CHOP. DO NOT PAINT THE CUT ROOT END. IF EXCAVATION IS FOR INSTALLATION OF UNDERGROUND UTILITIES, LEAVE THE ROOT INTACT AND THREAD THE LINES UNDERNEATH.
 - ROOT PRUNING SHALL TAKE PLACE PRIOR TO ANY CLEARING AND GRADING. EXACT LOCATION OF TREE PROTECTION AREAS SHALL BE STAKED OR FLAGGED PRIOR TO TRENCHING AND SHALL BE APPROVED BY ARLINGTON COUNTY URBAN FORESTER.
 - ROOT PRUNING SHALL BE CONDUCTED WITH THE SUPERVISION OF AN ISA CERTIFIED ARBORIST.
 - BACKFILL THE ROOT-PRUNING TRENCH WITH APPROVED LOOSE TOPSOIL MIX AND TOP WITH 3'-4" BARK MULCH AND MARK LOCATION FOR FUTURE REFERENCE. SILT FENCE MAY BE INSTALLED IN TRENCH PRIOR TO BACKFILLING AS LONG AS THE TRENCH IS NOT OPEN FOR LONGER THAN 48 HOURS WITHOUT WATERING.
 - ROOT PRUNING WORK SHALL NOT BE DONE WHEN MORE THAN THE TOP 1 INCH OF SOIL IS FROZEN. ROOT PRUNING SHALL NOT BE UNDERTAKEN WHEN THE SOIL IS WET AND CONDITIONS ARE MUDDY.
 - THE ARLINGTON COUNTY URBAN FORESTER SHALL BE NOTIFIED 72 HOURS PRIOR TO TRENCHING AND WHEN ALL ROOT PRUNING AND TREE PROTECTION FENCE INSTALLATION IS COMPLETE.

3 ROOT PRUNING
311300.5 (2019) N.T.S.



- NOTES:**
- TRUNK WRAP MATERIAL SHALL BE DOUBLE SIDED GEOCOMPOSITE, GEONET CORE WITH NON-WOVEN COVERING (SUCH AS TENAX TENDRAIN 770/2) OR AN APPROVED EQUAL.
 - WRAP SHALL BE INSTALLED BY A CERTIFIED ARBORIST.
 - WRAP SHALL BE INSTALLED PRIOR TO ANY SITE WORK, CLEARING OR DEMOLITION.
 - WRAP SHALL BE MAINTAINED THROUGHOUT CONSTRUCTION. REMOVE WRAP ONLY WITH APPROVAL AND AFTER ALL SITE WORK HAS BEEN COMPLETED. ARLINGTON COUNTY URBAN FORESTER SHALL BE NOTIFIED 72 HOURS PRIOR TO REMOVAL.
 - WRAP SHALL BE REMOVED PROMPTLY AFTER CONSTRUCTION.
 - MAJOR SCAFFOLD LIMBS MAY ALSO REQUIRE THIS PROTECTION AS DIRECTED BY THE PROJECT ARBORIST OR REQUESTED BY ARLINGTON COUNTY URBAN FORESTER.
 - WRAP SHALL EXTEND AS HIGH AS ADJACENT MACHINERY THAT IS WORKING ADJACENT TO TREES. PROJECT ARBORIST AND ARLINGTON COUNTY URBAN FORESTER MAY REQUIRE DOUBLE WRAP OR HEAVY DUTY WRAP IN AREAS OF MAJOR EXCAVATION.

4 TREE TRUNK AND LIMB PROTECTION WRAP
311300.15NS (2019) N.T.S.



- NOTES:**
- GRAPHICALLY, THE CRITICAL ROOT ZONE (CRZ) IS REPRESENTED AS A CIRCULAR REGION MEASURED OUTWARD FROM A TREE TRUNK REPRESENTING THE AREA OF ROOTS THAT MUST BE MAINTAINED OR PROTECTED FOR THE TREE'S SURVIVAL.
 - THE CRZ OF A TREE IS THE ZONE IN WHICH THE MAJORITY OF THE ROOTS LAY. 95% OF THE ROOTS OF MOST TREES WILL BE FOUND IN THE UPPER 12-18" OF THE SOIL. MOST OF THE ROOTS THAT SUPPLY THE NUTRIENTS AND WATER TO THE TREE ARE FOUND JUST BELOW THE SOIL SURFACE. THE TOTAL AMOUNT OF A TREE'S ROOTS ARE GENERALLY PROPORTIONAL TO THE VOLUME OF THE TREE'S CANOPY. THEREFORE, IF THE ROOTS ONLY PENETRATE A THIN LAYER OF SOIL, THEN THE ROOTS MUST SPREAD FAR FROM THE TREE, BEYOND THE EXTENSION OF THE CANOPY.
 - PLOT ACCURATE TRUNK LOCATIONS OF ALL TREES GREATER THAN 3" DIAMETER AT BREAST HEIGHT (DBH) AND/OR TREE STANDS WITHIN DEVELOPMENT AREAS ON ALL PLANS FOR THE PROJECT AND DELINEATE THEIR ESTIMATED CRITICAL ROOT ZONE.
 - PLOT ACCURATE TRUNK LOCATIONS OF OFFSITE TREES WHICH WILL HAVE THEIR CRZ AFFECTED BY DEVELOPMENT AND DELINEATE THEIR ESTIMATED CRITICAL ROOT ZONE.

5 TREE PROTECTION DETAIL FOR DETERMINING CRITICAL ROOT ZONE
311300.3 (2019) N.T.S.



A. MORTON THOMAS AND ASSOCIATES, INC.
CONSULTING ENGINEERS
14555 AVON PARKWAY SUITE 150
CHANTILLY, VA 20151
PHONE (703) 817-1373
EMAIL: AMT1@AMTENGINEERING.COM

CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1
601 SOUTH CARLIN SPRINGS ROAD
ARLINGTON, VA 22204

MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID

PROJECT NO:	19-0679.001
SCALE:	N/A
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS
SHEET TITLE	

TREE PRESERVATION DETAILS


1-C-106

CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1

601 SOUTH CARLIN SPRINGS ROAD
 ARLINGTON, VA 22204



- DEMOLITION KEYNOTES**
- 1. BUILDING TO BE REMOVED
 - 2. STAIRS TO BE PROTECTED AND PRESERVED
 - 3. STAIRS TO BE REMOVED
 - 4. CONCRETE PAVING TO BE REMOVED
 - 5. AREA DRAIN AND ASSOCIATED PIPING TO BE REMOVED
 - 6. PLUG STRUCTURE AFTER REMOVAL OF INCOMING STORM DRAIN PIPE


- DEMOLITION LEGEND**
- LOD LIMITS OF DISTURBANCE
 - [Cross-hatched box] BUILDING TO BE REMOVED
 - [Solid black box] CONCRETE PAVEMENT TO BE REMOVED
 - [Hexagonal pattern box] ASPHALT TO BE REMOVED
 - [Dashed line] UTILITY LINE TO BE REMOVED

DEMOLITION NOTES

1. LOCATION OF ALL UTILITIES SHOWN ARE APPROXIMATE. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO FIELD VERIFY AND DETERMINE THE EXACT LOCATION AND DEPTH OF ALL UTILITIES WITHIN THE LIMIT OF DISTURBANCE PRIOR TO COMMENCING WORK. REPORT ANY DISCREPANCY TO THE PROJECT OFFICER. THE CONTRACTOR SHALL CONTACT MISS UTILITY AT 811 A MINIMUM OF 72 HOURS PRIOR TO ANY EXCAVATION TO DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES AND SHALL BE FULLY RESPONSIBLE FOR ANY AND ALL DAMAGES WHICH MAY BE OCCASIONED BY THE CONTRACTOR'S FAILURE TO EXACTLY LOCATE AND PRESERVE ANY AND ALL EXISTING UTILITIES.
2. THE DEMOLITION PLAN IS A GENERAL GUIDE OF WHAT ITEMS NEED TO BE DEMOLISHED. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO IDENTIFY ALL ITEMS THAT REQUIRED DEMOLITION TO COMPLETE THE PROPOSED CONSTRUCTION. REFER TO THE SEQUENCE OF CONSTRUCTION ON SHEET 1-C-111 FOR ADDITIONAL NOTES RELATED TO DEMOLITION.
3. CONTRACTOR SHALL PROTECT AND PRESERVE ALL EXISTING SITE STRUCTURES AND FEATURES NOT SCHEDULED FOR DEMOLITION AND/OR CONSTRUCTION FROM DAMAGE DUE TO DEMOLITION PROCEDURES. ANY RESULTING DAMAGE SHALL BE THE CONTRACTOR'S RESPONSIBILITY AND SHALL BE RESTORED AT THE CONTRACTOR'S EXPENSE TO THE SATISFACTION OF THE PROJECT OFFICER.
4. TREE PROTECTION AND CONSTRUCTION FENCE SHALL BE THE SAME WHEREVER THEY OVERLAP.
5. THE CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR SAFETY AND SECURITY AT THE PROJECT SITE FOR THE DURATION OF THE CONTRACT.
5. CONTRACTOR SHALL COORDINATE WITH THE PROJECT OFFICER TO IDENTIFY ANY NECESSARY STAGING/STORAGE AREAS. PROPOSED STAGING AND STORAGE AREAS SHALL BE REVIEWED AND APPROVED BY THE PROJECT OFFICER, AND THE LIMITS OF WORK WILL BE ADJUSTED ACCORDINGLY.
6. ANY STOCKPILING, REGARDLESS OF LOCATION ON SITE, SHALL BE STABILIZED IMMEDIATELY AFTER ITS ESTABLISHMENT AND FOR THE DURATION OF THE PROJECT. STOCKPILES SHALL BE CONTAINED BY STRAW BALES OR EROSION CONTROL FENCING AND COVERED WITH PLASTIC OR CANVAS AT THE END OF EACH WORK DAY FOR THE DURATION OF THE PROJECT.
7. TEMPORARY CONSTRUCTION FENCING SHALL BE ERECTED AS SHOWN ON THE PLANS PRIOR TO BEGINNING CONSTRUCTION OPERATIONS AND MAINTAINED UNTIL COMPLETION OF PROJECT.
8. WHERE ITEMS TO BE REMOVED OCCUR WITHIN TREE PROTECTION ZONES, THE CONTRACTOR SHALL REMOVE THE ITEMS WORKING WITH A COUNTY ARBORIST (PROVIDED BY COUNTY) ON-SITE TO OBSERVE AND MINIMIZE TREE DAMAGE. CONTRACTOR SHALL NOTIFY THE PROJECT OFFICER FIVE BUSINESS DAYS PRIOR TO THESE REMOVALS.
9. CARE SHALL BE TAKEN TO PRESERVE EXISTING TREES AND THEIR ROOT SYSTEMS. TREES INCURRING ROOT DAMAGE DUE TO CONSTRUCTION SHALL BE PRUNED AND FERTILIZED PER THE SPECIFICATIONS.
10. NO MATERIALS OR EQUIPMENT SHALL BE PERMITTED WITHIN THE TREE PROTECTION AREA.

NOTE: CONTRACTOR SHALL PROTECT AND PRESERVE EXISTING 5-STORY OFFICE BUILDING AND MULTI-STORY PARKING GARAGE.

11. UNAUTHORIZED TREE REMOVALS, TREE DEATH OR SEVERE DAMAGE DUE TO THE CONTRACTOR'S FAILURE TO EXERCISE PROPER CARE WHEN WORKING NEAR TREES, SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
12. COUNTY ARBORIST INSPECTION IS REQUIRED PRIOR TO ANY SITE LAND DISTURBANCE ACTIVITY.
13. CONTRACTOR SHALL NOTIFY "MISS UTILITY" AT 811 OR (800) 552-7001, 72 HOURS PRIOR TO START OF ANY EXCAVATION OR CONSTRUCTION FOR THE MARKING OF EXISTING UNDERGROUND UTILITIES.
14. DEMOLITION STAGE EROSION AND SEDIMENT CONTROLS AND TREE PROTECTION MEASURES SHALL BE INSTALLED PRIOR TO DEMOLITION.
15. REFER TO TREE PRESERVATION DETAILS AND EROSION AND SEDIMENT CONTROL DRAWINGS FOR TREE PROTECTION AND OTHER REQUIRED TREE CARE.
16. ALL MATERIAL FROM DEMOLITION NOT IDENTIFIED FOR REUSE SHALL BE REMOVED FROM THE SITE AND DISPOSED OF IN ACCORDANCE WITH APPROPRIATE REGULATIONS.
17. ALL PAVEMENT REMOVED SHALL BE DONE SUCH THAT REMAINING PAVEMENT IS LEFT WITH CLEAN STRAIGHT EDGE. CONCRETE PAVEMENT/CURBING SHALL BE REMOVED TO THE NEAREST JOINT.
18. EXISTING PAVEMENT SHALL BE SAW CUT WHEN NEXT TO REMAINING PAVEMENT BEFORE REMOVAL. ALL SAW CUTS SHALL BE STRAIGHT, EVEN CUTS; JAGGED CUTS WILL NOT BE PERMITTED.
19. CONCRETE REMOVAL: SHALL INCLUDE CONCRETE, STEEL REINFORCEMENT, AND GRAVEL BASE WHERE NO PROPOSED CONCRETE.
20. ASPHALT REMOVAL FOR STABILIZED CONSTRUCTION ENTRANCE SHALL INCLUDE SURFACE AND BASE MATERIALS. SUBBASE MATERIAL SHALL REMAIN.
21. CONTRACTOR SHALL PROVIDE EXISTING DAMAGE PHOTOS PRIOR TO MOBILIZING OR PERFORMING ANY WORK. LOCATIONS OF PICTURES TO BE RECORDED ON THIS SHEET.
22. TO PREVENT DAMAGES OUTSIDE THE LIMITS OF DISTURBANCE, NO AREAS OUTSIDE THE LOD SHALL BE USED FOR STAGING OR STORAGE.
23. UPON COMPLETION OF THE PROJECT, ALL EXCESS SOIL, TEMPORARY FENCING, EROSION CONTROL MEASURES, STABILIZATION MATERIALS, AND OTHER DEBRIS SHALL BE REMOVED FROM THE SITE AND DISPOSED OF LEGALLY. ALL PAVED AREAS, WALLS, ETC. SHALL BE THOROUGHLY WASHED AND CLEANED UPON COMPLETION OF THE PROJECT.
24. CONTRACTOR MAY USE EXISTING PARKING LOT AS A STAGING AREA DURING DEMOLITION.
25. CONTRACTOR SHALL PROTECT EXISTING LIGHT POLES TO REMAIN THROUGHOUT CONSTRUCTION. ANY DAMAGE SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.



MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID


PROJECT NO:	19-0679.001
SCALE:	1"=20'
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS
SHEET TITLE	

DEMOLITION PLAN

CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1
 601 SOUTH CARLIN SPRINGS ROAD
 ARLINGTON, VA 22204



REFER TO SEQUENCE OF CONSTRUCTION PHASE 1, NOTE E ON 1-C-111.

REFER TO SEQUENCE OF CONSTRUCTION PHASE 1, NOTE D ON 1-C-111.

CRITICAL SLOPE NOTE:
 REFER TO SEQUENCE OF CONSTRUCTION NOTES ON 1-C-111. CONTRACTOR SHALL TAKE SPECIAL CARE TO MONITOR AND MAINTAIN SUPER SILT FENCE WITHIN AND UPSTREAM OF STEEP SLOPES TO PROTECT FROM EXCESSIVE EROSION POTENTIAL.

MULTI-STORY CONCRETE PARKING STRUCTURE FOR 611 SOUTH CARLIN SPRINGS ROAD (NOT INCLUDED)


5 STORY BRICK DOCTORS OFFICE BUILDING 611 SOUTH CARLIN SPRINGS ROAD (NOT INCLUDED)

**PARCEL B
 RPC: 21028144
 NORTHERN VIRGINIA DOCTORS MEDICAL CENTER CONDOMINIUM**

SUBDIVISION OF THE PROPERTY OF
NORTHERN VIRGINIA DOCTORS HOSPITAL CORPORATION & NVDH CORPORATION
 D.B. 2022, PG. 739

EROSION AND SEDIMENT CONTROL PLAN LEGEND

NO.	KEY	SYMBOL	DESCRIPTION
		---	PROPERTY LINE
		---	LIMITS OF DISTURBANCE
		---	BUILDING RESTRICTION LIMITS FOR PUBLIC UTILITIES
		---	SUPER SILT FENCE
3.02	CE	[Symbol]	MODIFIED 10' x 40' STONE CONSTRUCTION ENTRANCE WITH WASH RACK
3.07	IP	[Symbol]	INLET PROTECTION



MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID

PROJECT NO:	19-0679.001
SCALE:	1"=20'
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS
SHEET TITLE	


EROSION & SEDIMENT CONTROL PLAN - PHASE I

1-C-109

CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1
 601 SOUTH CARLIN SPRINGS ROAD
 ARLINGTON, VA 22204



CRITICAL SLOPE NOTE:
 REFER TO SEQUENCE OF CONSTRUCTION NOTES ON 1-C-111. CONTRACTOR SHALL TAKE SPECIAL CARE TO MONITOR AND MAINTAIN SUPER SILT FENCE WITHIN AND UPSTREAM OF STEEP SLOPES TO PROTECT FROM EXCESSIVE EROSION POTENTIAL.

MULTI-STORY CONCRETE PARKING STRUCTURE FOR 611 SOUTH CARLIN SPRINGS ROAD (NOT INCLUDED)

5 STORY BRICK DOCTORS OFFICE BUILDING 611 SOUTH CARLIN SPRINGS ROAD (NOT INCLUDED)

PARCEL B
 RPC: 21028144
 NORTHERN VIRGINIA DOCTORS MEDICAL CENTER CONDOMINIUM

SUBDIVISION OF THE PROPERTY OF
NORTHERN VIRGINIA DOCTORS HOSPITAL CORPORATION & NVDH CORPORATION
 D.B. 2022, PG. 739

EROSION AND SEDIMENT CONTROL PLAN LEGEND


NO.	KEY	SYMBOL	DESCRIPTION
		---	EASEMENT FOR EMERGENCY EGRESS PURPOSES
		---	PROPERTY LINE
		---	LIMITS OF DISTURBANCE
		---	BUILDING RESTRICTION LIMITS FOR PUBLIC UTILITIES
		---	SSF
		---	SUPER SILT FENCE
3.02	CE	[Symbol]	MODIFIED 10' x 40' STONE CONSTRUCTION ENTRANCE WITH WASH RACK
3.36	B/M	[Symbol]	PROTECTIVE BLANKET / SOIL STABILIZATION MATTING
3.07	IP	[Symbol]	INLET PROTECTION

MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID

PROJECT NO:	19-0679.001
SCALE:	1"=20'
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS
SHEET TITLE	

EROSION & SEDIMENT CONTROL PLAN - PHASE II

1-C-110



CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1

601 SOUTH CARLIN SPRINGS ROAD
 ARLINGTON, VA 22204


MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID

PROJECT NO:	19-0679.001
SCALE:	N/A
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS


SHEET TITLE

EROSION & SEDIMENT CONTROL DETAILS


1-C-112



SSP SUPER SILT FENCE DETAIL
NOT TO SCALE



SOURCE: VA. DSWC PLATE: 3.07-2



DocuSign Envelope ID: 8947E8D3-0D7C-47FF-8664-FC667BCDF48B

7/28/2020
date

Qianqian Li, P.E.
 ESC Program Administrator
 Department of Environmental Services
 2100 Clarendon Boulevard, Suite 813
 Arlington, Virginia 22201

Re: Erosion and Sediment Control Permit Application for:
601 S Carlin Springs Road
 street address
RPC: 21-028-097
 lot, block, section subdivision
SWM 20-0148; LDA20123
 permit number

Dear Mrs. Li:

I hereby certify that I accept the responsibilities of Responsible Land Disturber for the above referenced project. I understand that these responsibilities include:


- Reviewing the erosion and sedimentation (E&S) plan for the project.
- Walking the site prior to construction to identify critical areas.
- Conducting a pre-construction briefing with earth moving and site contractors to present the E&S plan and highlight the presence of critical areas, the limits of clearing and the required E&S controls and tree protection measures to be installed. Call 703-228-0760 to schedule pre-construction meeting.
- Regularly inspecting the site during construction to ensure that all E&S controls are functioning and are adequate to address erosion and sedimentation. Inspect the site 48 hours after a runoff-generating storm, and provide a copy of the inspection findings to the county.
- Reporting to the owner the presence inadequate or non functioning E&S controls when they are observed.
- Ensuring that temporary soil stabilization is applied within 7 days to areas denuded that will remain undisturbed for longer than 14 days. Permanent stabilization shall be applied to areas that are to be left dormant for more than one year.
- Calling (703) 228-0760 at least 80 hours before demolishing any structure.

I may be reached at 301-984-4221 with questions about this plan or my execution of the duties of Responsible Land Disturber.

Sincerely,


DocuSigned by:
Ziba Parsa
 EUS00AS12E0E473

signed
 Ziba Parsa
 name printed
 Professional Engineer 45037
 professional registration (type and number)



Source: Adapted from Ludlow Products Brochure Plate 3.36-1

PORTABLE SEDIMENT TANK




SOURCE: USDA - SCS PLATE: 3.26-1

CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1

601 SOUTH CARLIN SPRINGS ROAD
 ARLINGTON, VA 22204




SITE KEYNOTES

- 1 BUILDING ADDITION
(REFER TO ARCHITECTURAL DRAWINGS FOR DETAILS)
- 2 CONCRETE PAVING
(SEE DETAIL 2/1-C-501, R-2.0/1-C-501)
- 3 RETAINING WALL
(REFER TO STRUCTURAL PLANS FOR DETAIL)
- 4 CONCRETE STEPS
(SEE DETAIL R-3.0/1-C-501)
- 5 ASPHALT PAVEMENT PATCH
(SEE DETAIL 2/1-C-501)
- 6 SPLASH BLOCK
(REFER TO ARCHITECTURAL PLANS FOR DETAILS)

SITE AND GRADING LEGEND

- PROPERTY LINE
- - - EASEMENT FOR EMERGENCY EGRESS PURPOSES
- - - BUILDING RESTRICTION LIMITS FOR PUBLIC UTILITIES
- LOD --- LIMITS OF DISTURBANCE
- /// BUILDING ADDITION
- 250--- PROPOSED MAJOR CONTOUR
- 249--- PROPOSED MINOR CONTOUR
- [Pattern] CONCRETE PAVEMENT
- [Pattern] ASPHALT PAVEMENT PATCH
- ▶ DOOR
- RETAINING WALL



MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID

PROJECT NO:	19-0679.001
SCALE:	1"=20'
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS
SHEET TITLE	

SITE, GRADING & UTILITY PLAN





1-C-113

CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1

601 SOUTH CARLIN SPRINGS ROAD
 ARLINGTON, VA 22204



MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID

PROJECT NO:	19-0679.001
SCALE:	N/A
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS
SHEET TITLE	


SITE DETAILS

1-C-501



CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1
 601 SOUTH CARLIN SPRINGS ROAD
 ARLINGTON, VA 22204



PRE-DEVELOPMENT PERVIOUS AREAS		PRE-DEVELOPMENT IMPERVIOUS AREAS	
	MANAGED TURF - 1,887 SF (0.0433 AC)		BUILDING (2,494 SF)
	LIMITS OF DISTURBANCE - 5,436 SF (0.1248 AC)		CONCRETE (585 SF)
			ASPHALT (470 SF)
			TOTAL - 3,549 SF (0.0815 AC)



MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID

PROJECT NO:	19-0679.001
SCALE:	1"=20'
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS



SHEET TITLE
PRE-DEVELOPMENT WATER QUALITY MAP

1-C-701

CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1
 601 SOUTH CARLIN SPRINGS ROAD
 ARLINGTON, VA 22204



SUBDIVISION OF THE PROPERTY OF
NORTHERN VIRGINIA DOCTORS HOSPITAL CORPORATION & NVDH CORPORATION
 D.B. 2022, PG. 739

MULTI-STORY CONCRETE PARKING STRUCTURE FOR 611 SOUTH CARLIN SPRINGS ROAD (NOT INCLUDED)

PARCEL B
 RPC: 21028144
 NORTHERN VIRGINIA DOCTORS MEDICAL CENTER CONDOMINIUM


5 STORY BRICK DOCTORS OFFICE BUILDING 611 SOUTH CARLIN SPRINGS ROAD (NOT INCLUDED)

POST-DEVELOPMENT PERVIOUS AREAS

- MANAGED TURF - 4,365 SF (0.1002 AC)
- LOD - LIMITS OF DISTURBANCE - 5,436 SF (0.1248 AC)

POST-DEVELOPMENT IMPERVIOUS AREAS

- BUILDING (295 SF)
- CONCRETE (297 SF)
- RETAINING WALL (9 SF)
- ASPHALT (470 SF)
- TOTAL - 1,071 SF (0.0246 AC)



MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID

PROJECT NO:	19-0679.001
SCALE:	1"=20'
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS
SHEET TITLE	

POST-DEVELOPMENT WATER QUALITY MAP

1-C-702

WATER QUALITY NARRATIVE

THE SITE IS DEFINED BY THE TOTAL APPLICABLE AREA WITHIN THE LIMITS OF DISTURBANCE OF 0.1248 ACRES. THE IMPERVIOUS AREA FOR THE EXISTING CONDITION IS 0.0815 ACRES (65.3%) AND 0.0246 ACRES (19.7%) FOR THE PROPOSED CONDITION. THE PLANS DO NOT PROPOSE ANY STORMWATER MANAGEMENT FACILITIES DUE TO THE DECREASE IN IMPERVIOUS AREA.

Project Name: VIRGINIA HOSPITAL CENTER DEMOLITION (PHASE 1)
Date: 10/24/2020
Linear Development Project? No
Enter design storm rainfall depths (in): 1-year storm 2.61, 2-year storm 3.16, 10-year storm 4.85
Enter Total Disturbed Area (acres): 0.1248
Maximum reduction required: 100%
TP Load Reduction for Site (lb/yr): -0.0707
TP LOAD REDUCTION NOT REQUIRED

LAND COVER SUMMARY - PRE DEVELOPMENT
LAND COVER SUMMARY - POST DEVELOPMENT
Tables showing land cover percentages and volumes before and after development.

Treatment Volume and Nutrient Load
Pre-Development Treatment Volume (acre-ft): 0.0074
Post-Development Treatment Volume (acre-ft): 0.0040
TP Load Reduction (lb/yr): -0.0707

Post-Development Requirement for Site Area
TP Load Reduction Required (lb/yr): -0.0707
TP LOAD REDUCTION NOT REQUIRED

Site Results (Water Quality Compliance)
Area Checks: Forest/Open Space, Impervious Cover, etc.
Site Treatment Volume: 175,7646
Runoff Reduction Volume and TP by Drainage Area
Total Phosphorus: -0.0707
Total Nitrogen: 0.7900

Runoff Volume and Curve Number Calculations

*Notes (see below):
[1] The curve numbers and runoff volumes computed in this spreadsheet are limited in their applicability...
[2] Runoff Volume (RV) for pre- and post-development drainage areas...
[3] Adjusted C/Ns are based on runoff reduction volumes as calculated in D.A. tabs.

Drainage Area Curve Numbers and Runoff Depths
Curve numbers (CN, CNadj) and runoff depths (RV) are computed with and without reduction practices.
Tables for Drainage Area A and B showing runoff reduction volumes.

Site Information - Revised 9/19/2017
Table with 30 columns: Project Name, IDA, Percent, Disturbance, etc.

POLLUTION PREVENTION NOTES

- 1. ONLY THE FOLLOWING NON-STORMWATER DISCHARGES ARE AUTHORIZED BY ARLINGTON COUNTY'S MS4 PERMIT...
2. APPROPRIATE CONTROLS MUST BE IMPLEMENTED TO PREVENT ANY NON-STORMWATER DISCHARGES...
3. PER CHAPTER 26 OF THE ARLINGTON COUNTY CODE...

2.0 Authorized Non-Stormwater Discharges

Type of Authorized Non-Stormwater Discharge
Likely Present at Your Project Site?
External buildings wash down
Uncontaminated foundation or footing drains

5.0 Potential Sources of Pollution & Pollution Prevention Practices

Table with columns: Pollutant-Generating Activity, Likely Present at your Project Site?, Pollutants (Sediment, Nutrients, etc.), Pollution Prevention Practice, Responsible Party.

WATER QUANTITY NARRATIVE

PER THE ARLINGTON COUNTY CODE, CHAPTER 60, AND THE ARLINGTON COUNTY STORMWATER MANAGEMENT GUIDEBOOK, MARCH 2020 VERSION, THE DEVELOPED SITE SHALL PASS THE 1-YEAR AND 10-YEAR 24-HOUR PEAK FLOW RATES UTILIZING THE ENERGY BALANCE METHOD...

IT IS THE ENGINEER'S OPINION THAT THE LIMITED BUILDING DEMOLITION AND NEW EGRESS STAIRWELL WITH NEW PEDESTRIAN CONNECTION TO THE EXISTING ON-SITE STAIRS PROPOSED WITH THIS APPLICATION WILL HAVE NO ADVERSE IMPACT TO THE ADJACENT PROPERTIES...

PER FEMA FLOODPLAIN MAP 510I3C0057C, DATED AUGUST 19, 2013, THIS PROJECT IS OUTSIDE THE FLOODPLAIN. THERE ARE RESOURCE PROTECTION AREAS LOCATED ON THE SUBJECT PROPERTY OUTSIDE OF THE LIMITS OF

SWM Water Quantity Energy Balance Worksheet

Table with columns: SITE AREA (acre), PRE, POST (adjusted), 10-year PRE, 10-year POST (adjusted).
Shows runoff reduction volumes and peak runoff rates.

Channel Protection (1-Year), QPost Development, QPost Development (with runoff reduction), Qallowable.
Flood Control (10-Year), Qpre-development, Qpost development, RVPost Development, Qallowable.



CONSULTANTS
Professional Engineer Seal for Keith Sinclair, License No. 11195, dated 06/18/2020.

DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1
601 SOUTH CARLIN SPRINGS ROAD, ARLINGTON, VA 22204

- Pollution Prevention Practices:
(1) Clearing, grading, excavating and un-stabilized areas...
(2) Paving operations...
(3) Concrete washout and cement waste...
(4) Structure construction, stucco, painting and cleaning...
(5) Dewatering operations...
(6) Material delivery and storage...
(7) Material use during building process...
(8) Solid waste disposal...
(9) Sanitary waste...
(10) Landscaping operations...
(11) Others - If applicable, describe your Pollution Prevention Practice.

7.0 Spill Prevention & Response

Most spills can be cleaned up following manufacturer specifications. Absorbent/oil dry, sealable containers, plastic bags, and shovels/brushes are suggested minimum spill response items that should be available at this location.

- 1st Priority: Protect all people
2nd Priority: Protect equipment and property
3rd Priority: Protect the environment
1. Check for hazards (flammable material, noxious fumes, cause of spill)...
2. Make sure the spill area is safe to enter and that it does not pose an immediate threat to health or safety...


Emergency Contacts:

Normal Working Hours: DEQ Northern Regional Office 703-583-3800
Nights, Holidays & Weekends: VA Dept. of Emergency Management 804-674-2400
Local Contacts: Arlington County Fire & Police 703-558-2222

MARK DATE DESCRIPTION
PROJECT NO: 19-0679.001
SCALE: 1"=20'
DESIGNED BY: CMB
DRAWN BY: JES
CHECKED BY: JKS
SHEET TITLE: STORMWATER MANAGEMENT NARRATIVES, CALCULATIONS, AND POLLUTION PREVENTION PLAN
1-C-703
SHEET 17 OF 20



EXISTING RPA ENCROACHMENT MAP



PROPOSED RPA ENCROACHMENT MAP

CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1
 601 SOUTH CARLIN SPRINGS ROAD
 ARLINGTON, VA 22204

Appendix C. Water Quality Impact Assessment Data Sheet

Project Address 601 S CARLIN SPRINGS ROAD		Date 06/18/2020
Applicant Name/Affiliation: Jesus Almarino - Department of Environmental Services, Facilities, Design & Construction 703-228-4509; jalmarino@arlingtonva.us		Applicant Contact Information (phone and email): 703-228-4509; jalmarino@arlingtonva.us
Owner/Client Name: THE COUNTY BOARD OF ARLINGTON COUNTY VIRGINIA 703-228-3130; county.board@arlingtonva.us		Owner/Client Contact Information (phone and email): 703-228-3130; county.board@arlingtonva.us
Section 1: Type of activity proposed		
Activity type (check all that apply):		
<input checked="" type="checkbox"/> New construction (residential, commercial, public, etc.)	<input checked="" type="checkbox"/> Landscaping (includes tree removal)	
<input checked="" type="checkbox"/> Alteration of non-residential structure	<input type="checkbox"/> Utility work	
<input type="checkbox"/> Residential addition	<input type="checkbox"/> Fence	
<input type="checkbox"/> Detached residential structure	<input checked="" type="checkbox"/> Other (please describe): Grading	
Section 2: Key details of the proposed activity		
Complete all that apply		
Total area of disturbance on parcel (sf)	5,436 SF	Explanation Includes building footprint plus a 10 foot buffer. Also includes all soil disturbance, ingress/egress areas, stockpiling areas, etc.
Area of disturbance within RPA (sf)	0 SF	Includes removal of trees > 3" in diameter
Area of disturbance on slopes greater than or equal to 15 percent located adjacent to landward RPA boundary (sf)	0 SF	Does not apply to RPA parcels along Chain Bridge Road (15 percent and greater slopes are included as part of RPA)
Complete all fields		
	Existing condition	Proposed condition
RPA encroachment (ft)	310	310
	275	275
	257	257
Total development footprint in RPA (sf)	0	0
Impervious footprint in RPA (sf)	0	0
(OVER)		
STAFF USE ONLY		
Building/demolition/DA/Fence permit number(s):		
Major WQIA required? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
Date WQIA/Exception request information complete:		
Date Chesapeake Bay Preservation Ordinance and E/S ordinance (if applicable) approvals issued in Permits Plus:		

Section 3: Plan and Narrative

Provide a plan showing the location of the proposed activity, along with the RPA boundary. Briefly describe the proposed project, including any potential water quality impacts and mitigation measures proposed. The narrative must address three impact categories: 1. Tree/vegetation impacts, 2. Stormwater and runoff, 3. Erosion and sediment control. Please refer to the WQIA plan/narrative checklist for additional information.

- Refer to sheets 1-C-104, 1-C-106 and 1-C-107 for Tree Preservation Plans, Details and Existing Tree Inventory.
- Refer to Sheet 1-C-703 for stormwater Management Plan and Sheet runoff information.
- Refer to sheets 1-C-109, 1-C-110, 1-C-111 and 1-C-112 for erosion and sediment control plan, narrative, notes and details.

PROJECT NARRATIVE:

PROJECT CONSISTS OF PARTIAL DEMOLITION LOCATED AT 601 S CARLIN SPRINGS ROAD TO SEPARATE THE HOSPITAL COMPLEX FROM THE 5-STORY OFFICE BUILDING WHICH INCLUDES REMOVAL OF AN AREA DRAIN ASSOCIATED WITH THE BUILDING TO BE REMOVED. IMPROVEMENTS INCLUDE AN EMERGENCY EGRESS STAIRWELL ADDITION, SIDEWALK, STAIRS AND RETAINING WALL AND GRADING. NO TREES ARE TO BE REMOVED WITHIN THE RESOURCE PROTECTION AREA (RPA) AND NO GRADING IS PROPOSED AROUND THEM. THEREFORE, THERE WILL BE NO IMPACTS TO TREES OR CRITICAL ROOT ZONES (CRZS) WITHIN THE RPA. CRZ PROTECTION MEASURES FOR TREES OUTSIDE OF THE RPA LIMITS INCLUDE TREE TRUNK AND LIMB PROTECTING MATTING. TREE PROTECTION NOTES HAVE BEEN INCLUDED ON THE TREE PRESERVATION PLAN TO FURTHER HIGHLIGHT THE IMPORTANCE OF PROTECTING THE EXISTING TREES. SITE RESTORATION INCLUDES PLANTING OF NEW TREES AS SHOWN ON SHEET 14-101. STORMWATER RUNOFF FROM THE SITE IS IN THE FORM OF SHEET FLOW TO THE SOUTH. STORMWATER QUALITY AND QUANTITY CONTROL TREATMENT REQUIREMENTS ARE MET BY THE REDUCTION OF IMPERVIOUS AREA. EROSION AND SEDIMENT CONTROL MEASURES HAVE BEEN PROVIDED FOR BOTH THE DEMOLITION AND PROPOSED PHASES OF WORK.

Additional Water Quality Impact Assessment Information

The information supplied on this form satisfies the minimum requirements for a Minor Water Quality Impact Assessment. For projects that disturb over 2500 square feet, elements of a Major Water Quality Impact Assessment may also be required, depending on the nature and extent of the proposed RPA encroachment, as outlined in Section 61-12 of the ordinance.

Appendix D. Exception Request Form

Applicant: JESUS ALMARIO	Project address: 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
Section 1: Brief description of exception request	
N/A	
Section 2: Parcel, structure, and ownership information	
Date parcel ownership began: 7/15/2019	Date(s) of construction of any prior work by current owner (alterations, additions, decks, patios, etc.)—list individually:
Date existing principal structure built: 1959	Date: _____ Type of prior work: _____
Will existing principal structure remain intact? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	1. _____ 2. _____ 3. _____ 4. _____
STAFF USE ONLY	
<input type="checkbox"/> Allowable development in RPA (§ 61-7 A)	<input type="checkbox"/> New development in the RPA, redevelopment that increases impervious area in the RPA or encroaches further into the RPA, or any other proposed disturbance of any RPA component (exception request required)
<input type="checkbox"/> Allowable modification in RPA (§ 61-7 B)	<input type="checkbox"/> Exempted activity in RPA (§ 61-15)
<input type="checkbox"/> Allowable encroachment in RPA (§ 61-7 C)	<input type="checkbox"/> Proposed development in RMA on 15 percent slopes adjacent to RPA in RPA (§ 61-14) (exception request required)
<input type="checkbox"/> Expansion of nonconforming structure or use in RPA (§ 61-14) (exception request required)	<input type="checkbox"/> Other RMA activity: _____
CBORC hearing required? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	
Date public notification sent certified mail:	
Hearing date:	
CBORC decision: <input type="checkbox"/> Approved <input checked="" type="checkbox"/> Not approved	
Date of final approval letter:	

MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID

PROJECT NO:	19-0679.001
SCALE:	1"=20'
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS
SHEET TITLE	


WATER QUALITY IMPACT ASSESSMENT

CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1

601 SOUTH CARLIN SPRINGS ROAD
 ARLINGTON, VA 22204



TREE PROTECTION LEGEND:

- TREE TRUNK AND LIMB PROTECTION WRAP (1-C-106)
- TREE TO BE REMOVED, CONTRACTOR TO GRIND STUMPS
- 6' CHAIN LINK TREE PROTECTION (1-C-106)
- ROOT PRUNING (1-C-106)
- CRITICAL ROOT ZONE
- TREE CANOPY AREA


IMPACTED TREES								
TREE #	BOTANICAL NAME	COMMON NAME	SIZE (DBH)	CONDITION	ACTION	CRZ IMPACTED	CANOPY PRESERVED	NOTES
T140	PRUNUS SEROTINA	BLACK CHERRY	16	50	PRESERVE	13%	719	TO BE PROTECTED
T141	PINUS VIRGINIANA	VIRGINIA PINE	16	59	PRESERVE	19%	970	TO BE PROTECTED
T144	CORNUS KOUSA	KOUSA DOGWOOD	29	77	REMOVE	100%	0	TO BE REMOVED, CONTRACTOR TO GRIND STUMPS

PLANT SCHEDULE						
TREES	CODE	QTY	BOTANICAL / COMMON NAME	CONT	CAL	SIZE
	AA	2	AMELANCHIER CANADENSIS / SERVICEBERRY	B & B		8'-10" H
	CP	2	CELTIS OCCIDENTALIS / HACKBERRY	B & B		2-2.5' CAL.
GROUND COVERS	CODE	QTY	BOTANICAL / COMMON NAME	CONT	SPACING	
	SED	883 SF	SEED TURF GRASS DROUGHT TOLERANT FESCUE BLEND	AREA		

CANOPY CALCULATIONS (SQUARE FEET)	
PARCEL SIZE	503,996
TREE CANOPY REQUIRED (10%)	50,400
EXISTING FOREST CANOPY	51,549
LARGE CANOPY TREE CANOPY CONSERVED (2X BONUS)	N/A
SMALL CANOPY TREE CANOPY CONSERVED	N/A
TREE CANOPY REMAINING TO PLANT	N/A
TREE CANOPY PLANTED	0

TREE REPLACEMENTS							
TREE NUMBER	SPECIES	NUMBER TREES REMOVED	D.B.H. (INCHES)	CONDITION	SPECIES RATING	TOTAL SCORE	REPLACEMENTS REQUIRED
T144	KOUSA DOGWOOD	1	29.00	0.77	0.80	17.86	4
TOTAL							4

*SHADED CELLS INDICATE TREES WITH 10" DBH AND SMALLER, WHICH ARE AUTOMATICALLY REPLACED AT A RATE OF ONE-FOR-ONE ACCORDING TO THE POLICY




MARK	DATE	DESCRIPTION
	06.18.2021	ISSUED FOR BID

PROJECT NO:	19-0679.001
SCALE:	1"=20'
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS
SHEET TITLE	

LANDSCAPE CONSERVATION PLAN

1-L-101

CONSULTANTS



DECONSTRUCTION OF VIRGINIA HOSPITAL CENTER COMPLEX - PHASE 1

601 SOUTH CARLIN SPRINGS ROAD
ARLINGTON, VA 22204

06.18.2021	ISSUED FOR BID	
MARK	DATE	DESCRIPTION

PROJECT NO:	19-0679.001
SCALE:	N/A
DESIGNED BY:	CMB
DRAWN BY:	JES
CHECKED BY:	JKS

SHEET TITLE

LANDSCAPE NOTES & DETAILS

1-L-501

PLANTING GENERAL NOTES

- THIS PLAN IS FOR PLANTING PURPOSES ONLY, AND ANY OTHER INFORMATION SHOWN IS FOR REFERENCE ONLY. SEE SITE PLAN FOR INFORMATION ABOUT ALL LAYOUT, GRADING AND OTHER SITE IMPROVEMENTS.
- CALL MISS UTILITY AT 811 OR 1-800-257-7777 TO MARK UTILITIES AT LEAST 48 HOURS BEFORE DIGGING.
- ALL MATERIALS AND PLANTING PROCEDURES EXCEPT AS OTHERWISE NOTED SHALL CONFORM TO THE LATEST EDITION OF "LANDSCAPE SPECIFICATION GUIDELINES" BY THE LANDSCAPE CONTRACTORS ASSOCIATION MD-DC-VA.
- PLANTS SHALL CONFORM TO THE CURRENT EDITION OF THE AMERICAN STANDARD FOR NURSERY STOCK. (ANSI Z60.1)
- PLANT NAMES SHALL BE THOSE GIVEN IN THE LATEST EDITION OF STANDARD PLANT NAMES, AMERICAN COMMITTEE ON HORTICULTURAL NOMENCLATURE.
- TOPSOIL SHALL MEET SPECIFICATIONS AS PER THE DEQ VIRGINIA EROSION AND SEDIMENT CONTROL HANDBOOK.
- THE CONTRACTOR SHALL SUBMIT REPRESENTATIVE SOIL SAMPLES FROM BOTH IN-SITU SOILS AND SOILS BROUGHT IN FROM OFF-SITE TO A STATE LICENSED TESTING LABORATORY. THE CONTRACTOR SHALL INCORPORATE OR APPLY SOIL AMENDMENTS AND FERTILIZATION BASED UPON RESULTS OF THE SOIL TESTS AND RECOMMENDATIONS BY THE TEST LAB.
- THE CONTRACTOR SHALL APPLY GRASS ACCORDING TO THE DEQ VIRGINIA EROSION AND SEDIMENT CONTROL HANDBOOK. DO NOT USE KENTUCKY 31 TALL FESCUE.
- THE CONTRACTOR SHALL STAKE OUT ALL PLANTING BEDS AND TREE LOCATIONS AND THESE MUST BE APPROVED BY THE LANDSCAPE ARCHITECT OR OWNER BEFORE DIGGING. IT IS THE CONTRACTOR'S RESPONSIBILITY TO LOCATE AND COORDINATE PLANTINGS WITH ALL EXISTING UTILITIES. IF DISCREPANCIES OCCUR BECAUSE OF UTILITY LOCATIONS OR OTHER EXISTING CONDITIONS THE CONTRACTOR SHALL NOTIFY THE LANDSCAPE ARCHITECT IMMEDIATELY TO COORDINATE ANY NECESSARY ADJUSTMENTS.
- ALL PLANT MATERIAL SHALL BE LABELED BY THE NURSERY AND DELIVERED WITH LABELS IN PLACE FOR INSPECTION. SUBSTITUTIONS IN PLANT SPECIES OR SIZE WILL NOT BE PERMITTED EXCEPT WITH THE APPROVAL OF THE LANDSCAPE ARCHITECT OR OWNER. PRUNING IS NOT TO OCCUR UNTIL MATERIAL HAS BEEN PLANTED. CONTRACTOR SHALL PRUNE PLANT MATERIAL AS SOON THEREAFTER AS IS ADVISABLE UNDER STANDARD HORTICULTURAL PRACTICES.
- IT IS OF UTMOST IMPORTANCE THAT ALL PLANT MATERIAL BE SET SLIGHTLY HIGHER IN RELATION TO GRADE THAN IT WAS GROWN IN THE NURSERY AND WITH GOOD EARTH TO ROOT CONTACT. ANY MATERIALS OR WORK MAY BE REJECTED BY THE LANDSCAPE ARCHITECT IF IT DOES NOT MEET THIS OR ANY OTHER REQUIREMENT OF THE SPECIFICATIONS, AND REJECTED MATERIALS SHALL BE REMOVED FROM THE SITE BY THE CONTRACTOR AT CONTRACTOR'S EXPENSE.
- THE CONTRACTOR SHALL MULCH AND WATER ALL PLANTS WELL ON THE DAY THEY ARE PLANTED. THE SURFACE MULCH LAYER SHALL CONSIST OF STANDARD FINE SHREDDED AGED HARDWOOD MULCH. THE CONTRACTOR SHALL APPLY THE MULCH UNIFORMLY TO A 2 TO 3 INCH DEPTH. BARK SHALL BE KEPT 3 TO 4 INCHES AWAY FROM ALL TRUNKS AND WOODY STEMS.
- IN CASE OF DISCREPANCIES BETWEEN QUANTITIES ON THE PLANT LIST AND THE PLAN, THE PLAN SHALL GOVERN.
- SEED OR SOO BARE AREAS AS DIRECTED BY OWNER FOR ALL DISTURBED AREAS TO BE STABILIZED THAT ARE NOT LANDSCAPED OR COVERED.
- ANY PLANTING WITHIN A FOREST RETENTION AREA, AS DESIGNATED ON THE FOREST CONSERVATION PLAN AND SHOWN ON THIS PLAN, MUST BE DONE TO AVOID ANY ADVERSE IMPACT TO THE ROOTS OF EXISTING TREES. THE CONTRACTORS PERFORMING WORK ON THE SITE ARE RESPONSIBLE FOR PROTECTING EXISTING NATIVE AND NON-INVASIVE PLANTINGS DURING CONSTRUCTION.

NOTES

1. AT PLANTING PRUNE ONLY CROSSING LIMBS, BROKEN OR DEAD BRANCHES, AND ANY BRANCHES THAT POSE A HAZARD TO PEDESTRIANS PER ANSI STANDARD A300. DO NOT PRUNE INTO OLD WOOD ON EVERGREENS.

2. CONTRACTOR SHALL MAXIMIZE EXCAVATED AREA FOR TREE PIT WITHOUT ADVERSELY IMPACTING ADJACENT SITE FEATURES.

3. UNLESS OTHERWISE DIRECTED BY ARLINGTON COUNTY URBAN FORESTER, BACKFILL SOIL MIXTURE WILL BE 3/4 EXISTING SOIL CLEANED OF DEBRIS (GRAVEL, ROCKS, STICKS, TRASH, ETC.) AND MIXED WITH 1/4 ORGANIC MATERIAL (COMPOSTED BARK, LEAF MOLD, OR OTHER PLANT DEBRIS PROCESSED TO A POINT OF DECAY AND APPROVED BY THE URBAN FORESTER; PEAT MOSS SHALL NOT BE USED).


4. CONTRACTOR SHALL LEGALLY REMOVE EXCESS SOIL & DEBRIS FROM SITE.

5. TREES PLANTED WITHOUT THE TRUNK FLARE VISIBLE WILL BE REJECTED.

6. TREES MAY ONLY BE STAKED IF REQUIRED BY THE COUNTY URBAN FORESTER. REFER TO STAKING DETAILS.

3 IN. SHREDDED HARDWOOD MULCH; MULCH MUST BE 6 IN. AWAY FROM TREE TRUNK

ROUGHEN SIDES OF PLANTING HOLE BACKFILL SOIL MIXTURE FOR ENTIRE TREE PIT AREA X ROOTBALL DEPTH SOIL SHALL BE FIRMED IN 8" LIFTS



ALL PLANTS MUST BE WATERED TWICE: ONCE AT INSTALLATION AND AGAIN WITHIN 48-HOURS OF INSTALLATION, PER THE SPECIFICATIONS.

THIS DETAIL SUPERSEDES ALL OTHER TREE PLANTING DETAILS IN ARLINGTON COUNTY.

CENTER TREE IN PIT AND SET TOP OF ROOT BALL 2 IN. ABOVE ADJACENT GRADE. THE TRUNK FLARE SHALL BE VISIBLE AT THE TOP OF THE ROOT BALL. DO NOT COVER THE TOP OF THE ROOT BALL WITH SOIL.

4 IN. HIGH EARTH SAUCER BEYOND EDGE OF ROOT BALL

REMOVE ALL TWINE, ROPE, WIRE, AND BURLAP FROM TOP 2/3 OF ROOT BALL

TAMP SOIL AROUND ROOT BALL BASE FIRMLY WITH FOOT PRESSURE SO THAT ROOT BALL DOES NOT SHIFT

UNDISTURBED SUBGRADE

TREE PLANTING DETAIL

FOR OPEN PLANTING AREAS FREE OF PAVING OR GRATES

NOT TO SCALE

NOTES

1. AT PLANTING PRUNE ONLY BROKEN OR DEAD BRANCHES PER ANSI 300 STANDARD.

2. PLANTING PIT/TRENCH SHALL BE DUG DEEP ENOUGH TO ALLOW AT LEAST 1/8TH OF ROOT BALL TO SET ABOVE EXISTING GRADE.

3. SET PLANTS IN ERECT, STABLE, AND UNIFORM POSITIONS. ORIENT BEST FACE OF PLANT TO BE THE MOST VISIBLE.


4. GROUND COVERS AND PERENNIALS SHALL BE INSTALLED WITH TRIANGULAR SPACING. REFER TO CHART.

4. UNLESS OTHERWISE DIRECTED BY PROJECT SPECIFICATIONS OR COUNTY URBAN FORESTER, BACKFILL SOIL MIXTURE WILL BE 3/4 EXISTING SOIL CLEANED OF DEBRIS (GRAVEL, ROCKS, STICKS, TRASH, ETC.) AND MIXED WITH 1/4 ORGANIC MATERIAL (COMPOSTED BARK, LEAF MOLD, OR OTHER PLANT DEBRIS PROCESSED TO A POINT OF DECAY AND APPROVED BY THE COUNTY URBAN FORESTER; PEAT MOSS SHALL NOT BE USED).

5. CONTRACTOR SHALL REMOVE EXCESS SOIL & DEBRIS FROM SITE.


6. DO NOT PLACE MULCH IN CONTACT WITH STEM OF PLANTS.

ALL PLANTS MUST BE WATERED TWICE ONCE AT INSTALLATION AND AGAIN WITHIN 48-HOURS OF INSTALLATION, PER THE SPECIFICATIONS.



TRIANGULAR SPACING PLAN & CHART
NOT TO SCALE

PLANT SPACING "D" O.C.	ROW "A" O.C.	PLANTS PER S.F.
6"	5"	4.00
8"	7"	2.25
9"	8"	1.77
12"	10"	1.00
15"	13"	0.77
18"	16"	0.44



PLACE TOP 1/8 OF ROOT BALL ABOVE FINISHED GRADE (TYP.)

3" SHREDDED HARDWOOD MULCH OVER ENTIRE PLANTING BED

BACKFILL SOIL MIXTURE

LOOSEN THE ROOT BALL OF ANY ROOT BOUND PLANTS (TYP.)

UNDISTURBED SUBGRADE OR COMPACTED BACKFILL SOIL MIXTURE

THIS DETAIL SUPERSEDES ALL OTHER GROUND COVER PLANTING DETAILS IN ARLINGTON COUNTY.


GROUND COVERS & PERENNIAL PLANTING

NOT TO SCALE

DEMOLITION KEYNOTES - FOURTH FLOOR LEVEL	
NO.	NOTE
1	LIMIT OF DEMOLITION TO BE DETERMINED IN THE FIELD. DEMOLISH ALL OF THE STRUCTURE TO THIS POINT INCLUDING BELOW GRADE STRUCTURES TO AN ELEVATION OF APPROXIMATELY 242.00'. SAWCUT FLOOR, ROOF, AND WALLS CLEANLY. MAINTAIN STABILITY OF STRUCTURE TO REMAIN.
2	DEMOLISH ENTIRE MRI ADDITION INCLUDING ALL ABOVE & BELOW GRADE CONSTRUCTION.
3	TEMPORARY 1-HR. RATED STUD WALL TO SEPARATE NEW WORK FROM EXISTING EGRESS PATH.
4	DEMOLISH EXISTING EXTERIOR DOOR & FRAME.
5	DEMOLISH EXISTING STOREFRONT & GLAZING.
6	SAWCUT SLAB ALONG BASE OF EXISTING RAMP.
7	DEMOLISH EXISTING DOOR & FRAME.
8	MAINTAIN EXISTING CONSTRUCTION IN BUILDING TO REMAIN - DEMOLISH ONLY TO THE EXTENT NECESSARY FOR NEW MECHANICAL AND ELECTRICAL WORK. PATCH ALL FINISHES TO MATCH EXISTING.
9	DEMOLISH BRICK AT CORNER WITHOUT DAMAGE TO BRICK TO REMAIN. CLEAN ALL MORTAR OR SEALANT FROM ORIGINAL JOINT. REPLACE DAMAGED BRICK WITH SALVAGED BRICK.
10	DEMOLISH ALL FINISHES BACK TO FACE OF MASONRY.
11	DEMOLISH EXISTING CONCRETE STEPS & SIDEWALK TO THE EXTENT SHOWN - REFER TO CIVIL DRAWINGS.
12	DEMOLISH EXISTING INTERIOR DOOR & FRAME. PREPARE OPENING FOR REPLACEMENT DOOR & FRAME.
13	SALVAGE SUFFICIENT EXISTING BRICK FROM DEMOLITION TO REPAIR THE NEW OUTSIDE CORNER WITH A 8" RETURN AND TO INFILL THE WALL OPENING AT THE DEMOLISHED MRI CONNECTION.


FINISH SCHEDULE									
ROOM NUMBER	ROOM NAME	FLOOR	WALL BASE	WALLS				CEILING	
				N	S	E	W		
401	NEW VESTIBULE	VCT	RBR	PAINT	PAINT	PAINT	PAINT	SAT	
501	NEW VESTIBULE	VCT	RBR	PAINT	PAINT	PAINT	PAINT	SAT	

DOOR SCHEDULE									
NUMBER	MATL	DOOR			FRAME			Door Fire Rating	
		WIDTH	HEIGHT	THICKNESS	MAT	TYPE	HDW		
01	H.M.	3'-0"	7'-10"	1 3/4"	H.M.	1	1		
02	H.M.	3'-0"	6'-8"	1 3/4"	H.M.	1	2	60 MIN.	




DOOR & FRAME TYPE 1
SCALE: 1/4" = 1'-0"


- DOOR HARDWARE NOTES:**
1. HDW 1 INCLUDES PANIC DEVICE AND CLOSER.
 2. HDW 2 INCLUDES PASSAGE SET AND CLOSER.
 3. REFER TO SPECIFICATIONS FOR FULL HARDWARE SET DESCRIPTIONS.




DOOR JAMB DETAIL - ALTERNATE 1
SCALE: 1 1/2" = 1'-0"




HEAD/SILL DETAIL - ALTERNATE 1
SCALE: 1 1/2" = 1'-0"




DOOR JAMB DETAIL - ALTERNATE 2
SCALE: 1 1/2" = 1'-0"



HEAD/SILL DETAIL - ALTERNATE 2
SCALE: 1 1/2" = 1'-0"



FOURTH FLOOR - DEMOLITION SEE SHEET 1-G-1-2 FOR SEQUENCING INFORMATION
SCALE: 1/8" = 1'-0"




FOURTH FLOOR - NEW WORK SEE SHEET 1-G-1-2 FOR SEQUENCING INFORMATION
SCALE: 1/8" = 1'-0"

CD Revisions	DES
05-15-2020	
07-30-2020	
12-04-2020	
05-31-2121	

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06-18-2021	13356-28	KDL	DWH	KDL

RRMM ARCHITECTS, PC
2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
DRAWING **FOURTH FLOOR DEMOLITION AND NEW WORK PLANS**


SHEET
1-A-101

BIN 360-113356-28 Virginia Hospital Center - Arch.rvt 6/15/2021 11:45:46 AM


DEMOLITION KEYNOTES - FIFTH FLOOR LEVEL	
NO.	NOTE
1	LIMIT OF DEMOLITION. DEMOLISH ALL OF THE STRUCTURE TO THIS POINT INCLUDING BELOW GRADE STRUCTURES TO AN ELEVATION OF APPROXIMATELY 242.00'. SAWCUT FLOOR, ROOF, AND WALLS CLEANLY. MAINTAIN STABILITY OF STRUCTURE TO REMAIN.
2	DEMOLISH ENTIRE MRI ADDITION INCLUDING ALL ABOVE & BELOW GRADE CONSTRUCTION.
3	TEMPORARY 1-HR RATED STUD WALL TO SEPERATE NEW WORK FROM EXISTING EGRESS PATH.
4	EXISTING FLOOR TO REMAIN. MODIFY SUPPORTING STRUCTURE PER THE STRUCTURAL DWGS. SAWCUT FLOOR SLAB EDGE TO ALIGN WITH NEW CONSTRUCTION.
5	DEMOLISH ALL FINISHES BACK TO FACE OF MASONRY.
6	RETAIN EXISTING GYPSUM BOARD FURRED WALL TO THE EXTENT OF THE NEW WORK.
7	NOT USED.
8	MAINTAIN EXISTING CONSTRUCTION IN BUILDING TO REMAIN - DEMOLISH ONLY TO THE EXTENT NECESSARY FOR NEW MECHANICAL AND ELECTRICAL WORK. PATCH ALL FINISHES TO MATCH EXISTING.




D2 ALT1
1-A-102
SCALE: 1 1/2" = 1'-0"




D2 ALT2
1-A-102
SCALE: 1 1/2" = 1'-0"




ROOF PLAN - NEW WORK
SCALE: 1/8" = 1'-0"



ROOF PLAN - DEMOLITION
SCALE: 1/8" = 1'-0"



FIFTH FLOOR - DEMOLITION
SCALE: 1/8" = 1'-0"




FIFTH FLOOR - NEW WORK
SCALE: 1/8" = 1'-0"

CD Revisions	Permit Revisions	Amended Permit	DES
05.15.2020	07.30.2020	05.31.2121	BY
1	2	4	MARK DATE
			REVISIONS

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	KDL	DWH	KDL

RRMM ARCHITECTS, PC
2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
DRAWING FIFTH FLOOR AND ROOF DEMOLITION AND NEW WORK PLANS

SHEET
1-A-102

6/15/2021 11:45:48 AM BIN 360/13356-28 Virginia Hospital Center/13356-28 v20 Virginia Hospital Center - Arch.rvt



6/16/2021 11:45:49 AM BIN 360/13356-28 Virginia Hospital Center/13356-28 v20 Virginia Hospital Center - Arch.vt

NEW LAY IN ACOUSTIC CEILING AT 8'-4" A.F.F.
EXISTING STAIR FINISHES TO REMAIN

REPAIR EXISTING CEILINGS DAMAGED BY NEW WORK, INCLUDING WORK IN THIRD FLOOR CEILING SPACES - TYPICAL
NEW SOFFIT


04-FOURTH FLOOR CEILING - NEW

SCALE: 1/8" = 1'-0"

REPAIR EXISTING CEILINGS DAMAGED BY NEW WORK - TYPICAL
NEW LAY IN ACOUSTIC CEILING AT 8'-0" A.F.F.
EXISTING STAIR FINISHES TO REMAIN


05-FIFTH FLOOR CEILING - NEW

SCALE: 1/8" = 1'-0"




04-FOURTH FLOOR CEILING - DEMOLITION

SCALE: 1/8" = 1'-0"



05-FIFTH FLOOR CEILING - DEMOLITION

SCALE: 1/8" = 1'-0"



DATE	PROJECT	DESIGNED	DRAWN	CHECKED	MARK	DATE	REVISIONS
06.18.2021	13356.28	KDL	DWH	KDL			
							DES
							BY


06.18.2021	13356.28	KDL	DWH	KDL
DATE	PROJECT	DESIGNED	DRAWN	CHECKED

RRMM ARCHITECTS, PC
 2900 South Quincy Street, Suite 710
 Arlington, Virginia 22206
 (703)998-0101




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 DRAWING REFLECTED CEILING DEMOLITION AND NEW WORK PLANS


SHEET
1-A-103




C1 EAST ELEVATION - DEMOLITION
1-A-201 SCALE: 1/8" = 1'-0"




C3 ALT1 EAST ELEVATION - NEW WORK - ALTERNATE 1
1-A-201 SCALE: 1/8" = 1'-0"




C3 ALT2 EAST ELEVATION - NEW WORK - ALTERNATE 2
1-A-201 SCALE: 1/8" = 1'-0"




A1 WEST ELEVATION - DEMOLITION
1-A-201 SCALE: 1/8" = 1'-0"



A3 ALT1 WEST ELEVATION - NEW WORK - ALTERNATE 1
1-A-201 SCALE: 1/8" = 1'-0"



A3 ALT2 WEST ELEVATION - NEW WORK - ALTERNATE 2
1-A-201 SCALE: 1/8" = 1'-0"



CD Revisions Amended Permit	DES
05.15.2020 05.31.2121	BY
1	MARK
4	DATE
	REVISIONS

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356-28	KDL	DWH	KDL


RRMM ARCHITECTS, PC
2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
DRAWING EAST AND WEST ELEVATIONS - DEMOLITION AND NEW WORK

SHEET
1-A-201


6/15/2021 11:45:51 AM BIN 360/13356-28 Virginia Hospital Center/13356-28 v20 Virginia Hospital Center - Arch.vt




C1 TEMPORARY END WALL ELEVATION
1-A-202 SCALE: 1/8" = 1'-0"




B3 ALT2 NORTH ELEVATION - NEW WORK - ALTERNATE 2
1-A-202 SCALE: 1/8" = 1'-0"




B1 NORTH ELEVATION - DEMOLITION
1-A-202 SCALE: 1/8" = 1'-0"




B3 ALT1 NORTH ELEVATION - NEW WORK - ALTERNATE 1
1-A-202 SCALE: 1/8" = 1'-0"




A1 ALT1 CORNER DETAIL AT FOURTH FLOOR - ALTERNATE 1
1-A-202 SCALE: 1 1/2" = 1'-0"



A1 ALT2 CORNER DETAIL AT FOURTH FLOOR - ALTERNATE 2
1-A-202 SCALE: 1 1/2" = 1'-0"



A3 ALT1 CORNER DETAIL AT FIFTH FLOOR - ALTERNATE 1
1-A-202 SCALE: 1 1/2" = 1'-0"



A3 ALT2 CORNER DETAIL AT FIFTH FLOOR - ALTERNATE 2
1-A-202 SCALE: 1 1/2" = 1'-0"



CD Revisions	DES
Permit Revisions	BY
Amended Permit	MARK
DATE	DATE
06.15.2020	06.18.2021
07.30.2020	07.30.2020
05.31.2121	05.31.2121
1	2
2	4

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	KDL	DWH	KDL

RRMM ARCHITECTS, PC
2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
DRAWING NORTH ELEVATION - DEMOLITION AND NEW WORK

SHEET
1-A-202

6/15/2021 11:45:53 AM BIN 380 / 13356-28 Virginia Hospital Center / 13356-28 v20 Virginia Hospital Center - Arch.vt

6/15/2021 11:45:54 AM BIN 360/13356-28 Virginia Hospital Center/13356-28 v20 Virginia Hospital Center - Arch.vt



SECTION AT TEMPORARY END WALL

SECTION AT VESTIBULE - DEMOLITION

SECTION AT VESTIBULE - NEW - ALTERNATE 1

SECTION AT VESTIBULE - NEW - ALTERNATE 2

A1 1-A-301 SCALE: 1/2" = 1'-0" A2 1-A-301 SCALE: 1/2" = 1'-0" A3 ALT1 1-A-301 SCALE: 1/2" = 1'-0" A3 ALT2 1-A-301 SCALE: 1/2" = 1'-0"



CD Revisions	05.15.2020	DES
Permit Revisions	07.30.2020	BY
Permit Revisions 2	12.04.2020	MARK
Amended Permit	05.31.2121	DATE

DATE	06.18.2021	PROJECT	DESIGNED	DRAWN	CHECKED
		13356-28	KDL	DWH	KDL


RRMM ARCHITECTS, PC
 2900 South Quincy Street, Suite 710
 Arlington, Virginia 22206
 (703)998-0101




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 DRAWING WALL SECTIONS

SHEET
1-A-301


6/15/2021 11:45:55 AM BIN 360/13356-28 Virginia Hospital Center/13356-28 v20 Virginia Hospital Center - Arch.rvt



A1
1-A-302
SCALE: 1/2" = 1'-0"
CROSS SECTION AT VESTIBULE - DEMOLITION



A3 ALT1
1-A-302
SCALE: 1/2" = 1'-0"
CROSS SECTION AT VESTIBULE - NEW - ALTERNATE 1



A3 ALT2
1-A-302
SCALE: 1/2" = 1'-0"
CROSS SECTION AT VESTIBULE - NEW - ALTERNATE 2



CD Revisions	DATE	PROJECT	DESIGNED	DRAWN	CHECKED	MARK	DATE	BY	REVISIONS
1	06.18.2021	13356.28	KDL	DWH	KDL			DES	
2									
3									
4									

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	KDL	DWH	KDL


RRMM ARCHITECTS, PC
2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
DRAWING WALL SECTIONS

SHEET
1-A-302


6/15/2021 11:45:57 AM BIN 360/13356-28 Virginia Hospital Center/13356-28 v20 Virginia Hospital Center - Arch.vt




WALL SECTION - DEMOLITION
A1 1-A-303 SCALE: 1/2" = 1'-0"




WALL SECTION - NEW WORK - ALTERNATE 1
A2 ALT1 1-A-303 SCALE: 1/2" = 1'-0"




WALL SECTION - NEW WORK - ALTERNATE 2
A2 ALT2 1-A-303 SCALE: 1/2" = 1'-0"




WALL SECTION - DEMOLITION
A3 1-A-303 SCALE: 1/2" = 1'-0"



WALL SECTION AT DOOR - NEW WORK - ALTERNATE 1
A4 ALT1 1-A-303 SCALE: 1/2" = 1'-0"



WALL SECTION AT DOOR - NEW WORK - ALTERNATE 2
A4 ALT2 1-A-303 SCALE: 1/2" = 1'-0"



CD Revisions	DATE	MARK	DATE	BY	DES
1	06.15.2020				
2	07.30.2020				
3	12.04.2020				
4	05.31.2121				


DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	KDL	DWH	KDL

RRMM ARCHITECTS, PC
2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
DRAWING WALL SECTIONS


SHEET
1-A-303




D1 TEMP. END WALL EDGE DETAIL
1-A-304 SCALE: 1 1/2" = 1'-0"




C1 ALT1 COPING DETAIL - ALTERNATE 1
1-A-304 SCALE: 1 1/2" = 1'-0"




C1 ALT2 COPING DETAIL - ALTERNATE 2
1-A-304 SCALE: 1 1/2" = 1'-0"




B1 ALT1 DETAIL AT BASE OF WALL - ALTERNATE 1
1-A-304 SCALE: 1 1/2" = 1'-0"




B1 ALT2 DETAIL AT BASE OF WALL - ALTERNATE 2
1-A-304 SCALE: 1 1/2" = 1'-0"




A1 SECTION AT STEPS
1-A-304 SCALE: 1/4" = 1'-0"



A3 WALL SECTION - DEMOLITION
1-A-304 SCALE: 1/2" = 1'-0"



A4 WALL SECTION - NEW WORK
1-A-304 SCALE: 1/2" = 1'-0"



MARK	DATE	BY	REVISIONS
1	05.15.2020		CD Revisions
2	07.30.2020		Permit Revisions
3	12.04.2020		Amended Permit
4	05.31.2121		

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	KDL	DWH	KDL

RRMM ARCHITECTS, PC
2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
DRAWING WALL SECTIONS AND MISCELLANEOUS DETAILS

SHEET
1-A-304

6/15/2021 11:45:58 AM BIN 360/13356-28 Virginia Hospital Center/13356-28 v20 Virginia Hospital Center - Arch.rvt

STRUCTURAL GENERAL NOTES

A. GENERAL:

1. STRUCTURAL DRAWINGS SHALL BE USED IN CONJUNCTION WITH ALL OTHER CONTRACT DOCUMENTS AND SPECIFICATIONS.
2. CONTRACTOR SHALL VERIFY ALL DIMENSIONS BEFORE BEGINNING WORK.
3. SECTIONS AND DETAILS PROVIDED ON THESE DRAWINGS DESCRIBE STANDARD CONSTRUCTION REQUIREMENTS TO BE APPLIED THROUGHOUT THE PROJECT. THE DETAILS SHALL BE ADJUSTED AS REQUIRED TO ACCOUNT FOR VARYING CONDITIONS IN THE FIELD. SIGNIFICANT ADJUSTMENTS SHALL BE PRESENTED TO THE PROJECT ENGINEER FOR REVIEW AND APPROVAL PRIOR TO INSTALLATION OR FABRICATION. ALL TYPICAL DETAILS SHALL BE REVIEWED BY THE CONTRACTOR AND APPROPRIATE SUBCONTRACTORS PRIOR TO ANY DETAILING, FABRICATION, AND INSTALLATION. ANY CONFLICTS OR CLARIFICATIONS SHALL BE RESOLVED BEFORE BEGINNING WORK.
4. PROVIDE ADEQUATE SHORING AND BRACING DURING CONSTRUCTION UNTIL LOAD FRAMES ARE IN PLACE.
5. COORDINATE SIZE AND INSTALLATION OF ALL OPENINGS, SLEEVES, INSERTS, TIES, EQUIPMENT PADS, EQUIPMENT SUPPORTS, ETC. WITH APPROPRIATE TRADES AND CONTRACT DRAWINGS PRIOR TO INSTALLATION OR FABRICATION.
6. BOTH SIDES OF FOUNDATION WALLS SHALL BE BACKFILLED SIMULTANEOUSLY SO AS TO PREVENT OVERTURNING OR LATERAL MOVEMENT OF WALLS.

B. DESIGN CRITERIA:

1. CODES: (USE LATEST EDITIONS AS OF DRAWING DATE, UON)
 - a. VIRGINIA CONSTRUCTION CODE (VCC) 2015
 - b. INTERNATIONAL BUILDING CODE (IBC) 2015
 - c. BUILDING CLASSIFICATION: RISK CATEGORY III
 - d. AMERICAN SOCIETY OF CIVIL ENGINEERS (ASCE) MINIMUM DESIGN LOADS FOR BUILDINGS 7-10
 - e. BUILDING CODE REQUIREMENTS FOR REINFORCED CONCRETE (ACI-318) AS AMENDED BY IBC 2015.
 - f. SPECIFICATIONS FOR STRUCTURAL STEEL BUILDINGS ANSI/AISC 360.
 - g. DESIGN HANDBOOK OF THE CRSI (CONCRETE REINFORCING STEEL INSTITUTE).
2. GRAVITY LOADS:

a. ROOF MINIMUM LIVE LOAD	30 PSF (300# CONCENTRATED)
b. COLLATERAL ROOF LOAD	10 PSF
c. OFFICE AREAS	50 PSF
d. CORRIDORS	100 PSF
3. WIND LOADS:

a. WIND SPEED (Vult)	120 MPH
b. EXPOSURE	B
c. INTERNAL PRESSURE COEFFICIENTS	+0.18 & -0.18
d. WALL COMPONENTS & CLADDING	33.0 PSF & -35.0 PSF
4. SNOW LOAD:

a. GROUND SNOW LOAD (Pg)	25 PSF
b. FLAT ROOF SNOW LOAD (Pf)	25 PSF (PLUS DRIFT LOADS)
c. EXPOSURE FACTOR (Ce)	1.0
d. THERMAL FACTOR (Ct)	1.0
e. SLOPE FACTOR (Cs)	1.0
f. IMPORTANCE FACTOR (Ie)	1.1
5. EARTHQUAKE LOAD:

a. SEISMIC DESIGN CATEGORY	B
b. SITE CLASS	D
c. SITE COEFFICIENTS	$F_a = 1.6$; $F_v = 2.4$
	$S_{DS} = 0.144$; $S_{D1} = 0.07$
d. IMPORTANCE FACTOR (Ie)	1.25
6. EARTHWORK:
 - a. DESIGN SOILS BEARING PRESSURE: FOUNDATION AND FOOTING
 - b. DESIGN BASED ON AN ALLOWABLE BEARING PRESSURE OF 1500 PSF

C. FOUNDATIONS:

1. NEW GRADE BEAM IS DESIGNED TO BEAR ON COMPACTED EXISTING SUBGRADE MATERIALS. REMOVE ANY SOFT OR LOOSE FILL AND REPLACE WITH #57 STONE TO ACHIEVE FULL BEARING.
2. ANY EXISTING LOOSE OR UNCOMPACTED FILL MATERIALS ENCOUNTERED BELOW THE BUILDING SLAB ON GRADE SHALL BE REMOVED AS PART OF THE SITE PREPARATIONS AND EXCAVATION. REPLACE WITH STRUCTURAL ENGINEERED FILL OR COMPACTED #57 STONE DURING BACKFILLING EFFORTS.
3. INSTALL ENGINEERED FILL AND/OR STONE BACKFILL TO ACHIEVE REQUIRED SUBGRADES. ANY SUBGRADES SUPPORTING SLABS ON GRADE SHALL ALSO BE TESTED BY THE THE SOILS ENGINEER PRIOR TO SURFACE STABILIZATION.
4. WHEN BACKFILLING, BOTH SIDES OF SUBGRADE WALLS SHALL BE BACKFILLED SIMULTANEOUSLY TO PREVENT OVERTURNING OR LATERAL MOVEMENT OF WALLS. STRUCTURAL ENGINEERED FILL SHALL BE FREE OF ORGANIC OR OTHER DELETERIOUS MATTER AND FALL INTO A USCS GROUP SC, SM, SW, SP, SP-SM, SP-SC, OR GRAVELS. THE LIQUID LIMIT SHALL NOT EXCEED 40 AND THE PLASTIC LIMIT SHALL NOT EXCEED 12. INSTALL WITHIN 2% OF OPTIMAL MOISTURE CONTENT AT 98% OF THE STANDARD PROCTOR ASTM D-698 (THE UPPER 12" SHALL BE AT 100%)
5. ALL EXCAVATIONS SHALL BE INSPECTED, PRIOR TO FILL PLACEMENT AND/OR CONCRETE PLACEMENT, BY THE SOILS ENGINEER TO VERIFY SUITABLE BEARING MATERIAL AND CAPACITIES AS NOTED. ANY AND ALL UNSUITABLE MATERIAL SHALL BE REMOVED AND REPLACED WITH SUITABLE ENGINEERED FILL MATERIAL FILL MATERIAL AS REQUIRED. SOILS ENGINEER SHALL BE A REGISTERED PROFESSIONAL IN THE COMMONWEALTH OF VIRGINIA.

D. DRILLED AND EPOXIED ADHESIVE ANCHOR BOLTS:

1. ALL DRILLED AND EPOXIED ANCHOR BOLTS PLACED IN CONCRETE SHALL BE HILTI, HAS THREADED RODS WITH HIT HY 200 ADHESIVE SYSTEM OR APPROVED EQUAL (TYP., U.N.O.) ICBO ER-5193. USE HIT HY-270 AT MASONRY ANCHORAGE.
2. INSTALL ACCORDING TO MANUFACTURER'S SPECIFICATIONS. ANCHOR SIZES AND EMBEDMENT LENGTHS SHALL BE AS NOTED ON DRAWINGS.

E. CONCRETE:

1. CONCRETE USED IN THE WORK SHALL MEET OR EXCEED THE FOLLOWING COMPRESSIVE STRENGTH AT 28 DAYS:

GRADE BEAM	4000 PSI NORMAL WT
SLABS ON GRADE	4000 PSI NORMAL WT
MASONRY GROUT	3000 PSI NORMAL WT
2. ALL CONCRETE SUBJECT TO FREEZE/THAW CYCLES SHALL BE AIR ENTRAINED
3. SAW-CUT OR TOOLED CONTROL JOINTS (CJ ON PLANS) SHALL BE AS DETAILED. SAW-CUTS ARE TO BE MADE AS SOON AS PRACTICAL WITHOUT DAMAGING THE SURFACE (12 HOURS MAX). TOOLED JOINTS PREFERRED.
4. SLAB CONSTRUCTION JOINTS SHALL BE LOCATED, AS REQUIRED FOR CONSTRUCTION, AT CONTROL JOINT (CJ) LOCATIONS NOTED ON PLANS.
5. PROVIDE ISOLATION JOINTS AT ALL COLUMNS WITH 1/2" PREFORMED JOINT FILLER AS INDICATED ON TYPICAL DETAILS.
6. CONSTRUCTION JOINTS IN WALLS AND SLABS SHALL HAVE REINFORCING CONTINUE THROUGH JOINT UON ON DETAILS. CONSTRUCTION JOINTS ARE TO BE LOCATED BY THE CONTRACTOR, TO LEAST IMPAIR THE STRENGTH OF THE STRUCTURE, AND SHALL BE APPROVED BY THE ENGINEER.
7. CUTTING AND/OR CORING CONCRETE SHALL BE APPROVED BY THE STRUCTURAL ENGINEER PRIOR TO CONSTRUCTION. NO REINFORCEMENT SHALL BE CUT.
8. EXPOSED CONCRETE EDGES SHALL BE BUILT SQUARE AND RUBBED TO A MINIMUM RADIUS CHAMFER, UNLESS SPECIFIC CHAMFERS ARE CALLED FOR IN DETAILS.
9. SEE ARCHITECTURAL, MECHANICAL ELECTRICAL, & PLUMBING DRAWINGS FOR LOCATIONS OF OPENINGS AND SLEEVES. DO NOT CUT REINFORCEMENT.
10. DEPRESS FLOOR SLABS AS INDICATED. SEE ARCHITECTURAL DRAWINGS FOR LOCATION OF DEPRESSED AREAS AND DEPTH REQUIREMENTS.

F. REINFORCEMENT:

1. REINFORCING STEEL SHALL BE DEFORMED BARS IN ACCORDANCE WITH ASTM A615 SPECIFICATIONS, GRADE 60.
2. WELDED WIRE FABRIC REINFORCING SHALL CONFIRM TO ASTM A185.
3. MAINTAIN MINIMUM CONCRETE COVERAGE FOR REINFORCING AS SPECIFIED IN ACI-318 AND AS FOLLOWS:

CONCRETE CAST AGAINST GROUND 3"	CONCRETE EXPOSED TO GROUND OR WEATHER; #6 & LARGER 2"
CONCRETE EXPOSED TO GROUND OR WEATHER; #5 & SMALLER 1-1/2"	CONCRETE NOT EXPOSED TO GROUND OR WEATHER;
SLABS, WALLS, & JOISTS 1" TOP & 3/4" BOTTOM	BEAMS & COLUMNS 1-1/2"
4. ALL CONTINUOUS REINFORCING IN FOOTINGS SHALL BE LAP-SPLICED 1'-6". ALL OTHER SPLICE SHALL BE CLASS B TENSION, U.O.N.
5. ALL HOLES IN CONCRETE SLABS AND WALLS SHALL HAVE, ADDITIONALLY, 2 #5 X (OPENING DIM. + 2 FT.) ALONG EACH SIDE OF OPENING AND 2 #5 X 5'-0" DIAGONALLY AT EACH CORNER.
6. DETAILING, FABRICATION, AND INSTALLATION OF REINFORCING BARS SHALL COMPLY WITH THE "DESIGN HANDBOOK OF THE CRSI" AND THE MANUAL OF STANDARD PRACTICE OF THE ACI.
7. PROVIDE DOWELS TO MATCH REINFORCEMENT IN ALL WALLS, PIERS, COLUMNS, AND FOUNDATIONS.

G. MASONRY:

1. MASONRY DESIGNED BY THE ALLOWABLE STRESS DESIGN PROVISIONS OF IBC SECTION 2101.2.1.
2. CONCRETE MASONRY UNITS SHALL HAVE A MINIMUM COMPRESSIVE STRENGTH OF 1900 PSI @ 28 DAYS AND BE NORMAL WEIGHT.
3. MORTAR SHALL BE TYPE M OR S.
4. MINIMUM CONCRETE PRISM STRENGTH (fm) SHALL BE 1500 PSI.
5. REINFORCEMENT AND CONCRETE FILL ARE NOTED ABOVE.
6. ALL MASONRY BELOW GRADE SHALL BE GROUTED SOLID.
7. ALL MASONRY CELLS WITH REINFORCEMENT SHALL BE GROUTED SOLID.
8. SOLID MASONRY PIERS, IDENTIFIED AS SMP ON PLAN, SHALL BE GROUTED SOLID FULL HEIGHT OF WALL TO FOUNDATION.
9. INSTALL LINTELS AT ALL OPENINGS IN MASONRY WALLS. REFER TO LINTEL SCHEDULE AND ARCHITECTURAL DRAWINGS FOR SIZES AND LOCATIONS. PRECAST CONCRETE LINTELS ARE NOT ACCEPTABLE IN ANY LOCATIONS EXPOSED TO VIEW.
10. MASONRY CONSTRUCTION SHALL BE INSPECTED AND VERIFIED IN ACCORDANCE WITH TMS 402/ACI 530/ASCE 5 AND TMS 602/ACI 530.1/ASCE 6 LEVEL B QUALITY ASSURANCE PROGRAM REQUIREMENTS.

H. DEMOLITION NOTES:

1. PHASE 1 PROJECT INCLUDES THE PARTIAL DEMOLITION AND REMOVAL OF THE BUILDING ADJACENT TO THE EXISTING PHYSICIAN'S OFFICE BUILDING AND EXPANDED STAIR TOWER ATTACHED THERETO.
2. THE STRUCTURAL DEMOLITION SHALL BE SCHEDULED AFTER ANY AND ALL INTERIOR DEMOLITION IS COMPLETE FOR SAFETY CONCERNS.
3. DEBRIS, INCLUDING BRICK, CONCRETE, STONE, METALS AND SIMILAR MATERIALS FROM THE DEMOLITION SHALL BECOME PROPERTY OF CONTRACTOR AND SHALL BE DISPOSED OF DAILY OFF SITE TO AVOID ACCUMULATION AT THE DEMOLITION SITE.
4. MATERIALS THAT CANNOT BE REMOVED DAILY SHALL BE STORED IN AREAS THAT WILL NOT CURTAIL OPERATIONS OR DIVERT STORM RUN-OFF.
5. DEMOLITION SHALL BE SCHEDULED AND PROSECUTED TO ASSURE STABILITY OF THE REMAINING STRUCTURE AT THE END OF EACH WORKDAY.
6. BREAK UP CONCRETE SLABS, WALLS, AND FOUNDATION AND REMOVE FROM THE SITE.
7. CONTRACTOR SHALL DISPOSE DEBRIS IN COMPLIANCE WITH APPLICABLE FEDERAL, STATE OR LOCAL PERMITS, RULES AND/OR REGULATIONS.

I. SPECIAL INSPECTIONS


1. SPECIAL INSPECTIONS ARE REQUIRED FOR SOILS, CONCRETE, STEEL, AND LIGHT GAGE FRAMING CONSTRUCTION. IN ACCORDANCE WITH THE VIRGINIA CONSTRUCTION CODE AND IBC 2015; CHAPTER 17.
2. REFER TO STATEMENT OF SPECIAL INSPECTIONS FOR APPLICABLE ITEMS.
3. PROVIDE SPECIAL INSPECTIONS ENGINEER OF RECORD AND TESTING AGENCY FULL ACCESS TO SITE AND CONSTRUCTION.

MARK	DATE
BY	DES
REVISIONS	

DATE	PROJECT	DESIGNED	DRAWN
06.18.2021	133556.28	BTY	BTY
		RKS	
		CHECKED	



2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 DRAWING STRUCTURAL GENERAL NOTES




Engineering and Construction Services
8001 Braddock Road, Suite 200, Springfield, VA 22151
703-978-0100 www.gpinet.com
Project #: 2019322.00

SHEET
1-S-001




6/18/2021 11:52:54 AM BIN:360;133556-28 Virginia Hospital Center/201952200 v20 - Structural.rvt


6/16/2021 11:52:54 AM BIN 360/13356-28 Virginia Hospital Center/201952200 v20 - Structural.rvt



1 FOURTH FLOOR FRAMING - DEMOLITION
1-S-101 1/8" = 1'-0"




2 FOURTH FLOOR FRAMING - NEW WORK
1-S-101 1/8" = 1'-0"



NOTE: FOR ALTERNATE #1 ONLY


3 SECTION
1-S-101 3/4" = 1'-0"



CD Revisions	Amended Permit	DES
5-15-2020	5-31-2021	BY
1	4	MARK DATE
		REVISIONS

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356-28	BTY	BTY	RKS

RRMM ARCHITECTS, PC
 2900 South Quincy Street, Suite 710
 Arlington, Virginia 22206
 (703)998-0101




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204


DRAWING FOURTH FLOOR FRAMING- DEMOLITION & NEW WORK

GPI
 Greenman-Pedersen, Inc.
 Engineering and Construction Services
 8001 Braddock Road, Suite 200, Springfield, VA 22151
 703-978-0100 www.gpinet.com
 Project #: 2019322.00

SHEET
1-S-101



1 FIFTH FLOOR FRAMING - DEMOLITION
1-S-102 1/8" = 1'-0"



2 FIFTH FLOOR FRAMING - NEW WORK
1-S-102 1/8" = 1'-0"



GPI
 Greenman-Pedersen, Inc.
 Engineering and Construction Services
 8001 Braddock Road, Suite 200, Springfield, VA 22151
 703-978-0100 www.gpinet.com
 Project #: 2019322.00

DATE	PROJECT	DESIGNED	DRAWN	CHECKED	MARK	DATE	BY	DES
06.18.2021	13356.28	BTY	BTY	RKS				


DATE 06.18.2021
 PROJECT 13356.28
 DESIGNED BTY
 DRAWN BTY
 CHECKED RKS




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 DRAWING FIFTH FLOOR FRAMING - DEMOLITION & NEW WORK

SHEET
1-S-102

6/16/2021 11:52:55 AM BIN 360/713356-28 Virginia Hospital Center/20195200 v20 - Structural.rvt



1 ROOF BEARING FRAMING - DEMOLITION
1-S-103 1/8" = 1'-0"



2 ROOF BEARING FRAMING - NEW WORK
1-S-103 1/8" = 1'-0"

GPI
Greenman-Pedersen, Inc.
Engineering and Construction Services
8001 Braddock Road, Suite 200, Springfield, VA 22151
703-978-0100 www.gpinet.com
Project #: 2019322.00

MARK	DATE	BY	DES

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	BTY	BTY	RKS


RRMM ARCHITECTS, PC
2300 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101

PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
DRAWING ROOF FRAMING - DEMOLITION & NEW WORK

SHEET
1-S-103






6/16/2021 11:52:55 AM BIN 360/13356-28 Virginia Hospital Center/201952200 v20 - Structural.rvt



CD Revisions	DES
5-15-2020	BY
1	MARK DATE REVISIONS


DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	BTY	BTY	RKS



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204

DRAWING SECTIONS

SHEET
1-S-301



NOTES:
1. EXISTING JOISTS SHALL BE SHORED PRIOR TO PERFORMING THE WORK. CONTRACTOR TO SUBMIT SIGNED AND SEALED SHORING DRAWINGS TO THE ENGINEER OF RECORD FOR REVIEW AND APPROVAL.

GENERAL DEMOLITION NOTES

- ENTIRE HVAC SYSTEMS - EQUIPMENT, DUCTWORK, PIPING, CONTROLS, ETC. - SHALL BE DEMOLISHED IN THE AREA OF CONSTRUCTION, EXCEPT THE WORK CONNECTED TO THE PHYSICIANS BUILDING SYSTEMS TO REMAIN SHALL BE DISCONNECTED AND CAPPED. DESCRIPTIONS OF THE SYSTEMS BELOW AND FLOOR PLANS ARE PROVIDED FOR INFORMATION ONLY, AND THEY DO NOT INCLUDE ALL WORK REQUIRED TO BE DEMOLISHED. CONTRACTOR IS RESPONSIBLE FOR COMPLETE DEMOLITION OF ALL SYSTEMS IN THE AREA OF CONSTRUCTION WITH THE EXCEPTION NOTED ABOVE.
- THE EXISTING HEATING AND COOLING FOR THE STRUCTURES TO BE DEMOLISHED IS PROVIDED BY A VARIETY OF SYSTEMS INCLUDING, CONSTANT VOLUME DX COOLING ROOFTOP UNIT, ROOF MOUNTED CONDENSER, MINI-SPLIT SYSTEM HEAT PUMPS, WALL MOUNTED PACKAGED WATER-SOURCE HEAT PUMP UNITS, EXHAUST FANS, AND GRAVITY VENTILATORS. AIR DISTRIBUTION IS PROVIDED TO SUPPLY AIR REGISTERS BY SHEET METAL DUCTS CONCEALED ABOVE THE CEILINGS WITH DUCTED RETURNS.
- IN OTHER AREAS THERE ARE ELECTRIC AIR-TO-AIR MINI-SPLIT SYSTEM HEAT PUMPS. THE OUTDOOR HEAT PUMP UNITS ARE PAD-MOUNTED ON GRADE. THESE SYSTEMS USE R-410A AS A REFRIGERANT.
- THE PROJECT INCLUDES THE COMPLETE DEMOLITION OF ALL OF THESE SYSTEMS. REMOVE ALL EQUIPMENT, DUCTWORK AND MECHANICAL SYSTEM PIPING, AND CAP DUCTS AND PIPING AS REQUIRED WHERE DISCONNECTED.
- DISCONNECT ALL UTILITY CONNECTIONS INCLUDING ELECTRICAL WIRE AND CONDUITS, AND PIPING CONNECTED TO ALL MECHANICAL EQUIPMENT. SALVAGE EACH ITEM OF EQUIPMENT LISTED IN THE COUNTY'S SALVAGE SCHEDULE AS A WHOLE UNIT, LISTED, INDEXED, TAGGED, AND STORED. SALVAGE EACH SCHEDULED UNIT WITH ITS NORMAL OPERATING AUXILIARY EQUIPMENT. TRANSPORT SALVAGED EQUIPMENT, INCLUDING MOTORS, TO A DESIGNATED STORAGE AREA. DO NOT REMOVE EQUIPMENT FROM THE STORAGE AREA UNTIL APPROVED BY THE COUNTY. REMOVE EQUIPMENT NOT SCHEDULED FOR SALVAGE FROM THE SITE AND DISPOSE OF IT AS REQUIRED BY THE LOCAL AUTHORITY.
- DISCONNECT PIPING AT UNIONS, FLANGES AND VALVES, AND FITTINGS AS REQUIRED TO REDUCE THE PIPES INTO STRAIGHT LENGTHS FOR REMOVAL. CAREFULLY DISMANTLE PIPING THAT PREVIOUSLY CONTAINED GAS, GASOLINE, OIL, OR OTHER DANGEROUS FLUIDS, WITH PRECAUTIONS TAKEN TO PREVENT INJURY TO PERSONS AND PROPERTY. STORE PIPING MATERIALS OUTDOORS UNTIL ALL FUMES AND RESIDUES ARE REMOVED AND OR DISSIPATED. DISCARD ALL SUPPORTS, HANGERS, PLATES, VALVES, AND SPECIALTY ITEMS. TRANSPORT ANY PIPING MATERIALS SCHEDULED FOR SALVAGE TO A DESIGNATED STORAGE AREA, AND STORE ACCORDING TO SIZE AND TYPE. DO NOT REMOVE PIPING MATERIALS FROM THE STORAGE AREA UNTIL APPROVED BY THE OWNER. CLASSIFY THESE PIPING MATERIALS NOT DESIGNATED FOR SALVAGE AS SCRAP METAL. CLASSIFY ALL REMOVED DUCT WORK AS SCRAP METAL. REMOVE MATERIALS NOT SCHEDULED FOR SALVAGE FROM THE SITE AND DISPOSE OF IT AS REQUIRED BY THE LOCAL AUTHORITY.
- THERMOMETERS, THERMOSTATS, ETC. THAT CONTAINING MERCURY SHALL BE TAGGED FOR IDENTIFICATION AS POTENTIALLY HAZARDOUS MATERIALS, PROTECTED FROM BREAKAGE, AND PROPERLY DISPOSED OF.
- ALL REFRIGERANT TO BE REMOVED FROM THE EXISTING SYSTEMS SHALL BE FULLY RECOVERED IN ACCORDANCE WITH FEDERAL REGULATIONS.
- A SALVAGE SCHEDULE WILL BE PREPARED AND INCLUDED IN THE CONTRACT DOCUMENTS.

SCHEDULE

THE DEMOLITION SHALL OCCUR IN TWO PHASES:

PHASE 1

THE FIRST PHASE SHALL INCLUDE THE ISOLATION OF THE MULTI-STORY PHYSICIAN'S OFFICE BUILDING FROM THE REST OF THE STRUCTURE. THIS EFFORT SHALL INCLUDE THE DEMOLITION OF A PART OF THE CONNECTOR BUILDING, THE DEMOLITION OF THE MRI ADDITION, AND THE CONSTRUCTION OF AN EXPANDED VESTIBULE AND ACCESS PATHS AT THE EXISTING STAIR TOWER. THE EFFORT SHALL ALSO INCLUDE SOME BUILDING UTILITY WORK AS NOTED BELOW.

HVAC AND PLUMBING:

TO MECHANICALLY ISOLATE THE MULTI-STORY PHYSICIAN'S OFFICE BUILDING, THE CONTRACTOR SHALL FIRST REMOVE PORTIONS OF DUCTS AND PIPES, WHICH CROSS THE EXTERIOR WALL OF THE PHYSICIAN'S OFFICE BUILDING, AS REQUIRED FOR THIS PHASE OF DEMOLITION, AND CAP BOTH ENDS, ONE END INSIDE THE PHYSICIAN'S OFFICE BUILDING AND THE OTHER END INSIDE THE TO BE DEMOLISHED CONNECTOR BUILDING. PRIOR TO DEMOLITION OF MRI ADDITION, THE CONTRACTOR SHALL LOCATE UNDERGROUND CONDENSER WATER PIPES RUN FROM THE MECHANICAL ROOM IN THE MULTI-STORY PHYSICIAN'S OFFICE BUILDING TO THE COOLING TOWER SET ON GRADE AS IT IS POSSIBLE THAT THE PIPES REMAINED IN PLACE UNDER MRI ADDITION WHEN MRI ADDITION WAS BUILT UNLESS THEY WERE REROUTED. THESE PIPES SHOULD REMAIN IN SERVICE FOR THE PHYSICIAN'S OFFICE BUILDING. THE COOLING TOWER AS WELL AS THE NEARBY UNDERGROUND OIL STORAGE TANK SHALL BE PROTECTED FROM DAMAGE AND KEPT OPERATIONAL DURING THE ENTIRE CONSTRUCTION PERIOD (BOTH PHASES 1 AND 2).

PHASE 2 (REFER TO SEPARATE CONSTRUCTION DOCUMENTS)

ONCE THE PHYSICIAN'S OFFICE BUILDING IS FULLY ISOLATED AND THE EGRESS STAIR TOWER RENOVATION AND EGRESS PATH IS COMPLETE, THE SECOND PHASE OF THE DEMOLITION CAN PROCEED. THE SECOND PHASE OF DEMOLITION SHALL INCLUDE THE COMPLETE DEMOLITION OF THE EXISTING VIRGINIA HOSPITAL CENTER (BUILDING 601) AND THE REMAINING PART OF THE CONNECTOR BUILDING.

DUCTWORK LEGEND

	EXISTING DUCTWORK, EQUIPMENT OR PIPING TO REMAIN
	EXISTING DUCTWORK, EQUIPMENT OR PIPING TO BE REMOVED OR RELOCATED
	NEW DUCTWORK, EQUIPMENT OR PIPING
	DUCTWORK WITH SOUNDLINING
	SUPPLY AIR DUCT TURNING UP/DOWN
	RETURN AIR DUCT TURNING UP/DOWN
	EXHAUST AIR DUCT TURNING UP/DOWN
	CHANGE IN ELEVATION OF DUCTWORK IN DIRECTION OF AIRFLOW - RISE
	CHANGE IN ELEVATION OF DUCTWORK IN DIRECTION OF AIRFLOW - DROP
	MOTORIZED DAMPER
	DUCT MOUNTED SMOKE DETECTOR
	SQUARE TO SQUARE TRANSITION
	SQUARE TO ROUND TRANSITION
	BRANCH DUCT
	ELBOW WITH TURNING VANES
	ELBOW WITHOUT TURNING VANES
	RADIUS ELBOW
	SPIN-IN COLLAR WITH INTEGRAL VOLUME DAMPER
	VOLUME DAMPER
	FIRE DAMPER
	FIRE SMOKE DAMPER
	THERMOSTAT WITH CONTROL WIRE
	HUMIDISTAT
	CARBON MONOXIDE SENSOR
	SQUARE CEILING DIFFUSER
	LINEAR SLOT DIFFUSER
	LINEAR RETURN DIFFUSER
	CFM DESIGNATION
	DIFFUSER OR GRILLE TYPE DESIGNATION
	RETURN GRILLE
	KEYED NOTE DEMOLITION
	KEYED NOTE NEW WORK
	POINT OF REMOVAL
	POINT OF CONNECTION

PIPING LEGEND

	CHILLED WATER SUPPLY
	CHILLED WATER RETURN
	CONDENSER WATER SUPPLY
	CONDENSER WATER RETURN
	GLYCOL SUPPLY
	GLYCOL RETURN
	HOT WATER SUPPLY
	HOT WATER RETURN
	REFRIGERANT SUCTION
	REFRIGERANT LIQUID
	FUEL OIL SUPPLY
	FUEL OIL RETURN
	CONDENSATE DRAIN
	PUMPED CONDENSATE DRAIN
	MAKE-UP WATER
	PIPE TURNING UP
	PIPE TURNING DOWN
	VALVE IN VERTICAL
	CONCENTRIC PIPE REDUCER
	PIPE BRANCH BOTTOM TAKEOFF
	PIPE BRANCH TOP TAKEOFF
	DIRECTION OF FLOW
	PITCHED IN DIRECTION OF FLOW
	UNION
	2-WAY CONTROL VALVE
	3-WAY CONTROL VALVE
	BALL VALVE
	BUTTERFLY VALVE
	COMBINATION BALANCING/SHUT-OFF VALVE
	STRAINER WITH VALVE AND CAP
	STRAINER
	TRIPLE DUTY VALVE
	CHECK VALVE
	THERMOMETER
	PRESSURE GAUGE
	MANUAL AIR VENT
	PRESSURE/TEMPERATURE PORT
	PRESSURE REDUCING VALVE

ABBREVIATIONS

(E)	EXISTING TO REMAIN	KW	KILOWATTS
(R)	EXISTING TO BE RELOCATED	LAT	LEAVING AIR TEMPERATURE
(RE)	EXISTING TO BE REMOVED AND RELOCATED	LBS	POUNDS
AC	AIR CONDITIONER	LWT	LEAVING WATER TEMPERATURE
AFF	ABOVE FINISHED FLOOR	MBH	THOUSAND BRITISH THERMAL UNITS PER HOUR
AHU	AIR HANDLING UNIT	MCA	MINIMUM CIRCUIT AMPACITY
BAS	BUILDING AUTOMATION SYSTEM	OA	OUTSIDE AIR
BTUH	BRITISH THERMAL UNITS PER HOUR	PH	PHASE
CFM	CUBIC FEET PER MINUTE	RA	RETURN AIR
CRAC	COMPUTER ROOM AIR CONDITIONING UNIT	RLA	RATED LOAD AMPS
CU	CONDENSING UNIT	RTU	ROOFTOP UNIT
DB	DRY BULB	SA	SUPPLY AIR
DX	REFRIGERANT	TAD	TRANSFER AIR DUCT
EAT	ENTERING AIR TEMPERATURE	TAO	TRANSFER AIR OPENING
EF	EXHAUST FAN	TF	TRANSFER FAN
ESP	EXTERNAL STATIS PRESSURE	TSP	TOTAL STATIC PRESSURE
EWT	ENTERING WATER TEMPERATURE	TYP	TYPICAL
FLA	FULL LOAD AMPS	V	VOLT, VOLTS
FPB	FAN POWERED BOX	VAV	VARIABLE AIR VOLUME
FT	FOOT, FEET	VFD	VARIABLE FREQUENCY DRIVE
GPM	GALLONS PER MINUTE	WB	WET BULB
HP	HORSEPOWER	WG	WATER GAUGE
HZ	HERTZ		
IN	INCH, INCHES		

DRAWING LIST





- 1-M-001 COVER SHEET
- 1-M-102 FOURTH FLOOR DEMOLITION & NEW WORK PLANS
- 1-M-103 FIFTH FLOOR DEMOLITION & NEW WORK PLANS

GPI
Greenman-Pedersen, Inc.
Engineering and Construction Services
8001 Braddock Road, Suite 200, Springfield, VA 22151
703-978-0100 www.gpinet.com
Project #: 2019322.00

CD Revision		DES
05-15-2020		BY
	MARK	DATE
		REVISIONS

DATE	06.18.2021
PROJECT	13356.28
DESIGNED	
DRAWN	
CHECKED	


RRMM ARCHITECTS, PC
2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204

DRAWING COVER SHEET

SHEET
1-M-001



KEYED NOTES - DEMOLITION

1. REMOVE ALL HVAC EQUIPMENT, DUCTWORK PIPING, AND CONTROLS IN THESE AREAS BEING DEMOLISHED, EXCEPT THE WORK IN EXISTING BUILDING TO REMAIN. CAP UNUSED DUCT OPENINGS RESULTING FROM DEMOLITION WORK. ALL WORK TO BE REMOVED IS NOT SHOWN.


KEYED NOTES - NEW WORK

1. WSHP-1: TRANE GEC006, 1/2 TON WATER SOURCE HEAT PUMP CONSOLE UNIT. 1.1 GPM SYSTEM WATER FLOW, FLA 4.1, COMP LRA 14.0, MCA 4.9, MOCP 15 AT 208/1/60 ELECTRICAL CHARACTERISTICS, WITH HOT GAS REHEAT COIL WITH UNIT-MOUNTED HUMIDISTAT, CONDENSATE OVERFLOW SENSOR, STANDALONE UNIT-MOUNTED CONTROLS, PLEATED AIR FILTERS, POWER CORD/RECEPTACLE BOX WITH CIRCUIT BREAKER. DESIGN BASIS EFFICIENCIES - COOLING EER 12.5; HEATING COP 4.90. UNIT EFFICIENCIES SHALL MEET CODE MINIMUM EER 12.2 AND COP 4.3.


PROVIDE ALL PIPING AND POWER WIRING AS REQUIRED FOR OPERATION OF UNIT.

PIPING: RUN PIPING BELOW FLOOR AND CONNECT TO (E) MAIN PIPING. PROVIDE ISOLATION BALL VALVES IN PIPING INSIDE UNIT CABINET TO FACILITATE UNIT REPLACEMENT. PIPING MATERIALS SHALL MATCH (E) PIPING MATERIALS. INSULATE CONDENSATE DRAIN LINES WITH 1/2" THICK FIBERGLASS PREFORMED PIPE INSULATION WITH ALL SERVICE VAPOR RETARDER JACKET PER MANUFACTURER'S INSTALLATION INSTRUCTIONS.

WIRING: ELECTRICAL CONTRACTOR SHALL INSTALL AND WIRE ALL ELECTRICAL ACCESSORIES (FURNISHED WITH UNIT) INSIDE UNIT CABINET. ALL INSTALLATION AND WIRING SHALL BE PER UNIT MANUFACTURER'S INSTALLATION RECOMMENDATIONS.



2 FOURTH FLOOR - DEMOLITION
1-M-102 SCALE: 1/8" = 1'-0"



1 FOURTH FLOOR - NEW WORK
1-M-102 SCALE: 1/8" = 1'-0"

GPI
Greenman-Pedersen, Inc.
Engineering and Construction Services
8001 Braddock Road, Suite 200, Springfield, VA 22151
703-978-0100 www.gpinet.com
Project #: 2019322.00


CD Revision	Permit Revisions	DES
05-15-2020	06-12-2020	BY
1	2	MARK DATE
		REVISIONS

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	KDL	DWH	KDL

RRMM ARCHITECTS, PC
2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101

PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
DRAWING **FOURTH FLOOR DEMOLITION & NEW WORK**
PLANS

SHEET
1-M-102



KEYED NOTES - DEMOLITION

1. REMOVE ALL HVAC EQUIPMENT, DUCTWORK AND CONTROLS IN THESE AREA BEING DEMOLISHED, EXCEPT THE WORK IN EXISTING OFFICE BUILDING TO REMAIN. ALL WORK TO BE REMOVED IS NOT SHOWN.

KEYED NOTES - NEW WORK

1. WSH-1: TRANE GEC006, 1/2 TON WATER SOURCE HEAT PUMP CONSOLE UNIT, 1.1 GPM SYSTEM WATER FLOW, FLA 4.1, COMP LRA 14.0, MCA 4.9, MOCP 15 AT 208/1/60 ELECTRICAL CHARACTERISTICS, WITH HOT GAS REHEAT COIL WITH UNIT-MOUNTED HUMIDISTAT, CONDENSATE OVERFLOW SENSOR, STANDALONE UNIT-MOUNTED CONTROLS, PLEATED AIR FILTERS, POWER CORD RECEPTACLE BOX WITH CIRCUIT BREAKER. DESIGN BASIS EFFICIENCIES - COOLING EER 12.5; HEATING COP 4.90. UNIT EFFICIENCIES SHALL MEET CODE MINIMUM EER 12.2 AND COP 4.3.

PROVIDE ALL PIPING AND POWER WIRING AS REQUIRED FOR OPERATION OF UNIT.


PIPING: RUN PIPING BELOW FLOOR AND CONNECT TO (E) MAIN PIPING. PROVIDE ISOLATION BALL VALVES IN PIPING INSIDE UNIT CABINET TO FACILITATE UNIT REPLACEMENT. PIPING MATERIALS SHALL MATCH (E) PIPING MATERIALS. INSULATE CONDENSATE DRAIN LINES WITH 1/2" THICK FIBERGLASS PREFORMED PIPE INSULATION WITH ALL SERVICE VAPOR RETARDER JACKET PER MANUFACTURER'S INSTALLATION INSTRUCTIONS.

WIRING: ELECTRICAL CONTRACTOR SHALL INSTALL AND WIRE ALL ELECTRICAL ACCESSORIES (FURNISHED WITH UNIT) INSIDE UNIT CABINET. ALL INSTALLATION AND WIRING SHALL BE PER UNIT MANUFACTURER'S INSTALLATION RECOMMENDATIONS.

CD Revision	Permit Revisions	DES
05-15-2020	06-12-2020	BY
1	2	MARK DATE
		REVISIONS

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	KDL	DWH	KDL

RRMM ARCHITECTS, PC
 2900 South Quincy Street, Suite 710
 Arlington, Virginia 22206
 (703)998-0101




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204

DRAWING FIFTH FLOOR DEMOLITION & NEW WORK PLANS

GPI
 Greenman-Pedersen, Inc.
 Engineering and Construction Services
 8001 Braddock Road, Suite 200, Springfield, VA 22151
 703-978-0100 www.gpinet.com
 Project #: 2019322.00

1 FIFTH FLOOR - DEMOLITION
 1-M-103 SCALE: 1/8" = 1'-0"

2 FIFTH FLOOR - NEW WORK
 1-M-103 SCALE: 1/8" = 1'-0"



6/16/2021 11:49:02 AM C:\Users\jnguyen\Documents\201932200_v20 - Mechanical_injuyen\RR32E.rvt

GENERAL NOTES

- ENTIRE PLUMBING AND FIRE PROTECTION SYSTEMS - EQUIPMENT, TANKS, PIPING, CONTROLS, ETC. ABOVE AND BELOW GROUND SHALL BE DEMOLISHED. DESCRIPTIONS OF THE SYSTEMS ARE PROVIDED FOR INFORMATION ONLY AND DO NOT INCLUDE ALL WORK REQUIRED TO BE DEMOLISHED. CONTRACTOR IS RESPONSIBLE FOR COMPLETE DEMOLITION OF ALL SYSTEMS IN THE AREA OF CONSTRUCTION.
- PLUMBING SYSTEMS
 - THE EXISTING PLUMBING SYSTEMS INCLUDES THE HOT AND COLD WATER PIPING SYSTEM, THE SANITARY SEWER AND VENT SYSTEMS, AND THE STORM WATER SYSTEM. THE RISERS AND THE HORIZONTAL DISTRIBUTION PIPING ARE GENERALLY COPPER THROUGHOUT THE BUILDINGS. THE SOIL AND VENT SYSTEMS AND STORM WATER SYSTEM ARE CAST IRON AND PVC.
 - THERE ARE STORM LINES UNDER SLAB OF MRI ADDITION.
 - THE PROJECT INCLUDES THE COMPLETE DEMOLITION OF ALL OF THESE PLUMBING AND PIPING SYSTEMS.
 - DEMOLITION OF STORM LINES EXITING THE BUILDINGS SHALL BE COORDINATED WITH CIVIL DEMOLITION WORK.
 - CLASSIFY REMOVED MATERIALS AS SCRAP METAL AND REMOVE THE MATERIALS FROM THE SITE AS DESCRIBED UNDER MECHANICAL SYSTEMS UNLESS ON THE SALVAGE SCHEDULE.

SCHEDULE

THE DEMOLITION SHALL OCCUR IN TWO PHASES:

PHASE 1
 THE FIRST PHASE SHALL INCLUDE THE ISOLATION OF THE MULTI-STORY PHYSICIAN'S OFFICE BUILDING FROM THE REST OF THE STRUCTURE. THIS EFFORT SHALL INCLUDE THE DEMOLITION OF A PART OF THE CONNECTOR BUILDING, THE DEMOLITION OF THE MRI ADDITION, AND THE CONSTRUCTION OF AN EXPANDED VESTIBULE AND ACCESS PATHS AT THE EXISTING STAIR TOWER. THE EFFORT SHALL ALSO INCLUDE SOME BUILDING UTILITY WORK AS NOTED BELOW:

HVAC AND PLUMBING:
 TO MECHANICALLY ISOLATE THE MULTI-STORY PHYSICIAN'S OFFICE BUILDING, THE CONTRACTOR SHALL FIRST REMOVE PORTIONS OF DUCTS AND PIPES, WHICH CROSS THE EXTERIOR WALL OF THE PHYSICIAN'S OFFICE BUILDING, AS REQUIRED FOR THIS PHASE OF DEMOLITION, AND CAP BOTH ENDS, ONE END INSIDE THE PHYSICIAN'S OFFICE BUILDING AND THE OTHER END INSIDE THE TO BE DEMOLISHED CONNECTOR BUILDING.
 PRIOR TO DEMOLITION OF MRI ADDITION, THE CONTRACTOR SHALL LOCATE UNDERGROUND CONDENSER WATER PIPES RUN FROM THE MECHANICAL ROOM IN THE MULTI-STORY PHYSICIAN'S OFFICE BUILDING TO THE COOLING TOWER SET ON GRADE AS IT IS POSSIBLE THAT THE PIPES REMAINED IN PLACE UNDER MRI ADDITION WHEN MRI ADDITION WAS BUILT UNLESS THEY WERE REROUTED. THESE PIPES SHOULD REMAIN IN SERVICE FOR THE PHYSICIAN'S OFFICE BUILDING. THE COOLING TOWER AS WELL AS THE NEARBY UNDERGROUND OIL STORAGE TANK SHALL BE PROTECTED FROM DAMAGE AND KEPT OPERATIONAL DURING THE ENTIRE CONSTRUCTION PERIOD (BOTH PHASES 1 AND 2).
 AN EXHAUST FAN ON THE ROOF OF THE CONNECTOR BUILDING, WHICH SERVES MULTIPLE TOILETS IN THE CONNECTOR BUILDING, ALSO SERVES TELECOM ROOM ON THE FIFTH FLOOR OF THE MULTI-STORY PHYSICIAN'S OFFICE BUILDING 611. A NEW, SMALLER, FAN AND DUCTWORK SHALL BE INSTALLED IN THE PHYSICIAN'S OFFICE BUILDING FOR THE ROOM PRIOR TO ANY DISCONNECTION AS DESCRIBED ABOVE TO MAINTAIN REQUIRED AIR FLOW.

PHASE 2 (REFER TO SEPARATE CONSTRUCTION DOCUMENTS)
 ONCE THE PHYSICIAN'S OFFICE BUILDING IS FULLY ISOLATED AND THE EGRESS STAIR TOWER RENOVATION AND EGRESS PATH IS COMPLETE, THE SECOND PHASE OF THE DEMOLITION CAN PROCEED. THE SECOND PHASE OF DEMOLITION SHALL INCLUDE THE COMPLETE DEMOLITION OF THE EXISTING VIRGINIA HOSPITAL CENTER (BUILDING 601) AND THE REMAINING PART OF THE CONNECTOR BUILDING.

PLUMBING LEGEND

SYMBOL	ABBREVIATION	DESCRIPTION
		EXISTING PIPING OR EQUIPMENT TO BE REMOVED
	CW	DOMESTIC COLD WATER
	HW	DOMESTIC HOT WATER
	HWC	DOMESTIC HOT WATER RECIRCULATION
		SANITARY SOIL AND WASTE
		SANITARY VENT
		STORM WATER
		PIPE TURNING UP
		PIPE TURNING DOWN
		PIPE BRANCH BOTTOM TAKEOFF
		PIPE BRANCH TOP TAKEOFF
		OFFSET IN PIPE
		CAPPED PIPE
		POINT OF REMOVAL
		KEYED NOTE, DEMOLITION
		KEYED NOTE, NEW WORK

ABBREVIATION

(E) EXISTING
 FHV FIRE HOSE VALVE
 (N) NEW

DRAWING LIST


1-P-001 COVER SHEET
 1-P-102 FOURTH FLOOR DEMOLITION PLAN
 1-P-103 FIFTH FLOOR DEMOLITION PLAN



CD Revisions


NO.	DATE	BY	DES
1	06-15-2020	MARK	DATE

DATE	PROJECT	DESIGNED	DRAWN	CHECKED	TTN	RMD
06.18.2021	13356.28	BKM	TTN	RMD		




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 DRAWING COVER SHEET

SHEET
1-P-001



KEYED NOTES - DEMOLITION

- REMOVE ALL PIPING - DOMESTIC HOT AND COLD WATER, SANITARY SEWER, VENT, STORM SEWER, FOUNDATION DRAIN, SPRINKLER PIPING, AND SPRINKLER HEAD IN THESE AREAS BEING DEMOLISHED, EXCEPT THE WORK IS INDICATED TO REMAIN. REMOVE ALL SANITARY SEWER AND VENT PIPING TO WITHIN 2 FEET OF ACTIVE PIPING TO NOT CREATE DEAD ENDS AS DESCRIBED IN PLUMBING CODE.
- SEE CIVIL DRAWINGS FOR CONTINUATION.




2 FOURTH FLOOR - DEMOLITION
 1-P-102 SCALE: 1/8" = 1'-0"

GPI
 Greenman-Pedersen, Inc.
 Engineering and Construction Services
 8001 Braddock Road, Suite 200, Springfield, VA 22151
 703-978-0100 www.gpinet.com
 Project #: 2019322.00

CD Revisions	MARK	DATE	BY	DES
1		05-15-2020		

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28			


RRMM
 ARCHITECTS, PC
 2900 South Quincy Street, Suite 710
 Arlington, Virginia 22206
 (703)998-0101



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204.
 DRAWING FOURTH FLOOR DEMOLITION PLAN

SHEET
1-P-102

6/16/2021 11:51:12 AM C:\Users\jnguyen\Documents\201932200_v20 - Plumbing_jnguyenR32E.rvt




KEYED NOTES - DEMOLITION

- REMOVE ALL PIPING - DOMESTIC HOT AND COLD WATER, SANITARY SEWER, VENT, STORM SEWER, FOUNDATION DRAIN, SPRINKLER PIPING, AND SPRINKLER HEAD IN THESE AREAS BEING DEMOLISHED, EXCEPT THE WORK IS INDICATED TO REMAIN. REMOVE ALL SANITARY SEWER AND VENT PIPING TO WITHIN 2 FEET OF ACTIVE PIPING TO NOT CREATE DEAD ENDS AS DESCRIBED IN PLUMBING CODE.
- SEE CIVIL DRAWINGS FOR CONTINUATION.

CD Revisions	MARK	DATE	BY	DES
1		05-15-2020		

DATE	06.18.2021
PROJECT	13356.28
DESIGNED	
DRAWN	
CHECKED	


RRMM
ARCHITECTS, PC
2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
DRAWING FIFTH FLOOR DEMOLITION PLAN

GPI
Greenman-Pedersen, Inc.
Engineering and Construction Services
8001 Braddock Road, Suite 200, Springfield, VA 22151
703-978-0100 www.gpinet.com
Project #: 2019322.00

SHEET
1-P-103



1 FIFTH FLOOR - DEMOLITION
1-P-103 SCALE: 1/8" = 1'-0"



6/16/2021 11:51:15 AM C:\Users\jnguyen\Documents\201932200_v20 - Plumbing_jnguyenR32E.rvt

ELECTRICAL SPECIFICATIONS

A. GENERAL

- REFER TO BOOK SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS AND SCOPE.
- THE CONTRACTOR SHALL COMPLY WITH ALL THE LAWS, ORDINANCES, RULES AND REGULATIONS OF ALL LOCAL AND STATE GOVERNMENTAL AUTHORITIES, THE RULES OF THE NATIONAL FIRE PROTECTION ASSOCIATION AS INTERPRETED BY THE ENFORCING AUTHORITY HAVING JURISDICTION AND OF THE PUBLIC UTILITIES HAVING CONNECTION WITH ANY OF THE SYSTEMS HEREIN SPECIFIED.
- THE CONTRACTOR SHALL SECURE AND PAY FOR ALL PERMITS AND INSPECTIONS REQUIRED BY ANY OF THE FOREGOING AUTHORITIES, AND PAY FOR ALL OTHER COSTS IN CONNECTION WITH THE WORK. ALL CERTIFICATES SHALL BE IN DUPLICATE AND SHALL BE DELIVERED TO THE ARCHITECT/ENGINEER/OWNER.
- THE SITE, LOCATION AND ROUTING OF SYSTEMS INDICATED TO HAVE NEW CONNECTIONS MADE TO THEM ARE SHOWN AS ACCURATELY AS FIELD CONDITIONS WOULD PERMIT. BIDDERS SHALL VISIT THE SITE AND THOROUGHLY EXAMINE THE CONTRACT DRAWINGS. BIDDERS WHO DO NOT VISIT THE SITE MAY BE UNLATERALLY NOT PERMITTED TO SUBMIT A BID IF THE OWNER SO DESIGNATES. ALL EXISTING CONDITIONS SHALL BE EXAMINED AND THEIR EXACT LOCATIONS VERIFIED. THE CONTRACTOR SHALL REPORT TO THE ARCHITECT/ENGINEER/OWNER BEFORE SUBMITTING A BID, ANY CONDITIONS WHICH MIGHT MAKE INSTALLATION OF REQUIRED EQUIPMENT A PROBLEM. NO CONSIDERATION OR ALLOWANCE WILL BE GRANTED FOR FAILURE TO INVESTIGATE CONDITIONS OR MISUNDERSTANDINGS OF THE CONTRACTUAL REQUIREMENTS.
- THE CONTRACTOR SHALL REMOVE ALL EQUIPMENT NOT INDICATED TO BE REUSED TO A DESIGNATED LOCATION AT THE PROJECT SITE. AFTER THE EQUIPMENT HAS BEEN ASSEMBLED FOR THE OWNER'S INSPECTION AND POSSIBLE RETENTION, ALL EQUIPMENT NOT TO BE RETAINED BY THE OWNER SHALL BE REMOVED FROM THE SITE BY THE CONTRACTOR. ALL BUILDING SYSTEMS SHALL REMAIN IN SERVICE UNLESS INDICATED OTHERWISE. ALL OUTAGES OR INTERRUPTIONS SHALL BE KEPT TO A MINIMUM DURATION. NOTIFY THE OWNER 48 HOURS IN ADVANCE OF ANY OUTAGE OR INTERRUPTION.
- THE CONTRACTOR SHALL INSTALL AND CONNECT ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH THE BEST ENGINEERING PRACTICE AND, UNLESS OTHERWISE SHOWN OR SPECIFIED, FOLLOW THE MANUFACTURER'S INSTRUCTIONS AND RECOMMENDATIONS AND FURNISH AND INSTALL ALL REQUIRED AUXILIARY ITEMS COMPLETE.
- DRAWINGS SHALL BE CONSIDERED DIAGRAMMATIC AND FOR BIDDING PURPOSES ONLY. WHILE THE DRAWINGS ARE GENERALLY TO SCALE AND ARE AS ACCURATE AS THE SCALE WILL PERMIT, ALL IMPORTANT DIMENSIONS SHALL BE DETERMINED IN THE FIELD. THEY ARE NOT TO BE CONSIDERED TO BE ERECTION DRAWINGS.
- COORDINATE WITH ALL TRADES TO AVOID INTERFERENCE AMONG MECHANICAL, ELECTRICAL, ARCHITECTURAL AND STRUCTURAL ITEMS. PROVIDE ALL NECESSARY OFFSETS AND FITTINGS IN CIRCUITRY AND OTHER ITEMS REQUIRED TO INSTALL THE WORK WITHOUT INTERFERENCES.
- THE CONTRACTOR SHALL TEST ALL EQUIPMENT INSTALLED UNDER THIS CONTRACT AND DEMONSTRATE TO THE OWNER ITS PROPER OPERATION. ALL NEW EQUIPMENT SHALL BE MOUNTED VIBRATION FREE.
- ALL EQUIPMENT AND WORKMANSHIP SHALL BE GUARANTEED IN FULL FROM ALL DEFECTS FOR ONE (1) YEAR FROM THE DATE OF FINAL ACCEPTANCE OF THIS WORK.
- ALL EQUIPMENT INSTALLED SHALL BE NEW AND SHALL CONFORM IN ALL RESPECTS TO THE LATEST APPROVED STANDARDS OF IEEE, ANS, NEMA AND UNDERWRITERS LABORATORIES, INC., UNLESS INDICATED OTHERWISE.
- SHOP DRAWINGS AND PRODUCT DATA, SUBMIT SHOP DRAWINGS AND PRODUCT DATA FOR ALL NEW MATERIAL AND EQUIPMENT PROVIDED UNDER THIS WORK. MATERIAL AND EQUIPMENT SHALL BE SUBMITTED AND APPROVED BEFORE ORDERING. SUBMIT A MINIMUM OF 6 COPIES TO THE ARCHITECT/ENGINEER/OWNER FOR REVIEW. ELECTRONIC SUBMISSIONS ARE ACCEPTABLE. SUBSTITUTION ARE SUBJECT TO DISCRETION OF THE ARCHITECT/ENGINEER/OWNER. IF CONSIDERED, THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE INSTALLATION AND SHALL MEET THE INTENT OF THE CONSTRUCTION DOCUMENTS.
- REPAIR OF EXISTING WORK: ALL WORK SHALL BE CAREFULLY LAID OUT IN ADVANCED, AND WHERE CUTTING, CHANNELING, CHASING, OR DRILLING OF FLOORS, WALL, PARTITIONS, CEILING, OR OTHER SURFACES IS NECESSARY FOR THE PROPER INSTALLATION, SUPPORT, OR ANCHORAGE OF THE CONDUIT, RACEWAYS OR OTHER ELECTRICAL WORK, THIS WORK SHALL BE CAREFULLY DONE, AND ANY DAMAGE TO BUILDING, PIPING, OR EQUIPMENT SHALL BE REPAIRED BY SKILLED MECHANICS OF THE TRADE INVOLVED, AT NO ADDITIONAL COST TO THE OWNER. METHODS FOR AND EXACT LOCATIONS OF PROPOSED CUTTING, CHANNELING, CHASING OR DRILLING OF EXISTING CONSTRUCTION SHALL BE AS APPROVED BY THE OWNER.
- THE CONTRACTOR SHALL REPAIR ALL WALL, CEILING, FLOOR, OR ROOF OPENINGS WHICH ARE CREATED BY DEMOLITION OR PENETRATION. THE REPAIRS SHALL BE WITH MATERIALS AND FINISHES TO MATCH EXISTING. ALL FIRE RATED PENETRATIONS SHALL BE SEALED WITH SUITABLE MATERIALS TO PRESERVE FIRE RATED INTEGRITY.
- DEFINITIONS: "PROVIDE" UNDER THIS CONTRACT IS DEFINED AS FURNISH AND INSTALL. "CONCEALED" UNDER THIS CONTRACT IS DEFINED AS WITHIN ARCHITECTURAL WALLS AND ABOVE CEILINGS. "EXPOSED" UNDER THIS CONTRACT IS DEFINED AS VISIBLE TO VIEW, INCLUDING ELECTRICAL ROOMS. "INDICATED" UNDER THIS CONTRACT IS DEFINED AS SHOWN IN THE CONTRACT DOCUMENTS. "CIRCUITRY" UNDER THIS CONTRACT IS DEFINED AS CONDUIT, FEEDER AND OR CIRCUIT.
- UPON COMPLETION OF THE WORK, THE CONTRACTOR SHALL THOROUGHLY CLEAN THE CONTRACT AREA AND ALL OTHER AREAS USED FOR STORAGE, STAGING, ETC.
- THE CONTRACTOR SHALL NOTIFY THE ARCHITECT/ENGINEER/OWNER WHEN THE PROJECT IS APPROXIMATELY 75% COMPLETED IN ORDER TO SCHEDULE A PRE-FINAL REVIEW OF CONSTRUCTION. NO WORK SHALL BE CONCEALED BY CEILING, WALLS, ETC. FINAL REVIEW SHALL BE SCHEDULED AT 100% COMPLETION. ALL PUNCH LIST ITEMS MUST BE ACCOMPLISHED PRIOR TO FINAL ACCEPTANCE.
- THE CONTRACTOR SHALL PREPARE A COMPREHENSIVE METHOD OF PROCEDURE AND SUBMIT IT TO THE OWNER WITH SHOP DRAWINGS FOR REVIEW. THE SUBMITTAL SHALL ITEMIZE METHODS OF PROCEDURE FOR ALL POTENTIAL EMERGENCY SITUATIONS AND SHALL INCLUDE A LIST OF PERSONS REPRESENTING THE OWNER AND THE CONTRACTOR ALONG WITH DAYTIME EMERGENCY PHONE NUMBERS INDICATING WHO SHALL BE CONTACTED IN THE EVENT OF AN EMERGENCY. THIS LIST SHALL BE DISTRIBUTED TO THE OWNER'S REPRESENTATIVE AND THE CONTRACTOR'S SUPERINTENDENT OR FOREMAN AT THE SITE. EMERGENCY SITUATIONS SHALL INCLUDE BUT NOT BE LIMITED TO POWER OUTAGES, CHILLED AND CONDENSER WATER SYSTEM RUPTURES, AUTOMATIC TEMPERATURE CONTROL OUTAGES AND OWNER'S EQUIPMENT DAMAGE. THE COMPREHENSIVE METHOD OF PROCEDURE SHALL BE SUBMITTED TO THE OWNER PRIOR TO COMMENCEMENT OF ANY WORK.
- PROVIDE TEMPORARY SERVICE FOR LIGHTING AND POWER EQUIPMENT (DRILLS, SAW, ETC.). VERIFY TEMPORARY REQUIREMENTS WITH GENERAL CONTRACTOR. TEMPORARY LIGHTING AND POWER SHALL MEET OSHA REQUIREMENTS AND LOCAL CODE. TEMPORARY POWER SHALL BE 120 VOLTS.
- PROTECT ADJACENT MATERIALS INDICATED TO REMAIN. INSTALL AND MAINTAIN DUST AND NOISE BARRIERS TO KEEP DIRT, DUST, AND NOISE FROM BEING TRANSMITTED TO ADJACENT AREAS. REMOVE PROTECTION AND BARRIERS AFTER DEMOLITION OPERATIONS ARE COMPLETE.
- FINAL TESTING: AT THE TIME OF FINAL INSPECTION AND TESTS, ALL CONNECTIONS AT PANELBOARDS, DEVICES AND EQUIPMENT AND ALL SPLICES MUST BE COMPLETED. EACH BRANCH CIRCUIT AND ITS RESPECTIVE CONNECTED EQUIPMENT MUST TEST FREE OF SHORT CIRCUITS. UPON COMPLETION OF THE WORK, CLEAN AND POLISH ALL EXPOSED SURFACES IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.
- CONTRACTOR SHALL PROVIDE ACCESS PANEL FOR JUNCTION BOXES, DISCONNECT SWITCHES, OR OTHER DEVICES WHICH REQUIRE SERVICE ACCESS PER NEC.

B. LIGHTING

- COORDINATE RECESSED LIGHTING FIXTURES WITH MECHANICAL EQUIPMENT AND ARCHITECTURAL CEILING PLAN. GRID LAYOUT ON PLANS IS APPROXIMATE. ADJUST LIGHTING FIXTURES IN FIELD PER ARCHITECT.
- PROVIDE FINISHING FRAMES FOR ALL RECESSED LIGHTING FIXTURES. TYPE TO BE COMPATIBLE WITH CEILING. COORDINATE ALL FIXTURE TYPES WITH CEILING SYSTEM BEFORE ORDERING FIXTURES. PROVIDE ALL MOUNTING ATTACHMENTS FOR A COMPLETE INSTALLATION.
- IN LOCATIONS WHERE NEW DUCTWORK OR CEILING IS INSTALLED UNDER THIS CONTRACT BUT LIGHTING FIXTURES HAVE NOT BEEN REVISED, REMOVE EXISTING FIXTURES AS NECESSARY TO RUN THE NEW DUCTWORK OR CEILING AND RE-HANG AFTER THE MECHANICAL OR ARCHITECTURAL WORK IS COMPLETED.
- PROVIDE ALL REQUIRED ACCESSORIES FOR A COMPLETE AND OPERATIONAL INSTALLATION TO SUIT PROJECT CONDITIONS.
- PROVIDE MEANS OF SUPPORT PER NEC 410.36.

C. EQUIPMENT CONNECTION

- EXTEND WIRING TO ALL EQUIPMENT REQUIRING ELECTRICAL CONNECTIONS AND MAKE FINAL AND COMPLETE CONNECTIONS TO ALL EQUIPMENT. BEFORE ROUGHING IN THE LOCATION AND TYPE OF DEVICES SHALL BE VERIFIED FROM SHOP DRAWINGS OF THE EQUIPMENT. STARTERS AND DISCONNECTS AND OTHER ELECTRICAL CIRCUITRY AND DEVICES SHALL BE LOCATED TO ALLOW ACCESS TO DEVICES AND NOT INTERFERE WITH THE OPERATION OF THE MECHANICAL OR ARCHITECTURAL DEVICES OR THEIR POSSIBLE MAINTENANCE OR REMOVAL.

D. DEMOLITION

- PROVIDE DEMOLITION AS INDICATED ON DEMOLITION PLANS. CIRCUITRY NOTED FOR REMOVAL SHALL BE REMOVED BACK TO THE SOURCE BUS UNLESS OTHERWISE NOTED. BE RESPONSIBLE FOR THE COMPLETE REMOVAL FROM THE SITE FOR ALL EQUIPMENT AND MATERIAL REMOVED UNDER DEMOLITION WORK, UNLESS OTHERWISE NOTED OR DIRECTED. EXISTING CIRCUITS TO REMAIN INTERRUPTED BY DEMOLITION SHALL BE RESTORED FOR OPERATION AS BEFORE. OUTAGES REQUIRED TO PERFORM DEMOLITION SHALL BE COORDINATED WITH THE OWNER AND PROCESSED OUTSIDE OF NORMAL BUSINESS HOURS. REPAIR ALL WALL, CEILING, FLOOR OR ROOF OPENINGS CREATED BY DEMOLITION. REPAIRS SHALL BE PROVIDED BY WORKMAN SKILLED IN THE TRADE AND SHALL CONFORM WITH MATERIAL AND FINISHES TO MATCH EXISTING.
- LOCATE, IDENTIFY AND PROTECT ELECTRICAL SERVICES PASSING THROUGH DEMOLITION AREA AND SERVING OTHER AREAS OUTSIDE THE DEMOLITION LIMITS. MAINTAIN SERVICES TO AREAS OUTSIDE DEMOLITION LIMITS. WHEN SERVICES MUST BE INTERRUPTED, INSTALL TEMPORARY SERVICES FOR AFFECTED AREAS.

SCHEDULE

THE DEMOLITION WILL OCCUR IN TWO PHASES:

PHASE 1

THE FIRST PHASE WILL INCLUDE THE ISOLATION OF THE MULTI-STORY PHYSICIAN'S OFFICE BUILDING FROM THE REST OF THE STRUCTURE. THIS EFFORT WILL INCLUDE THE CONSTRUCTION OF AN EXPANDED VESTIBULE AND ACCESS PATHS AT THE EXISTING STAIR TOWER. THE EFFORT WILL ALSO INCLUDE SOME BUILDING UTILITY WORK AS NOTED BELOW:

ELECTRICAL:

IN ORDER TO ELECTRICALLY ISOLATE AND MAINTAIN SYSTEM OPERATIONS OF THE MULTI-STORY PHYSICIAN'S OFFICE BUILDING, THE CONTRACTOR SHALL DISCONNECT ALL ELECTRICAL DEVICES, LIGHTING CIRCUITS, AND MECHANICAL EQUIPMENT FEEDERS SERVING IN THE CONNECTOR BUILDING AND MRI BUILDING. THE MRI BUILDING, THE STAIR TOWER, AND CONNECTOR BUILDING ARE DETERMINED TO FEED FROM THE PHYSICIAN'S OFFICE BUILDING.

AS PART OF THIS FIRST PHASE OF THE WORK, ALL POWER AND LIGHTING PANELS AND TRANSFORMERS WITHIN THE MRI ADDITION ARE TO BE REMOVED ALONG WITH ALL ASSOCIATED FEEDERS BACK TO THE SOURCE CONNECTION POINT IN THE PHYSICIAN'S OFFICE BUILDING. AT THE SOURCE PANELBOARDS AND SWITCHBOARDS WITHIN THE PHYSICIAN'S OFFICE BUILDING, TURN CIRCUIT BREAKER(S) TO THE OFF POSITION AND LABEL AS "SPARE". RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION. REMOVE ALL CIRCUITRY CROSSING BETWEEN BUILDINGS BACK TO THE NEXT ACTIVE OUTLET, FIXTURE, OR EQUIPMENT OR BACK TO THE SOURCE PANELBOARD IF THE CIRCUIT IS NO LONGER ACTIVE AS NOTED ABOVE.

ELECTRICAL DEVICES, FIXTURES, AND EQUIPMENT IN THE EXISTING STAIR TOWER ARE EXISTING TO REMAIN. CIRCUITS SERVING THIS AREA ARE TO BE MAINTAINED AND ADJUSTED AS REQUIRED TO KEEP THE EGRESS STAIR TOWER OPERATIONAL THROUGHOUT THE PROJECT DURATION. EXIT DISCHARGE LIGHTING AT THE STAIR EXIT SHALL BE RELOCATED AS NECESSARY TO ACCOMMODATE THE NEW DOOR LOCATION.

ALL FIRE ALARM DEVICES IN THE CONNECTOR BUILDING AND THE EXISTING STAIR TOWER SHALL BE DISCONNECTED, AND ALL WIRING SHALL BE REMOVED BACK TO THE SOURCE IN VHS BUILDING. FIRE ALARM DEVICES IN THE EXISTING STAIR TOWER SHALL BE RECONNECTED TO THE FIRE ALARM SYSTEM IN PHYSICIAN'S OFFICE BUILDING. THE EXISTING FIRE ALARM CONTROL PANEL SHALL BE ADJUSTED TO ACCOMMODATE THESE ADDITIONAL DEVICES. OTHER FIRE ALARM DEVICES IN THE CONNECTOR BUILDING SHALL BE REMOVED AS WELL AS ALL FIRE ALARM, BRANCH CIRCUITRY, ELECTRICAL DEVICES AND FIXTURES, PANELBOARDS, AND FEEDERS IN THE MRI ADDITION.

PHASE 2 (REFER TO SEPARATE CONSTRUCTION DOCUMENTS)

THE TEMPORARY ELECTRICAL SERVICES PROVIDED IN PHASE ONE SHALL BE DISCONNECTED, ONCE THE PHYSICIAN'S OFFICE BUILDING IS FULLY ISOLATED AND THE EGRESS STAIR TOWER RENOVATION AND EGRESS PATH IS COMPLETE. THE SECOND PHASE OF THE DEMOLITION CAN PROCEED. THE SECOND PHASE OF DEMOLITION WILL INCLUDE THE COMPLETE DEMOLITION OF THE EXISTING VIRGINIA HOSPITAL CENTER (BUILDING 601), THE REMAINING PORTION OF THE CONNECTOR BUILDING.































ABBREVIATIONS

A	AMPS		
AIC	AMPERES INTERRUPTING CAPACITY		
ATS	AUTOMATIC TRANSFER SWITCH		
AWG	AMERICAN WIRE GAUGE	MIN	MINIMUM
BLDG	BUILDING	MLO	MAIN LUG ONLY
C	CONDUIT	MOCP	MAXIMUM OVERCURRENT PROTECTION
CATV	CLOSED CIRCUIT TELEVISION	MTS	MANUAL TRANSFER SWITCH
CB	CIRCUIT BREAKER	N	NEUTRAL
CKT	CIRCUIT	NEC	NATIONAL ELECTRICAL CODE
CO	CARBON MONOXIDE	NEMA	NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION
DED	DEDICATED	NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
DISC SW	DISCONNECT SWITCH		
DP	DISTRIBUTION PANEL		
DWG	DRAWING	NFSS	NON FUSED SAFETY SWITCH
EA	EACH	NIC	NOT IN CONTRACT
EC	EMPTY CONDUIT	NO	NUMBER
EGC	EQUIPMENT GROUND CONDUCTOR	NTS	NOT TO SCALE
EM/NL	EMERGENCY/NIGHT LIGHT	OCPO	OVER-CURRENT PROTECTION DEVICE
EMT	ELECTRICAL METALLIC TUBING		
ENGR	ENGINEER	OSHA	OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
EPO	EMERGENCY POWER OFF	P	POLE
EQUIP	EQUIPMENT	PB	PULL BOX
EUH	CABINET UNIT HEATER	PC	PERSONAL COMPUTER
EWC	ELECTRIC WATER COOLER	PH	PHASE
FA	FIRE ALARM	PNL	PANEL
FAAP	FIRE ALARM ANNUCATOR PANEL	PVC	POLYVINYL CHLORIDE
FACP	FIRE ALARM CONTROL PANEL	RCPT	RECEPTACLE
FLR	FULL LOAD AMPS	RECEPT	RECEPTACLE
FLUOR	FLUORESCENT	RLA	RUN LOAD AMP
FPVAV	FAN POWER VAV BOX	RM	ROOM
FSS	FUSED SAFETY SWITCH	RSC	RIGID STEEL CONDUIT
G.GND.GRD.G	GROUND CONDUCTOR	SD	SMOKE DETECTOR
GAP	GRAPHIC ANNUCATOR PANEL	SW	SWITCH
GC	GENERAL CONTRACTOR	SWB	SWITCHBOARD
GEC	GROUND ELECTRODE CONDUCTOR	SYS FURN	SYSTEM FURNITURE
GI	GROUND FAULT INTERRUPTER	TEL	TELEPHONE
HP	HORSE POWER	TF	TRANSFER FAN WITH LOCAL TOGGLE SWITCH
HWH	HOT WATER HEATER	TYP	TYPICAL
HZ	HERTZ	UL	UNDERWRITER LABORATORIES
IG	ISOLATED GROUND	UON	UNLESS OTHERWISE NOTED
JJB	JUNCTION BOX	V	VOLT
KVA	KILO-VOLT AMPERE	W	WIRE
KW	KILO-WATT	W	WITH
LRA	LOCKED ROTOR AMPS	W/	WATT
LTG	LIGHT	WATT, #W	WATT
MAX	MAXIMUM	WH	WATER HEATER
MC	METAL CLAD CABLE	WP	WATER PROOF
MCA	MINIMUM CIRCUIT AMPS	WSA	WIRE SIZE AMPS
MCB	MAIN CIRCUIT BREAKER	WT	WIRING TROUGH
MCC	MOTOR CONTROL CENTER	XFMR	TRANSFORMER
MDP	MAIN DISTRIBUTION PANEL		
MH	MOUNTING HEIGHT		

GENERAL NOTES

- ALL WORK IS NEW UNLESS OTHERWISE NOTED.
- SHADED REGIONS ON THE FLOOR PLANS ARE OUTSIDE THE AREA OF WORK UNLESS OTHERWISE NOTED.

ELECTRICAL LEGEND

DESIGNATION	DESCRIPTION	MTG HGT TO CENTER LINE AFF. (UON)
	FLUORESCENT LIGHTING FIXTURE - "UPPER CASE" INDICATES FIXTURE TYPE "LOWER CASE" (IF SHOWN) INDICATES SWITCH CONTROL	-
	FLUORESCENT LIGHTING FIXTURE - "UPPER CASE" INDICATES FIXTURE TYPE "LOWER CASE" (IF SHOWN) INDICATES SWITCH CONTROL	-
	FLUORESCENT EMERGENCY LIGHTING FIXTURE - "UPPER CASE" INDICATES FIXTURE TYPE "LOWER CASE" (IF SHOWN) INDICATES SWITCH CONTROL	-
	LED EMERGENCY EXTERIOR WALLPACK LIGHTING FIXTURE - "UPPER CASE" INDICATES FIXTURE TYPE	9'-0"
	FLUORESCENT LIGHTING FIXTURE - "UPPER CASE" INDICATES FIXTURE TYPE "LOWER CASE" (IF SHOWN) INDICATES SWITCH CONTROL	-
	CEILING MOUNTED EXIT LIGHT SINGLE FACE/DOUBLE FACE WITH ARROWS AS INDICATED	-
	SINGLE POLE SWITCH	-
	DUPLEX RECEPTACLE - NEMA 5-20R	18"
	DUPLEX RECEPTACLE - NEMA 5-20R WITH INTEGRAL GROUND FAULT CIRCUIT INTERRUPTER	18"
	DOUBLE DUPLEX RECEPTACLE - NEMA 5-20R	18"
	CEILING MOUNTED JUNCTION BOX	-
	WALL MOUNTED JUNCTION BOX	-
	CARD READER - PROVIDE 4" SQUARE BOX AND STUB OUT 3/4" EC 6" INTO CEILING SPACE. PROVIDE MATCHING OUTLET FOR PUSH EXIT BUTTON AS REQUIRED.	4'-0"
	TRANSFORMER	-
	GROUND	-
	PANELBOARD 120/208V SYSTEM	6'-0" TO TOP
	PANELBOARD 277/480V SYSTEM	6'-0" TO TOP
	MOTOR CONNECTION	-
	NON-FUSED SAFETY DISCONNECT SWITCH - NUMERAL DENOTES SWITCH SIZE - 3 POLE UON	5'-0" TO TOP
	FUSED SAFETY DISCONNECT SWITCH - UPPER NUMERAL DENOTES SWITCH SIZE, LOWER NUMERAL DENOTES FUSE SIZE - 3 POLE UON	5'-0" TO TOP
	HOMERUN TO PANELBOARD - NO. OF ARROWHEADS INDICATE NO. OF CIRCUITS. NUMERALS & LETTERS ADJACENT TO ARROWHEADS INDICATE ASSIGNED PANEL & CIRCUIT NO.'S	-
	TICK MARKS IN HOMERUN OR BRANCH CIRCUITRY, UNLESS OTHERWISE SCHEDULED, INDICATE THE QUANTITY (WHERE MORE THAN TWO) OF CURRENT CARRYING CONDUCTORS. NUMERAL ADJACENT TO TICKS INDICATES WIRE SIZE IF OTHER THAN #12. ALL WRING SHALL ALSO CONTAIN AN INSULATED EQUIPMENT GROUND CONDUCTOR SIZE PER NEC. (NOT SHOWN)	-
	GENERAL CIRCUITRY	-
	CIRCUITRY INSTALLED CONCEALED IN OR BELOW FLOOR SLAB	-
	DENOTES PLAN SPECIFIC NOTE	-
	METER	-
	EXISTING TO REMAIN - CONTINUE IN SERVICE	-
	REMOVE EXISTING AND RELOCATE	-
	RELOCATED EQUIPMENT	-
	REMOVE WITH ALL CIRCUITRY THERETO	-

DRAWING LIST

1-E-001	COVER SHEET - ELECTRICAL
1-E-101	SITE PLAN - ELECTRICAL
1-E-102	FOURTH FLOOR DEMOLITION & NEW WORK - ELECTRICAL
1-E-103	FIFTH FLOOR DEMOLITION & NEW WORK - ELECTRICAL
1-E-104	FOURTH & FIFTH FLOOR NEW WORK - FIRE ALARM
1-E-701	DETAILS & SCHEDULES

GPI
Greenman-Pedersen, Inc.

Engineering and Construction Services
8001 Braddock Road, Suite 200, Springfield, VA 22151
703-978-0100 www.gpinet.com
Project #: 20193220.00

PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1

ARLINGTON, VA
601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204.

DRAWING COVER SHEET - ELECTRICAL

SHEET

1-E-001



GENERAL NOTES - ELECTRICAL

1. REFER TO ELECTRICAL COVER SHEET FOR SPECIFICATIONS, GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS.

KEYED NOTES - ELECTRICAL

1. TO BE REMOVED FROM SERVICE: DOMINION ENERGY UTILITY TRANSFORMER FEEDING THE VIRGINIA HOSPITAL CENTER (BLDG 601). OWNER SHALL APPLY FOR AND OBTAIN UTILITY DISCONNECT LETTERS.

2. EXISTING TO REMAIN: DOMINION ENERGY UTILITY TRANSFORMER FEEDING THE DOCTOR'S OFFICE BUILDING (BLDG 611).

3. DIESEL GENERATOR FEEDING THE VIRGINIA HOSPITAL CENTER (BLDG 601). REMOVE FROM SERVICE. REPROGRAM FIRE ALARM SYSTEM TO PREVENT SUPERVISORY AND TROUBLE SIGNALS FROM GENERATOR DISCONNECTION.


THE WORK INDICATED ON THIS DRAWING IS NOT IN CONTRACT AND IS INCLUDED FOR INFORMATION ONLY.

2 STORY BRICK AND BLOCK HOSPITAL BUILDING
601 SOUTH CARLIN SPRINGS ROAD

PARCEL A
RPC 21028097
VIRGINIA HOSPITAL CENTER
ARLINGTON HEALTH SYSTEM

2 STORY BRICK AND BLOCK HOSPITAL BUILDING
601 SOUTH CARLIN SPRINGS ROAD

MULTI-STORY CONCRETE PARKING STRUCTURE FOR



CD Revisions	DES
GTH	BY
5/15/2020	MARK DATE
1	REVISIONS

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	GTH	GTH	GTH

RRMM ARCHITECTS, PC
2900 South Quincy Street, Suite 710
Arlington, Virginia 22206
(703)998-0101

PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 2
ARLINGTON, VA
601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
DRAWING SITE PLAN - ELECTRICAL


SHEET
1-E-101

Electrical Site Plan
SCALE: 1" = 24'





6/16/2021 10:54:58 AM C:\Users\ghagem\Documents\201932200_v20 - Electrical_gghagem\XAT3.rvt

6/16/2021 10:55:00 AM C:\Users\ghagem\Documents\201932200_v20 - Electrical - ghagem\HAT3.rvt



1 FOURTH FLOOR - DEMOLITION - ELECTRICAL
 E-102 SCALE: 1/8" = 1'-0"



2 FOURTH FLOOR - NEW WORK - ELECTRICAL
 E-102 SCALE: 1/8" = 1'-0"

GENERAL NOTES - DEMOLITION

- REFER TO ELECTRICAL COVER SHEET FOR SPECIFICATIONS, GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS. REFER TO FIRE ALARM NEW WORK PLAN FOR FIRE ALARM SYMBOLS.
- REFER TO MECHANICAL AND PLUMBING DRAWINGS FOR EXACT LOCATIONS FOR ALL RELOCATED/DEMOLISHED EQUIPMENT.
- PROVIDE COMPLETE ELECTRICAL DEMOLITION IN THE AREA OF WORK UNLESS OTHERWISE NOTED SO AS TO ELECTRICALLY ISOLATE EXISTING TO REMAIN BUILDING PORTIONS.
- PROTECT EXISTING EMERGENCY LIGHTS, EXIT SIGNS AND FIRE ALARM DEVICES EXCEPT WHERE DEMOLITION IS NEEDED.
- DEMOLITION WORK INDICATED IS DIAGRAMMATIC AND NOT SHOWN INCLUSIVE. DEMOLITION DRAWING IS INTENDED TO DEMONSTRATE MAJOR ITEMS ONLY. CONTRACTOR IS REQUIRED TO PERFORM SELECTIVE DEMOLITION AS NEEDED TO ACCOMPLISH THE PROJECT INTENT. IF DEMOLITION WORK IS UNCLEAR FOR ANY ITEM, THE CONTRACTOR SHALL BRING IT TO THE ATTENTION OF THE ARCHITECT/ENGINEER FOR RESOLUTION BEFORE PROCEEDING.
- REMOVE ALL ABANDONED WIRING BACK TO THE PANEL/SOURCE AS APPLICABLE.
- COORDINATE WITH OWNERS/BUILDING ENGINEERS PRIOR TO SCHEDULING ANY SHUTDOWN REQUIRED DURING CONSTRUCTION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) LIGHTING FIXTURES AND ASSOCIATED CONTROLS IN AREA OF WORK UNLESS OTHERWISE NOTED. REMOVE WIRING FROM FIXTURE/DEVICE LOCATION BACK TO NEXT ACTIVE OUTLET (OR BACK TO SOURCE PANELBOARD IF CIRCUIT IS NO LONGER ACTIVE. AT PANELBOARD, TURN CIRCUIT BREAKER(S) TO THE OFF POSITION AND LABEL AS "SPARE". RESTORE CONNECTION TO EXISTING FIXTURES/DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) EMERGENCY LIGHTING FIXTURES AND EXIT SIGNS IN AREA OF WORK UNLESS OTHERWISE NOTED. SAFELY TERMINATE EMERGENCY LIGHTING CIRCUITRY ABOVE CEILING FOR REUSE. RESTORE CONNECTION TO EXISTING EMERGENCY FIXTURES AND EXIT SIGNS FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) FIRE ALARM DEVICES IN AREA OF WORK UNLESS OTHERWISE NOTED. SAFELY TERMINATE FA CIRCUITRY ABOVE CEILING FOR REUSE. COORDINATE REMOVAL OF FIRE ALARM WIRING WITH BUILDING ENGINEER BEFORE PROCEEDING WITH DEMOLITION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) RECEPTACLES, POKE-THRU DEVICES, SYSTEMS FURNITURE POWER/DATA FEEDS, AND CABLE TRAY SYSTEMS IN AREA OF WORK UNLESS OTHERWISE NOTED. REMOVE CIRCUITRY FROM DEVICE LOCATION BACK TO NEXT ACTIVE OUTLET (OR BACK TO SOURCE PANELBOARD IF CIRCUIT IS NO LONGER ACTIVE. AT PANELBOARD, TURN CIRCUIT BREAKER(S) TO THE OFF POSITION AND LABEL AS "SPARE". RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) TELEPHONE/DATA OUTLETS AND SECURITY DEVICES IN AREA OF WORK UNLESS OTHERWISE NOTED.

KEYED NOTES - DEMOLITION


- REMOVAL: DISCONNECT POWER AND REMOVE ASSOCIATED SAFETY DISCONNECT FROM MECHANICAL AND PLUMBING EQUIPMENT AS SHOWN ON PLAN, UNLESS OTHERWISE NOTED. REMOVE EXISTING WIRING FROM UNIT LOCATIONS BACK TO SOURCE PANELBOARD. TURN CIRCUIT BREAKER(S) TO THE OFF POSITION, AND LABEL BREAKER(S) AS "SPARE". RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- EXISTING TO REMAIN CONCRETE ENCASED 16-WAY DUCTBANK BENEATH MRI BUILDING AND STAIRWELL.
- UNDERGROUND ELECTRICAL PRIMARY CONDUIT AND CONDUCTORS SERVING THE ADJACENT BLDG 601. COORDINATE ELECTRICAL UTILITY DISCONNECTION FOR BLDG 601 PRIOR TO ANY DEMOLITION WORK.
- DISCONNECT POWER FOR LINE CONDITIONER CIRCUIT AT THE MAIN SWITCHBOARD AND LABEL BREAKER AS "SPARE". REMOVE ASSOCIATED SAFETY DISCONNECT AND CIRCUITRY FOR THE LINE CONDITIONER BACK TO THE TRANSFORMER SECONDARY DISCONNECT IN THE MAIN ELECTRICAL ROOM ON THE THIRD FLOOR.
- DISCONNECT POWER FOR EXISTING PANEL 'X' AT THE MAIN SWITCHBOARD LABEL AS BREAKER AS "SPARE". REMOVE PANEL AND REMOVE CIRCUITRY BACK TO THE METER IN THE MAIN ELECTRICAL ROOM ON THE THIRD FLOOR.
- DISCONNECT POWER AND REMOVE ASSOCIATED SAFETY DISCONNECT FROM EXISTING WATER SOURCE HEAT PUMP (208V/1PH, 4.8 FLA). SAFELY TERMINATE CIRCUITRY ABOVE THE FIFTH FLOOR CEILING WITHIN BLDG 611 FOR REUSE. RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- FIRE ALARM DEVICES IN THE STAIRWELL ARE CURRENTLY FED FROM THE BLDG 601 FIRE ALARM SYSTEM AND SHALL BE PREPARED FOR RECONNECTION TO THE BLDG 611 FIRE ALARM SYSTEM, UNLESS OTHERWISE NOTED. DISCONNECT ALL FIRE ALARM DEVICES AND REMOVE CIRCUITRY BACK TO NEXT ACTIVE DEVICE IN BLDG 601.

GENERAL NOTES - NEW WORK

- REFER TO ELECTRICAL COVER SHEET FOR SPECIFICATIONS, GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS.
- REFER TO ELECTRICAL DETAIL SHEET FOR LIGHTING FIXTURE SCHEDULE AND ADDITIONAL INFORMATION.
- COORDINATE ALL HVAC EQUIPMENT CONNECTION REQUIREMENTS WITH THE MANUFACTURER PRIOR TO ORDERING AND ROUGH-IN.


KEYED NOTES - NEW WORK

- CONNECT NEW OR RELOCATED EMERGENCY LIGHTS & EXIT SIGNS TO EXISTING 277V EMERGENCY LIGHTING CIRCUIT PREVIOUSLY FEEDING THIS AREA, LOCATED IN (E) EMERGENCY PANEL "E". PANEL DIRECTORY DOES NOT CHANGE UNDER THIS WORK. CIRCUIT SHALL NOT EXCEED 350VA.
- EXISTING TO REMAIN CONCRETE ENCASED 16-WAY DUCTBANK BENEATH MRI BUILDING AND STAIRWELL.
- SPLICE AND EXTEND EXISTING WATER SOURCE HEAT PUMP CIRCUITRY TO NEW WATER SOURCE HEAT PUMP (208V/1PH, 4.1 FLA). PROVIDE NEMA RECEPTACLE IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS. THE ELECTRICAL CONTRACTOR IS RESPONSIBLE FOR INSTALLING THE ELECTRICAL ACCESSORIES FURNISHED WITH UNIT INSIDE THE UNIT CABINET. COORDINATE INSTALLATION WITH THE MECHANICAL CONTRACTOR AND THE MANUFACTURER'S INSTRUCTIONS PRIOR TO PROCEEDING WITH WORK.



DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	GTH	GTH	GTH


CD Revisions	BY	DES
5.15.2020	GTH	DES
1	MARK	DATE
		REVISIONS



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204.
 DRAWING FOURTH FLOOR DEMOLITION & NEW WORK - ELECTRICAL

SHEET
1-E-102

6/18/2021 10:55:03 AM C:\Users\ghagem\Documents\201932200_v20 - Electrical_ghagem\HAT13.rvt



1 FIFTH FLOOR - DEMOLITION - ELECTRICAL
 E-107 SCALE: 1/8" = 1'-0"

2 FIFTH FLOOR - NEW WORK - ELECTRICAL
 E-107 SCALE: 1/8" = 1'-0"

GENERAL NOTES - DEMOLITION

- REFER TO ELECTRICAL COVER SHEET FOR SPECIFICATIONS, GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS. REFER TO FIRE ALARM NEW WORK PLAN FOR FIRE ALARM SYMBOLS.
- REFER TO MECHANICAL AND PLUMBING DRAWINGS FOR EXACT LOCATIONS FOR ALL RELOCATED/DEMOLISHED EQUIPMENT.
- PROVIDE COMPLETE ELECTRICAL DEMOLITION IN THE AREA OF WORK UNLESS OTHERWISE NOTED SO AS TO ELECTRICALLY ISOLATE EXISTING TO REMAIN BUILDING PORTIONS.
- PROTECT EXISTING EMERGENCY LIGHTS, EXIT SIGNS AND FIRE ALARM DEVICES EXCEPT WHERE DEMOLITION IS NEEDED.
- DEMOLITION WORK INDICATED IS DIAGRAMATIC AND NOT SHOWN INCLUSIVE. DEMOLITION DRAWING IS INTENDED TO DEMONSTRATE MAJOR ITEMS ONLY. CONTRACTOR IS REQUIRED TO PERFORM SELECTIVE DEMOLITION AS NEEDED TO ACCOMPLISH THE PROJECT INTENT. IF DEMOLITION WORK IS UNCLEAR FOR ANY ITEM, THE CONTRACTOR SHALL BRING IT TO THE ATTENTION OF THE ARCHITECT/ENGINEER FOR RESOLUTION BEFORE PROCEEDING.
- REMOVE ALL ABANDONED WIRING BACK TO THE PANEL/SOURCE AS APPLICABLE.
- COORDINATE WITH OWNERS/BUILDING ENGINEERS PRIOR TO SCHEDULING ANY SHUTDOWN REQUIRED DURING CONSTRUCTION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) LIGHTING FIXTURES AND ASSOCIATED CONTROLS IN AREA OF WORK UNLESS OTHERWISE NOTED. REMOVE WIRING FROM FIXTURE/DEVICE LOCATION BACK TO NEXT ACTIVE OUTLET (OR BACK TO SOURCE PANELBOARD IF CIRCUIT IS NO LONGER ACTIVE. AT PANELBOARD, TURN CIRCUIT BREAKER(S) TO THE OFF POSITION AND LABEL AS "SPARE". RESTORE CONNECTION TO EXISTING FIXTURES/DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) EMERGENCY LIGHTING FIXTURES AND EXIT SIGNS IN AREA OF WORK UNLESS OTHERWISE NOTED. SAFELY TERMINATE EMERGENCY LIGHTING CIRCUITRY ABOVE CEILING FOR REUSE. RESTORE CONNECTION TO EXISTING EMERGENCY FIXTURES AND EXIT SIGNS FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) FIRE ALARM DEVICES IN AREA OF WORK UNLESS OTHERWISE NOTED. SAFELY TERMINATE FA CIRCUITRY ABOVE CEILING FOR REUSE. COORDINATE REMOVAL OF FIRE ALARM WIRING WITH BUILDING ENGINEER BEFORE PROCEEDING WITH DEMOLITION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) RECEPTACLES, POKE-THRU DEVICES, SYSTEMS FURNITURE POWER/DATA FEEDS, AND CABLE TRAY SYSTEMS IN AREA OF WORK UNLESS OTHERWISE NOTED. REMOVE CIRCUITRY FROM DEVICE LOCATION BACK TO NEXT ACTIVE OUTLET (OR BACK TO SOURCE PANELBOARD IF CIRCUIT IS NO LONGER ACTIVE. AT PANELBOARD, TURN CIRCUIT BREAKER(S) TO THE OFF POSITION AND LABEL AS "SPARE". RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) TELEPHONE/DATA OUTLETS AND SECURITY DEVICES IN AREA OF WORK UNLESS OTHERWISE NOTED.

KEYED NOTES - DEMOLITION


- REMOVAL. DISCONNECT POWER AND REMOVE ASSOCIATED SAFETY DISCONNECT FROM MECHANICAL AND PLUMBING EQUIPMENT AS SHOWN ON PLAN, UNLESS OTHERWISE NOTED. REMOVE EXISTING WIRING FROM UNIT LOCATIONS BACK TO SOURCE PANELBOARD, TURN CIRCUIT BREAKER(S) TO THE OFF POSITION, AND LABEL BREAKER(S) AS "SPARE". RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- NOT USED.
- DISCONNECT POWER AND REMOVE ASSOCIATED SAFETY DISCONNECT FROM EXISTING WATER SOURCE HEAT PUMP (208V/1PH, 4.3 FLA). SAFELY TERMINATE CIRCUITRY ABOVE THE FIFTH FLOOR CEILING WITHIN BLDG 611 FOR REUSE. RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- FIRE ALARM DEVICES IN THE STAIRWELL ARE CURRENTLY FED FROM THE BLDG 601 FIRE ALARM SYSTEM AND SHALL BE PREPARED FOR RECONNECTION TO THE BLDG 611 FIRE ALARM SYSTEM, UNLESS OTHERWISE NOTED. DISCONNECT ALL FIRE ALARM DEVICES AND REMOVE CIRCUITRY BACK TO NEXT ACTIVE DEVICE IN BLDG 601.

GENERAL NOTES - NEW WORK

- REFER TO ELECTRICAL COVER SHEET FOR SPECIFICATIONS, GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS.
- REFER TO ELECTRICAL DETAIL SHEET FOR LIGHTING FIXTURE AND OCCUPANCY SENSOR SCHEDULES AND ADDITIONAL INFORMATION.
- COORDINATE ALL HVAC EQUIPMENT CONNECTION REQUIREMENTS WITH THE MANUFACTURER PRIOR TO ORDERING AND ROUGH-IN.

KEYED NOTES - NEW WORK

- CONNECT NEW OR RELOCATED EMERGENCY LIGHTS & EXIT SIGNS TO EXISTING 277V EMERGENCY LIGHTING CIRCUIT PREVIOUSLY FEEDING THIS AREA. LOCATED IN (E) EMERGENCY PANEL "E" - PANEL DIRECTORY DOES NOT CHANGE UNDER THIS WORK. CIRCUIT SHALL NOT EXCEED 3500VA.
- NOT USED.
- SPLICE AND EXTEND EXISTING WATER SOURCE HEAT PUMP CIRCUITRY TO NEW WATER SOURCE HEAT PUMP (208V/1PH, 4.3 FLA). PROVIDE NEMA RECEPTACLE IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS. THE ELECTRICAL CONTRACTOR IS RESPONSIBLE FOR INSTALLING THE ELECTRICAL ACCESSORIES FURNISHED WITH UNIT INSIDE THE UNIT CABINET. COORDINATE INSTALLATION WITH THE MECHANICAL CONTRACTOR AND THE MANUFACTURER'S INSTRUCTIONS PRIOR TO PROCEEDING WITH WORK.




CD Revisions	DATE	PROJECT	DESIGNED	DRAWN	CHECKED	MARK	DATE	BY	DES
1	06.18.2021	13356.28	GTH	GTH	GTH				


DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	GTH	GTH	GTH




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 DRAWING FIFTH FLOOR DEMOLITION & NEW WORK - ELECTRICAL

SHEET
1-E-103





1 FOURTH FLOOR - NEW WORK - FIRE ALARM
 1-E-104 SCALE: 1/8" = 1'-0"



2 FIFTH FLOOR - NEW WORK - FIRE ALARM
 1-E-104 SCALE: 1/8" = 1'-0"

GENERAL NOTES - FIRE ALARM

- REFER TO ELECTRICAL COVER SHEET FOR SPECIFICATIONS, GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL FIRE ALARM WORK INCLUDING BUT NOT LIMITED TO: ADDITION OF STROBES, AUDIBLE DEVICES, CIRCUITRY EXTENSION, AND SYSTEM PROGRAM MODIFICATIONS. FURNISH AND INSTALL ALL NECESSARY CONTROL EQUIPMENT INCLUDING EXTENDER PANEL, INITIATING DEVICES AND NOTIFICATION APPLIANCES REQUIRED FOR THE EXPANSION OF THE EXISTING FIRE ALARM SYSTEMS DETAILED ON THE CONTRACT DRAWINGS AND AS SPECIFIED HEREIN. THE EQUIPMENT FURNISHED SHALL BE COMPATIBLE WITH THE EXISTING EQUIPMENT. THE CONTRACTOR SHALL SURVEY THE EXISTING CONTROL PANEL TO DETERMINE ANY NECESSARY MODIFICATIONS AND/OR ADDITIONS NECESSARY TO INCORPORATE THE DEVICES ADDED UNDER THIS CONTRACT. PROVIDE SYNCHRONIZING OF STROBES FOR ALL EXISTING, NEW & RELOCATED DEVICES WITHIN THE AREA OF WORK. SYNCHRONIZATION OF STROBES SHALL BE PER NFPA72 REQUIREMENTS. IN THE EVENT OF A BUILDING EVACUATION ALARM, PROVIDE CONTROL WIRING FROM THE BUILDING FACP TO ALL SECURED DOORS IN THE PATH OF EGRESS TO RELEASE THE LOCK. COORDINATE WORK WITH THE SECURITY CONTRACTOR. PROVIDE REQUIRED DRY CONTACTS IN BUILDING FACP. SHOP DRAWINGS SHALL BE PREPARED AND SUBMITTED TO THE LOCAL AUTHORITY AND SHALL INCLUDE, BUT NOT LIMITED TO EQUIPMENT CUT SHEET, SEQUENCE OF OPERATION, BATTERY CALCULATIONS, CIRCUIT CAPACITY CALCULATIONS, WIRING DIAGRAMS, RISER DIAGRAMS AND FLOOR PLANS.
- PROVIDE ALL VISUAL AND AUDIBLE DEVICES (SPEAKER OR HORNS) IN WHITE COLOR W/ RED LETTERING UNLESS OTHERWISE NOTED. INSTALL ALL CEILING MOUNTED FIRE ALARM DEVICES IN THE CENTER OF CEILING TILE.
- PROTECT EXISTING BUILDING SMOKE/FIRE DETECTION SYSTEM AS REQUIRED TO PREVENT FALSE ALARMS DUE TO CONSTRUCTIONS.
- ALL FIRE ALARM EQUIPMENT SHALL BE REMAIN OPERATIONAL AND IN PLACE AS THE BUILD OUT OCCURS.
- IF THE CONSTRUCTION REQUIRES INTERRUPTION OF THE BUILDING FIRE ALARM, OBTAIN WRITTEN 7-DAY NOTICE FROM THE BUILDING OWNER PRIOR TO THE INTERRUPTION. FOLLOW ALL RULES AND REGULATIONS PROVIDED BY THE BUILDING OWNER AND ALL CODE REQUIREMENTS FOR A FIRE ALARM INTERRUPTION.
- FINAL CONNECTION TO BUILDING FIRE ALARM SYSTEM SHALL BE PERFORMED BY BASE BUILDING FIRE ALARM CONTRACTOR BUT SHALL BE RESPONSIBILITY OF THE ELECTRICAL CONTRACTOR.
- THE SYSTEM SHALL COMPLY WITH NFPA 72.

KEYED NOTES - FIRE ALARM

- RECONNECT EXISTING FIRE ALARM DEVICES IN STAIRWELL TO BLDG 611 FIRE ALARM SYSTEM. VERIFY OPERATIONAL STATUS OF DEVICES AND REPLACE DEFECTIVE DEVICES. PROVIDE UPDATED GRAPHIC ANNUNCIATOR PANEL AS REQUIRED.
- NOT USED.
- CARD READERS/MAG LOCKS: PROVIDE CONTROL WIRING FROM SECURITY SYSTEM TO CONNECT TO BASE BUILDING FIRE ALARM SYSTEM FOR RELEASE OF DOORS UPON SIGNAL FROM BASE BUILDING FIRE ALARM SYSTEM.


FIRE ALARM SYMBOLS

DESIGNATION	DESCRIPTION	MTG HGT TO AFF CENTERLINE (UGN)
15-1	FIRE ALARM VISUAL ALARM SIGNAL MOUNTED AT LOWER OF 80" OR 6" BELOW CEILING - NUMBER ADJACENT TO SYMBOL DENOTES MINIMUM REQUIRED LIGHT OUTPUT, CANDELA	4'-0"
15-1	FIRE ALARM COMBINATION AUDIBLE/VISUAL ALARM SIGNAL - MOUNTED AT LOWER OF 80" OR 6" BELOW CEILING. NUMBER ADJACENT TO SYMBOL DENOTES MINIMUM REQUIRED LIGHT OUTPUT, CANDELA	
15-2	CEILING FIRE ALARM VISUAL ALARM SIGNAL. NUMBER ADJACENT TO SYMBOL DENOTES MINIMUM REQUIRED LIGHT OUTPUT, CANDELA	
15-2	CEILING FIRE ALARM COMBINATION AUDIBLE/VISUAL ALARM SIGNAL. NUMBER ADJACENT TO SYMBOL DENOTES MINIMUM REQUIRED LIGHT OUTPUT, CANDELA	
F	FIRE ALARM MANUAL STATION	
(#)	DENOTES PLAN SPECIFIC KEYED NOTE	
(E)	EXISTING TO REMAIN - CONTINUE IN SERVICE	
(R)	EXISTING TO BE REMOVED AND RELOCATED	
(RE)	RELOCATED EQUIPMENT	
P	CEILING MOUNTED PHOTOELECTRIC SMOKE DETECTOR - SUBSCRIPT D DENOTES DUCT DETECTOR	




DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	GTH	GTH	GTH
5.15.2020				
		MARK	DATE	REVISIONS
		GTH	BY	DES

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	GTH	GTH	GTH



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204.
 DRAWING FOURTH & FIFTH FLOOR NEW WORK - FIRE ALARM

SHEET
1-E-104



6/18/2021 10:55:06 AM C:\Users\ghagen\Documents\201932200_v20 - Electrical_gghagen\HAT3.rvt

ELECTRICAL SPECIFICATIONS

- A. GENERAL
1. REFER TO BOOK SPECIFICATIONS FOR ADDITIONAL REQUIREMENTS AND SCOPE.
2. THE CONTRACTOR SHALL COMPLY WITH ALL THE LAWS, ORDINANCES, RULES AND REGULATIONS OF ALL LOCAL AND STATE GOVERNMENTAL AUTHORITIES...
3. THE CONTRACTOR SHALL SECURE AND PAY FOR ALL PERMITS AND INSPECTIONS REQUIRED BY ANY OF THE FOREGOING AUTHORITIES...
4. THE SITE, LOCATION AND ROUTING OF SYSTEMS INDICATED TO HAVE NEW CONNECTIONS MADE TO THEM ARE SHOWN AS ACCURATELY AS FIELD CONDITIONS WOULD PERMIT...
5. THE CONTRACTOR SHALL REMOVE ALL EQUIPMENT NOT INDICATED TO BE REUSED TO A DESIGNATED LOCATION AT THE PROJECT SITE...
6. THE CONTRACTOR SHALL INSTALL AND CONNECT ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH THE BEST ENGINEERING PRACTICE AND, UNLESS OTHERWISE SHOWN OR SPECIFIED, FOLLOW THE MANUFACTURER'S INSTRUCTIONS AND RECOMMENDATIONS...
7. DRAWINGS SHALL BE CONSIDERED DIAGRAMMATIC AND FOR BIDDING PURPOSES ONLY...
8. COORDINATE WITH ALL TRADES TO AVOID INTERFERENCE AMONG MECHANICAL, ELECTRICAL, ARCHITECTURAL AND STRUCTURAL ITEMS...
9. THE CONTRACTOR SHALL TEST ALL EQUIPMENT INSTALLED UNDER THIS CONTRACT AND DEMONSTRATE TO THE OWNER ITS PROPER OPERATIONS...
10. ALL EQUIPMENT AND WORKMANSHIP SHALL BE GUARANTEED IN FULL FROM ALL DEFECTS FOR ONE (1) YEAR FROM THE DATE OF FINAL ACCEPTANCE...
11. ALL EQUIPMENT INSTALLED SHALL BE NEW AND SHALL CONFORM IN ALL RESPECTS TO THE LATEST APPROVED STANDARDS OF IEEE, ANSI, NEMA AND UNDERWRITERS LABORATORIES, INC., UNLESS INDICATED OTHERWISE...
12. SHOP DRAWINGS AND PRODUCT DATA, SUBMIT SHOP DRAWINGS AND PRODUCT DATA FOR ALL NEW MATERIAL AND EQUIPMENT PROVIDED UNDER THIS WORK...
13. REPAIR OF EXISTING WORK: ALL WORK SHALL BE CAREFULLY LAID OUT IN ADVANCED, AND WHERE CUTTING, CHANNELING, CHASING, OR DRILLING OF FLOORS, WALL, PARTITIONS, CEILINGS, OR OTHER SURFACES IS NECESSARY FOR THE PROPER INSTALLATION, SUPPORT, OR ANCHORAGE OF THE CONDUIT, RACEWAYS OR OTHER ELECTRICAL WORK...
14. THE CONTRACTOR SHALL REPAIR ALL WALL, CEILING, FLOOR, OR ROOF OPENINGS WHICH ARE CREATED BY DEMOLITION OR PENETRATION...
15. DEFINITIONS: "PROVIDE" UNDER THIS CONTRACT IS DEFINED AS FURNISH AND INSTALL "CONCEALED" UNDER THIS CONTRACT IS DEFINED AS WITHIN ARCHITECTURAL WALLS AND ABOVE CEILINGS "EXPOSED" UNDER THIS CONTRACT IS DEFINED AS VISIBLE TO VIEW...
16. UPON COMPLETION OF THE WORK, THE CONTRACTOR SHALL THOROUGHLY CLEAN THE CONTRACT AREA AND ALL OTHER AREAS USED FOR STORAGE, STAGING, ETC.
17. THE CONTRACTOR SHALL NOTIFY THE ARCHITECT/ENGINEER/OWNER WHEN THE PROJECT IS APPROXIMATELY 75% COMPLETED IN ORDER TO SCHEDULE A PRE-FINAL REVIEW OF CONSTRUCTION...
18. THE CONTRACTOR SHALL PREPARE A COMPREHENSIVE METHOD OF PROCEDURE AND SUBMIT IT TO THE OWNER WITH SHOP DRAWINGS FOR REVIEW...
19. PROVIDE TEMPORARY SERVICE FOR LIGHTING AND POWER EQUIPMENT (DRILLS, SAW, ETC.). VERIFY TEMPORARY REQUIREMENTS WITH GENERAL CONTRACTOR...
20. PROTECT ADJACENT MATERIALS INDICATED TO REMAIN, INSTALL AND MAINTAIN DUST AND NOISE BARRIERS TO KEEP DIRT, DUST, AND NOISE FROM BEING TRANSMITTED TO ADJACENT AREAS...
21. FINAL TESTING: AT THE TIME OF FINAL INSPECTION AND TESTS, ALL CONNECTIONS AT PANELBOARDS, DEVICES AND EQUIPMENT AND ALL SPLICES MUST BE COMPLETED...
22. CONTRACTOR SHALL PROVIDE ACCESS PANEL FOR JUNCTION BOXES, DISCONNECT SWITCHES, OR OTHER DEVICES WHICH REQUIRE SERVICE ACCESS PER NEC.
B. LIGHTING
1. COORDINATE RECESSED LIGHTING FIXTURES WITH MECHANICAL EQUIPMENT AND ARCHITECTURAL CEILING PLAN...
2. PROVIDE FINISHING FRAMES FOR ALL RECESSED LIGHTING FIXTURES...
3. IN LOCATIONS WHERE NEW DUCTWORK OR CEILING IS INSTALLED UNDER THIS CONTRACT BUT LIGHTING FIXTURES HAVE NOT BEEN REVISED...
4. PROVIDE ALL REQUIRED ACCESSORIES FOR A COMPLETE AND OPERATIONAL INSTALLATION TO SUIT PROJECT CONDITIONS.
5. PROVIDE MEANS OF SUPPORT PER NEC 410.36.
C. EQUIPMENT CONNECTION
1. EXTEND WIRING TO ALL EQUIPMENT REQUIRING ELECTRICAL CONNECTIONS AND MAKE FINAL AND COMPLETE CONNECTIONS TO ALL EQUIPMENT...
D. DEMOLITION
1. PROVIDE DEMOLITION AS INDICATED ON DEMOLITION PLANS...
2. LOCATE, IDENTIFY AND PROTECT ELECTRICAL SERVICES PASSING THROUGH DEMOLITION AREA AND SERVING OTHER AREAS OUTSIDE THE DEMOLITION LIMITS...

SCHEDULE

THE DEMOLITION WILL OCCUR IN TWO PHASES:
PHASE 1
THE FIRST PHASE WILL INCLUDE THE ISOLATION OF THE MULTI-STORY PHYSICIAN'S OFFICE BUILDING FROM THE REST OF THE STRUCTURE...
ELECTRICAL:
IN ORDER TO ELECTRICALLY ISOLATE AND MAINTAIN SYSTEM OPERATIONS OF THE MULTI-STORY PHYSICIAN'S OFFICE BUILDING, THE CONTRACTOR SHALL DISCONNECT ALL ELECTRICAL DEVICES, LIGHTING CIRCUITS, AND MECHANICAL EQUIPMENT FEEDERS SERVING IN THE CONNECTOR BUILDING AND MRI BUILDING...
PHASE 2 (REFER TO SEPARATE CONSTRUCTION DOCUMENTS)
THE TEMPORARY ELECTRICAL SERVICES PROVIDED IN PHASE ONE SHALL BE DISCONNECTED...
ABBREVIATIONS
A AMPS
A/C AMPERES INTERRUPTING CAPACITY
ATS AUTOMATIC TRANSFER SWITCH
AWG AMERICAN WIRE GAUGE
BLDG BUILDING
C CONDUIT
CATV CLOSED CIRCUIT TELEVISION
CB CIRCUIT BREAKER
CKT CIRCUIT
CO CARBON MONOXIDE
DED DEDICATED
DISC SW DISCONNECT SWITCH
DP DISTRIBUTION PANEL
DWG DRAWING
EACH EACH
EC EMPTY CONDUIT
EGC EQUIPMENT GROUND CONDUCTOR
EM/NL EMERGENCY/NIGHT LIGHT
EMT ELECTRICAL METALLIC TUBING
ENGR ENGINEER
EPO EMERGENCY POWER OFF
EQUIP EQUIPMENT
EUH CABINET UNIT HEATER
EWC ELECTRIC WATER COOLER
FA FIRE ALARM
FAAP FIRE ALARM ANNUNCIATOR PANEL
FACP FIRE ALARM CONTROL PANEL
FLR FULL LOAD AMPS
FLOR FLORESCENT
FPYAV FAN POWER VAV BOX
FSS FUSED SAFETY SWITCH
G.GND.GRD.G GROUND CONDUCTOR
GAP GRAPHIC ANNUNCIATOR PANEL
GC GENERAL CONTRACTOR
GEC GROUND ELECTRODE CONDUCTOR
SYS FURN SYSTEM FURNITURE
HP HORSE POWER
HWH HOT WATER HEATER
HZ HERTZ
IG ISOLATED GROUND
JJB JUNCTION BOX
KVA KILO-VOLT AMPERE
KW KILO-WATT
LRA LOCKED ROTOR AMPS
LTG LIGHT
MAX MAXIMUM
MC METAL CLAD CABLE
MCA MINIMUM CIRCUIT AMPS
MOB MAIN CIRCUIT BREAKER
MCC MOTOR CONTROL CENTER
MDP MAIN DISTRIBUTION PANEL
MH MOUNTING HEIGHT

ABBREVIATIONS

Table listing abbreviations and their meanings: A (AMPS), A/C (AMPERES INTERRUPTING CAPACITY), ATS (AUTOMATIC TRANSFER SWITCH), AWG (AMERICAN WIRE GAUGE), BLDG (BUILDING), C (CONDUIT), CATV (CLOSED CIRCUIT TELEVISION), CB (CIRCUIT BREAKER), CKT (CIRCUIT), CO (CARBON MONOXIDE), DED (DEDICATED), DISC SW (DISCONNECT SWITCH), DP (DISTRIBUTION PANEL), DWG (DRAWING), EACH (EACH), EC (EMPTY CONDUIT), EGC (EQUIPMENT GROUND CONDUCTOR), EM/NL (EMERGENCY/NIGHT LIGHT), EMT (ELECTRICAL METALLIC TUBING), ENGR (ENGINEER), EPO (EMERGENCY POWER OFF), EQUIP (EQUIPMENT), EUH (CABINET UNIT HEATER), EWC (ELECTRIC WATER COOLER), FA (FIRE ALARM), FAAP (FIRE ALARM ANNUNCIATOR PANEL), FACP (FIRE ALARM CONTROL PANEL), FLR (FULL LOAD AMPS), FLOR (FLORESCENT), FPYAV (FAN POWER VAV BOX), FSS (FUSED SAFETY SWITCH), G.GND.GRD.G (GROUND CONDUCTOR), GAP (GRAPHIC ANNUNCIATOR PANEL), GC (GENERAL CONTRACTOR), GEC (GROUND ELECTRODE CONDUCTOR), SYS FURN (SYSTEM FURNITURE), HP (HORSE POWER), HWH (HOT WATER HEATER), HZ (HERTZ), IG (ISOLATED GROUND), JJB (JUNCTION BOX), KVA (KILO-VOLT AMPERE), KW (KILO-WATT), LRA (LOCKED ROTOR AMPS), LTG (LIGHT), MAX (MAXIMUM), MC (METAL CLAD CABLE), MCA (MINIMUM CIRCUIT AMPS), MOB (MAIN CIRCUIT BREAKER), MCC (MOTOR CONTROL CENTER), MDP (MAIN DISTRIBUTION PANEL), MH (MOUNTING HEIGHT), MIN (MINIMUM), MLO (MAIN LUG ONLY), MOC (MAXIMUM OVERCURRENT PROTECTION), MTS (MANUAL TRANSFER SWITCH), N (NEUTRAL), NEC (NATIONAL ELECTRICAL CODE), NEMA (NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION), NFPA (NATIONAL FIRE PROTECTION ASSOCIATION), NFS (NON FUSED SAFETY SWITCH), NIC (NOT IN CONTRACT), NO (NUMBER), NTS (NOT TO SCALE), OCPD (OVER-CURRENT PROTECTION DEVICE), OSHA (OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION), P (POLE), PB (PULL BOX), PC (PERSONAL COMPUTER), PH (PHASE), PNL (PANEL), PVC (POLYVINYL CHLORIDE), RCP (RECEPTACLE), RE (RELOCATED EQUIPMENT), RLA (RUN LOAD AMP), RM (ROOM), RSC (RIGID STEEL CONDUIT), SD (SMOKE DETECTOR), SW (SWITCH), SWB (SWITCHBOARD), SYS FURN (SYSTEM FURNITURE), TEL (TELEPHONE), TF (TRANSFER FAN WITH LOCAL TOGGLE SWITCH), TYP (TYPICAL), UL (UNDERWRITER LABORATORIES), UNLESS (UNLESS OTHERWISE NOTED), V (VOLT), W (WIRE), WITH (WITH), WATT (WATT), WH (WATER HEATER), WP (WATER PROOF), WSA (WIRE SIZE AMPS), WT (WIRING TROUGH), XFMR (TRANSFORMER)

GENERAL NOTES


- 1. ALL WORK IS NEW UNLESS OTHERWISE NOTED.
2. SHADED REGIONS ON THE FLOOR PLANS ARE OUTSIDE THE AREA OF WORK UNLESS OTHERWISE NOTED.

ELECTRICAL LEGEND


Table with columns: DESIGNATION, DESCRIPTION, MTG HGT TO CENTER LINE AFF. (UN). Includes symbols for fluorescent lighting fixtures, emergency lighting fixtures, LED emergency exterior wallpack lighting fixtures, ceiling mounted exit lights, single pole switches, duplex receptacles, double duplex receptacles, ceiling mounted junction boxes, wall mounted junction boxes, card readers, transformers, panelboards, motor connections, non-fused safety disconnect switches, fused safety disconnect switches, homerun to panelboard, tick marks, general circuitry, and circuitry installed concealed.


DRAWING LIST

Table listing drawing sheets: 1-E-001 COVER SHEET - ELECTRICAL, 1-E-101 SITE PLAN - ELECTRICAL, 1-E-102 FOURTH FLOOR DEMOLITION & NEW WORK - ELECTRICAL, 1-E-103 FIFTH FLOOR DEMOLITION & NEW WORK - ELECTRICAL, 1-E-104 FOURTH & FIFTH FLOOR NEW WORK - FIRE ALARM, 1-E-701 DETAILS & SCHEDULES



Project: VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1, ARLINGTON, VA. Includes drawing title: COVER SHEET - ELECTRICAL, sheet number: 1-E-001, and revision table with dates and descriptions.





GENERAL NOTES - ELECTRICAL

1. REFER TO ELECTRICAL COVER SHEET FOR SPECIFICATIONS, GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS.

KEYED NOTES - ELECTRICAL

1. TO BE REMOVED FROM SERVICE: DOMINION ENERGY UTILITY TRANSFORMER FEEDING THE VIRGINIA HOSPITAL CENTER (BLDG 601). OWNER SHALL APPLY FOR AND OBTAIN UTILITY DISCONNECT LETTERS.

2. EXISTING TO REMAIN: DOMINION ENERGY UTILITY TRANSFORMER FEEDING THE DOCTOR'S OFFICE BUILDING (BLDG 611).





3. DIESEL GENERATOR FEEDING THE VIRGINIA HOSPITAL CENTER (BLDG 601). REMOVE FROM SERVICE. REPROGRAM FIRE ALARM SYSTEM TO PREVENT SUPERVISORY AND TROUBLE SIGNALS FROM GENERATOR DISCONNECTION.

THE WORK INDICATED ON THIS DRAWING IS NOT IN CONTRACT AND IS INCLUDED FOR INFORMATION ONLY.

CD Revisions	BY	DES
5/15/2020	GTH	
1		

DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	GTH	GTH	GTH

RRMM ARCHITECTS, PC
 2900 South Quincy Street, Suite 710
 Arlington, Virginia 22206
 (703)998-0101



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 2
 ARLINGTON, VA
 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204

DRAWING SITE PLAN - ELECTRICAL

SHEET
1-E-101


Electrical Site Plan
 SCALE: 1" = 24'




GPI
 Greenman-Pedersen, Inc.
 Engineering and Construction Services
 8001 Braddock Road, Suite 200, Springfield, VA 22151
 703-978-0100 www.gpinet.com
 Project #: 2019322.00

6/16/2021 1:32:19 PM C:\Users\ghagen\Documents\201932200_v20 - Electrical_gghagen\HAT3.rvt

C:\Users\ghagem\Documents\201932200_v20 - Electrical_gghagem\HAT3.rvt
6/16/2021 1:32:24 PM



1 FOURTH FLOOR - DEMOLITION - ELECTRICAL
E-102 SCALE: 1/8" = 1'-0"



2 FOURTH FLOOR - NEW WORK - ELECTRICAL
E-102 SCALE: 1/8" = 1'-0"

GENERAL NOTES - DEMOLITION

- REFER TO ELECTRICAL COVER SHEET FOR SPECIFICATIONS, GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS. REFER TO FIRE ALARM NEW WORK PLAN FOR FIRE ALARM SYMBOLS.
- REFER TO MECHANICAL AND PLUMBING DRAWINGS FOR EXACT LOCATIONS FOR ALL RELOCATED/DEMOLISHED EQUIPMENT.
- PROVIDE COMPLETE ELECTRICAL DEMOLITION IN THE AREA OF WORK UNLESS OTHERWISE NOTED SO AS TO ELECTRICALLY ISOLATE EXISTING TO REMAIN BUILDING PORTIONS.
- PROTECT EXISTING EMERGENCY LIGHTS, EXIT SIGNS AND FIRE ALARM DEVICES EXCEPT WHERE DEMOLITION IS NEEDED.
- DEMOLITION WORK INDICATED IS DIAGRAMMATIC AND NOT SHOWN INCLUSIVE. DEMOLITION DRAWING IS INTENDED TO DEMONSTRATE MAJOR ITEMS ONLY. CONTRACTOR IS REQUIRED TO PERFORM SELECTIVE DEMOLITION AS NEEDED TO ACCOMPLISH THE PROJECT INTENT. IF DEMOLITION WORK IS UNCLEAR FOR ANY ITEM, THE CONTRACTOR SHALL BRING IT TO THE ATTENTION OF THE ARCHITECT/ENGINEER FOR RESOLUTION BEFORE PROCEEDING.
- REMOVE ALL ABANDONED WIRING BACK TO THE PANEL/SOURCE AS APPLICABLE.
- COORDINATE WITH OWNERS/BUILDING ENGINEERS PRIOR TO SCHEDULING ANY SHUTDOWN REQUIRED DURING CONSTRUCTION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) LIGHTING FIXTURES AND ASSOCIATED CONTROLS IN AREA OF WORK UNLESS OTHERWISE NOTED. REMOVE WIRING FROM FIXTURE/DEVICE LOCATION BACK TO NEXT ACTIVE OUTLET (OR BACK TO SOURCE PANELBOARD IF CIRCUIT IS NO LONGER ACTIVE. AT PANELBOARD, TURN CIRCUIT BREAKER(S) TO THE OFF POSITION AND LABEL AS "SPARE") RESTORE CONNECTION TO EXISTING FIXTURES/DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) EMERGENCY LIGHTING FIXTURES AND EXIT SIGNS IN AREA OF WORK UNLESS OTHERWISE NOTED. SAFELY TERMINATE EMERGENCY LIGHTING CIRCUITRY ABOVE CEILING FOR REUSE. RESTORE CONNECTION TO EXISTING EMERGENCY FIXTURES AND EXIT SIGNS FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) FIRE ALARM DEVICES IN AREA OF WORK UNLESS OTHERWISE NOTED. SAFELY TERMINATE FA CIRCUITRY ABOVE CEILING FOR REUSE. COORDINATE REMOVAL OF FIRE ALARM WIRING WITH BUILDING ENGINEER BEFORE PROCEEDING WITH DEMOLITION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) RECEPTACLES, POKE-THRU DEVICES, SYSTEMS FURNITURE POWER/DATA FEEDS, AND CABLE TRAY SYSTEMS IN AREA OF WORK UNLESS OTHERWISE NOTED. REMOVE CIRCUITRY FROM DEVICE LOCATION BACK TO NEXT ACTIVE OUTLET (OR BACK TO SOURCE PANELBOARD IF CIRCUIT IS NO LONGER ACTIVE. AT PANELBOARD, TURN CIRCUIT BREAKER(S) TO THE OFF POSITION AND LABEL AS "SPARE") RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- DISCONNECT AND REMOVE ALL (NOT SHOWN) TELEPHONE/DATA OUTLETS AND SECURITY DEVICES IN AREA OF WORK UNLESS OTHERWISE NOTED.

KEYED NOTES - DEMOLITION


- REMOVAL: DISCONNECT POWER AND REMOVE ASSOCIATED SAFETY DISCONNECT FROM MECHANICAL AND PLUMBING EQUIPMENT AS SHOWN ON PLAN, UNLESS OTHERWISE NOTED. REMOVE EXISTING WIRING FROM UNIT LOCATIONS BACK TO SOURCE PANELBOARD. TURN CIRCUIT BREAKER(S) TO THE OFF POSITION, AND LABEL BREAKER(S) AS "SPARE". RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- EXISTING TO REMAIN CONCRETE ENCASED 16-WAY DUCTBANK BENEATH MRI BUILDING AND STAIRWELL.
- UNDERGROUND ELECTRICAL PRIMARY CONDUIT AND CONDUCTORS SERVING THE ADJACENT BLDG 601. COORDINATE ELECTRICAL UTILITY DISCONNECTION FOR BLDG 601 PRIOR TO ANY DEMOLITION WORK.
- DISCONNECT POWER FOR LINE CONDITIONER CIRCUIT AT THE MAIN SWITCHBOARD AND LABEL BREAKER AS "SPARE". REMOVE ASSOCIATED SAFETY DISCONNECT AND CIRCUITRY FOR THE LINE CONDITIONER BACK TO THE TRANSFORMER SECONDARY DISCONNECT IN THE MAIN ELECTRICAL ROOM ON THE THIRD FLOOR.
- DISCONNECT POWER FOR EXISTING PANEL X AT THE MAIN SWITCHBOARD LABEL AS BREAKER AS "SPARE". REMOVE PANEL AND REMOVE CIRCUITRY BACK TO THE METER IN THE MAIN ELECTRICAL ROOM ON THE THIRD FLOOR.
- DISCONNECT POWER AND REMOVE ASSOCIATED SAFETY DISCONNECT FROM EXISTING WATER SOURCE HEAT PUMP (208V/1PH, 4.8 FLA). SAFELY TERMINATE CIRCUITRY ABOVE THE FIFTH FLOOR CEILING WITHIN BLDG 611 FOR REUSE. RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
- FIRE ALARM DEVICES IN THE STAIRWELL ARE CURRENTLY FED FROM THE BLDG 601 FIRE ALARM SYSTEM AND SHALL BE PREPARED FOR RECONNECTION TO THE BLDG 611 FIRE ALARM SYSTEM, UNLESS OTHERWISE NOTED. DISCONNECT ALL FIRE ALARM DEVICES AND REMOVE CIRCUITRY BACK TO NEXT ACTIVE DEVICE IN BLDG 601.

GENERAL NOTES - NEW WORK

- REFER TO ELECTRICAL COVER SHEET FOR SPECIFICATIONS, GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS.
- REFER TO ELECTRICAL DETAIL SHEET FOR LIGHTING FIXTURE SCHEDULE AND ADDITIONAL INFORMATION.
- COORDINATE ALL HVAC EQUIPMENT CONNECTION REQUIREMENTS WITH THE MANUFACTURER PRIOR TO ORDERING AND ROUGH-IN.



KEYED NOTES - NEW WORK

- CONNECT NEW OR RELOCATED EMERGENCY LIGHTS & EXIT SIGNS TO EXISTING 277V EMERGENCY LIGHTING CIRCUIT PREVIOUSLY FEEDING THIS AREA, LOCATED IN (E) EMERGENCY PANEL "E". PANEL DIRECTORY DOES NOT CHANGE UNDER THIS WORK. CIRCUIT SHALL NOT EXCEED 350VA.
- EXISTING TO REMAIN CONCRETE ENCASED 16-WAY DUCTBANK BENEATH MRI BUILDING AND STAIRWELL.
- SPLICE AND EXTEND EXISTING WATER SOURCE HEAT PUMP CIRCUITRY TO NEW WATER SOURCE HEAT PUMP (208V/1PH, 4.1 FLA). PROVIDE NEMA RECEPTACLE IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS. THE ELECTRICAL CONTRACTOR IS RESPONSIBLE FOR INSTALLING THE ELECTRICAL ACCESSORIES FURNISHED WITH UNIT INSIDE THE UNIT CABINET. COORDINATE INSTALLATION WITH THE MECHANICAL CONTRACTOR AND THE MANUFACTURER'S INSTRUCTIONS PRIOR TO PROCEEDING WITH WORK.




DATE	PROJECT	DESIGNED	DRAWN	CHECKED	MARK	DATE	REVISIONS
06.18.2021	13356.28	GTH	GTH	GTH			

CD	Revisions
GTH	DES
5.15.2020	BY
1	MARK DATE




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA
601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204.
DRAWING FOURTH FLOOR DEMOLITION & NEW WORK - ELECTRICAL

SHEET
1-E-102



6/16/2021 1:32:27 PM C:\Users\ghagem\Documents\201932200_v20 - Electrical_ghagem\HAT13.rvt



1 FIFTH FLOOR - DEMOLITION - ELECTRICAL
 E-107 SCALE: 1/8" = 1'-0"


2 FIFTH FLOOR - NEW WORK - ELECTRICAL
 E-107 SCALE: 1/8" = 1'-0"

- ### GENERAL NOTES - DEMOLITION
- REFER TO ELECTRICAL COVER SHEET FOR SPECIFICATIONS, GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS. REFER TO FIRE ALARM NEW WORK PLAN FOR FIRE ALARM SYMBOLS.
 - REFER TO MECHANICAL AND PLUMBING DRAWINGS FOR EXACT LOCATIONS FOR ALL RELOCATED/DEMOLISHED EQUIPMENT.
 - PROVIDE COMPLETE ELECTRICAL DEMOLITION IN THE AREA OF WORK UNLESS OTHERWISE NOTED SO AS TO ELECTRICALLY ISOLATE EXISTING TO REMAIN BUILDING PORTIONS.
 - PROTECT EXISTING EMERGENCY LIGHTS, EXIT SIGNS AND FIRE ALARM DEVICES EXCEPT WHERE DEMOLITION IS NEEDED.
 - DEMOLITION WORK INDICATED IS DIAGRAMMATIC AND NOT SHOWN INCLUSIVE. DEMOLITION DRAWING IS INTENDED TO DEMONSTRATE MAJOR ITEMS ONLY. CONTRACTOR IS REQUIRED TO PERFORM SELECTIVE DEMOLITION AS NEEDED TO ACCOMPLISH THE PROJECT INTENT. IF DEMOLITION WORK IS UNCLEAR FOR ANY ITEM, THE CONTRACTOR SHALL BRING IT TO THE ATTENTION OF THE ARCHITECT/ENGINEER FOR RESOLUTION BEFORE PROCEEDING.
 - REMOVE ALL ABANDONED WIRING BACK TO THE PANEL/SOURCE AS APPLICABLE.
 - COORDINATE WITH OWNERS/BUILDING ENGINEERS PRIOR TO SCHEDULING ANY SHUTDOWN REQUIRED DURING CONSTRUCTION.
 - DISCONNECT AND REMOVE ALL (NOT SHOWN) LIGHTING FIXTURES AND ASSOCIATED CONTROLS IN AREA OF WORK UNLESS OTHERWISE NOTED. REMOVE WIRING FROM FIXTURE/DEVICE LOCATION BACK TO NEXT ACTIVE OUTLET (OR BACK TO SOURCE PANELBOARD IF CIRCUIT IS NO LONGER ACTIVE. AT PANELBOARD, TURN CIRCUIT BREAKER(S) TO THE OFF POSITION AND LABEL AS "SPARE". RESTORE CONNECTION TO EXISTING FIXTURES/DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
 - DISCONNECT AND REMOVE ALL (NOT SHOWN) EMERGENCY LIGHTING FIXTURES AND EXIT SIGNS IN AREA OF WORK UNLESS OTHERWISE NOTED. SAFELY TERMINATE EMERGENCY LIGHTING CIRCUITRY ABOVE CEILING FOR REUSE. RESTORE CONNECTION TO EXISTING EMERGENCY FIXTURES AND EXIT SIGNS FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
 - DISCONNECT AND REMOVE ALL (NOT SHOWN) FIRE ALARM DEVICES IN AREA OF WORK UNLESS OTHERWISE NOTED. SAFELY TERMINATE FA CIRCUITRY ABOVE CEILING FOR REUSE. COORDINATE REMOVAL OF FIRE ALARM WIRING WITH BUILDING ENGINEER BEFORE PROCEEDING WITH DEMOLITION.
 - DISCONNECT AND REMOVE ALL (NOT SHOWN) RECEPTACLES, POKE-THRU DEVICES, SYSTEMS FURNITURE POWER/DATA FEEDS, AND CABLE TRAY SYSTEMS IN AREA OF WORK UNLESS OTHERWISE NOTED. REMOVE CIRCUITRY FROM DEVICE LOCATION BACK TO NEXT ACTIVE OUTLET (OR BACK TO SOURCE PANELBOARD IF CIRCUIT IS NO LONGER ACTIVE. AT PANELBOARD, TURN CIRCUIT BREAKER(S) TO THE OFF POSITION AND LABEL AS "SPARE". RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
 - DISCONNECT AND REMOVE ALL (NOT SHOWN) TELEPHONE/DATA OUTLETS AND SECURITY DEVICES IN AREA OF WORK UNLESS OTHERWISE NOTED.

- ### KEYED NOTES - DEMOLITION
- REMOVAL. DISCONNECT POWER AND REMOVE ASSOCIATED SAFETY DISCONNECT FROM MECHANICAL AND PLUMBING EQUIPMENT AS SHOWN ON PLAN, UNLESS OTHERWISE NOTED. REMOVE EXISTING WIRING FROM UNIT LOCATIONS BACK TO SOURCE PANELBOARD, TURN CIRCUIT BREAKER(S) TO THE OFF POSITION, AND LABEL BREAKER(S) AS "SPARE". RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
 - NOT USED.
 - DISCONNECT POWER AND REMOVE ASSOCIATED SAFETY DISCONNECT FROM EXISTING WATER SOURCE HEAT PUMP (208V/1PH, 4.3 FLA). SAFELY TERMINATE CIRCUITRY ABOVE THE FIFTH FLOOR CEILING WITHIN BLDG 611 FOR REUSE. RESTORE CONNECTION TO EXISTING DEVICES FOR OPERATION AS BEFORE IF INTERRUPTED BY DEMOLITION.
 - FIRE ALARM DEVICES IN THE STAIRWELL ARE CURRENTLY FED FROM THE BLDG 601 FIRE ALARM SYSTEM AND SHALL BE PREPARED FOR RECONNECTION TO THE BLDG 611 FIRE ALARM SYSTEM, UNLESS OTHERWISE NOTED. DISCONNECT ALL FIRE ALARM DEVICES AND REMOVE CIRCUITRY BACK TO NEXT ACTIVE DEVICE IN BLDG 601.


- ### GENERAL NOTES - NEW WORK
- REFER TO ELECTRICAL COVER SHEET FOR SPECIFICATIONS, GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS.
 - REFER TO ELECTRICAL DETAIL SHEET FOR LIGHTING FIXTURE AND OCCUPANCY SENSOR SCHEDULES AND ADDITIONAL INFORMATION.
 - COORDINATE ALL HVAC EQUIPMENT CONNECTION REQUIREMENTS WITH THE MANUFACTURER PRIOR TO ORDERING AND ROUGH-IN.

- ### KEYED NOTES - NEW WORK
- CONNECT NEW OR RELOCATED EMERGENCY LIGHTS & EXIT SIGNS TO EXISTING 277V EMERGENCY LIGHTING CIRCUIT PREVIOUSLY FEEDING THIS AREA. LOCATED IN (E) EMERGENCY PANEL "E". PANEL DIRECTORY DOES NOT CHANGE UNDER THIS WORK. CIRCUIT SHALL NOT EXCEED 3500VA.
 - NOT USED.
 - SPLICE AND EXTEND EXISTING WATER SOURCE HEAT PUMP CIRCUITRY TO NEW WATER SOURCE HEAT PUMP (208V/1PH, 4.3 FLA). PROVIDE NEMA RECEPTACLE IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS. THE ELECTRICAL CONTRACTOR IS RESPONSIBLE FOR INSTALLING THE ELECTRICAL ACCESSORIES FURNISHED WITH UNIT INSIDE THE UNIT CABINET. COORDINATE INSTALLATION WITH THE MECHANICAL CONTRACTOR AND THE MANUFACTURER'S INSTRUCTIONS PRIOR TO PROCEEDING WITH WORK.




CD Revisions	DATE	PROJECT	DESIGNED	DRAWN	CHECKED	MARK	DATE	BY	DES
1	06.18.2021	13356.28	GTH	GTH	GTH				
	5.15.2020								


RRMM
 ARCHITECTS, PC
 2900 South Quincy Street, Suite 710
 Arlington, Virginia 22206
 (703)998-0101




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 DRAWING FIFTH FLOOR DEMOLITION & NEW WORK - ELECTRICAL

SHEET
1-E-103





1 FOURTH FLOOR - NEW WORK - FIRE ALARM
 1-E-104 SCALE: 1/8" = 1'-0"



2 FIFTH FLOOR - NEW WORK - FIRE ALARM
 1-E-104 SCALE: 1/8" = 1'-0"

GENERAL NOTES - FIRE ALARM

- REFER TO ELECTRICAL COVER SHEET FOR SPECIFICATIONS, GENERAL NOTES, SYMBOLS, AND ABBREVIATIONS.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL FIRE ALARM WORK INCLUDING BUT NOT LIMITED TO: ADDITION OF STROBES, AUDIBLE DEVICES, CIRCUITRY EXTENSION, AND SYSTEM PROGRAM MODIFICATIONS. FURNISH AND INSTALL ALL NECESSARY CONTROL EQUIPMENT INCLUDING EXTENDER PANEL, INITIATING DEVICES AND NOTIFICATION APPLIANCES REQUIRED FOR THE EXPANSION OF THE EXISTING FIRE ALARM SYSTEMS DETAILED ON THE CONTRACT DRAWINGS AND AS SPECIFIED HEREIN. THE EQUIPMENT FURNISHED SHALL BE COMPATIBLE WITH THE EXISTING EQUIPMENT. THE CONTRACTOR SHALL SURVEY THE EXISTING CONTROL PANEL TO DETERMINE ANY NECESSARY MODIFICATIONS AND/OR ADDITIONS NECESSARY TO INCORPORATE THE DEVICES ADDED UNDER THIS CONTRACT. PROVIDE SYNCHRONIZING OF STROBES FOR ALL EXISTING, NEW & RELOCATED DEVICES WITHIN THE AREA OF WORK. SYNCHRONIZATION OF STROBES SHALL BE PER NFPA72 REQUIREMENTS. IN THE EVENT OF A BUILDING EVACUATION ALARM, PROVIDE CONTROL WIRING FROM THE BUILDING FACP TO ALL SECURED DOORS IN THE PATH OF EGRESS TO RELEASE THE LOCK. COORDINATE WORK WITH THE SECURITY CONTRACTOR. PROVIDE REQUIRED DRY CONTACTS IN BUILDING FACP. SHOP DRAWINGS SHALL BE PREPARED AND SUBMITTED TO THE LOCAL AUTHORITY AND SHALL INCLUDE, BUT NOT LIMITED TO EQUIPMENT CUT SHEET, SEQUENCE OF OPERATION, BATTERY CALCULATIONS, CIRCUIT CAPACITY CALCULATIONS, WIRING DIAGRAMS, RISER DIAGRAMS AND FLOOR PLANS.
- PROVIDE ALL VISUAL AND AUDIBLE DEVICES (SPEAKER OR HORNS) IN WHITE COLOR W/ RED LETTERING UNLESS OTHERWISE NOTED. INSTALL ALL CEILING MOUNTED FIRE ALARM DEVICES IN THE CENTER OF CEILING TILE.
- PROTECT EXISTING BUILDING SMOKE/FIRE DETECTION SYSTEM AS REQUIRED TO PREVENT FALSE ALARMS DUE TO CONSTRUCTIONS.
- ALL FIRE ALARM EQUIPMENT SHALL BE REMAIN OPERATIONAL AND IN PLACE AS THE BUILD OUT OCCURS.
- IF THE CONSTRUCTION REQUIRES INTERRUPTION OF THE BUILDING FIRE ALARM, OBTAIN WRITTEN 7-DAY NOTICE FROM THE BUILDING OWNER PRIOR TO THE INTERRUPTION. FOLLOW ALL RULES AND REGULATIONS PROVIDED BY THE BUILDING OWNER AND ALL CODE REQUIREMENTS FOR A FIRE ALARM INTERRUPTION.
- FINAL CONNECTION TO BUILDING FIRE ALARM SYSTEM SHALL BE PERFORMED BY BASE BUILDING FIRE ALARM CONTRACTOR BUT SHALL BE RESPONSIBILITY OF THE ELECTRICAL CONTRACTOR.
- THE SYSTEM SHALL COMPLY WITH NFPA 72.

KEYED NOTES - FIRE ALARM

- RECONNECT EXISTING FIRE ALARM DEVICES IN STAIRWELL TO BLDG 611 FIRE ALARM SYSTEM. VERIFY OPERATIONAL STATUS OF DEVICES AND REPLACE DEFECTIVE DEVICES. PROVIDE UPDATED GRAPHIC ANNUNCIATOR PANEL AS REQUIRED.
- NOT USED.
- CARD READERS/MAG LOCKS: PROVIDE CONTROL WIRING FROM SECURITY SYSTEM TO CONNECT TO BASE BUILDING FIRE ALARM SYSTEM FOR RELEASE OF DOORS UPON SIGNAL FROM BASE BUILDING FIRE ALARM SYSTEM.


FIRE ALARM SYMBOLS

DESIGNATION	DESCRIPTION	MTG HGT TO AFF CENTERLINE (UGN)
15-1	FIRE ALARM VISUAL ALARM SIGNAL MOUNTED AT LOWER OF 80" OR 6" BELOW CEILING - NUMBER ADJACENT TO SYMBOL DENOTES MINIMUM REQUIRED LIGHT OUTPUT, CANDELA	4'-0"
15-1	FIRE ALARM COMBINATION AUDIBLE/VISUAL ALARM SIGNAL - MOUNTED AT LOWER OF 80" OR 6" BELOW CEILING. NUMBER ADJACENT TO SYMBOL DENOTES MINIMUM REQUIRED LIGHT OUTPUT, CANDELA	
15-2	CEILING FIRE ALARM VISUAL ALARM SIGNAL. NUMBER ADJACENT TO SYMBOL DENOTES MINIMUM REQUIRED LIGHT OUTPUT, CANDELA	
15-3	CEILING FIRE ALARM COMBINATION AUDIBLE/VISUAL ALARM SIGNAL. NUMBER ADJACENT TO SYMBOL DENOTES MINIMUM REQUIRED LIGHT OUTPUT, CANDELA	
F	FIRE ALARM MANUAL STATION	
(#)	DENOTES PLAN SPECIFIC KEYED NOTE	
(E)	EXISTING TO REMAIN - CONTINUE IN SERVICE	
(R)	EXISTING TO BE REMOVED AND RELOCATED	
(RE)	RELOCATED EQUIPMENT	
P	CEILING MOUNTED PHOTOELECTRIC SMOKE DETECTOR - SUBSCRIPT D DENOTES DUCT DETECTOR	




DATE	PROJECT	DESIGNED	DRAWN	CHECKED
06.18.2021	13356.28	GTH	GTH	GTH

CD Revisions	BY	DES
5.15.2020	GTH	DES
1	MARK	DATE
		REVISIONS



PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
 ARLINGTON, VA
 601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
 611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204.
 DRAWING FOURTH & FIFTH FLOOR NEW WORK - FIRE ALARM

SHEET
1-E-104



6/16/2021 1:32:30 PM C:\Users\ghagen\Documents\201932200_v20 - Electrical_ghagen\HAT3.rvt

1

1

2

1

3

1

4

1

5

LIGHTING FIXTURE SCHEDULE

FITURE ID	DESCRIPTION	MANUFACTURER	CATALOG NO.	LAMP		VOLTS	MOUNTING	DIMMING (YES OR NO)	KEYED NOTES
				QUANTITY	TYPE				
A	2'X4' VOLUMETRIC LED TROFFER	ELITE	24-0VHP-LED-400L-DIM10-MVOLT-35K-85	-	LED-41W	120/277	RECESSED	NO	
B	EXTERIOR LED WALLPACK	LITHONIA	LIL LED 30K MVOLT PE BB DDBTXD	-	LED-8.4W	120/277	SURFACE	NO	2
X	EXIT SIGN	LITHONIA	LRP-X-X-RC-X-120/277	-	LED (INCLUDED)	120/277	RECESSED	NO	1

GENERAL NOTES


- COORDINATE MOUNTING HEIGHT (PENDANT/SUSPENDED/WALL LUMINARIES) & LENGTH (LINEAR FLUORESCENT/LED LUMINARIES) WITH ARCHITECT.
- PROVIDE LAMP(S) AT 80 CRI OR BETTER. REFER TO ARCHITECTURAL DRAWINGS FOR FINAL LAMP COLOR TEMPERATURE.

KEYED NOTES



- PROVIDE QUANTITY OF FACES, DIRECTIONAL ARROWS, AND MOUNTING AS SHOWN ON DRAWINGS. MATCH BUILDING STANDARD AS REQUIRED.
- PROVIDE INTEGRAL PHOTOCELL AND CONDUIT BACKBOX.

DES
BY
MARK DATE
REVISIONS

DATE 06.18.2021
PROJECT 13356.28
DESIGNED GTH
DRAWN GTH
CHECKED GTH




RRMM ARCHITECTS, PC
2900 South Quincey Street, Suite 710
Arlington, Virginia 22206
(703)998-0101




PROJECT VIRGINIA HOSPITAL CENTER DEMOLITION - PHASE 1
ARLINGTON, VA

601 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204
611 S CARLIN SPRINGS ROAD, ARLINGTON, VA 22204

DRAWING DETAILS & SCHEDULES



Engineering and Construction Services
8001 Braddock Road, Suite 200, Springfield, VA 22151
703-978-0100 www.gpinet.com
Project #: 2019322.00



SHEET

1-E-701

