



## WILLIAMSON COUNTY GOVERNMENT

November 29, 2018

To Whom It May Concern:

Williamson County is accepting bids for thermal imaging cameras for the Office of Public Safety. Minimum bid specifications are enclosed. Please note any exceptions to the bid. We are requesting that bidders agree to hold their price for twelve months from date of award of bid. We are requesting that pricing be extended to the cities of Brentwood, Fairview, Franklin and Spring Hill.

It is not the intent of Williamson County to favor one vendor; however, we do, from time to time, have to rely on vendors' help in writing specifications. We will accept all bids with exceptions noted, and all bids will be given equal consideration.

Bids will be opened on Thursday, January 10, 2019, 2:00 p.m. Bids should be submitted in a sealed envelope to the County Mayor's Office, 1320 West Main Street, Suite 125, Franklin, TN 37064. Each envelope should be plainly marked: **Bid – Thermal Imaging Camera, January 10, 2019, 2:00 p.m. Envelope must also include bidder's company name. PLEASE NOTE: IF THE SEALED PACKAGE IS NOT LABELED EXACTLY AS SPECIFIED ABOVE, THE BID WILL NOT BE OPENED.**

Williamson County reserves the right to reject any and/or all proposals, to waive technicalities or informalities, and to accept any proposal deemed to be in the best interest of Williamson County. **No bid shall be valid unless signed.** No bid shall be accepted by FAX machine.

Enclosed is an *Ethical Standards Affidavit*, *Iran Divestment Act Affidavit*, *Fair Employment Affidavit*, *Immigration Attestation and Immigration Compliance Affidavit*, and *Business Tax and License Affidavit*. Please complete these documents and return them with your bid.

If you have any questions, please e-mail [leslie.mitchell@williamsoncounty-tn.gov](mailto:leslie.mitchell@williamsoncounty-tn.gov). All questions must be submitted in writing by 4:30 p.m. CST on January 4, 2019. No addenda will be issued within 48 hours of the bid opening date and time.

Sincerely,

Leslie Mitchell, CPPO, CPPB  
Purchasing Agent



November 29, 2018

To Whom It May Concern:

Williamson County is accepting bids for thermal imaging cameras for the Office of Public Safety. Minimum bid specifications are enclosed. Please note any exceptions to the bid. We are requesting that bidders agree to hold their price for twelve months from date of award of bid. We are requesting that pricing be extended to the cities of Brentwood, Fairview, Franklin and Spring Hill.

It is not the intent of Williamson County to favor one vendor; however, we do, from time to time, have to rely on vendors' help in writing specifications. We will accept all bids with exceptions noted, and all bids will be given equal consideration.

Bids will be opened on Thursday, January 10, 2019, 2:00 p.m. Bids should be submitted in a sealed envelope to the County Mayor's Office, 1320 West Main Street, Suite 125, Franklin, TN 37064. Each envelope should be plainly marked: **Bid – Thermal Imaging Camera, January 10, 2019, 2:00 p.m. Envelope must also include bidder's company name. PLEASE NOTE: IF THE SEALED PACKAGE IS NOT LABELED EXACTLY AS SPECIFIED ABOVE, THE BID WILL NOT BE OPENED.**

Williamson County reserves the right to reject any and/or all proposals, to waive technicalities or informalities, and to accept any proposal deemed to be in the best interest of Williamson County. **No bid shall be valid unless signed.** No bid shall be accepted by FAX machine.

Enclosed is an *Ethical Standards Affidavit*, *Iran Divestment Act Affidavit*, *Fair Employment Affidavit*, *Immigration Attestation and Immigration Compliance Affidavit*, and *Business Tax and License Affidavit*. Please complete these documents and return them with your bid.

If you have any questions, please e-mail [leslie.mitchell@williamsoncounty-tn.gov](mailto:leslie.mitchell@williamsoncounty-tn.gov). All questions must be submitted in writing by 4:30 p.m. CST on January 4, 2019. No addenda will be issued within 48 hours of the bid opening date and time.

Sincerely,

Leslie Mitchell, CPPO, CPPB  
Purchasing Agent

# Evolution 6000 Plus TIC Bid Specification

## Specification Purpose

Williamson County Office of Public Safety is seeking bids to purchase a minimum five (5) MSA Evolution 6000 Plus Thermal Imaging Cameras within the 2018/2019 FY.

This specification establishes minimum standards for thermal imaging cameras and associated battery charging systems. Thermal imaging cameras are tools for firefighters and first response emergency personnel that are used for search and rescue, fire scene size-up, overhaul, location of victims, and advanced firefighting and first response applications.

## Specification Type

Thermal imaging cameras covered by this specification shall be of the type incorporating 320X240 vanadium oxide microbolometer focal plane array sensor. TIC displays black and white scene representations on 3.5" diagonal LCD display. Design is optimized for firefighters in ergonomic design and ease of incorporation with firefighting gear. TIC features dual-handle design for onehanded operation, easy handoff and handling and high-impact, heat-resistant housing to ensure that TIC withstands rigors of firefighting environments. TIC is further enhanced by rubber bumper system to provide additional protection from extremely harsh environments. TIC shall be tested to and comply with the following standards:

- NFPA compliance NFPA 1801-2013 Edition
- Water/dust ingress International Standard CEI, IEC 529, IP67 Classification
- Direct flame/heat exposure NFPA 1801-2013 Edition
- Radio frequency interference IEC 61000-6-3, IEC 61000-6-2, FCC Part 15
- Rollover (truck charger) Simulated NFPA 1901-12, 1.7
- Non-explosive rating ANSI/UL 12.12.01 (Class I, Div. 2, Groups C and D)

## TIC Components

TIC, kits and accessories can be purchased individually. TIC shall consist of component parts direct temperature measurement, Heat Seeker PLUS Indicator, 2X and 4X digital zoom, 6 user-selectable color palettes, flashlight, laser pointer, distance range finder (optional), magnetic compass, integrated video transmitter (optional). Components are sold in kit format and/or individually, consisting of lithium-ion battery packs; desktop/vehicle cup holder; dual battery charger with wall plug and cigarette lighter adapter; truck-mounted charging system and attachments consisting of:

- Carabiner
- wrist strap
- shoulder strap
- retractable lanyard
- Carrying case.

## Sensor Technology

Sensor shall be uncooled vanadium oxide microbolometer focal plane array detector, with array size of 320X240, spectral response of 7.0-14.0 microns, Netd  $\leq 78\text{mK}$  max.  $\leq 40\text{mK}$  typ. (in High Sensitivity),  $\leq 234\text{mK}$  (in Low Sensitivity), dynamic range of  $-40^{\circ}\text{F}$  to  $320^{\circ}\text{F}$  ( $-40^{\circ}\text{C}$  to  $160^{\circ}\text{C}$ ) in High Sensitivity,  $-40^{\circ}\text{F}$  to  $1112^{\circ}\text{F}$ , ( $-40^{\circ}\text{C}$  to  $600^{\circ}\text{C}$ ) in Low Sensitivity.

## Mechanical Requirements

Dimensions shall be 7.3" x 4.8" x 11.6" (185 mm x 122 mm x 295 mm) with base weight of 42.4 oz. (2.65 lbs/1.2 kg).

Outer case and bumper materials pass NFPA 1801:2013 edition direct flame and heat exposure tests.

Outer housing is of polyphenylsulfone with flame-retardant silicone rubber bumpers.

Display cover is constructed of UV-stabilized polycarbonate with NFPA anti-scratch coating.

Camera floats in water.

## **Electrical Requirements**

Power is supplied by integral battery pack; power consumption is <6 w nominal.  
USB ports comprise 1 configuration.  
Display is 3.5" backlit LCD.

## **Configuration Requirements**

The camera will be configurable on the camera or on a PC application.

## **Environmental Requirements**

Ambient temperature operating times are:

- 80° C, 176° F > 30 minutes
- 120° C, 248° F > 20 minutes
- 260° C, 500° F > 6 minutes
- -30° C, -22° F > 40 minutes
- -40° C, -40° F > 25 minutes

## **Water/Dust Ingress**

TIC shall resist dust and water and must conform to International Standard CEI IEC 529; Degrees of Protection Provided by Enclosures (IP Code); IP67 classification.

## **Impact/Drop**

TIC will survive 6-ft drop at any angle with no operational defaults or outer housing physical compromise.

## **RFI/EMC**

TIC should not interfere with standard firefighter frequency bands at power levels found in hand-held (3-5W) and vehicle-mounted systems (~100W).

Communication/electronic devices cannot affect TIC to the point where navigation is compromised when TIC is subjected to RF interference of 80 MHz to 1 GHz at 30V/m.

TIC must meet RFI emissions and IEC susceptibility.

## **Optical Requirements**

Lens shall be 9mm and F1.25, field of view of 48° horizontal and 37° vertical.

Focus shall be optimal 3 ft to ∞ (1m to ∞).

Digital zoom shall be 2X and 4X.

## **Battery Status Indicators**

Total battery capacity shall be indicated in viewing area with row of 4 LEDs, functioning as follows:

- 4 green LEDs indicate 75% to 100% capacity
- 3 green LEDs indicate 50% to 75% capacity
- 2 yellow LEDs indicate 25% to 50% capacity
- 1 red LED indicates less than 25% capacity
- 1 red (flashing) LED indicates less than 5 minutes remaining.

On-screen shutter indicator appears as small block in upper left display corner when camera shutters indicate that area re-scan is necessary.

On-screen low sensitivity indicator appears as green triangle in upper left screen portion, indicating activities when TIC is in Low Sensitivity.

## **Over-Temperature Warning**

Warning shall be indicated via on-screen red triangle in display's upper center.

When not lit, TIC is within operational thermal limits.

Flashing red TIC has exceeded recommended operational thermal limits.

## **Rechargeable Lithium-Ion Battery Pack**

Battery type shall be rechargeable lithium-ion battery pack, with pack located inside of handle; pack weight of 3.2oz.

Operating time shall be 3.5 hours nominal, 4 hours maximum.

## **Battery Charger**

Stand-alone battery charger will charge two batteries simultaneously.

Charger design allows for desktop or vehicle cup holder use.

Battery charge time is 4 hours nominal, power supply is 110/240 VAC 50/60HZ with included 12 VDC cigarette adapter.

## **Vehicle-Mounted Charger**

Optional vehicle-mounted charger will charge TIC and 1 spare battery when properly installed.

Each vehicle charger includes installation/mounting kit.

Charger will draw less than 1.5 amps of power.

Battery charge time is 4 hours nominal, trickle maintenance charge; power supply is 12-24 VDC.

Vehicle-mounted charger must safely charge TIC while in a moving vehicle.

Vehicle-mounted charger must meet rollover requirements identified in NFPA 1901-12-1.7.

Dimensions are 10 3/8" L, 5 3/4"W, and 6" H.

Vehicle-mounted charger LED indicators are comprised of camera charging indicator on camera front panel with LEDs as follows: red: charging, green: complete.

Spare battery charging indicator located on charger indicates status as follows: red: charging, green: complete.

## **Attachments and Carrying Options**

TIC shall come equipped with 3 carabiner attachment points.

Battery charger kits shall come with carabiner for securing TIC to tool belt or other gear and retractable lanyard for use with TIC/carabiner assembly is available.

Retraction line is to be made of Kevlar core material; housing is to be heat-resistant.

Optional wrist strap/bunker clip attachment is available, constructed of fire-and heat-resistant materials.

Optional flame-and heat-resistant shoulder strap is offered, including emergency release clip.

## **Carrying Case**

Carrying case will hold as minimum; TIC, 2 lithium-ion battery packs, manual, carrying attachments, and stand-alone battery charger assembly.

Case shall resist dust and water ingress and must conform to international standard CEI IEC 529; degrees of protection provided by enclosures (IP code); IP54 classification.

Case impact/drop testing: dropped 3 consecutive times onto concrete from 3 ft (1m) at any angle with no operational defaults or physical compromise of case or contents.

## **Operation and Instruction Manual**

Comprehensive manual includes all aspects of use, care and camera maintenance.

Quick-start guide easy reference card covers basic camera operation.

Online video training includes camera use, care and maintenance, with available certification.

## **Direct Temperature Measurement**

Tool is integrated within TIC without add-on devices, with measurement taken from FPA.

Temperature range shall be:

- -40° to 320°F (-40°C to 160°C) in High Sensitivity
- -40°F to 1112°F, (-40°C to 600°C) in Low Sensitivity.
- Tick marks occur at:
- 75°F, 150°F and 225°F (24°C, 65°C and 107°C) in High Sensitivity
- 250°F, 500°F and 750°F (120°C, 260°C and 399°C) in Low Sensitivity.

Accuracy will be  $\pm 18^{\circ}\text{F}$  ( $10^{\circ}\text{C}$ ) or  $\pm 10\%$ , whichever is greater.

Intended for temperatures greater than 435°F (225°C)  $\pm 20\%$ .

Thermometer-style readout bar indicator in Fahrenheit or Celsius is available.

Digital temperature feature displays approximate number value of object temperatures located in spotter.

## **Heat Seeker PLUS Indicator**

Tool is integrated within TIC without add-on devices, with measurement taken from FPA.

Readout is of graduated color (yellow to orange to red) of portions of scheme that are above 275°F, (135°C)-yellow, 297°F (147°C)-red, in High Sensitivity, or 842°F (450°C)-yellow, 914°F, (490°C)-red, in Low Sensitivity mode.

## **User-Selectable Palettes**

Palette tool is integrated within TIC without add-on devices.

User-selectable palette offers 6 options: white hot, black hot, and color options fusion, fire and ice, rainbow.

## **Magnetic Compass**

Compass is integrated inside TIC without add-on devices, with accuracy of  $\pm 10^{\circ}$ .

## **Laser Pointer**

Laser pointer is integrated inside TIC without add-on devices.

## **Flashlight**

Tool is integrated inside TIC without add-on devices.

## **Distance Range Finder**

Tool is integrated within TIC without add-on devices, with effective distance of 16-210 ft (5-70m) and accuracy of  $\pm 3$  ft (1m).

## **Wireless Video Transmitter**

Tool is integrated within TIC without add-on devices, with effective range of 3280 ft (1000m), line of sight. 2 channels are offered. Transmission frequencies shall be 2.458GHz, 2.474GHz (North America).

## **EXCEPTIONS TO SPECIFICATIONS**

Any and all exceptions to the above specifications must be clearly stated for each heading on a separate sheet of paper.

**Bid Sheet**  
**MSA Evolution 6000 Plus Thermal Imaging Camera**  
**Williamson County Public Safety**

**Unit Price \$** \_\_\_\_\_

**Will you hold your price thru January 31, 2019? Yes or No** \_\_\_\_\_  
**Bid must include delivery to 304 Beasley Drive, Franklin, TN 37064.**

The bidder has received the following addenda:

Addendum #	_____	Dated	_____
Addendum #	_____	Dated	_____
Addendum #	_____	Dated	_____
Addendum #	_____	Dated	_____
Addendum #	_____	Dated	_____

**Company Name** \_\_\_\_\_

**Physical Address** \_\_\_\_\_

\_\_\_\_\_  
**Remittance Address** \_\_\_\_\_

**Authorized Signature** \_\_\_\_\_

**Printed Name** \_\_\_\_\_

**Phone** \_\_\_\_\_

**Fax** \_\_\_\_\_

**Email Address** \_\_\_\_\_

**Date** \_\_\_\_\_