



Opportunity in every direction.

Office of the Purchasing Manager

TO: ALL VENDORS
FROM: MAMIE M. JACKSON
DATE: January 18, 2023
RE: Request for Bid

The City of Waycross, Georgia will receive sealed bids until 11:00 a.m., Thursday,
June 1, 2023

For: Fire Uniforms

As specified in the attached specifications.

The City reserves the right to accept or reject any or all bids, to waive formalities and technicalities, to make an award in the best interest of the City and to make an award item by item unless otherwise stipulated by the bidder. Bidder must comply with all Federal, State and Local Laws.

Factors to be considered in making this award, if awarded, will be prices, quality, and references. The City will be the sole judge of the weights given these factors.

Bids will be opened and read aloud in the conference room at City Hall, on the second floor – 417 Pendleton Street, Waycross, Georgia, on the hour and date specified above. **No bids will be accepted after bid opening time. No faxed or emailed bids will be accepted.**

**BIDS SHOULD BE MAILED TO: CITY OF WAYCROSS, PURCHASING MANAGER
P. O. DRAWER 99
WAYCROSS, GEORGIA 31502-0099**

**OR HAND DELIVERED TO: CITY HALL – PURCHASING DEPARTMENT
(PRIOR TO OPENING) 417 PENDLETON STREET, ROOM 201
WAYCROSS, GEORGIA 31501**

BID ENVELOPE SHOULD BE MARKED: Bid # FY23-13 Fire Uniforms

The City has provided a quote sheet for your convenience. All blank spaces shall be completed and returned with your bid package. Prices quoted shall be firm prices and remain firm until delivery is made. If awarded, the City will place an order with the successful bidder within 60 (sixty) days after bid opening.



Opportunity in every direction.

BIDDER INFORMATION

Name of Company: _____

Address: _____

Phone: _____ Fax: _____

Email: _____

Bid Submitted by: _____

Signature: _____

Title: _____

Date: _____

FIREFIGHTERS SHIRTS

WAYCROSS FIRE DEPARTMENT

Color: Medium Blue.

Fabric: 65% polyester/35% cotton poplin, permanent press with soil release finish. Fabric weight shall be approximately 4.3 ounces per square yard.

Style: security style shirt with banded collar, badge tab, two piece yoke, bellows pockets with flaps, military creases and round dress style hem.

Long Sleeves: Long sleeves with rounded cuffs lined with approximately 4.25 weight permanent press 100% cotton, one button closure. Cuff width 2-1/2", topstitched 1/4". Sleeves have a 1-1/8" wide finished sleeve placket with 14 ligne button and buttonhole closure.

Short Sleeves: Half sleeves shall measure 9-1/2" from shoulder seam with 1" hem and bartack reinforcement at sleeve seam.

Collar: Dress style banded collar, fully lined with approximately 2.50 weight 50% polyester/50% cotton, 3" x 1/2" collar stays and 1/4" topstitching. Crease N' Tack lined band.

Front: Top center left front, shall be fully lined, 7/8" hemmed right front, front military creases. Six buttons plus one at collar-band, plus one each 14 ligne and 18 ligne spare replacement buttons at bottom right front. Buttonholes shall be lock-stitched. One pocket and flap each front.

Badge Reinforcement Strip: Centered inside left front from shoulder seam and extending past attached flap seam. Two cut buttonholes as to provide additional support for badge.

Back: Two piece yoke, topstitched. Three military pleats.

Epaulets: Self fabric with cut buttonhole and shall be attached with an X-tack.

Pockets: One each front, with mitered corners and 1" box pleat. Pocket dimensions: 5-1/4" wide and 5-7/8" deep with triangle tacks at each upper corner and hook and loop fasteners for flaps. Self material pencil compartment shall be contained in the left pocket.

Flaps: Self fabric scalloped flap over each pocket, with one button and buttonhole. Velcro fasteners shall be sewn in corners of each flap.

Patches: Waycross Fire Department patches will be sewn on both left and right sleeves. Patches will be provided by the Waycross Fire Department

Thread: Colorfast thread used in all operations.

Finishing: Finished shirts are steam pressed. The completed shirt shall be folded on a back board with a collar strip and enclosed in a polyurethane bag.

Label: All shirts have a label permanently attached showing size in inches and centimeters, brand identifications, **CAUTION: NOT FLAME RESISTANT**. Also attached is a separate label with lot number, fiber content and care instructions. Also included is a permanent label stating this garment does not meet NFPA 1975.

FIRE OFFICERS SHIRT

WAYCROSS FIRE DEPARTMENT

Color: White.

Fabric: 65% polyester/35% cotton ring/ring poplin with soil release finish. Fabric weight is shall be approximately 4.1 ounces per square yard.

Style: Long sleeve, military style shirt with banded collar, badge tab, two piece yoke, bellows pockets with flaps, military creases and round dress style hem.

Long Sleeves: Long sleeves with rounded cuffs lined with 4.0 oz. polyester/cotton, one button closure. Cuff width 2-1/2", topstitched 1/4". Sleeves have a 1-1/8" wide finished sleeve placket with a 14 ligne button/buttonhole closure.

Short Sleeves: Half sleeves measure 9-1/2" from shoulder seam with 1" hem and bartack reinforcement at sleeve seam.

Collar: Dress style banded collar, fully lined with 2.60 weight 50% polyester/50% cotton, 2-7/8" x 1/2" collar stays and 1/4" topstitching. Crease N' Tack lined band.

Front: Top center left front, fully lined, 7/8" hemmed right front, front military creases. Six buttons plus one at collarband. One each 14 ligne and 17 ligne spare replacement buttons located at bottom right front. Buttonholes shall be lock-stitched. One pocket and flap each front.

Badge Reinforcement Strip: Centered inside left front from shoulder seam and extending past attached flap seam. Two cut buttonholes shall be included to provide additional support for badge.

Back: Two piece yoke, topstitched. Bottom shall be double turned and narrow hemmed 3/16". Three military pleats.

Epaulets: Self fabric epaulets, lined, shall have functional button/buttonhole and are attached with X-tack.

Pockets: One each front, with mitered corners and 1" box pleat. Pocket dimensions shall be 5-1/4" wide and 5-7/8" deep with triangle tacks at each upper corner. Velcro fasteners shall be attached for securing pocket flaps. A separate, self material pencil compartment is located inside the left pocket.

Flaps: Self fabric scalloped flap over each pocket, with one button and buttonhole. Velcro fasteners shall be sewn in corners of each flap. Flaps are secured with bartacks and both flaps shall have an additional bartack forming a pencil slot.

Patches: Waycross Fire Department patches will be sewn on both left and right sleeves. Patches will be provided by the Waycross Fire Department

Thread: Colorfast thread used in all operations.

Finishing: The completed shirt shall be folded on a back board with a collar strip and enclosed in a polyurethane bag.

Label: All shirts shall have a label permanently attached showing size in inches, brand identification, [REDACTED] CAUTION: NOT FLAME RESISTANT. Also attached shall be a separate label with lot number, fiber content, care instructions, and unique barcode identification. Also included is a permanent label stating this garment does not meet NFPA 1975.

FEMALE OFFICERS SHIRTS

WAYCROSS FIRE DEPARTMENT

Color: White.

Fabric: 65% polyester/35% cotton ring/ring poplin with soil release finish. Fabric weight approximately 4.1 ounces per square yard.

Style: military style blouse with banded collar, badge tab, two piece yoke, bellows pockets with flaps, military creases and round dress style hem.

Sleeves: Long sleeves with rounded cuffs and one button/buttonhole closure lined with 4.0 weight, woven, polyester/cotton. Cuff width 2-1/4", topstitched 1/4". Sleeves shall have a 1-1/8" wide finished sleeve placket with button/buttonhole closure.

Sleeves: Short sleeves with 1" hem and bar-tack reinforcement at sleeve hem.

Collar: Dress style banded collar, fully lined with 2.60 weight 50% polyester/50% cotton, 2-7/8" X 1/2" collar stays and 1/4" topstitching. Crease 'N Tack lined band.

Front: Top center right front 1-1/4", fully lined, 7/8" hemmed left front, front military creases. Six buttons plus one at collar band. Buttonholes shall be lock-stitched. Replacement button at bottom left front. One pocket and flap each front.

Badge Reinforcement Strip: Centered inside left front from shoulder seam and extending past attached flap seam. Two cut buttonholes as to provide additional support for badge.

Back: Two piece yoke, topstitched. Bottom shall be double turned and narrow hemmed 3/16". Three military pleats.

Epaulets: Shall be white in color. Shall be attached with X-tack.

Pockets: One each front, with mitered corners and 1" box pleat. Pocket dimensions shall be 5-1/4" wide and 5-7/8" deep with triangle tacks at each upper corner. Velcro fasteners shall be attached for securing pocket flaps. A separate, self material pencil compartment shall be located inside the left pocket.

Flaps: Shall be white in color. One scalloped flap over each pocket, with one button and buttonhole. Velcro fasteners shall be sewn in corners of each flap.

Patches: Waycross Fire Department patches will be sewn on both left and right sleeves. Patches will be provided by the Waycross Fire Department

Thread: Colorfast thread used in all operations.

Finishing: Finished blouses are steam pressed. The completed blouse shall be folded on a back board with a collar strip and enclosed in a polyurethane bag.

Label: All blouses shall have a label permanently attached showing size, brand identification, [REDACTED]
[REDACTED] **CAUTION: NOT FLAME RESISTANT.** Also attached shall be a separate label with lot number, fiber content and care instructions. Also included is a permanent label stating this garment does not meet NFPA 1975.

FIRE OFFICERS TROUSERS

WAYCROSS FIRE DEPARTMENT

Color: Navy

Fabric: 100% texturized woven polyester with soil release finish. Approximately 6.8 ounces per square yard.

Style: Plain front, zipper fly with tab, quarter top front pockets, welt face back pockets.

Pockets: Quarter top front pockets reinforced with an additional ply of material across bottom. Two double welt back pockets with button tab and button closure on the left. Material shall be 65% polyester/35% cotton, 2.30 weight. All pocket openings are bar-tacked at each end.

Waistband: Two piece, finished 1-1/2" with lining and 7/8" stretch band. Curtain shall be 65% polyester/35% cotton, 2.60 weight and finishes 1-5/8", and shall contain a shirt retaining ribbon. Stainless steel hook and eye closure. stainless steel hook and eye closure with 7/8" reinforced stay.

Belt Loops: Shall have seven belt loops with additional loops added for size 40 and above. Loops shall be double thickness, lined, finished 5/8" wide and shall accommodate a 2" belt. Each loop shall be bar-tacked through shell fabric and lining for sturdy reinforcement.

Zipper: Industrial weight brass type with heavy duty slider and metal stops on permanent press tape.

Length: Trousers will be hemmed to lengths specified by the department by a machine blind hem with a serged seam finish.

Sewing: Colorfast thread shall be used in all operations. Side seams and inseams should be chain stitched to reduce the possibility of seam breaks. Seat-seam and fly shall be taped. Seat-seam should be double needle chain stitched with heavy duty thread. Trousers shall provide for allowance for waist alterations. All points of stress shall be bar-tacked.

Finishing: Side seams and inseams shall be pressed open in the manufacturing process. Assembled trousers shall be steam pressed.

Label: All trousers shall have a label permanently attached showing size in inches and centimeters, brand identification, **CAUTION: NOT FLAME RESISTANT.** Also attached shall be a separate label with lot number, fiber content, and care instructions. Also included shall be a permanent label stating this garment does not meet NFPA 1975.

FEMALE OFFICERS TROUSERS

WAYCROSS FIRE DEPARTMENT

Color: Navy

Fabric: 100% texturized woven polyester with soil release finish. Approximately 6.8 ounces per square yard.

Style: Pleated front, zipper fly with tab, quarter top front pockets, welt face back pockets.

Pockets: Quarter top front pockets reinforced with an additional ply of material across bottom. Right back pocket with button tab and button closure. Material shall be 65% polyester/35% cotton, approximately 2.30 weight. All pocket openings shall be bar-tacked at each end.

Waistband: Two piece, finished 1-1/2" with lining and 7/8" stretch Ban Rol®. Curtain shall be 65% polyester/35% cotton, AND finish 1-5/8" and contains Snugtex. Stainless steel hook and eye closure with 7/8" reinforcement stay.

Belt Loops: Seven loops of double thickness, lined, finished 5/8" wide as to accommodate a 2" belt. Each loop shall be bar-tacked through shell fabric and lining for sturdy reinforcement.

Zipper: Industrial weight brass type with heavy duty slider and metal stops on permanent press tape.

Length: Trousers will be hemmed to lengths specified by the department by a machine blind hem with a serged seam finish

Sewing: Colorfast thread shall be used in all operations. Sideseams and inseams should be chain stitched to reduce the possibility of seam breaks. Seatseam and fly shall be taped. Seat-seam shall be double needle chain stitched with heavy duty thread. Trousers shall have allowance for waist alterations. All points of stress shall be bar-tacked.

Finishing: Assembled trousers are steam pressed. Creaset applied to leg creases.

Label: All trousers shall have a label permanently attached showing size in inches and centimeters, brand identification, **CAUTION: NOT FLAME RESISTANT**. Also attached shall be a separate label with lot number, fiber content, and care instructions. Also included shall be a permanent label stating this garment does not meet NFPA 1975.

FIREFIGHTERS TROUSERS

WAYCROSS FIRE DEPARTMENT

Color: Navy Blue.

Fabric: 65% polyester/35% cotton twill with mechanical stretch; Approximately 7.5 oz. per square yard. Pocketing is black 75% polyester/25% cotton; approximately 3.95 ounces per square yard.

Style: Trousers shall be constructed on a uniform pattern, having a plain front with quarter top front pockets, 1" belt loops, and double welt back pockets.

Pockets: The front pocket opening shall be quarter top style, clean finished on both inside and outside of pocket bag. Pocket edge (facing) shall be reinforced with a woven lining for stability. 42-stitch bar-tacks reinforce points of stress on front pocket openings for superior durability. Minimum pocket opening shall be 5 1/2". Lined, double welt back pockets finish 5 1/2" wide x 6 1/2" deep, clean finished on both inside and outside of pocket bag. Triangular bar-tacks on pocket ends as to provide increased strength at stress points. Button and button tab closure on both back pockets. Shall also include side patch pockets on left and right leg have a mock bellows, zipper pouch and flap enclosed pouch. Corners of flap shall be reinforced with bar-tacks.

Waistband: Outside waistband shall be approximately 2" wide (self-material) sewn to a 3" black, waistbanding with grip surface. stainless steel hook and eye closure with 7/8" reinforced stay.

Inside Trim: The right fly lining/crotch piece extension shall be the pocketing fabric, and is sewn flat. The right fly shall be a continuous French fly extension with a buttonhole that attaches to a button sewn on the left side of the waistband curtain. The right fly lining is sewn to the left fly below the zipper and continues, centered on the joined seam, across the inseam and end at least 1" onto the back seam. A non-woven interlining is sewn to the left fly for improved smoothness.

Zipper: The trousers shall have a brass, memory-lock zipper with a brass bottom stop. A bar-tack shall be sewn from the outside of the garment to the inside at the bottom of the fly capturing the zipper tape, the right and left fly and the right fly lining. The right and left fly shall be joined by an additional bar-tack located below the bottom zipper stop on the inside of the trouser.

Belt Loops: All belt loops shall be lined, sewn with a 2-row cover-stitch, and attached in the waist-band seams. There shall be a minimum of seven belt loops, including one at the center back for outlet seam. The belt loops shall be approximately 1" wide with a minimum 2 1/4" loop opening.

Length: Trousers will be hemmed to lengths specified by the department by a machine blind hem with a serged seam finish

Seaming: The entire trouser shall be sewn with polyester core or 100% polyester spun thread. The seat seam shall be stitched with a tandem needle seat-seaming machine.

Labels: There shall be an attached labels showing care instructions, lot number, size, date code, manufacturing order number, fiber content, ~~XXXXXXXXXX~~ CAUTION: NOT FLAME RESISTANT. Duration hangtag is attached to trouser at waistband. Also included shall be a permanent label stating this garment does not meet NFPA 1975.

Finishing & Pressing: All loose threads shall be removed. Trousers shall be pressed along front and back leg creases