

BURN BUILDING  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA


---

(ARCHITECTURAL)

PROJECT NUMBER 1730

FOR BIDDING

26 FEB 2018



Architecture - Planning  
Construction Administration

[www.smithdesigngroup.net](http://www.smithdesigngroup.net)

206 West Haralson Street - LaGrange Georgia 30240

**ABBREVIATIONS:**


@	Anchor Bolt	JAN.	Janitor
A.B.	Anchor Bolt	J.B.	Joist Bearing
A.C.	Air Conditioner	J.S.T.	Joist
ACOUST.	Acoustical	J.T.	Joist
ALUM.	Aluminum		
ARCH.	Architectural	LAV.	Lavatory
A.T.	Acoustical Tile	LLV.	Long Leg Vertical
		MAS., MSRY	Masonry
B.C.	Bottom of Curb	MCS	Modular Cabinet System
BLK.	Block	MECH.	Mechanical
BOTT.	Bottom	MIN.	Minimum
		N	North
CER.	Ceramic	NA	Not Applicable
CHM.	Custom Hollow Metal	N.I.C.	Not In Contract
C.I.	Curb Inlet	NTS	Not to Scale
		O.C.	On Center
CLO.	Closet	OPP.	Opposite
CMU.	Concrete Masonry Unit		
C.O.	Clean Out	PL	Plate
COL.	Column	PT	Pressure Treated
CONC.	Concrete	PEJ	Premolded Expansion
CONST.	Construction	PLAST	Plaster
CONT.	Continuous	PSF	Pounds Per Square Foot
C.T.	Ceramic Tile	PSI	Pounds Per Square Inch
CHR.	Coat & Hat Rack	R	Radius
C.J.	Control Joint	REF	Refrigerator
		REQ'D	Required
D.	Diameter	RL	Roof Level
DIAM.	Diameter	RM	Room
DF	Drink Fountain	RT	Resilient Tile
DI	Drain Inlet	RW	Regular Weight
DN	Down	ROUND	Round
DRIV.	Driver	SQ.	Square
DS	Downspout	SIM	Similar
DWGS.	Drawings	SLV	Short Leg Vertical
DWLS.	Dowels	S.M.	Sheet Metal
DR	Drawer	STL	Steel
		STO., STOR	Storage
E.J.; EXP. JT.	Expansion Joint	STRUCT.	Structural
EL.; ELEV	Elevation	SH	Shelves
EQ	Equal		
EQUIP.	Equipment	TC	Teacher Cabinet
E.F.I.S.	Exterior Finish	T.C.	Top of Curb
		TD	Turn Down
F.E.	Fire Extinguisher	TFF	Top of Finished Floor
F.H.	Fire Hose	TFS	Top of Finished Slab
FES	Fire Extinguisher Sign	T & G	Tongue and Groove
FIN.	Finish	T.M.	Transitional Material
FLEX.	Flexible	TP	Top of Pavement
FLR.	Floor	T/S	Top of Steel
FT.	Foot	TYP.	Typical
FTG.	Footing		
		U.N.O.	Unless Noted Otherwise
GA	Gauge		
G.C.	General Contractor	Y.C.J.	Veneer Control Joint
GYP_BRD.	Gypsum Wallboard	VERT	Vertical
		VRS	Varies
H	Height	VWC	Vinyl Wall Covering
HC	Handicapped		
HCM	Hollow Concrete Masonry	W	Width
HORIZ.	Horizontal	W/	With
HW	Hand Wash	W.C.	Water Cooler
		WD	Wood
I.D.	Inside Diameter	WWF	Welded Wire Fabric
IND.	Industrial		
INV.	Invert		

**CONSTRUCTION MATERIALS:**

PLAN / SECTION

	face brick
	hollow concrete masonry
	gypsum wallboard
	ceramic/quarry tile
	acoustical tile
	resilient flooring
	carpet
	steel/iron
	aluminum
	small scale metal
	rough lumber
	large scale finish lumber
	small scale finish lumber
	large scale plywood
	small scale plywood
	batt/blanket insulation
	laminated plastic

**INDEX OF SYMBOLS:**



**Additive Alternates:**

**2.2.1 Add. Alt. No. 1:** Provide & install Scout Temperature Monitoring System in all burn rooms shown on the plan. See outline specification for design based on. See sheet A9-2.

**2.2.2 Add. Alt. No. 2:** Design based on Westec Insulation System to be installed with 2" insulation blanket on walls and ceiling and minimum of 1" insulation blanket on doors and windows. See specifications on drawings.

Floors of burn rooms to have 2" insulation blanket with framing system with 1/4" checkered plate sill floor. See drawings for burn rooms to receive Westec Insulation System on walls, ceiling, floors, doors, and windows. Insulated windows to be 1/2" plates on both sides.

**2.2.3 Add. Alt. No. 3:** Provide 2"x48"x24" mineral wool high temperature insulation, density #8, green, 1200°F (design based on Roxul insulation). Provide & install on all walls, ceilings, floors, doors, and windows in all burn rooms designated on the drawings. Cover with 1/4" plate steel panels, screwed to framing to minimize buckling. Insulated windows to be 1/2" plates on both sides.

**2.2.4 Add. Alt. No. 4:** Provide 0.82" X 5.5" composite deck board surface screwed to P.T. 2x8's @ 16" O.C. on steel frame for rappelling surface. P.T. 2x8 framing and composite deck boards purchase & installation. See drawings.

**The Current State Minimum Standard Codes**

The following are the current state minimum standard codes for construction as adopted by the Board of Community Affairs.

**Current Mandatory Codes as Adopted by DCA:**


- International Building Code, 2012 Edition, with Georgia Amendments (2014) (2015)
- International Residential Code, 2012 Edition, with Georgia Amendments (2014) (2015)
- International Fire Code, 2012 Edition, with Georgia Amendments (2014) (2015)
- International Plumbing Code, 2012 Edition, with Georgia Amendments (2014) (2015)
- International Mechanical Code, 2012 Edition, with Georgia Amendments (2014) (2015)
- International Fuel Gas Code, 2012 Edition, with Georgia Amendments (2014) (2015)
- International Electrical Code, 2014 Edition (No Georgia Amendments)
- International Energy Conservation Code, 2009 Edition, with Georgia Supplements and Amendments (2011) (2012)

For information and questions regarding the Life Safety Code (NFPA 101) or the Georgia Accessibility Code please contact the State Fire Marshal's Office.

NO SMOKING  
INSIDE BUILDING  
OR ON SITE

NOTE TO GENERAL CONTRACTOR AND SUB-CONTRACTORS.  
HARD HATS, SAFETY GLASSES, VESTS, ETC., ARE TO BE WORN AT ALL TIMES BY CONSTRUCTION PERSONNEL. ALL SAFETY REQUIREMENTS OF CITY OF LAGRANGE SYSTEM WILL BE IN FORCE ON THIS PROJECT. WEEKLY SAFETY MEETINGS ARE REQUIRED AND MINUTES OF ALL SAFETY MEETINGS TO BE SUBMITTED WITH MONTHLY PAY REQUESTS.

NOTE: WEEKLY PROJECT MEETINGS ON SITE WITH OWNER AND ARCHITECT WILL BE REQUIRED WITH CONTRACTOR.




NOT TO SCALE  
CITY OF LAGRANGE VICINITY MAP  
1900 WEST LUKKEN INDUSTRIAL DRIVE  
LAGRANGE, GEORGIA

**INDEX OF SHEETS**

G-1	COVER SHEET
G-2	INDEX OF SHEETS
SD-1	SITE PLAN EXISTING
SD-2	SITE PLAN PROPOSED
SD-3	PARTIAL SITE PLAN PROPOSED
SD-4	SITE DETAILS
SD-5	SITE DETAILS
SD-6	SITE DETAILS
S1	STRUCTURAL NOTES
S2	FOUNDATION PLAN
S3	EXTERIOR ELEVATIONS
S4	TOWER FRAMING
S5	TOWER FRAMING
S6	TOWER FRAMING
S7	FLOOR FRAMING PLANS
S8	FLOOR FRAMING PLANS
S9	CONTAINER SECTIONS / ELEVATIONS
S10	CONTAINER SECTIONS / ELEVATIONS
S11	CONTAINER SECTIONS / ELEVATIONS
S12	CONTAINER SECTIONS / ELEVATIONS
S13	FOOTING DETAILS
S14	HANDRAIL / GUARDRAIL DETAILS
S15	STRUCTURAL DETAILS
S16	STRUCTURAL DETAILS
S17	TOWER STAIR DETAILS
S18	CONTAINER OPENING DETAILS
S19	STRUCTURAL DETAILS
S20	STRUCTURAL DETAILS
AS-1	ARCHITECTURAL STRUCTURAL DETAILS
AS-2	ARCHITECTURAL STRUCTURAL DETAILS
AS-3	ARCHITECTURAL STRUCTURAL DETAILS
A1-0	TYPICAL CONTAINER DIMENSIONS
A1-1	FLOOR PLANS
A1-2	FLOOR PLANS
A1-3	FLOOR PLANS
A1-4	STAIR TOWER FLOOR PLANS
A1-5	STAIR TOWER FLOOR PLANS
A1-5A	STAIR TOWER FLOOR PLANS
A1-6	DETAILS
A1-7	DETAILS
A1-8	DETAILS / REFERENCE PHOTOS
A2-1	DOOR / WINDOW FRAME DETAILS
A2-2	DOOR / WINDOW FRAME DETAILS
A3-1	EXTERIOR ELEVATIONS
A3-2	EXTERIOR ELEVATIONS
A3-3	EXTERIOR ELEVATIONS
A3-4	EXTERIOR ELEVATIONS
A4-1	BUILDING SECTION
A4-2	BUILDING SECTION
A5-1	TOWER SECTION
A5-2	TOWER SECTION / ELEVATION
A5-3	STAIR SECTION / DETAILS
A5-4	STAIR SECTION / DETAILS
A9-1	SAFETY LADDER DETAILS
A9-2	DETAILS

SET NO:



SIGNATURE REQUIRED

**REVISIONS**

DATE	DESCRIPTION


SMITH DESIGN GROUP, INC.  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA

**INDEX OF SHEETS**

**ABBREVIATIONS LEGENDS**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>G-2</b>



SET NO:

ARCHITECT'S STAMP



SIGNATURE REQUIRED

REVISIONS

DATE	DESCRIPTION

SMITH DESIGN GROUP, INC.

206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:

BURN BUILDING

TITLE:

SITE PLAN - EXISTING

MODIFIED DATE:

JOB NO:



1730

ISSUED DATE:


SHEET:


SCHEMATIC DESIGN  
26 FEB 2018

SD-1



**SITE PLAN - EXISTING**  
SCALE: 1" = 30'-0"





SET NO:

ARCHITECT'S STAMP

SIGNATURE REQUIRED

LEGEND

15 FOOT SOIL BORING  
SB

REVISIONS


DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net


PROJECT:  
**BURN BUILDING**

TITLE:  
**SITE PLAN - PROPOSED**


MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: SCHEMATIC DESIGN 26 FEB 2018	SHEET: <b>SD-2</b>



**1**  
SD-2 **SITE PLAN - PROPOSED**  
SCALE: 1" = 30'-0"







SET NO:

ARCHITECT'S STAMP

SIGNATURE REQUIRED

REVISIONS

DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**


TITLE:  
**PARTIAL SITE PLAN - PROPOSED**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: SCHEMATIC DESIGN 26 FEB 2018	SHEET: <b>SD-3</b>


SET NO:




SIGNATURE REQUIRED




TEMPORARY CONSTRUCTION EXIT




RIP RAP DETAIL




TYPICAL RIP-RAP SECTION




SILT GRATE FOR DROP INLETS



RIP-RAP PLACEMENT DETAIL



SEDIMENT TRAP BOX



SILT FENCE DETAIL

NOTE: "RIP-RAP"  
 #1 RIP-RAP IS LARGE STONE HAVING A WEIGHT OF APPROXIMATELY 40 TO 60 LBS., THIS MATERIAL WILL SUFFICE TO VELOCITIES UP TO 6 FEET PER SECOND. TO MEET WEIGHT CRITERIA FOR HIGHER VELOCITIES RIP-RAP SHOULD BE GROUTED. FOR VELOCITIES FROM 6.5 TO 10 FT./SEC. A 12" DOUBLE LAYER OF GROUTED RIP-RAP SHOULD BE USED. FROM 10 TO 15 FT./SEC. A 18" TRIPLE LAYER OF RIP-RAP SHOULD BE USED. DIMENSIONS OF THIS BLANKET ARE TO BE 6 TIMES THE PIPE DIAMETER FOR THE LENGTH AND AT LEAST 3 TIMES THE DIAMETER FOR THE WIDTH, THIS WIDTH SHOULD BE UP THE SIDES OF THE SECTION AND SHOULD ACCOMMODATE THE 10 YEAR STORM LEVEL.

GRADED RIP-RAP STONE


D.O.T. NO.	SIZE INCHES (sq. opening)			COMMON USES
	MAX.	AVG.	MIN.	
TYPE 3	12	9	5	CREEK BANKS PIPE OUTLETS LAKES & SHORELINES RIVERS
TYPE 1	24	12	7	

Georgia Department of Transportation


FILTER BEDDING STONE

D.O.T. NO.	NOMINAL SIZES (inches)
3	2" - 1"
4	1 1/2" - 3/4"
5	1" - 1/2"
6	3/4" - 3/8"
57	1" - NO. 4

Georgia Department of Transportation



TEMPORARY SEDIMENT TRAP



PLAN  
NO SCALE

THE INSTALLATION OF EROSION CONTROL MEASURES AND PRACTICES SHALL OCCUR PRIOR TO AND CONCURRENT WITH LAND DISTURBING ACTIVITIES.

REVISIONS

DATE	DESCRIPTION

SMITH DESIGN GROUP, INC.  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**

TITLE:  
**SITE DETAILS**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: SCHEMATIC DESIGN 26 FEB 2018	SHEET: <b>SD-4</b>

**PROJECT DESCRIPTION**

This project site is approximately 2.49 acres of a total site acreage. Approximately 0.3 acres will be developed for a Burn Building for Fire Fighter training.

**VEGETATION:**

The site is presently paved. Topsoil will be stockpiled, and spread on areas to be vegetated. Trees outside the clearing limits will be protected from damage by appropriate markings. Supplemental vegetation will be established.

**EROSION CONTROL PROGRAM:**

Clearing will be kept to an absolute minimum. Vegetation and mulch will be applied to applicable areas immediately after grading is completed. Gravel will be applied to roadways as soon as grading is completed. Land disturbing activities will be scheduled to limit exposure of bare soils to erosive elements. Storm water management structures will be used to prevent erosion in areas of concentrated water flows. Erosion at the exits of all storm water structures will be prevented by the installation of storm drain outlet protection devices. Approximately 0.30 acres are to be disturbed as part of this project.

**SEDIMENT CONTROL PROGRAM:**

Sediment control will be accomplished by the installation of approximately 300 linear feet of silt fence.

**STANDARDS AND SPECIFICATIONS:**

All designs will conform to and all work will be performed in accordance with the 2003 EPA Construction General Permit and specific Sediment Control in Georgia, as well as all local ordinances.

**SAFETY PROTECTION:**

Construction activities will be performed in compliance with all applicable laws, rules, and regulations.

**MAINTENANCE PROGRAM:**

Sediment and erosion control measures will be inspected daily, and any damages observed will be repaired by the end of that day. Clean out of sediment control structures will be accomplished in accordance with the specifications and sediment disposal will be accomplished by spreading on the site. Sediment barriers will remain in place until sediment contributing areas are stabilized. Silt fences and other barriers will then be removed and the areas occupied by these structures planted. Guidelines for the maintenance of established vegetation will be provided to the owner when all disturbed areas are stabilized.

**GENERAL NOTES:**

- All work performed shall be in accordance with all applicable standards, specifications and practices as established by the local governing agency and City of LaGrange, County of Troup, State of Georgia.
- The Contractor shall meet all applicable Federal, State, and local codes, laws, regulations, and requirements.
- The Contractor is responsible for obtaining and maintaining all permit requirements. Prior to starting construction the general contractor shall be responsible to verify that all required permits and approvals have been obtained. No construction or fabrication of any item shall begin until the contractor has received all plans and any other documentation from all of the permitting and other authorities. Failure of the contractor to follow this procedure constitutes his financial responsibility for any subsequent modification of the work mandated by any regulatory authority.
- The general contractor shall be responsible for on site mulching of all existing vegetation and demolition of structures necessary to develop the site. The general contractor shall remove and recycle all trash and debris from the site upon completion of the project.
- Dimensions, building location and grading of this site are based on available information at the time layout. Deviations may be necessary in the field. Any such changes or conflicts between this plan and the field conditions are to be reported to the Architect in writing prior to starting construction.
- Do not scale from drawings.
- Contractor shall be responsible for verification of all property lines, setbacks and/or easements before beginning construction on all buildings and canopies.
- All new side slopes shall not exceed 1' vertical to 3' horizontal.
- All slopes are to be stabilized at earliest practical time.
- All areas shall be graded to provide positive drainage - into appropriate drainage inlets - and away from proposed building structures.
- All final grading shall be smooth and uniform.
- All disturbed uncovered areas shall be appropriately grassed or mulched 6" after topsoil is re-spread.
- All pavement surfaces that are to be removed, both concrete and asphalt, shall be saw cut in a straight line before pavement is removed.
- All building and painting subgrade areas shall be compacted in 8" layers to 95% of the maximum dry density at optimum moisture content as determined in accordance with ASTM D-1557 current edition.
- Commercial driveways are to be constructed in accordance with applicable standard regulations, standards and specifications of the City, County, or State Department of Transportation.
- For all paved surfaces, the following grades shall be maintained: 10% maximum and 1.5% minimum.

**GENERAL NOTES FOR SOIL EROSION AND SEDIMENT CONTROL**

- THE AREA TO BE DISTURBED ON THIS PROJECT IS APPROXIMATELY 0.30 ACRES.
- ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE INSTALLED IF DEEMED NECESSARY BY ON-SITE INSPECTION DUE TO CONDITIONS NOT SHOWN ON PLANS.
- FAILURE TO PROPERLY INSTALL AND MAINTAIN EROSION CONTROL PRACTICES MAY RESULT IN CONSTRUCTION BEING HALTED.
- EROSION CONTROL MEASURES WILL BE INSPECTED AT LEAST WEEKLY AND FOLLOWING RAINFALL AND REPAIRED BY CONTRACTOR OR OWNER.
- ALL SILT FENCING SHALL COMPLY WITH DEPARTMENT OF TRANSPORTATION STANDARDS AND SPECIFICATIONS. CONTRACTOR SHALL PROVIDE A LETTER OF WARRANTY THAT MATERIALS MEET THESE SPECIFICATIONS AND THAT THE FABRIC IS ON THE D.O.T. QUALIFIED PRODUCTS LIST (QPL) #36.
- TEMPORARY OR PERMANENT VEGETATIVE STABILIZATION SHALL BE PROVIDED WITHIN TWO WEEKS OF REACHING FINAL GRADE.
- STORM DRAIN SYSTEMS SHALL BE MAINTAINED CLEAN AND FREE OF SILT AND DEBRIS.
- A RESPONSE TO A NOTIFICATION OF NON-COMPLIANCE OR INADEQUATE MEASURES SHALL BE MADE WITHIN 3 WORKING DAYS AFTER RECEIVING SUCH NOTIFICATION.
- PERMANENT VEGETATION SHALL BE PROVIDED AT THE EARLIEST SUITABLE GROWING SEASON.
- CONSTRUCTION BEGIN DATE IS (VERIFY WITH OWNER).
- CONSTRUCTION COMPLETION DATE IS (VERIFY WITH OWNER).
- IMPLEMENTATION AND MAINTENANCE:
  - IMPLEMENTATION: NOTIFY THE DEPARTMENT OF ENGINEERING 24 HOURS PRIOR TO COMMENCING WORK.
    - NO CLEARING, GRADING, FILLING, OR OTHER LAND DISTURBING ACTIVITIES SHALL BE PERMITTED UNTIL APPROVED EROSION AND SEDIMENT CONTROL MEASURES HAVE BEEN INSTALLED, EXCEPT THOSE OPERATIONS NEEDED TO INSTALL SUCH MEASURES.
    - THESE EROSION AND SEDIMENT CONTROL MEASURES SHALL APPLY TO ALL FEATURES OF THE CONSTRUCTION SITE INCLUDING BUT NOT LIMITED TO STREET AND UTILITY INSTALLATIONS AS WELL AS TO THE PROTECTION OF INDIVIDUAL LOTS.
  - MAINTENANCE: ALL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE CONTINUOUSLY MAINTAINED BY THE CONTRACTOR OR PERMITEE DURING THE CONSTRUCTION PHASE OF THE DEVELOPMENT AND UNTIL PERMANENT STABILIZATION OF DITCHES, SHOULDERS, SLOPES AND ALL DISTURBED AREAS IS ACCOMPLISHED TO ELIMINATE THE NEED FOR THE TEMPORARY CONTROL MEASURES WHICH SHALL THEN BE REMOVED BY SAME.

**CONSTRUCTION SCHEDULE**

2018											
JAN	FEB	MAR	APR	MAY	JUNE	JULY	AUG	SEPT	OCT	NOV	DEC
			A								
			B								
			C	C							
			D								
			E								
					F	F	F				

- A. CLEARING AND GRUBBING
- B. SEDIMENT CONTROL MEASURES & INSTALLATION OF SILT FENCE
- C. ROUGH GRADING OF THE SITE
- D. TEMPORARY & PERMANENT VEGETATION OUTSIDE BUILDING AREA
- E. INSTALLATION OF STORM SEWER & EROSION CONTROL STRUCTURE
- F. BUILDING CONSTRUCTION

THE ESCAPE OF SEDIMENT FROM THE SITE SHALL BE PREVENTED BY THE INSTALLATION OF EROSION CONTROL MEASURES AND PRACTICES PRIOR TO, OR CONCURRENT WITH, LAND DISTURBING ACTIVITIES.

EROSION CONTROL MEASURES WILL BE MAINTAINED AT ALL TIMES. IF FULL IMPLEMENTATION OF THE APPROVED PLAN DOES NOT PROVIDE FOR EFFECTIVE EROSION CONTROL, ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE IMPLEMENTED TO CONTROL OR TREAT THE SEDIMENT SOURCE.

SET NO:

ARCHITECT'S STAMP



SIGNATURE REQUIRED

**REVISIONS**

DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**

206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:

**BURN BUILDING**

TITLE:

**SITE DETAILS**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: SCHEMATIC DESIGN 26 FEB 2018	SHEET: <b>SD-5</b>



GENERAL NOTES FOR SOIL EROSION AND SEDIMENT CONTROL

- The area to be disturbed on this project is 0.30 ACRES.
- Additional erosion and sediment control measures shall be installed if deemed necessary by site inspection due to conditions not shown on plans.
- Failure to properly install and maintain erosion control practices may result in construction being halted.
- Erosion control measures will be inspected at least weekly and following rainfall and repaired by contractor.
- All silt fences shall comply with Georgia Department of Transportation standards and specifications. Contractor shall provide a letter of warranty that materials meet these specifications and that the fabric is on the DOT qualified list (OPL) #36.
- Temporary or permanent vegetative stabilization shall be provided within two weeks of reaching final grade.
- Storm drain systems shall be maintained clean and free of silt and debris.
- A response to a notification of Non-Compliance or inadequate measures shall be made within 3 working days after receiving such notification.

- Construction begin date is (VERIFY WITH OWNER)
- Construction completion date is (VERIFY WITH OWNER)

14. IMPLEMENTATION AND MAINTENANCE:







- A. IMPLEMENTATION: Notify the Department of Engineering 24 hours prior to commencing work.
- No clearing, grading, filling or other land disturbing activities shall be permitted until approved erosion and sediment control measures have been installed, except those operations needed to install such measures.
  - These erosion and sediment control measures shall apply to all features of the construction site, including, but not limited to, street and utility installations as well as to the protection of individual lots.
- B. MAINTENANCE: All erosion and sediment control measures shall be continuously maintained by the contractor or owner during the construction phase of the development and until permanent stabilization of ditches, shoulders, slopes and all disturbed areas is accomplished to eliminate the need for the temporary control measures which shall then be removed by same.
- C. To facilitate acceptance of the streets and improvements prior to establishment of such permanent stabilization, a specific bond in the amount of a specific for the cost of maintaining the temporary control measures, including temporary grassing and establishing the permanent stabilization within a reasonable time relative to the growing season shall be provided with the request for acceptance.
- D. If full implementation of the approved plan does not provide for effective erosion control, additional erosion control measures shall be implemented to control or treat the sediment source.

**PERMANENT GRASSING SPECIFICATIONS**  
 MARCH 1 TO JUNE 30  
 BERMUDA, COMMON (HULLED) - 10 LBS/AC  
 OR  
 APRIL 1 TO JUNE 30  
 CENTIPEDE - BLOCK SOD ONLY

**TEMPORARY SEEDING SPECIFICATIONS**  
 AUGUST 1 TO APRIL 15  
 RYEGRASS, ANNUAL - 40 LBS/AC  
 OR  
 AUGUST 15 TO DECEMBER 30  
 RYE - 3 BU/AC  
 OR  
 APRIL 15 TO AUGUST 31  
 MILLET, PEARL - 50 LBS/AC

SPECIES	YEAR	ANALYSIS OR EQUIVALENT N-P-K	RATE	N DRESSING RATE
1. COOL SEASON GRASSES	FIRST MAINT	6-12-12	1500 lbs/AC	50-100 LBS/AC 1/2/
	SECOND MAINT	6-12-12	1000 lbs/AC	-
	THIRD MAINT	10-10-10	400 lbs/AC	30 LBS/AC
2. COOL SEASON GRASSES AND LEGUMES	FIRST MAINT	6-12-12	1500 lbs/AC	0-50 LBS/AC 1/
	SECOND MAINT	0-10-10	1000 lbs/AC	-
	THIRD MAINT	0-10-10	400 lbs/AC	-
3. GROUND COVERS	FIRST MAINT	10-10-10	1300 lbs/AC	-
	SECOND MAINT	10-10-10	1300 lbs/AC	-
	THIRD MAINT	10-10-10	1100 lbs/AC	-
4. PINE SEEDLINGS	FIRST	20-10-15	one 21 gram pellet per seedling placed in the closing hole	-
5. SHRUB LEEPEDEZA	FIRST MAINT	0-10-10	700 lbs/AC	-
	SECOND MAINT	0-10-10	700 lbs/AC	-
6. TEMP COVER CROP SEED DONE	FIRST	10-10-10	500 lbs/AC	30 LBS/AC 5/
7. WARM SEASON GRASSES	FIRST MAINT	6-12-12	1500 lbs/AC	50-100 LBS/AC 2/6/
	SECOND MAINT	6-12-12	800 lbs/AC	50-100 LBS/AC 2/
	THIRD MAINT	10-10-10	400 lbs/AC	30 LBS/AC
8. WARM SEASON GRASSES AND LEGUMES	FIRST MAINT	6-12-12	1500 lbs/AC	50 LBS/AC 6/
	SECOND MAINT	0-10-10	1000 lbs/AC	-
	THIRD MAINT	0-10-10	400 lbs/AC	-

- APPLY IN SPRING FOLLOWING SEEDING
- APPLY IN SPLIT APPLICATIONS WHEN HIGH RATES ARE USED
- APPLY IN THREE SPLIT APPLICATIONS
- APPLY WHEN PLANTS ARE PRUNED
- APPLY TO GRASS SPECIES ONLY
- APPLY WHEN PLANTS GROW TO A HEIGHT OF 2 TO 4 INCHES



**GA. UNIFORM CODING SYSTEM - STRUCTURAL PRACTICES**

CODE	PRACTICE	DETAIL	MAP SYMBOL	DESCRIPTION
Cd	CHECKDAMS			A small temporary barrier or dam constructed across a swale, drainage ditch or area of concentrated flow.
Ch	CHANNEL STABILIZATION			Improving, constructing or stabilizing an open channel, existing stream, or ditch.
Co	CONSTRUCTION EXIT			A crushed stone pad located at the construction site exit to provide a place for removing mud from tires thereby protecting public streets
Di	DIVERSION			An earth channel or dike located above, below or across a slope to divert runoff. This may be a temporary or permanent structure.
Dn1	TEMPORARY DOWNDRAIN STRUCTURE			A flexible conduit of heavy-duty fabric or other material designed to safely conduct surface runoff down a slope. This is temporary and inexpensive.
Dn2	PERMANENT DOWNDRAIN STRUCTURE			A paved chute, pipe, sectional conduit or similar material, temporary or permanent, designed to safely conduct surface runoff down a slope.
Ga	GABION			Rock filled baskets which are hand-placed into position forming soil stabilizing structures.
Gr	GRADE STABILIZATION STRUCTURE			Permanent structures installed to protect natural or artificial channels or waterways where otherwise the slope would be sufficient for the running water to form gullies.
Lv	LEVEL SPREADER			A structure to convert concentrated flow of water into less erosive sheet flow. This should be constructed only on undisturbed soils.
Rd	ROCK FILTER DAM			A permanent or temporary stone filter dam installed across small streams or drainage ways.
Re	RETAINING WALL			A wall installed to stabilize cut and fill slopes where maximum permissible slopes are not obtainable. Each situation will require special design.
Rt	RETROFITTING			A device or structure placed in front of a permanent stormwater detention pond outlet structure to serve as a temporary sediment filter.
Sd1	SEDIMENT BARRIER			A barrier to prevent sediment from leaving the construction site. It may be sandbags, bales of straw or hay, brush, logs and poles, gravel, or a sediment fence. The barriers are usually temporary and inexpensive.

CODE	PRACTICE	DETAIL	MAP SYMBOL	DESCRIPTION
Sd2	INLET SEDIMENT TRAP			An impounding area created by excavating around a storm drain drop inlet. The excavated area will be filled and stabilized on completion of construction activities.
Sd3	TEMPORARY SEDIMENT BASIN			A basin created by excavation or a dam across a waterway. The surface water runoff is temporarily stored allowing the bulk of the sediment to drop out. The basin is usually temporary but may be designed as a permanent pond or stormwater retention device.
Sr	TEMPORARY STREAM CROSSING			A temporary bridge or culvert-type structure protecting a stream or watercourse from damage by crossing construction equipment.
St	STORM DRAIN OUTLET PROTECTION			A paved or short section of riprap channel at the outlet of a storm drain system preventing erosion from the concentrated runoff.
Su	SURFACE ROUGHENING			A rough soil surface with horizontal depressions on a contour or slopes left in a roughened condition after grading.
Tp	TOPSOILING			The practice of stripping off the more fertile top soil, storing it, then spreading it over the disturbed area after the completion of construction activities.
Wt	VEGETATED WATERWAY OR STORMWATER CONVEYANCE CHANNEL			Paved or vegetative water outlets for diversions, terraces, berms, dikes or similar structures.

**VEGETATIVE PRACTICES**

CODE	PRACTICE	DETAIL	MAP SYMBOL	DESCRIPTION
Bf	BUFFER ZONE			An undisturbed natural "green belt" separating the land-disturbed site from surrounding property and bordering streams. It serves to reduce water velocity and remove some sediment. It is also at times a noise or "vision pollution" barrier.
Ds1	DISTURBED AREA STABILIZATION (WITH MULCHING ONLY)			Establishing temporary protection for disturbed areas where seedlings may not have a suitable growing season to produce an erosion retarding cover.
Ds2	DISTURBED AREA STABILIZATION (WITH TEMPORARY SEEDING)			Establishing a temporary vegetative cover with fast growing seedlings on disturbed areas.
Ds3	DISTURBED AREA STABILIZATION (WITH PERMANENT VEGETATION)			Establishing permanent vegetative cover such as trees, shrubs, vines, grasses, sod, or legumes on disturbed areas.
Du	DUST CONTROL ON DISTURBED AREAS			Controlling surface and air movement of dust on construction sites, roadways and similar sites.

SET NO:



SIGNATURE REQUIRED

**REVISIONS**

DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net


PROJECT: **BURN BUILDING**

TITLE: **SITE DETAILS**


MODIFIED DATE:      JOB NO: **1730**  
 ISSUED DATE:      SHEET: **SD-6**  
 SCHEMATIC DESIGN  
 26 FEB 2018





SET NO:



1 CLEANOUT AT END OF LINE  
SD-7 NOT TO SCALE




3 WATER MAIN ANCHOR DETAIL  
SD-7 NOT TO SCALE




		BLOCKING DIMENSIONS						
		TEES						
"X"		A	B	C	D	E	F	
12"	90° BEND	12"	1'-0"	3'-0"	4'-6"	3'-0"	4'-6"	3'-0"
		10"	1'-0"	3'-0"	4'-0"	2'-6"	4'-6"	3'-0"
		8"	1'-0"	3'-0"	3'-3"	2'-0"	4'-6"	3'-0"
		6"	1'-0"	3'-0"	2'-6"	1'-6"	4'-6"	3'-0"
		4"	1'-0"	3'-0"	1'-9"	1'-0"	4'-6"	3'-0"
10"	90° BEND	10"	1'-0"	2'-6"	4'-0"	2'-6"	4'-0"	2'-6"
		8"	1'-0"	2'-6"	3'-3"	2'-0"	4'-0"	2'-6"
		6"	1'-0"	2'-6"	2'-6"	1'-6"	4'-0"	2'-6"
8"	90° BEND	8"	0'-10"	2'-3"	3'-3"	2'-0"	3'-3"	2'-0"
		6"	0'-10"	2'-3"	2'-6"	1'-6"	3'-3"	2'-0"
		4"	0'-10"	2'-3"	1'-9"	1'-0"	3'-3"	2'-0"
6"	90° BEND	6"	0'-8"	1'-6"	2'-6"	1'-6"	2'-6"	1'-6"
		4"	0'-8"	1'-6"	1'-9"	1'-0"	2'-6"	1'-6"
		4"	0'-6"	1'-0"	1'-9"	1'-0"	1'-9"	1'-0"


		BLOCKING DIMENSIONS				
		TEES				
"X"		A	B	C	D	
12"	90° BEND	12"	12"	4'-3"	6'-0"	3'-3"
		10"	12"	3'-6"	5'-0"	2'-9"
		8"	10"	2'-9"	4'-0"	2'-3"
		6"	8"	2'-0"	3'-0"	1'-9"
10"	90° BEND	10"	12"	1'-9"	2'-6"	1'-0"
		4"	6"	1'-9"	2'-6"	1'-0"
8"	90° BEND	8"	12"	2'-9"	4'-3"	2'-6"
		10"	12"	1'-9"	3'-0"	2'-6"
		8"	10"	1'-6"	2'-6"	2'-0"
		6"	8"	1'-3"	2'-0"	1'-6"
6"	90° BEND	6"	8"	1'-3"	2'-0"	1'-6"
		4"	6"	1'-3"	2'-0"	0'-9"
4"	90° BEND	4"	12"	1'-9"	3'-0"	1'-9"
		10"	12"	1'-4"	2'-6"	1'-6"
		8"	10"	1'-0"	2'-0"	1'-3"
		6"	8"	0'-9"	1'-6"	1'-0"
4"	90° BEND	4"	6"	0'-9"	1'-0"	0'-9"




2 CLEANOUT UP TO GRADE  
SD-7 NOT TO SCALE



5 GAS PIPING UNDER WALK  
SD-7 NOT TO SCALE




7 FIRE HYDRANT (PROVIDED AND INSTALLED BY CITY OF LAGRANGE)  
SD-7 NOT TO SCALE



8 BASE AND PAVING DETAIL (NOT USED)  
SD-6 PATCHING DETAIL

FIRE HYDRANT				
DIMENSION DATA				
SIZE HYDRANT	A	B	C	D
4 1/4"	1 5/8"	16 3/4"	21 1/4"	35 1/8"
4 1/2"	1 5/8"	16 3/4"	21 1/4"	35 1/8"
5 1/4"	1 5/8"	18"	23"	38 1/8"
6 1/4"	2 1/8"	18 3/4"	23 3/4"	40 1/4"



9 VALVE BOX DETAIL  
SD-7 NOT TO SCALE

REVISIONS

DATE	DESCRIPTION

SMITH DESIGN GROUP, INC.  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT: BURN BUILDING

TITLE: SITE DETAILS

MODIFIED DATE:      JOB NO: 1730  
ISSUED DATE:      SHEET: SD-7  
SCHEMATIC DESIGN  
26 FEB 2018

**DRAIN INLET DIMENSIONS**

I.D. OF PIPE (INCHES)	H (MINIMUM)	NORMAL WIDTH		SKEWED WIDTH									
		W	W <sub>1</sub>	20'		30'		45'		60'		75'	
		W	W <sub>1</sub>	W	W <sub>1</sub>	W	W <sub>1</sub>	W	W <sub>1</sub>	W	W <sub>1</sub>	W	W <sub>1</sub>
≤12	4'-4"	3'-0"	3'-0"	6'-0"	6'-0"	4'-0"	4'-0"	3'-0"	3'-0"	3'-0"	3'-0"	3'-0"	3'-0"
15	4'-7"	3'-0"	3'-0"	6'-8"	6'-8"	4'-6"	4'-6"	3'-0"	3'-0"	3'-0"	3'-0"	3'-0"	3'-0"
18	4'-10"	3'-0"	3'-0"	7'-5"	7'-5"	5'-0"	5'-0"	3'-5"	3'-5"	3'-0"	3'-0"	3'-0"	3'-0"
24	5'-6"	3'-0"	3'-0"	6'-6"	6'-6"	4'-6"	4'-6"	3'-5"	3'-5"	3'-0"	3'-0"	3'-0"	3'-0"
30	6'-2"	3'-7"	3'-7"	7'-8"	7'-8"	5'-3"	5'-3"	4'-2"	4'-2"	3'-7"	3'-7"	3'-7"	3'-7"
36	6'-10"	5'-0"	5'-0"	8'-10"	8'-10"	6'-1"	6'-1"	5'-0"	5'-0"	5'-0"	5'-0"	5'-0"	5'-0"
42	7'-4"	5'-6"	5'-6"	10'-0"	10'-0"	6'-11"	6'-11"	5'-6"	5'-6"	5'-6"	5'-6"	5'-6"	5'-6"
48	8'-0"	6'-2"	6'-2"	11'-2"	11'-2"	7'-9"	7'-9"	6'-2"	6'-2"	6'-2"	6'-2"	6'-2"	6'-2"
54	8'-6"	6'-8"	6'-8"	12'-4"	12'-4"	8'-7"	8'-7"	6'-10"	6'-10"	6'-8"	6'-8"	6'-8"	6'-8"
60	9'-2"	7'-4"	7'-4"	13'-6"	13'-6"	9'-5"	9'-5"	7'-6"	7'-6"	7'-4"	7'-4"	7'-4"	7'-4"

NOTES:

1. THE MINIMUM "H" SHOWN APPLIES WHERE DEPTH OF PAVEMENT IS 12" OR LESS.
2. MINIMUM "H" WILL BE CONTROLLED BY THE SIZE OF THE LARGEST CONNECTING PIPE.
3. IT IS NOT NECESSARY THAT BOX ENCLOSURES BE CONSTRUCTED SQUARE. W & W<sub>1</sub> WILL VARY ACCORDING TO PIPE SIZE.

**DRAIN INLET WALLS**



DEPTH	T (MINIMUM)
0' TO 10'	8"
10' TO 20'	12"
20' TO 30'	16"

**DRAIN INLET BOTTOMS**




W & W <sub>1</sub>	Y
3'-0" THRU 4'-6"	6" NON-REINFORCED
4'-7" THRU 7'-9"	10" NON-REINFORCED
7'-10" THRU 13'-6"	12" NON-REINFORCED

**SCHEDULE OF DRAIN INLETS**

D.I. NUMBER	DETERMINING PIPE SIZE	GRATE SIZE		ELEVATIONS	
		A	B	RIM	BOTTOM
1		24"	24"		
2		24"	24"		
3		24"	24"		



NOTE:  
The dimensions for the skewed width as shown in the table are for 8" wall. If 12" or 16" wall is required the dimensions for the skewed width will be in accordance with the above layout. Minimum W or W<sub>1</sub> dimension is to be used according to the size of the long or cross drain pipe.



1 SD-8 DRAIN INLET DETAILS

SET NO:

ARCHITECT'S STAMP



SIGNATURE REQUIRED

REVISIONS

DATE	DESCRIPTION

SMITH DESIGN GROUP, INC.

206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:

BURN BUILDING

TITLE:

SITE DETAILS

MODIFIED DATE:

JOB NO:

1730

ISSUED DATE:

SCHEMATIC DESIGN

26 FEB 2018

SHEET:

SD-8

# CONSTRUCTION NOTES

## CONTAINER FABRICATION NOTES

- CONTAINERS USED SHALL BE ISO COMPLIANT AND SHALL HAVE NO MORE THAN MINOR SURFACE RUST. IT IS RECOMMENDED THAT THE CONTAINERS BE INSPECTED BY THE ENGINEER OR OTHER QUALIFIED AGENT PRIOR TO FABRICATION. CONTAINERS SHALL BE CLASSIFIED BY THE CONVENTION FOR SAFE CONTAINERS (CSCO) AS "CARGO WORTHY GRADE A". THE FABRICATED CONTAINER MUST BE INSPECTED AND CERTIFIED BY AN THIRD PARTY INSPECTOR APPROVED BY THE GEORGIA DEPARTMENT OF COMMUNITY AFFAIRS.
- CUTTING OF THE CONTAINER SIDES SHALL BE WITH A PLASMA TORCH, ACETYLENE TORCHES ARE NOT ACCEPTABLE.
- ALL WELDS SHALL BE WITH AN E70XX ELECTRODE AND SHALL BE  $\frac{3}{8}$ " UNLESS OTHERWISE NOTED.
- WELDING SHALL BE IN ACCORDANCE WITH AWS STANDARDS.
- THE FABRICATOR SHALL BE RESPONSIBLE FOR ALL NECESSARY SHORING AND BRACING OF THE CONTAINERS DURING TRANSPORT AND ERECTION.

## DESIGN CRITERIA

### LOADS:

- ROOF: LIVE LOAD = 20 PSF  
DEAD LOAD = 10 PSF  
SNOW LOAD = 40 PSF      ROOF DECK LOAD = 50 PSF

- FLOORS: LIVE LOAD = 50 PSF  
DEAD LOAD = 10 PSF  
PARTITION LOAD = 100 PLF

- STAIRS AND LANDINGS = 100 PSF

- WIND LOADS:  
CALCULATED WIND DESIGN IS DONE UNDER THE 2012 INTERNATIONAL BUILDING CODE USING 115 MPH (3 SEC GUST) EXPOSURE "B", IMPORTANCE FACTOR I = 1.0. USING ASCE 7-10.

- SEISMIC DESIGN:  
Ss: 0.150  
S1: 0.081  
SITE CLASS D  
SOURCE: ASCE/USGS DESIGN MAPS

### DEFLECTION:

- ROOFS: L/180

- FLOORS: L/480

### GOVERNING CODE AND DESIGN METHODOLOGY

- 2012 INTERNATIONAL BUILDING CODE WITH GEORGIA AMENDMENTS
- AMERICAN CONCRETE ASSOCIATION ACI 318
- AMERICAN INSTITUTE OF STEEL CONSTRUCTION, MANUAL OF STEEL CONSTRUCTION, 14TH EDITION, LOAD RESISTANCE FACTOR DESIGN.
- AMERICAN IRON AND STEEL INSTITUTE, AISI S100-2007, NORTH AMERICAN SPECIFICATION FOR THE DESIGN OF COLD FORMED STEEL STRUCTURAL MEMBERS.

## PREFABRICATED WOOD TRUSS NOTES

- TRUSSES SHALL BE SPACED AS SHOWN ON PLANS.
- SEE PLANS FOR TRUSS LOCATIONS AND SPANS.
- ACTUAL TRUSS SPACING SHALL BE USED TO DETERMINE UNIFORM LOADS PER FOOT.
- TRUSSES SHALL BE DESIGNED AND FABRICATED BY THE TRUSS MANUFACTURER.
- DESIGN SHALL CARRY THE SEAL OF AN ENGINEER REGISTERED IN THE STATE OF GEORGIA.
- CONFIGURATIONS AND SIZE OF WEB MEMBERS SHALL BE DETERMINED BY THE TRUSS MANUFACTURER.
- SHOP DRAWINGS AND CALCULATIONS FOR TRUSSES SHALL BE SUBMITTED FOR APPROVAL PRIOR TO FABRICATION.
- TOP CHORD DEAD LOAD SHOWN ABOVE INCLUDES 3 PSF FOR TRUSS SELF WEIGHT.
- MAXIMUM LIVE LOAD DEFLECTION FOR ROOF TRUSSES - L/240.
- LOADS ABOVE SHALL BE UTILIZED IN THE DESIGN OF GIRDERS, TRUSSES AND LAMINATED BEAMS, AS REQUIRED.
- PERMANENT BRACING OF ROOF TRUSSES, AS REQUIRED BY STRUCTURAL DESIGN OF THE TRUSSES, AND PERMANENT BRACING AS REQUIRED FOR STABILITY OF THE TRUSS SYSTEM UNDER ALL GRAVITY AND LATERAL LOADINGS, SHALL BE INDICATED AND FULLY DETAILED ON THE SHOP DRAWINGS.
- THE CONTRACTOR SHALL PROVIDE ADEQUATE TEMPORARY BRACING FOR THE TRUSSES DURING ERECTION, IN ACCORDANCE WITH TRUSS PLATE INSTITUTE "HANDLING, INSTALLING AND BRACING METAL PLATE CONNECTED WOOD TRUSSES, 1987".
- TRUSS DESIGN SHALL ACCOUNT FOR LOAD IMPOSED UPON TRUSSES BY WEIGHT OF MECHANICAL UNITS AS SHOWN ON MECHANICAL DRAWINGS.
- ALL PRE-ENGINEERED TRUSS SHOP DRAWINGS SHALL BE AVAILABLE ON THE JOB SITE, STAMPED, REVIEWED AND APPROVED BY THE STRUCTURAL ENGINEER OF RECORD.
- ALL WELDING (BOLTS, HANGERS, STRAPS, ETC.) REQUIRED FOR CONNECTIONS BETWEEN PRE-ENGINEERED TRUSSES SHALL BE DESIGNED AND SPECIFIED BY THE TRUSS DESIGN ENGINEER.

## SOIL

- FOR DESIGN PURPOSES, THE SOIL IS ASSUMED TO HAVE A BEARING CAPACITY OF 2000 PSF. BECAUSE OF THE POSSIBILITY OF EXPANSIVE SOILS, IT IS RECOMMENDED THAT A GEOTECHNICAL ENGINEER EVALUATION THE SOILS BEFORE POURING THE FOUNDATIONS.
- THE FOUNDATION EXCAVATION SHALL BE IN NATURAL SOIL. FILL MATERIAL, TRASH, TOPSOIL, BURIED TREES AND LIMBS, AND DELETERIOUS MATERIAL IS FORBIDDEN.
- IN THE EVENT THAT UNSUITABLE MATERIAL IS ENCOUNTERED, THE STRUCTURAL ENGINEER IS TO BE NOTIFIED.
- THE FOUNDATION WILL NOT BE POURED ON PIERS WITHOUT FIRST CONSULTING THE STRUCTURAL ENGINEER. CONCRETE AUGER PIERS DEEPER THAN 5' WILL NOT BE ALLOWED BY THE STRUCTURAL ENGINEER UNDER ANY CIRCUMSTANCES. PIERS THAT MUST BE DEEPER THAN 5' WILL ONLY BE STEEL HELICAL PIERS AS MANUFACTURED BY EARTH CONTACT PRODUCTS OR CHANCE PIERS.
- IF FILL IS REQUIRED, THE FOUNDATIONS MAY BE POURED ON FILL MATERIAL WITH APPROVAL OF THE STRUCTURAL ENGINEER PROVIDED THE FILL MATERIAL IS PROPERLY COMPACTED AND TESTED.

## CONCRETE

- CONCRETE SHALL BE MIXED OFFSITE AT A BATCH PLANT AND THE MIX SHALL BE DESIGNED IN ACCORDANCE WITH ACI 301, SPECIFICATIONS FOR STRUCTURAL CONCRETE.
- PLACEMENT OF CONCRETE SHALL BE IN ACCORDANCE WITH ACI 301 AND ACI 318.
- REINFORCEMENT FOR FOUNDATIONS SHALL BE GRADE 60 AND SUBWALLS GRADE 60.
- DO NOT ADD WATER TO THE CONCRETE MIX ON THE JOBSITE. CONCRETE THAT IS UNSUITABLE FOR POURING SHALL BE REJECTED, NOT WATERED DOWN TO MAKE IT MORE WORKABLE.
- CURING OF THE CONCRETE SHALL BE IN ACCORDANCE WITH SECTION 5.3.6.4 OF ACI 301 UTILIZING SPRAY CURING, WET MATS, CURING COMPOUND, OR OTHER METHODS CALLED OUT IN ACI 301.
- UNLESS NOTED OTHERWISE ON THE PLANS, CONCRETE SHALL HAVE AN  $f_c$  OF 3000 PSI.
- DO NOT PLACE CONCRETE WHEN TEMPERATURES ARE BELOW FREEZING UNLESS FOLLOWING ACI 306. COLD WEATHER CONCRETING. WHEN AMBIENT TEMPERATURES EXCEED 80° F AND EVAPORATION RATE EXCEEDS 1 kg/m<sup>2</sup>/h CONCRETE SHALL BE PLACED IN ACCORDANCE WITH ACI 305, SPECIFICATION FOR HOT WEATHER CONCRETING.
- ALL CONCRETE EXPOSED TO FREEZE/THAW CYCLES SHALL BE AIR ENTRAINED.
- THE FOLLOWING SAMPLES SHALL BE TAKEN FROM THE CONCRETE DURING PLACEMENT ACCORDING TO ASTM C31, STANDARD PRACTICE FOR MAKING AND CURING CONCRETE TEST SPECIMENS IN THE FIELD  
2 CYLINDERS: BREAK AT 7 DAYS  
2 CYLINDERS: BREAK AT 28 DAYS  
2 CYLINDERS: HOLD IN RESERVE  
SPECIMENS SHALL BE TAKEN FOR EACH DAY OF POURING WITH A MINIMUM OF A SAMPLE FOR EVERY 150 CUBIC YARDS.

## METAL BAR GRATING

METAL BAR GRATING SHALL COMPLY WITH ANSI/NAAM MBG 531-17, METAL BAR GRATING MANUAL, AND SHALL BE OF THE SIZE NOTED ON THE PLANS.

## REINFORCING STEEL

- ALL BAR REINFORCING STEEL SHALL CONFORM TO ASTM A615
- ALL REINFORCING WIRE SHALL CONFORM TO ASTM A185

## STRUCTURAL STEEL

- ALL STRUCTURAL STEEL SHALL CONFORM TO ASTM A990 FOR BEAMS AND ANGLES AND ASTM A500 GRADE C FOR TUBULAR MEMBERS. PLATES SHALL BE THE GRADE NOTED ON CONNECTION DRAWINGS.
- STRUCTURAL STEEL CONNECTIONS WHERE NOT SPECIFICALLY DETAILED ON THE DRAWING SHALL BE DESIGNED BY THE STEEL FABRICATOR IN COMPLIANCE WITH REQUIREMENTS OF THE AISC MANUAL OF STEEL CONSTRUCTION. STEEL CONNECTIONS DESIGNED BY THE FABRICATOR SHALL BE REVIEWED AND APPROVED BY A PROFESSIONAL ENGINEER RETAINED BY THE FABRICATOR. EXACT DIMENSIONS OF STEEL CONNECTIONS FOR FABRICATION ON DRAWING DETAILS SHALL BE DETERMINED BY THE FABRICATOR AND SUBMITTED TO THE ENGINEER FOR APPROVAL.
- ALL WELDING SHALL BE DONE WITH E70XX ELECTRODES AND SHALL BE  $\frac{3}{8}$ " THROAT WIDTH UNLESS OTHERWISE NOTED.
- ANCHOR AND CONNECTION BOLTS SHALL CONFORM TO ASTM A325 UNLESS OTHERWISE NOTED ON DRAWINGS.

## SHOP DRAWINGS:

- SHOP DRAWINGS SHALL INCLUDE MEMBER SIZES, DIMENSIONS, AND CONNECTION DETAILS TO INCLUDE BOLT SIZES AND WELD SYMBOLS. ALL SHOP DRAWINGS SHALL BE PROVIDED WITH APPROVAL BY A PROFESSIONAL ENGINEER.
- SHOP DRAWINGS SHALL BE PROVIDED FOR THE FOLLOWING:
  - STAIRWAYS
  - PLATFORMS
  - HANDRAILS AND GUARD RAILS
  - STEEL CONNECTIONS

## TOWER FOUNDATION:

- THE TOWER FOUNDATIONS AND BASEPLATES SHALL BE DESIGNED BY THE CONTRACTOR UNDER THE SUPERVISION OF A LICENSED PROFESSIONAL ENGINEER.
- LOADS FOR FOUNDATIONS CAN BE OBTAINED FROM THE ENGINEER

## THIRD PARTY (SPECIAL) INSPECTIONS:

A. THE FOLLOWING INSPECTIONS SHALL BE PERFORMED UNDER A QUALIFIED THIRD PARTY INSPECTOR. THE THIRD PARTY INSPECTOR SHALL BE UNDER THE SUPERVISION OF A LICENSED PROFESSIONAL ENGINEER IN GEORGIA, AND SHALL BE QUALIFIED AS THE FOLLOWING:

- STEEL INSPECTIONS: THE INSPECTOR SHALL BE QUALIFIED AS A CERTIFIED WELD INSPECTOR (CWI) UNDER THE AMERICAN WELDING SOCIETY.

- CONCRETE INSPECTIONS: THE INSPECTOR SHALL BE QUALIFIED AS A CONCRETE CONSTRUCTION SPECIAL INSPECTOR UNDER THE AMERICAN CONCRETE INSTITUTE (ACI).

- SOIL BEARING CAPACITY VERIFICATION: THE SOIL BEARING CAPACITY SHALL BE VERIFIED BY A LICENSED PROFESSIONAL ENGINEER THAT IS A PRACTICING GEOTECHNICAL ENGINEER, OR BY A LICENSED PROFESSIONAL GEOLOGIST.

B. THE FOLLOWING INSPECTIONS ARE REQUIRED FOR STEEL:

- BOLTED CONNECTIONS: OBSERVATION OF PLACEMENT AND TIGHTENING (TURN OF THE NUT)
- WELDED CONNECTIONS ON TOWER: 100% OBSERVATION BY ULTRASONIC OR MAGNETIC PARTICLE INSPECTION.
- WELDED CONNECTIONS ON CONTAINERS: VISUAL OBSERVATION

C. THE FOLLOWING INSPECTIONS ARE REQUIRED FOR FOUNDATIONS:

- OBSERVATION OF THE EXCAVATION AND VERIFY BEARING CAPACITY BY USE OF ASTM STP 399, "DYNAMIC CONE FOR SHALLOW IN-SITU PENETRATION TESTING."
- OBSERVATION OF DIMENSIONS OF FOUNDATIONS AND PLACEMENT OF REINFORCING.
- CONCRETE TESTING AS DESCRIBED UNDER THE "CONCRETE" SECTION OF THE NOTES.
- TOWER FOUNDATIONS SHALL BE INSPECTED AS REQUIRED BY THE DELEGATED DESIGN.

## General Notes



No.	Revision/Issue	Date

**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE 11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900



**DRAWN:**  
 AB

**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA

<b>Project</b> Preliminary Plans	<b>Sheet</b>
<b>Date</b> 02/26/18	<b>S1</b>
<b>Scale</b> N/A	

General Notes

TOWER FOUNDATION TO BE DESIGNED BY FOUNDATION CONTRACTOR



No.	Revision/Issue	Date

**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900





**DRAWN:**  
 AB

**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA

<b>Project</b> Preliminary Plans	<b>Sheet</b> <b>S2</b>
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	

① FOUNDATION  
 3/8" = 1'-0"





General Notes


No.	Revision/Issue	Date


**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900

**DRAWN:**  
 AB


**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA

<b>Project</b> Preliminary Plans	<b>Sheet</b> <b>S3</b>
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	







1 TOWER SOUTH  
1/8" = 1'-0"



2 TOWER EAST  
1/8" = 1'-0"



3 TOWER NORTH  
1/8" = 1'-0"



4 TOWER WEST  
1/8" = 1'-0"

General Notes




No.	Revision/Issue	Date

**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE 11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900


**DRAWN:**  
 AB

**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA

Project Preliminary Plans	Sheet
Date 02/26/18	S4
Scale N/A	




① TOWER COLUMN LAYOUT  
1/2" = 1'-0"



② TOWER MOMENT FRAM/COLUMN  
LAYOUT  
1/2" = 1'-0"

General Notes



No.	Revision/Issue	Date

Firm Name and Address

RUNCON, INC.  
930 NEW HOPE ROAD, STE11-145  
LAWRENCEVILLE, GA 30045  
678-225-4900

DRAWN:  
AB


Project Name and Address

BURN BUILDING  
LAGRANGE, GA


Project  
Preliminary Plans  
Date  
02/26/18  
Scale  
N/A

Sheet  
S5






1 STAIR TOWER FRAMING TYP.  
1/2" = 1'-0"



2 RAPPILING DECK FRAMMING  
1/2" = 1'-0"



No.	Revision/Issue	Date


**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE 11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900

**DRAWN:**  
 AB


**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA

<b>Project</b> Preliminary Plans	<b>Sheet</b> S6
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	





1 Level 1  
1/4" = 1'-0"



2 Level 2  
1/4" = 1'-0"

General Notes


No.	Revision/Issue	Date


**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900

**DRAWN:**  
 AB


**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA

<b>Project</b> Preliminary Plans	<b>Sheet</b>  <b>S7</b>
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	






① Level 3  
1/4" = 1'-0"



③ Level 4  
1/4" = 1'-0"

General Notes



No.	Revision/Issue	Date


**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900

**DRAWN:**  
 AB

**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA


<b>Project</b> Preliminary Plans	<b>Sheet</b> <b>S8</b>
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	

CONTAINER 1



① CONTAINER 1 MODIFICATION  
1/4" = 1'-0"

CONTAINER 2



② CONTAINER 2 MODIFICATION  
1/4" = 1'-0"



No.	Revision/Issue	Date


**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900

**DRAWN:**  
 AB


**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA

<b>Project</b> Preliminary Plans	<b>Sheet</b> S9
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	


CONTAINER 3




FRONT (53' HC)



RIGHT SIDE (53' HC)




LEFT SIDE (53' HC)




BACK (53' HC)

① CONTAINER 3 MODIFICATION  
1/4" = 1'-0"


CONTAINER 4




FRONT (53' HC)



RIGHT SIDE (53' HC)



LEFT SIDE (53' HC)



BACK (53' HC)

② CONTAINER 4 MODIFICATION  
1/4" = 1'-0"



No.	Revision/Issue	Date

**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900


**DRAWN:**  
 AB

**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA


<b>Project</b> Preliminary Plans	<b>Sheet</b> <b>S10</b>
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	




CONTAINER 5




FRONT (53' HC)



RIGHT SIDE (53' HC)




LEFT SIDE (53' HC)




BACK (53' HC)

① CONTAINER 5 MODIFICATION  
1/4" = 1'-0"


CONTAINER 6




FRONT (53' HC)



RIGHT SIDE (53' HC)



LEFT SIDE (53' HC)



BACK (53' HC)

② CONTAINER 6 MODIFICATION  
1/4" = 1'-0"

General Notes



No.	Revision/Issue	Date


**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900

**DRAWN:**  
 AB


**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA

<b>Project</b> Preliminary Plans	<b>Sheet</b>  <b>S11</b>
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	


CONTAINER 7




FRONT (53' HC)



RIGHT SIDE (53' HC)



LEFT SIDE (53' HC)



BACK (53' HC)

① CONTAINER 7 MODIFICATION  
1/4" = 1'-0"

General Notes



No.	Revision/Issue	Date

**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900


**DRAWN:**  
 AB

**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA


**Project**  
 Preliminary Plans  
**Date**  
 02/26/18  
**Scale**  
 N/A

**Sheet**  
 S12


General Notes




① FOOTER 1  
1 1/2" = 1'-0"




③ FOOTER 3  
1 1/2" = 1'-0"



② FOOTER 2  
1 1/2" = 1'-0"



④ SLAB TURNDOWN TYP.  
1 1/2" = 1'-0"



No.	Revision/Issue	Date


**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE 11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900

**DRAWN:**  
 AB


**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA

<b>Project</b> Preliminary Plans	<b>Sheet</b> <b>S13</b>
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	







① TOP RAIL STIFFENING  
6" = 1'-0"



② ROOF GUARDRAIL - TOP OF CONTAINER  
1 1/2" = 1'-0"



③  
1 1/2" = 1'-0"



④ STAIR TOWER HANDRAILS  
1 1/2" = 1'-0"









No.	Revision/Issue	Date

**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900

**DRAWN:**  
 AB

**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA


<b>Project</b> Preliminary Plans	<b>Sheet</b>  <b>S14</b>
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	




MOMENT FRAME FLANGE CONNECTION

MOMENT FRAME WEB CONNECTION


1 MOMENT FRAME CONNECTION  
1" = 1'-0"



TYPICAL CROSS BRACE TO FLANGE



TYPICAL CROSS BEAM CONNECTION AT CROSS BRACE



TYPICAL CROSS BRACE TO WEB

2 CROSS BRACE CONNECTION TYP.  
1" = 1'-0"

General Notes




No.	Revision/Issue	Date

**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900


**DRAWN:**  
 AB

**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA


Project Preliminary Plans	Sheet
Date 02/26/18	S15
Scale N/A	



1 TYPICAL CONTAINER ROOF DECK  
6" = 1'-0"




2 BOTTOM RAIL STIFFENING FOR COLUMN  
6" = 1'-0"




COLUMN SPLICE FLANGE CONNECTION

3 COLUMN SPLICE  
1" = 1'-0"




COLUMN SPLICE WEB CONNECTION



4 JOIST MOUNT  
1 1/2" = 1'-0"

General Notes



No.	Revision/Issue	Date


**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900

**DRAWN:**  
 AB


**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA

<b>Project</b> Preliminary Plans	<b>Sheet</b>  <b>S16</b>
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	





1 STAIRS  
1" = 1'-0"



No.	Revision/Issue	Date


**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE 11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900

**DRAWN:**  
 AB


**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA

<b>Project</b> Preliminary Plans	<b>Sheet</b> <b>S17</b>
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	


General Notes



③ CONTAINER WINDOW FRAMING TYP.  
1 1/2" = 1'-0"



② CONTAINER DOOR FRAMING TYP.  
1 1/2" = 1'-0"




No.	Revision/Issue	Date

**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900


**DRAWN:**  
 AB

**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA


<b>Project</b> Preliminary Plans	<b>Sheet</b> <b>S18</b>
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	



1 BOTTOM RAIL STIFFENING FOR STAIR  
OPENING  
6" = 1'-0"



2 CORNER POST STIFFENING  
3" = 1'-0"



3 BASEPLATE  
3" = 1'-0"

General Notes



No.	Revision/Issue	Date

**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900


**DRAWN:**  
 AB

**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA

<b>Project</b> Preliminary Plans	<b>Sheet</b>  <b>S19</b>
<b>Date</b> 02/26/18	
<b>Scale</b> N/A	



**DOUBLE CONE TWO POSITION TWISTLOC WITH "PRELOC" FEATURE (AE10000A-1GA)**  
 Cage Code: 65059 | Drawing No: SAE10000A-1GA Revision: - | Sheet: 1 of 1  
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES  
 SEE ELECTRONIC PARTS LIST FOR BILL OF MATERIALS




- NOTES:
1. MIN. BREAKING LOADS TENSION 112,000 LBS / 94,000 LBS
  2. PRE-LOCKING FUNCTION OF LOWER CONE
  3. LEFTHAND LOCKING AS STANDARD, RIGHTHAND LOCKING ON REQUEST
  4. HOTDIP GALVANIZED
  5. CALCULATED WEIGHT: 12.1 LBS
  6. INTERNAL LOCKING MECHANISM MADE OF STAINLESS STEEL COMPONENTS

To avoid lifter failure, potential death and property damage, never exceed WLL/W or Working Load Limit.  
 This document contains the proprietary information of Tandemloc, Inc. and your access and use shall be, and is at all times, pursuant to and limited by the Tandemloc, Inc. Terms of Use.  
 You shall not, and shall not encourage, assist, or authorize another party to copy, distribute, publicly display, modify, reverse engineer, decompile, or take any other action to reproduce or replicate this document or the information contained herein. © Copyright 2012 by Tandemloc, Inc.  
 Dimensions are subject to manufacturing tolerance and change.

**TANDEMLOC INC.**  
 Email: [info@tandemloc.com](mailto:info@tandemloc.com) • [www.tandemloc.com](http://www.tandemloc.com)  
 824 Highway 101 • Havelock, NC 28532  
 TEL: 1.800.258.7324 (252.447.7155)  
 FAX: 1.800.892.3273 (252.447.5502)


Tandemloc designs, manufactures and tests lifting, securing and mobilizing components for all industries. See our website for details and important safety information.  
 Read all safety labels and instructions prior to use. Product to be used by qualified personnel only

① VERTICAL TANDEMLOC  
 3/16" = 1'-0"




③ CORNER CASTING CONNECTION  
 3" = 1'-0"

**UNIVERSAL BRIDGE CLAMP FOR MOBILE FACILITIES (P0500AC-1PZ)**  
 Cage Code: 65059 | Drawing No: SP0500AC | Revision: E | Sheet: 1 of 1  
 UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES



PARTNO.	L	S	WEIGHT
P0500AC-1PZ	19"	12"	12.9 LB.
P0500AC-1PZ-L9	9"	2"	10.7 LB.

- NOTES:
1. PIN: P0500AC-1PZ UNIVERSAL BRIDGE CLAMP (L=19")  
 PIN: P0500AC-1PZ-L9 UNIVERSAL BRIDGE CLAMP (L=9")
  2. FOR CLAMPING ANY APERTURE OF TOP OR BOTTOM ISO 1161 CORNER FITTINGS UP TO "S" INCHES APART.
  3. TO OPERATE, ADJUST SPAN OF ITEM 1 TO PRESENT SPAN BETWEEN CORNER FITTINGS BY TURNING ITEM 3 COUNTER-CLOCKWISE TO LENGTHEN AND CLOCKWISE TO SHORTEN. PLACE ITEMS 1 AND 2 INTO THE DESIRED APERTURES OF THE CORNER FITTINGS. TURN HEX ON ITEM 3 USING A 25" DRIVE UNTIL CONTACTS ARE AT DESIRED SPACING.
  4. MAX SAFE WORK LOAD WITHOUT YIELD: 200 FT LBS OF TORQUE (20,000 LBS TENSION) WHEN ENGAGED TO THE RIGIDLY AFFIXED CORNERS OF ISO FREIGHT CONTAINERS.




REV	DESCRIPTION	DATE	APPROVED
A	ADDED 2D DWG & DIM DATA.	5/1/08	MD
B	ADDED WEIGHT	5/1/08	MD
C	LOAD RATING WAS "SWL: 200 FT. LB. OF TORQUE 20,000 LB TENSION"	10/19/07	MD
D	ADDED -12N-L9 PART WITH DATA	11/13/07	MD
E	-1PZ & -1PZ-L9 WAS SHOWN AS -12N & -12N-L9 RESPECTIVELY IN 3 PLACES	01/15/08	WT

To avoid lifter failure, potential death and property damage, never exceed WLL/W or Working Load Limit.  
 This document contains the proprietary information of Tandemloc, Inc. and your access and use shall be, and is at all times, pursuant to and limited by the Tandemloc, Inc. Terms of Use.  
 You shall not, and shall not encourage, assist, or authorize another party to copy, distribute, publicly display, modify, reverse engineer, decompile, or take any other action to reproduce or replicate this document or the information contained herein. © Copyright 2012 by Tandemloc, Inc.  
 Dimensions are subject to manufacturing tolerance and change.

**TANDEMLOC INC.**  
 Email: [info@tandemloc.com](mailto:info@tandemloc.com) • [www.tandemloc.com](http://www.tandemloc.com)  
 824 Highway 101 • Havelock, NC 28532  
 TEL: 1.800.258.7324 (252.447.7155)  
 FAX: 1.800.892.3273 (252.447.5502)

Tandemloc designs, manufactures and tests lifting, securing and mobilizing components for all industries. See our website for details and important safety information.  
 Read all safety labels and instructions prior to use. Product to be used by qualified personnel only

② HORIZONTAL TANDEMLOC  
 3/16" = 1'-0"




No.	Revision/Issue	Date

**Firm Name and Address**  
 RUNCON, INC.  
 930 NEW HOPE ROAD, STE 11-145  
 LAWRENCEVILLE, GA 30045  
 678-225-4900

**DRAWN:**  
 AB

**Project Name and Address**  
 BURN BUILDING  
 LAGRANGE, GA


Project	Sheet
Preliminary Plans	S20
Date	02/26/18
Scale	N/A




1 FOUNDATION PLAN  
 AS-1 SCALE: 1/4" = 1'-0"

KEYNOTES  
 ① INTERIOR OF ROOM IS LINED WITH FIRE AND WATER RESISTANT INSULATION AND COVERED WITH 1/4" PLATE STEEL PLATES OR STAINLESS STEEL PANELS. SEE ADDITIVE ALTERNATIVES. INSTALL ON ALL FLOORS, CEILINGS AND WALLS IN BURN ROOMS.

SET NO:



DESIGN LOADS  
 ROOF LIVE LOAD: 100PSF  
 FLOOR LIVE LOAD: 100 PSF  
 WIND LOAD: LOCAL  
 SEISMIC DESIGN CAT: LOCAL  
 SITE CLASS: LOCAL  
 DESIGN CODE: LOCAL & NFPA 1402

- WALL TYPES
- 1 BURN ROOM INTERIOR WALL (SEE 7/A1-6)
  - 2 BURN ROOM EXTERIOR WALL, CEILING AND FLOOR SEE DETAIL 2/A1-6
  - 3 NON-BURN ROOM INTERIOR WALL AND DOOR
  - 4 BURN ROOM INSULATED DOOR WITH 1/4" STEEL PLATE BOTH SIDES
  - 5 INSULATED WINDOW SHUTTERS SIMILAR TO BURN ROOM DOORS WITH LOCKING MECHANISM EXCEPT WITH 1/2" PLATE STEEL BOTH SIDES.
-  BURN ROOM: INSULATE THE FLOOR, WALLS, CEILING, DOORS & WINDOW SHUTTERS OF THIS SPACE.

REVISIONS

△	DATE	DESCRIPTION

SMITH DESIGN GROUP, INC.  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net

PROJECT:  
 BURN BUILDING  
 FOR  
 CITY OF LAGRANGE FIRE DEPARTMENT  
 LAGRANGE, GEORGIA

TITLE:  
 FOUNDATION PLAN

MODIFIED DATE: 01 JAN 2025	JOB NO: 1730
ISSUED DATE: 26 FEB 2018	SHEET: AS-1

SET NO:

ARCHITECT'S STAMP



SIGNATURE REQUIRED

15' FOOT SOIL BORING

REVISIONS

DATE	DESCRIPTION

SMITH DESIGN GROUP, INC.

206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:

BURN BUILDING

TITLE:

FOUNDATION / SLAB PLAN

MODIFIED DATE:

JOB NO:

1730



ISSUED DATE:

SHEET:


SCHEMATIC DESIGN  
26 FEB 2018

AS-2

2.2.5 Add. Alt. No. 5: To remove existing perimeter 6" concrete slab in its entirety from the site and install new 6" thick 4000 psi concrete slab of same dimensions with #5's@ 18" o.c. each way.




1 AS-2 FOUNDATION / SLAB PLAN  
SCALE: 1" = 10'-0"





SET NO:



**SECTION THROUGH SLAB AT CONTAINERS**  
 SCALE: 1/4" = 1'-0"

**REVISIONS**

DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
 FOR  
 CITY OF LAGRANGE FIRE DEPARTMENT  
 LAGRANGE, GEORGIA

TITLE:  
**FOUNDATION SECTION**


MODIFIED DATE: 01 JAN 2025	JOB NO: 1730
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>AS-3</b>

SET NO:


ARCHITECT'S STAMP




SIGNATURE REQUIRED




1 CROSS SECTION  
A1-0 SCALE: 1/4" = 1'-0"



2 PLAN  
A1-0 SCALE: 1/4" = 1'-0"



3 DOOR END  
A1-0 SCALE: 1/4" = 1'-0"



4 SIDE ELEVATION  
A1-0 SCALE: 1/4" = 1'-0"

**NOTE:**  
GENERAL CONTRACTOR TO PURCHASE AND MODIFY USED 53' LONG CONTAINERS WITH 9'-6" HEIGHT. THE GENERAL CONTRACTOR IS RESPONSIBLE FOR ALL COSTS ASSOCIATED WITH PURCHASE, ORDERING, DELIVERY AND MODIFICATION TO THE USED CONTAINERS. USED CONTAINERS ARE TO BE IN GOOD CONDITION WITH NO HOLES OR LARGE DENTS OR LARGE AMOUNTS OF RUST. ENTIRE EXTERIOR OF CONTAINERS TO BE PAINTED WITH ONE COAT OF RUST STOP AND 2 FINISH COATS OF PAINT.

REVISIONS


DATE	DESCRIPTION

SMITH DESIGN GROUP, INC.  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net


PROJECT:  
BURN BUILDING  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA

TITLE:  
TYPICAL CONTAINER  
DIMENSIONS

MODIFIED DATE:	JOB NO: 1730
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: A1-0




**FIRST FLOOR PLAN**  
SCALE: 1/4" = 1'-0"



**SECOND FLOOR PLAN**  
SCALE: 1/4" = 1'-0"


**KEYNOTES**  
 (1) INTERIOR OF ROOM IS LINED WITH FIRE AND WATER RESISTANT INSULATION AND COVERED WITH 1/4" PLATE STEEL PLATES OR STAINLESS STEEL PANELS. SEE ADDITIVE ALTERNATIVES. INSTALL ON ALL FLOORS, CEILINGS AND WALLS IN BURN ROOMS.

- GENERAL SPECIFICATIONS**
- General bids shall include a 5-year warranty on workmanship.
  - Bids shall include a yearly inspection of such structure to repair and/or replace any defects in workmanship.
- Wall Construction**
- All walls shall be a minimal 2" thickness, finished size.
  - All exterior walls and ceilings exposed to fire shall be insulated.
  - All insulation used shall be High-Temperature Insulation Wool (HTIW).
  - A comparable mineral wool or Rockwool can be used as substitution to lower cost.
- Doors**
- All exterior doors shall open outward for means of egress.
  - All exterior doors shall have a mechanical locking mechanism that can be activated from the inside and outside.
  - All interior doors shall have a 1/2" gap (or larger) around all sides to prevent sticking due to metal distortion & expansion during fire training.
  - All door openings shall be of a standard residential door size (3'-0" width) unless otherwise noted.
  - All doors shall have a 4" gap from the floor to the bottom of the door to allow for fire hose movement; this gap to be covered with a rubber and/or abrasion resistant material.
  - All interior doors shall open as so depicted into designated rooms.
  - All doors shall have a jamb installed to prevent hyper-extending such door.
  - All doors shall have a large handle used for opening and closing such door, capable of being operated while personnel is wearing Structural Firefighting Gloves.
  - All door hinges shall be of Heavy Duty design.
  - All doors to be 1/4" steel plate with 2"x2"x1/4" steel tube perimeter frame, midrib and diagonals; at burn rooms install 2" fire insulation and 1/4" plate steel on both sides of door.
- Windows**
- All windows shall open outwards for means of egress.
  - All window openings shall be 42" (3'-6") finished height to window sill.
  - All window openings shall be 78" (6'-6") total height, finished opening.
  - All window openings shall be 36" in height, finished opening.
  - All window openings shall be 32" in width, unless otherwise noted.
  - All window opening panels shall be in 2 pieces, unless otherwise noted.
  - All window opening panels for the burn rooms shall be of a 1/2" thickness of plate steel.
  - All window opening panels shall be hinged on both sides of the window, top & bottom.
  - All windows shall have a locking mechanism that can be operated from the inside and/or outside, unless otherwise noted.
  - All window openings on the tower shall only open from the inside.
  - All window hinges shall be of Heavy Duty design.
  - All windows shall have a large handle used for opening and closing such windows, capable of being operated while personnel is wearing Structural Firefighting Gloves.
  - All window openings shall be finished with Heavy Gauge angle iron to cover all framework and plate metal.
- Floor**
- All metal used on the floors in burn rooms shall be 1/4" thickness.
  - All floors in burn rooms shall be insulated.
  - All insulation used shall be High-Temperature Insulation Wool (HTIW).
  - A comparable mineral wool or Rockwool can be used as substitution to lower cost.
  - All flooring shall be securely screwed to the wood decking of the containers to prevent as much bucking as possible.
  - All metal flooring shall be of a tread plate pattern to prevent slips and falls.
- SUBMITTALS**
- General Contractor to submit detailed shop drawings and product data on all structural steel, tube steel, walls and doors, all hinges, all doors and window shutters and locking and unlocking mechanism design.
  - Provide steel trim around all window and door openings of 1/4" bent plate with 4" leg, each side of opening welded to wall.



**KEY ELEVATION**  
SCALE: NOT TO SCALE

SET NO:



**DESIGN LOADS**

ROOF LIVE LOAD:	100 PSF
FLOOR LIVE LOAD:	100 PSF
WIND LOAD:	LOCAL
SEISMIC DESIGN CAT:	LOCAL
DESIGN CODE:	LOCAL & NFPA 1402

**WALL TYPES**

1	BURN ROOM INTERIOR WALL (SEE 7/A1-6)
2	BURN ROOM EXTERIOR WALL, CEILING AND FLOOR SEE DETAIL 2/A1-6
3	NON-BURN ROOM INTERIOR WALL
4	BURN ROOM INSULATED DOOR WITH 1/4" STEEL PLATE BOTH SIDES
5	INSULATED WINDOW SHUTTERS SIMILAR TO BURN ROOM DOORS WITH LOCKING MECHANISM EXCEPT WITH 1/2" PLATE STEEL BOTH SIDES
6	NON-INSULATED DOOR
7	NON-INSULATED WINDOW SHUTTERS

BURN ROOM: INSULATE THE FLOOR, WALLS, CEILING, DOORS & WINDOW SHUTTERS OF THIS SPACE.

**REVISIONS**

DATE	DESCRIPTION


**SMITH DESIGN GROUP, INC.**  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
 FOR  
 CITY OF LAGRANGE FIRE DEPARTMENT  
 LAGRANGE, GEORGIA


TITLE:  
**FLOOR PLANS**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A1-1</b>





**1**  
A1-2  
**3RD FLOOR PLAN**  
SCALE: 1/4" = 1'-0"



**2**  
A1-2  
**4TH FLOOR PLAN**  
SCALE: 1/4" = 1'-0"

**KEYNOTES**

① INTERIOR OF ROOM IS LINED WITH FIRE AND WATER RESISTANT INSULATION AND COVERED WITH 1/4" PLATE STEEL PLATES OR STAINLESS STEEL PANELS. SEE ADDITIVE ALTERNATIVES. INSTALL ON ALL FLOORS, CEILINGS AND WALLS IN BURN ROOMS.

**GENERAL SPECIFICATIONS**

- General bids shall include a 5-year warranty on workmanship.
- Bids shall include a yearly inspection of such structure to repair and/or replace any defects in workmanship.

**Wall Construction**

- All walls shall be a minimal 2" thickness, finished size.
- All exterior walls and ceilings exposed to fire shall be insulated.
- All insulation used shall be High-Temperature Insulation Wool (HTIW).
- A comparable mineral wool or Rockwool can be used as substitution to lower cost.

**Doors**

- All exterior doors shall open outward for means of egress.
- All exterior doors shall have a mechanical locking mechanism that can be activated from the inside and outside.
- All interior doors shall have a 1/2" gap (or larger) around all sides to prevent sticking due to metal distortion & expansion during fire training.
- All door openings shall be of a standard residential door size (3'-0" width) unless otherwise noted.
- All doors shall have a 4" gap from the floor to the bottom of the door to allow for fire hose movement; this gap to be covered with a rubber and/or abrasion resistant material.
- All interior doors shall open as so depicted into designated rooms.
- All doors shall have a large handle used for opening and closing such door, capable of being operated while personnel is wearing Structural Firefighting Gloves.
- All door hinges shall be of Heavy Duty design.
- All doors to be 1/4" steel plate with 2"x2"x1/4" steel tube perimeter frame, midrib and diagonals; at burn rooms install 2" fire insulation and 1/4" plate steel on both sides of door.

**Windows**


- All windows shall open outwards for means of egress.
- All window openings shall be 42" (3'-6") finished height to window sill.
- All window openings shall be 78" (6'-6") total height, finished opening.
- All window openings shall be 36" in height, finished opening.
- All window openings shall be 32" in width, unless otherwise noted.
- All window opening panels shall be in 2 pieces, unless otherwise noted.
- All window opening panels for the burn rooms shall be of a 1/2" thickness of plate steel.
- All window opening panels shall be hinged on both sides of the window, top & bottom.
- All windows shall have a locking mechanism that can be operated from the inside and/or outside, unless otherwise noted.
- All window openings on the tower shall only open from the inside.
- All window hinges shall be of Heavy Duty design.
- All windows shall have a large handle used for opening and closing such windows, capable of being operated while personnel is wearing Structural Firefighting Gloves.
- All window openings shall be finished with Heavy Gauge angle iron to cover all framework and plate metal.

**Floor**

- All metal used on the floors in burn rooms shall be 1/4" thickness.
- All floors in burn rooms shall be insulated.
- All insulation used shall be High-Temperature Insulation Wool (HTIW).
- A comparable mineral wool or Rockwool can be used as substitution to lower cost.
- All flooring shall be securely screwed to the wood decking of the containers to prevent as much buckling as possible.
- All metal flooring shall be of a tread plate pattern to prevent slips and falls.


**SUBMITTALS**

- General Contractor to submit detailed shop drawings and product data on all structural steel, tube steel, walls and doors, all hinges, all doors and window shutters and locking and unlocking mechanism design.
- Provide steel trim around all window and door openings of 1/4" bent plate with 4" leg, each side of opening welded to wall.



**KEY ELEVATION**  
SCALE: NOT TO SCALE

SET NO:



**DESIGN LOADS**

ROOF LIVE LOAD: 100PSF  
 FLOOR LIVE LOAD: 100 PSF  
 WIND LOAD: LOCAL  
 SEISMIC DESIGN CAT: LOCAL  
 SITE CLASS: LOCAL  
 DESIGN CODE: LOCAL & NFPA 1402

**WALL TYPES**

1 BURN ROOM INTERIOR WALL (SEE 7/A1-6)  
 2 BURN ROOM EXTERIOR WALL, CEILING AND FLOOR SEE DETAIL 2/A1-8  
 3 NON-BURN ROOM INTERIOR WALL  
 4 BURN ROOM INSULATED DOOR WITH 1/4" STEEL PLATE BOTH SIDES  
 5 INSULATED WINDOW SHUTTERS SIMILAR TO BURN ROOM DOORS WITH LOCKING MECHANISM EXCEPT WITH 1/2" PLATE STEEL BOTH SIDES  
 6 NON-INSULATED DOOR  
 7 NON-INSULATED WINDOW SHUTTERS

BURN ROOM: INSULATE THE FLOOR, WALLS, CEILING, DOORS & WINDOW SHUTTERS OF THIS SPACE.

**REVISIONS**


DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net


PROJECT:  
**BURN BUILDING FOR CITY OF LAGRANGE FIRE DEPARTMENT LAGRANGE, GEORGIA**

TITLE:  
**FLOOR PLANS**


MODIFIED DATE:      JOB NO: **1730**  
 ISSUED DATE:      SHEET: **A1-2**  
 FOR BIDDING  
 26 FEB 2018



1  
A1-3 LADDER DECK PLAN  
SCALE: 1/4" = 1'-0"



2  
A1-3 RAPPELLING DECK FLOOR PLAN  
SCALE: 1/4" = 1'-0"



KEY ELEVATION  
SCALE: NOT TO SCALE

KEYNOTES  
 ① INTERIOR OF ROOM IS LINED WITH FIRE AND WATER RESISTANT INSULATION AND COVERED WITH 1/4" PLATE STEEL PLATES OR STAINLESS STEEL PANELS. SEE ADDITIVE ALTERNATIVES. INSTALL ON ALL FLOORS, CEILINGS AND WALLS IN BURN ROOMS.

**GENERAL SPECIFICATIONS**

- General bids shall include a 5-year warranty on workmanship.  
 - Bids shall include a yearly inspection of such structure to repair and/or replace any defects in workmanship.

**Wall Construction**

- All walls shall be a minimal 2" thickness, finished size.  
 - All exterior walls and ceilings exposed to fire shall be insulated.  
 - All insulation used shall be High-Temperature Insulation Wool (HTIW).  
 - A comparable mineral wool or Rockwool can be used as substitution to lower cost.

**Doors**

- All exterior doors shall open outward for means of egress.  
 - All exterior doors shall have a mechanical locking mechanism that can be activated from the inside and outside.  
 - All interior doors shall have a 1/2" gap (or larger) around all sides to prevent sticking due to metal distortion & expansion during fire training.  
 - All door openings shall be of a standard residential door size (3'-0" width) unless otherwise noted.  
 - All doors shall have a 4" gap from the floor to the bottom of the door to allow for fire hose movement; this gap to be covered with a rubber and/or abrasion resistant material.  
 - All interior doors shall open as so depicted into designated rooms.  
 - All doors shall have a jamb installed to prevent hyper-extending such door.  
 - All doors shall have a large handle used for opening and closing such door, capable of being operated while personnel is wearing Structural Firefighting Gloves.  
 - All door hinges shall be of Heavy Duty design.  
 - All doors to be 1/4" steel plate with 2"x2"x1/4" steel tube perimeter frame, midrib and diagonals; at burn rooms install 2" fire insulation and 1/4" plate steel on both sides of door.

**Windows**

- All windows shall open outwards for means of egress.  
 - All window openings shall be 42" (3'-6") finished height to window sill.  
 - All window openings shall be 78" (6'-6") total height, finished opening.  
 - All window openings shall be 36" in height, finished opening.  
 - All window openings shall be 32" in width, unless otherwise noted.  
 - All window opening panels shall be in 2 pieces, unless otherwise noted.  
 - All window opening panels for the burn rooms shall be of a 1/2" thickness of plate steel.  
 - All window opening panels shall be hinged on both sides of the window, top & bottom.  
 - All windows shall have a locking mechanism that can be operated from the inside and/or outside, unless otherwise noted.  
 - All window openings on the tower shall only open from the inside.  
 - All window hinges shall be of Heavy Duty design.  
 - All windows shall have a large handle used for opening and closing such windows, capable of being operated while personnel is wearing Structural Firefighting Gloves.  
 - All window openings shall be finished with Heavy Gauge angle iron to cover all framework and plate metal.

**Floor**

- All metal used on the floors in burn rooms shall be 1/4" thickness.  
 - All floors in burn rooms shall be insulated.  
 - All insulation used shall be High-Temperature Insulation Wool (HTIW).  
 - A comparable mineral wool or Rockwool can be used as substitution to lower cost.  
 - All flooring shall be securely screwed to the wood decking of the containers to prevent as much buckling as possible.  
 - All metal flooring shall be of a tread plate pattern to prevent slips and falls.

**SUBMITTALS**

- General Contractor to submit detailed shop drawings and product data on all structural steel, tube steel, walls and doors, all hinges, all doors and window shutters and locking and unlocking mechanism design.  
 - Provide steel trim around all window and door openings of 1/4" bent plate with 4" leg, each side of opening welded to wall.

SET NO:

ARCHITECT'S STAMP  
  
 SIGNATURE REQUIRED

**DESIGN LOADS**

ROOF LIVE LOAD: 100PSF  
 FLOOR LIVE LOAD: 100 PSF  
 WIND LOAD: LOCAL  
 SEISMIC DESIGN CAT: LOCAL  
 SITE CLASS: LOCAL  
 DESIGN CODE: LOCAL & NFPA 1402

**WALL TYPES**

- ① BURN ROOM INTERIOR WALL (SEE 7/A1-6)
- ② BURN ROOM EXTERIOR WALL, CEILING AND FLOOR SEE DETAIL 2/A1-8
- ③ NON-BURN ROOM INTERIOR WALL
- ④ BURN ROOM INSULATED DOOR WITH 1/4" STEEL PLATE BOTH SIDES
- ⑤ INSULATED WINDOW SHUTTERS SIMILAR TO BURN ROOM DOORS WITH LOCKING MECHANISM EXCEPT WITH 1/2" PLATE STEEL BOTH SIDES
- ⑥ NON-INSULATED DOOR
- ⑦ NON-INSULATED WINDOW SHUTTERS

BURN ROOM: INSULATE THE FLOOR, WALLS, CEILING, DOORS & WINDOW SHUTTERS OF THIS SPACE.

**REVISIONS**

△	DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING FOR CITY OF LAGRANGE FIRE DEPARTMENT LAGRANGE, GEORGIA**

TITLE:  
**STAIR TOWER PLAN**


MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A1-3</b>

KEYNOTES  
 ① KEYNOTES. KEYNOTES. KEYNOTES

SET NO:



LEGEND OF STRUCTURAL MEMBERS  
 SCALE: 3/4" = 1'-0"



REVISIONS


DATE	DESCRIPTION

SMITH DESIGN GROUP, INC.  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net


PROJECT:  
**BURN BUILDING**  
 FOR  
 CITY OF LAGRANGE FIRE DEPARTMENT  
 LAGRANGE, GEORGIA

TITLE:  
**STAIR TOWER PLAN  
 FIRST / GROUND FLOOR**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A1-4</b>



①  
 A1-4 **STAIR TOWER PLAN - 1ST FLOOR (F.F. 0'-0")**  
 SCALE: 1/2" = 1'-0"



②  
 A1-4 **STAIR TOWER PLAN - 2ND FLOOR (F.F. 9'-6")**  
 SCALE: 1/2" = 1'-0"

**STEPS AND LANDING TREADS**  
**48" WIDTHS AND 54" WIDTHS - SPECIFICATIONS**  
 DESIGN BASED ON DIAMOND GRIP, 14 GAUGE STEEL, GALVANIZED  
 11-3/4" CHANNEL WIDTH, CHANNEL HEIGHT 2", RETURN FLANGE 1",  
 5 DIAMOND, CATALOGUE # D5204 AS MANUFACTURED BY  
 METAL MART, INC.

P.T. 2X8'S @ 16" O.C. WITH  
 ENTIRE HEIGHT OF TOWER  
 WITH COMPOSITE DECK  
 BOARDS DRILLED &  
 SCREWED TO 2X8 FRAMING.

P.T. 2X8'S @ 16" O.C. WITH  
 ENTIRE HEIGHT OF TOWER  
 WITH COMPOSITE DECK  
 BOARDS DRILLED &  
 SCREWED TO 2X8 FRAMING.


11-3/4" X 48" X 2" STEP TREADS  
 WITH 1" OVERHANG

11-3/4" X 54" X 2" LANDING TREADS  
 (X12) PER LANDING


11-3/4" X 54" X 2" LANDING TREADS  
 (X12) PER LANDING



SET NO:




**3 RAPPPELLING DECK EDGE**  
 SCALE: 3" = 1'-0" (PART OF ADD. ALT. NO. 4)



**1 STAIR TOWER PLAN - 3RD FLOOR**  
 SCALE: 1/2" = 1'-0"

**STEPS AND LANDING TREADS**  
 48" WIDTHS AND 54" WIDTHS - SPECIFICATIONS

DESIGN BASED ON DIAMOND GRIP, 14 GAUGE STEEL, GALVANIZED 11-3/4" CHANNEL WIDTH, CHANNEL HEIGHT 2", RETURN FLANGE 1". 5 DIAMOND, CATALOGUE # D5204 AS MANUFACTURED BY METAL MART, INC.



**1 STAIR TOWER PLAN - 4TH FLOOR**  
 SCALE: 1/2" = 1'-0"

REVISIONS

DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
 FOR  
 CITY OF LAGRANGE FIRE DEPARTMENT  
 LAGRANGE, GEORGIA

TITLE:  
**STAIR TOWER PLAN**


MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A1-5</b>

SET NO:



P.T. 2X8'S FRAMING &  
COMPOSITE DECK BOARDS  
PURCHASE & INSTALLTION  
PART OF ADD. ALT. NO. 4

**STEPS AND LANDING TREADS**  
48" WIDTHS AND 54" WIDTHS - SPECIFICATIONS  
DESIGN BASED ON DIAMOND GRIP, 14 GAUGE STEEL, GALVANIZED  
11-3/4" CHANNEL WIDTH, CHANNEL HEIGHT 2", RETURN FLANGE 1".  
5 DIAMOND, CATALOGUE # D5204 AS MANUFACTURED BY  
METAL MART, INC.



REVISIONS	
DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net


PROJECT:  
**BURN BUILDING**  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA

TITLE:  
**STAIR TOWER PLAN**  
**RAPPELLING DECK**


**1 LADDER LANDING - FLOOR PLAN**  
SCALE: 1/2" = 1'-0"

**2 RAPPELLING DECK - FLOOR PLAN**  
SCALE: 1/2" = 1'-0"

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A1-5A</b>



**1**  
A1-6 **ROOF GUARDRAIL - ATOP CONTAINERS**  
SCALE: 1-1/2" = 1'-0"



**2**  
A1-6 **STAIR TOWER HANDRAILS**  
SCALE: 1-1/2" = 1'-0"

**GENERAL SPECIFICATIONS**

- General bids shall include a 5-year warranty on workmanship.
- Bids shall include a yearly inspection of such structure to repair and/or replace any defects in workmanship.

**Wall Construction**

- All walls shall be a minimal 2" thickness, finished size.
- All exterior walls and ceilings exposed to fire shall be insulated.
- All insulation used shall be High-Temperature Insulation Wool (HTIW).
- A comparable mineral wool or Rockwool can be used as substitution to lower cost.

**Doors**

- All exterior doors shall open outward for means of egress.
- All exterior doors shall have a mechanical locking mechanism that can be activated from the inside and outside.
- All interior doors shall have a 1/2" gap (or larger) around all sides to prevent sticking due to metal distortion & expansion during fire training.
- All door openings shall be of a standard residential door size (3'-0" width) unless otherwise noted.
- All doors shall have a 4" gap from the floor to the bottom of the door to allow for fire hose movement; this gap to be covered with a rubber and/or abrasion resistant material.
- All interior doors shall open as so depicted into designated rooms.
- All doors shall have a jamb installed to prevent hyper-extending such door.
- All doors shall have a large handle used for opening and closing such door, capable of being operated while personnel is wearing Structural Firefighting Gloves.
- All door hinges shall be of Heavy Duty design.
- All doors to be 1/4" steel plate with 2"x2"x1/4" steel tube perimeter frame, midrib and diagonals; at burn rooms install 2" fire insulation and 1/4" plate steel on both sides of door.

**Windows**


- All windows shall open outwards for means of egress.
- All window openings shall be 42" (3'-6") finished height to window sill.
- All window openings shall be 78" (6'-6") total height, finished opening.
- All window openings shall be 36" in height, finished opening.
- All window openings shall be 32" in width, unless otherwise noted.
- All window opening panels shall be in 2 pieces, unless otherwise noted.
- All window opening panels for the burn rooms shall be of a 1/2" thickness of plate steel.
- All window opening panels shall be hinged on both sides of the window, top & bottom.
- All windows shall have a locking mechanism that can be operated from the inside and/or outside, unless otherwise noted.
- All window openings on the tower shall only open from the inside.
- All window hinges shall be of Heavy Duty design.
- All windows shall have a large handle used for opening and closing such windows, capable of being operated while personnel is wearing Structural Firefighting Gloves.
- All window openings shall be finished with Heavy Gauge angle iron to cover all framework and plate metal.

**Floor**


- All metal used on the floors in burn rooms shall be 1/4" thickness.
- All floors in burn rooms shall be insulated.
- All insulation used shall be High-Temperature Insulation Wool (HTIW).
- A comparable mineral wool or Rockwool can be used as substitution to lower cost.
- All flooring shall be securely screwed to the wood decking of the containers to prevent as much buckling as possible.
- All metal flooring shall be of a tread plate pattern to prevent slips and falls.

**SUBMITTALS**


- General Contractor to submit detailed shop drawings and product data on all structural steel, tube steel, walls and doors, all hinges, all doors and window shutters and locking and unlocking mechanism design.
- Provide steel trim around all window and door openings of 1/4" bent plate with 4" leg, each side of opening welded to wall.




**4**  
A1-6 **TYPICAL INTERIOR WALL & DOOR NON-BURN ROOM LOCATIONS**  
SCALE: 3" = 1'-0"



**7**  
A1-6 **TYPICAL INTERIOR WALL & DOOR IN BURN ROOMS**  
SCALE: 3" = 1'-0"



**5**  
A1-6 **COLUMN HANDRAILS**  
SCALE: 3" = 1'-0"



**6**  
A1-6 **INTERIOR STAIR GUARDRAIL INSIDE CONTAINERS**  
SCALE: 1-1/2" = 1'-0"

SET NO:

ARCHITECT'S STAMP

SIGNATURE REQUIRED

REVISIONS	
DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  


 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING FOR CITY OF LAGRANGE FIRE DEPARTMENT LAGRANGE, GEORGIA**

TITLE:  
**STAIR / RAILINGS DETAILS**


MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A1-6</b>






**1**  
A1-7 **STAIR TREAD DETAIL**  
SCALE: 1-1/2" = 1'-0"

**STEPS AND LANDING TREADS**  
**48" WIDTHS AND 54" WIDTHS - SPECIFICATIONS**  
DESIGN BASED ON DIAMOND GRIP, 14 GAUGE STEEL, GALVANIZED 11-3/4" CHANNEL WIDTH, CHANNEL HEIGHT 2", RETURN FLANGE 1". 5 DIAMOND, CATALOGUE # D5204 AS MANUFACTURED BY METAL MART, INC.



**2**  
A1-7 **LANDING STAIR TREAD DETAIL**  
SCALE: 1-1/2" = 1'-0"

**STEPS AND LANDING TREADS**  
**48" WIDTHS AND 54" WIDTHS - SPECIFICATIONS**  
DESIGN BASED ON DIAMOND GRIP, 14 GAUGE STEEL, GALVANIZED 11-3/4" CHANNEL WIDTH, CHANNEL HEIGHT 2", RETURN FLANGE 1". 5 DIAMOND, CATALOGUE # D5204 AS MANUFACTURED BY METAL MART, INC.



**3**  
A1-7 **TOWER ROOF EAVE DETAIL**  
SCALE: 1-1/2" = 1'-0"

**GENERAL SPECIFICATIONS**

- General bids shall include a 5-year warranty on workmanship.
- Bids shall include a yearly inspection of such structure to repair and/or replace any defects in workmanship.

**Wall Construction**

- All walls shall be a minimal 2" thickness, finished size.
- All exterior walls and ceilings exposed to fire shall be insulated.
- All insulation used shall be High-Temperature Insulation Wool (HTIW).
- A comparable mineral wool or Rockwool can be used as substitution to lower cost.

**Doors**

- All exterior doors shall open outward for means of egress.
- All exterior doors shall have a mechanical locking mechanism that can be activated from the inside and outside.
- All interior doors shall have a 1/2" gap (or larger) around all sides to prevent sticking due to metal distortion & expansion during fire training.
- All door openings shall be of a standard residential door size (3'-0" width) unless otherwise noted.
- All doors shall have a 4" gap from the floor to the bottom of the door to allow for fire hose movement; this gap to be covered with a rubber and/or abrasion resistant material.
- All interior doors shall open as so depicted into designated rooms.
- All doors shall have a jamb installed to prevent hyper-extending such door.
- All doors shall have a large handle used for opening and closing such door, capable of being operated while personnel is wearing Structural Firefighting Gloves.
- All door hinges shall be of Heavy Duty design.
- All doors to be 1/4" steel plate with 2"x2"x1/4" steel tube perimeter frame, midrib and diagonals; at burn rooms install 2" fire insulation and 1/4" plate steel on both sides of door.

**Windows**

- All windows shall open outwards for means of egress.
- All window openings shall be 42" (3'-6") finished height to window sill.
- All window openings shall be 78" (6'-6") total height, finished opening.
- All window openings shall be 36" in height, finished opening.
- All window openings shall be 32" in width, unless otherwise noted.
- All window opening panels shall be in 2 pieces, unless otherwise noted.
- All window opening panels for the burn rooms shall be of a 1/2" thickness of plate steel.
- All window opening panels shall be hinged on both sides of the window, top & bottom.
- All windows shall have a locking mechanism that can be operated from the inside and/or outside, unless otherwise noted.
- All window openings on the tower shall only open from the inside.
- All window hinges shall be of Heavy Duty design.
- All windows shall have a large handle used for opening and closing such windows, capable of being operated while personnel is wearing Structural Firefighting Gloves.
- All window openings shall be finished with Heavy Gauge angle iron to cover all framework and plate metal.


**Floor**

- All metal used on the floors in burn rooms shall be 1/4" thickness.
- All floors in burn rooms shall be insulated.
- All insulation used shall be High-Temperature Insulation Wool (HTIW).
- A comparable mineral wool or Rockwool can be used as substitution to lower cost.
- All flooring shall be securely screwed to the wood decking of the containers to prevent as much buckling as possible.
- All metal flooring shall be of a tread plate pattern to prevent slips and falls.

**SUBMITTALS**

- General Contractor to submit detailed shop drawings and product data on all structural steel, tube steel, walls and doors, all hinges, all doors and window shutters and locking and unlocking mechanism design.
- Provide steel trim around all window and door openings of 1/4" bent plate with 4" leg, each side of opening welded to wall.

SET NO:



REVISIONS	
DATE	DESCRIPTION


**SMITH DESIGN GROUP, INC.**  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA

TITLE:  
**STAIR / RAILINGS**  
**DETAILS**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A1-7</b>





**RAPPELLING ROPE SUPPORT WITH 3"Ø GALVANIZED PIPE AT 20" AND 40" A.F.F. (TYPICAL) SEE DETAIL 3/A3-1**




**RAPPELLING ANCHORS TO BE PROVIDED AND INSTALLED (TYPICAL)**




**SUPPORT OF RAPPELLING ANCHORS UNDER DECK (FOR REFERENCE)**

**1 RAPPELLING TOWER REFERENCE PHOTOS**  
SCALE: NONE



**FIRE FURR WALL IN BURN ROOMS AT EXTERIOR WALL, CEILING OR FLOOR OF CONTAINER**

**2**  
SCALE: 3" = 1'-0"  
SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION



**3 RAPPELLING ANCHOR BOLT**  
SCALE: 3" = 1'-0"  
SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION

SET NO:



**REVISIONS**

DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING FOR CITY OF LAGRANGE FIRE DEPARTMENT LAGRANGE, GEORGIA**

TITLE:  
**RAPPELLING TOWER REFERENCE PHOTOS**

MODIFIED DATE:

JOB NO:

1730

ISSUED DATE:

SHEET:



A1-8

FOR BIDDING


26 FEB 2018




SET NO:




**1**  
A2-1 **TYPICAL NON-FIRE INSULATED DOOR**  
SCALE: 1/2" = 1'-0"




**2**  
A2-1 **TYPICAL FIRE INSULATED DOOR**  
SCALE: 1/2" = 1'-0"




**3**  
A2-1 **DOOR DETAIL (FOR INSULATED DOOR)**  
SCALE: 3" = 1'-0"  
SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION



**4**  
A2-1 **DOOR DETAIL (FOR NON-FIRE INSULATED DOOR)**  
SCALE: 3" = 1'-0"  
SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION



**5**  
A2-1 **DOOR DETAIL / HINGE JAMB**  
SCALE: 3" = 1'-0"  
SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION



**6**  
A2-1 **HEAD AT DOOR**  
SCALE: 3" = 1'-0"  
SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION

REVISIONS

DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net



PROJECT:  
**BURN BUILDING**  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA

TITLE:  
**DOOR / WINDOW  
FRAME DETAILS**


MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A2-1</b>




SET NO:




1 A2-2 **TYPICAL NON-FIRE INSULATED WINDOW**  
SCALE: 1/2" = 1'-0"  
SEE SHEET A9-2 FOR WINDOW LATCH DETAILS




2 A2-2 **TYPICAL FIRE INSULATED WINDOW**  
SCALE: 1/2" = 1'-0"  
SEE SHEET A9-2 FOR WINDOW LATCH DETAILS




3 A2-2 **WINDOW DETAIL (FOR INSULATED WINDOW)**  
SCALE: 3" = 1'-0"  
SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION  
SEE SHEET A9-2 FOR WINDOW LATCH DETAILS



4 A2-2 **WINDOW DETAIL (FOR NON-FIRE INSULATED WINDOW)**  
SCALE: 3" = 1'-0"  
SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION  
SEE SHEET A9-2 FOR WINDOW LATCH DETAILS



5 A2-2 **INSULATED WINDOW DETAIL / HINGE JAMB**  
SCALE: 3" = 1'-0"  
SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION  
SEE SHEET A9-2 FOR WINDOW LATCH DETAILS



6 A2-2 **HEAD AT WINDOW**  
SCALE: 3" = 1'-0"  
SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION  
SEE SHEET A9-2 FOR WINDOW LATCH DETAILS

REVISIONS

DATE	DESCRIPTION

SMITH DESIGN GROUP, INC.  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA

TITLE:  
**DOOR / WINDOW  
FRAME DETAILS**

MODIFIED DATE:

JOB NO:


1730

ISSUED DATE:


SHEET:

FOR BIDDING  
26 FEB 2018

A2-2



**1**  
A3-1  
EXTERIOR ELEVATION - EAST  
SCALE: 1/4" = 1'-0"



SET NO:

ARCHITECT'S STAMP

STATE OF GEORGIA  
GOSWAM SWITZER  
7575  
REGISTERED ARCHITECT

SIGNATURE REQUIRED

REVISIONS


DATE	DESCRIPTION

SMITH DESIGN GROUP, INC.  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net


PROJECT:  
**BURN BUILDING**  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA

TITLE:  
**EXTERIOR ELEVATIONS**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A3-1</b>




1 A3-2 **EXTERIOR ELEVATION - NORTH**  
SCALE: 1/4" = 1'-0"



**KEYPLAN**  
NOT TO SCALE

SET NO:




REVISIONS	
DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net


PROJECT:  
**BURN BUILDING**  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA

TITLE:  
**EXTERIOR ELEVATIONS**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A3-2</b>



**1**  
A3-3 **RAPPELLING TOWER ELEVATION - SOUTH**  
SCALE: 1/4" = 1'-0"



**KEYPLAN**  
NOT TO SCALE

SET NO:

ARCHITECT'S STAMP

SIGNATURE REQUIRED

REVISIONS

DATE	DESCRIPTION


**SMITH DESIGN GROUP, INC.**  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
 FOR  
 CITY OF LAGRANGE FIRE DEPARTMENT  
 LAGRANGE, GEORGIA

TITLE:  
**EXTERIOR ELEVATIONS**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A3-3</b>





SET NO:

ARCHITECT'S STAMP

SIGNATURE REQUIRED

REVISIONS

DATE	DESCRIPTION


SMITH DESIGN GROUP, INC.  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net


PROJECT:  
**BURN BUILDING**  
 FOR  
 CITY OF LAGRANGE FIRE DEPARTMENT  
 LAGRANGE, GEORGIA

TITLE:  
**EXTERIOR ELEVATIONS**


MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A3-4</b>

**1**  
A3-4 **EXTERIOR ELEVATION - WEST**  
SCALE: 1/4" = 1'-0"





**2**  
A4-1 **CONTAINER CONNECTION**  
SCALE: 3" = 1'-0" **SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION**



**1**  
A4-1 **BUILDING SECTION**  
SCALE: 1/4" = 1'-0"

- WALL TYPES**
- 1 BURN ROOM INTERIOR WALL (SEE 7(A1-6))
  - 2 BURN ROOM EXTERIOR WALL, CEILING AND FLOOR SEE DETAIL 2(A1-8)
  - 3 NON-BURN ROOM INTERIOR WALL AND DOOR
  - 4 BURN ROOM INSULATED DOOR WITH 1/4" STEEL PLATE BOTH SIDES
  - 5 INSULATED WINDOW SHUTTERS SIMILAR TO BURN ROOM DOORS WITH LOCKING MECHANISM EXCEPT WITH 1/2" PLATE STEEL BOTH SIDES.
  - 6 BURN ROOM: INSULATE THE FLOOR, WALLS, CEILING, DOORS & WINDOW SHUTTERS OF THIS SPACE.

SET NO:

ARCHITECT'S STAMP



SIGNATURE REQUIRED

**REVISIONS**


DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING FOR CITY OF LAGRANGE FIRE DEPARTMENT LAGRANGE, GEORGIA**

TITLE:  
**BUILDING SECTION**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A4-1</b>



- WALL TYPES**
- 1 BURN ROOM INTERIOR WALL (SEE 7(A)-6)
  - 2 BURN ROOM EXTERIOR WALL, CEILING AND FLOOR SEE DETAIL 2(A)-8
  - 3 NON-BURN ROOM INTERIOR WALL AND DOOR
  - 4 BURN ROOM INSULATED DOOR WITH 1/4" STEEL PLATE BOTH SIDES
  - 5 INSULATED WINDOW SHUTTERS SIMILAR TO BURN ROOM DOORS WITH LOCKING MECHANISM EXCEPT WITH 1/2" PLATE STEEL BOTH SIDES.
  - 6 BURN ROOM: INSULATE THE FLOOR, WALLS, CEILING, DOORS & WINDOW SHUTTERS OF THIS SPACE.

SET NO:

ARCHITECT'S STAMP

SIGNATURE REQUIRED

REVISIONS

DATE	DESCRIPTION


**SMITH DESIGN GROUP, INC.**  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
 FOR  
 CITY OF LAGRANGE FIRE DEPARTMENT  
 LAGRANGE, GEORGIA


TITLE:  
**BUILDING SECTION**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A4-2</b>

**BUILDING SECTION**  
 SCALE: 1/4" = 1'-0"



1  
A5-1 **TOWER SECTION**  
SCALE: 1/4" = 1'-0"



2  
A5-1 **TOWER SECTION**  
SCALE: 1/4" = 1'-0"

SET NO:

ARCHITECT'S STAMP



SIGNATURE REQUIRED

REVISIONS

DATE	DESCRIPTION

SMITH DESIGN GROUP, INC.

206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA

TITLE:  
**TOWER SECTION**

MODIFIED DATE:

JOB NO:

1730

ISSUED DATE:


SHEET:

A5-1


FOR BIDDING

26 FEB 2018






1  
A5-2 **TOWER ELEVATION WITH REPELLING SIDING**  
SCALE: 1/4" = 1'-0"



2  
A5-2 **TOWER SECTION / ELEVATION**  
SCALE: 1/4" = 1'-0"

SET NO:



REVISIONS


DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net


PROJECT:  
**BURN BUILDING**  
 FOR  
 CITY OF LAGRANGE FIRE DEPARTMENT  
 LAGRANGE, GEORGIA

TITLE:  
**TOWER SECTION**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A5-2</b>



**1**  
A5-3  
**STAIR SECTION (LEVEL 1 TO LEVEL 2)**  
SCALE: 3/4" = 1'-0"  
SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION



**2**  
A5-3  
**STAIR PLAN (LEVEL 1 TO LEVEL 2)**  
SCALE: 3/4" = 1'-0"

SET NO:

ARCHITECT'S STAMP

SIGNATURE REQUIRED

REVISIONS


DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA

TITLE:  
**STAIR SECTION**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A5-3</b>



1
A5-4
**INTERIOR STAIR SECTION**  
 SCALE: 3/4" = 1'-0"  
 SEE STRUCTURAL DRAWINGS  
 FOR ADDITIONAL INFORMATION

SET NO:



REVISIONS

△	DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
 206 WEST HARALSON STREET  
 LAGRANGE, GEORGIA 30240  
 PH: 706-882-5511  
 www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
 FOR  
 CITY OF LAGRANGE FIRE DEPARTMENT  
 LAGRANGE, GEORGIA

TITLE:  
**INTERIOR STAIR SECTION**

MODIFIED DATE:	JOB NO: <b>1730</b>
ISSUED DATE: FOR BIDDING 26 FEB 2018	SHEET: <b>A5-4</b>



**STEEL 3 PIECE HEAVY DUTY**


**REMOVABLE PIN TYPE:**

**A3E** - Mild Steel (1015) with case hardened steel pin and brass washers. A locking "snap ring" washer at the end of the removable pin, keeps the pin in place.

Model	L Length inches	D/S Cross Section inches	d Pin Diameter inches	Weight Load Per Hinge lbs.
A3E135	5.14"	23/32" - 29/32"	15/32"	1500
A3E150	6"	3/4" - 1"	1/2"	2000
A3E200	8"	29/32" - 1.1/8"	5/8"	4000



- Made from special profile steel for weld-on applications
- Pin with half-round head and sections with V-shaped flanges allow for ease of weld-on installation
- With brass washers




www.intercononline.com

Toll Free: 1-800 665-6655

**A**  
A9-1 **3 KNUCKLE WINDOW AND DOOR HINGE**  
SCALE: NONE

PROVIDE 3 HINGES PER DOOR LEAF AND 2 HINGES PER WINDOW SHUTTER LEAF.




3/8" X 1-1/2" BENT PLATE DOOR PULL ON BOTH SIDES OF ALL DOORS. WELD TO 2"X2" FRAME OF DOOR. MOUNT CENTER @ 36" A.F.F.


**B**  
A9-1 **DOOR PULL DETAIL**  
SCALE: 3" = 1'-0"

PROVIDE ON BOTH SIDES OF ALL DOORS.

TS 4"X4"X1/4" FULL HEIGHT OF LADDER. WELD TO MAIN STEEL SUPPORT STRUCTURE OF RAPPELLING TOWER



**1**  
A9-1 **LADDER SECTION**  
SCALE: 1-1/2" = 1'-0"




**2**  
A9-1 **TYPICAL LADDER FOOTING SECTION**  
SCALE: 1-1/2" = 1'-0"

G.C. TO SUBMIT DETAILED SHOP DWGS. THAT MEET OSHA REQUIREMENTS AND ANSI SPECIFICATIONS A 14.3

**SUGGESTED STEEL LADDER FRAMING**

MEMBER	SIZE	SUPPORT SPACING
LADDER SIDE RAILS	2 1/2" X 3/8"	8'-0" MAXIMUM
	3" X 3/8"	12'-0" MAXIMUM
	3 1/2" X 3/8"	16'-0" MAXIMUM
CAGE HOOP	5" X 3/8"	20'-0" MAXIMUM TOP AND BOTTOM
	2" X 3/8"	ALL INTERMEDIATES
CAGE VERTICALS	2" X 3/8"	SEE SECTION ABOVE
LADDER RUNGS	3/4" Ø PLUG WELDED INTO SIDE RAILS	



**3**  
A9-1 **LADDER RUNG DETAIL**  
SCALE: 1-1/2" = 1'-0"

SEE STRUCTURAL DRAWINGS FOR ADDITIONAL INFORMATION

SET NO:

ARCHITECT'S STAMP



SIGNATURE REQUIRED

**REVISIONS**

DATE	DESCRIPTION

**SMITH DESIGN GROUP, INC.**  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA

TITLE:  
**ACCESS LADDER DETAILS**

MODIFIED DATE:

JOB NO:

1730

ISSUED DATE:


SHEET:

A9-1


FOR BIDDING

26 FEB 2018






**A**  
A9-2  
**WINDOW LATCH CATCH DETAIL**  
SCALE: 3" = 1'-0"




**B**  
A9-2  
**WINDOW LATCH DETAIL**  
SCALE: 3" = 1'-0"



**1**  
A9-2  
**INTERIOR LOCKING DEVICE FOR WINDOW SHUTTERS**  
SCALE: 3" = 1'-0"

SET NO:



SIGNATURE REQUIRED

REVISIONS

DATE	DESCRIPTION

SMITH DESIGN GROUP, INC.  
206 WEST HARALSON STREET  
LAGRANGE, GEORGIA 30240  
PH: 706-882-5511  
www.smithdesigngroup.net

PROJECT:  
**BURN BUILDING**  
FOR  
CITY OF LAGRANGE FIRE DEPARTMENT  
LAGRANGE, GEORGIA

TITLE:

DETAILS

MODIFIED DATE:

JOB NO:

1730

ISSUED DATE:

SHEET:

A9-2

FOR BIDDING

26 FEB 2018

**SCOUT TEMPERATURE MONITORING SYSTEM**

**Continuous Monitoring. Early Detection. Improved Safety. It's What You Can Expect with a Scout on Your Side.**

The Scout gives you immediate access to critical data at all times to help you quickly detect any unsafe conditions and determine if the training environment should be modified. The system's precise early-warning capabilities help you keep trainees safe during exercises, as well as keeping your training tower's structure protected from damage by excessive heat.

The Scout is integrated with hardware that interfaces with your PC and supports the seamless, instant transfer and storage of real-time training data. The system features a touch-sensitive, backlit display and controls, advanced data-logging capabilities, Bluetooth connectivity, internal alarm and control of external alarms, and Secure Digital Memory card. In short, every detail of the Scout system has been carefully designed to maximize your monitoring and response capabilities during a live fire-training exercise.

**Scout Temperature Monitoring Systems Features**

The Scout Temperature Monitoring System is designed to provide immediate, accurate and early detection information



to help you keep personnel safe during live fire-training exercises.

- Bluetooth** - The Bluetooth connectivity features the ability to broadcast temperature information to a user supplied iPhone or Android device for a maximum range of 270 feet. The supplied phone app displays all of the information found on the screen of the pyrometer along with the ability to notify the user if the alarms are tripped or if you are disconnected from the pyrometer. This unique application allows the training/safety officer to be away from the area where the pyrometer is installed, while still being able to monitor the temperatures within the burn rooms.

- Simultaneous display** - LCD shows temperatures of nine separate thermocouples at the same time, with maximum temperature reading, built-in clock, and battery life indicator.

- Touch-sensitive controls** - Easy to use. No switches or dials to manipulate.

- Backlit display** - Read display in any light conditions.

- On-screen programming** - Provides access to adjust pyrometer controls, to enable specific data collection and safety parameter set-up.

- Support for training** - On-board memory sustains 90 hours of logged time and temperature data that is downloadable via Secure Digital Memory card.

- Adjustable sampling rate** - Allows data to be recorded into the memory at adjustable rates up to four samples per location each minute.

- Superior protection** - Polycarbonate housing provides durable moisture barrier and a tough exterior. The steel weather proof, lockable cabinet prevents loss or damage.




**SCOUT TEMPERATURE MONITORING SYSTEM**

- Battery powered** - Training site does not require AC power for pyrometer function. The separate battery pack is provided for easy access to the power supply.
- Smooth, secure instant data transfer** - Each unit includes a Data Transfer Device (DTD) to allow infrared transfer of data from the pyrometer. Data can then be brought to an offsite Windows based computer for download via the SD/SDHC data storage card provided.



- Interactive, Microsoft® based software** - A visual basic program is provided to allow the user to customize input and also automatically convert the temperature data to both an electronic data sheet and graph via the user's own Microsoft Excel software. (See examples below).
- Training documentation** - Is achieved by saving logged-data sets and incorporating participants for each training session. Documentation includes recorded temperatures and data, as well as time stamp information. Electronic or hard copies can be produced for training documentation and ISO classification.
- Internal audio alarm** - Each pyrometer provided with built-in, preset adjustable alarm for each thermocouple.
- External alarm controls** - Unit capable of supporting additional separate preset electrical devices, such as cellular texting alarms, warning systems, lights, buzzers, horns, and sirens.
- Warranted** - Supported by a one-year warranty.



A user can automatically convert the temperature data to both an electronic data sheet and graph via the user's own Microsoft Excel software.



For more information, contact us at:  
800-929-3726 • 866-639-7012 Fax  
314 Wilburn Road  
Sun Prairie, WI 53590 USA  
www.firefacilities.com  
info@firefacilities.com

**DOOR LOCKSETS CASH ALLOWANCE**  
**PROVIDE A CASH ALLOWANCE OF \$350 PER DOOR LEAF FOR PURCHASE OF FIRE RATED LOCKSETS. LOCKSET INSTALLATION COST IN BASE BID.**

**2**  
A9-2  
SCALE: NONE