

**PUBLIC NOTICE**  
**INVITATION TO BID #1251**

The Springfield Fire Department will be accepting sealed bids for **NFPA Approved Structural Firefighting Gear for Fiscal Year 2024**.

Bid documents may be downloaded at [www.springfieldtn.gov](http://www.springfieldtn.gov). Please contact Fire Chief Jeff Glodoski at 615-384-4381 for questions. Sealed bids will be received by the City of Springfield, in the Office of the City Recorder, at 405 N. Main St., Springfield, TN. 37172, until 3:00 PM. local time, on Thursday, July 6, 2023 at which time the bids received will be publicly opened and read aloud. Please reference BID #1251 on the outside of the sealed envelope.

The City reserves the right to reject any and all bids.

Lisa H. Crockett  
City Recorder



## Specifications for Protective Clothing for Structural Firefighting

The bid for Springfield Fire Department Structural Firefighting Protective Clothing will be for Fiscal year 2024 starting July 1<sup>st</sup>, 2023 through June 30<sup>th</sup>, 2024.

All costs must be included in the bid at the time of the opening.

Bids must be quoted per coat and pants.

All shall be delivered within ninety (90) days from the day any order is placed.

Will be ready to wear when delivered.

Outer Shell must be Kombat Flex 7 w/freefas Bronze.

Thermal Lining must be Glide Ice 2 layer.

Moisture barrier must be Crosstech 3-layer type 4AF.

Must have New York Style triple trim with Scotchlite (3")

Size each firefighter for proper fitting of protective gear.

Must be gender specific Men's and Women's patterns.

All Protective Clothing for Structural Firefighting orders shall be FOB:

Springfield Fire Department  
203 Central Avenue East  
Springfield, Tennessee 37172

If you have any questions please contact:

Jeff Glodoski, Fire Chief

615-384-4381

615-382-2238 (Fax)

[Jeff.glodoski@springfieldtn.gov](mailto:Jeff.glodoski@springfieldtn.gov)

# Detailed Technical Specifications for Protective Clothing for Structural Firefighting Coat



## Springfield Fire Department

## **LEGAL RIGHT TO SPECIFY**

The Fire Department (for the remainder of this section referred to as the “specifier”) chooses to exercise its Legal Right to Specify as determined by the U.S. Supreme Court’s affirmation of the decision handed down in the case of Whitten Corp. vs. Paddock, by the U.S. District Court of Massachusetts, the First Federal District Court, which in effect states:

- 1) That as trained professionals, specifiers make informed judgments on products that they feel best serve their needs. Also, that proprietary specifications (if chosen) DO NOT violate any antitrust laws. Technically, very few brands of material or equipment are exactly alike, and if the specifier wants to limit the specification to one source, he has the right to do so and enforce it.
- 2) Only the specifier has the responsibility and judgment for determining whether a proposed substitution is an “or equal”.
- 3) That from start to finish in the purchasing process, only the specifier can ultimately decide if another desirable product is available in lieu of the specification.
- 4) Finally, that the courts concluded “the burden is on the supplier or manufacturer, who has NOT been specified, to convince the specifier that their product is equal for the purpose of a particular project”.

The specifier has determined that this product specification shall represent the product to which all offerings shall be compared. Due to the fact that firefighting is an ULTRAHAZARDOUS, UNAVOIDABLY DANGEROUS activity, only trained Fire Department personnel with specific knowledge in the area of Personal Protective Equipment shall be allowed to make the final determining decision on the selection of the appropriate product to serve the Fire Department’s needs.

### **1.0 PURPOSE AND SCOPE**

This specification defines the minimum requirements for structural firefighter personal protective equipment (PPE) providing limited protection as defined by NFPA 1971, Standard on Protective Ensemble for Structural Fire Fighting, Latest Edition. In the absence of comment on a particular point, industry standard practice shall be presumed to prevail. Every exception to specifications must be clearly spelled out at the time of bid.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **2.0 UNITS OF MEASURE**

Current NFPA standards applicable to this product specification express values for measurement requirements in SI (metric-based) units, followed by US (inch-pound) approximate equivalents in parentheses. For the convenience of the fire department, this product specification reverses the order and presents the more familiar US approximation first, followed by the SI requirement in parentheses.

### **3.0 CERTIFICATION**

The manufacturer must certify that the garments proposed in its bid meet or exceed all requirements of NFPA 1971. The manufacturer must also list and label this product with Underwriters Laboratories Inc. (UL) or Safety Equipment Institute (SEI), as the third-party certification organization prescribed in NFPA 1971. All certification testing and test

preconditioning must have been performed by an ISO 17025-certified laboratory. UL, SEI or a UL Authorized Client Test Data Program laboratory will fulfill this requirement.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

The manufacturer shall be registered to ISO 9001, Quality Management Systems – Requirements, 2000.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

#### **4.0 WARRANTY**

The manufacturer must provide a lifetime warranty against defects in materials and workmanship with the bid package.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

#### **5.0 PRODUCT COUNTRY OF ORIGIN**

For liability reasons, garments must be manufactured in the United States of America or Canada by companies with their assets and incorporation within the United States of America or Canada.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

#### **6.0 LABELING REQUIREMENTS**

Labels shall be permanently and integrally printed onto materials that meet all the requirements for labels of NFPA 1971. The garment shall be clearly labeled to fully identify the material content of all three layers: outer shell, moisture barrier and thermal liner.

In addition, each separable outer shell component shall be labeled in an obvious location including the size, date of manufacturer and an individualized serial number and bar code that matches the corresponding garment liner.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

#### **7.0 CARE INSTRUCTIONS**

The manufacturer shall provide a user information guide for the garments, which complies with user information requirements of NFPA 1971. Topics shall include, but not necessarily be limited to: pre-use information, preparation for use, inspection frequency and details, don/doff, use consistent with NFPA 1500, maintenance and cleaning, and retirement and disposal criteria and considerations.

This document shall be packaged with each garment along with a specification summary sheet describing garment custom options, sizing and production details. This written information shall be in complete compliance with NFPA 1971 requirements, and shall reference same.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

#### **8.0 TRACEABILITY PROGRAM**

The manufacturer shall have in place a computer-maintained traceability program that provides for the assignment of a production control number to each garment. The traceability program must be capable of tracing the garment through production, from the bolts of cloth used in all three layers of the garment composite construction, to the assignment of

the garment to the individual firefighter. This production control number shall be visibly located on the garment label and on other protected areas of garment.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**9.0 PATENT CONSIDERATIONS**

The Bidder, without exception, shall indemnify and save harmless the Purchaser and its employees from liability of any nature and kind, including cost and expenses for or on account of any copyrighted, patented or un-patented invention, process, or article manufactured or used in the performance of the contract, including its use by the Purchaser. If the Bidder uses any design, device, or materials covered by letters, patent or copyright, it is mutually agreed and understood without exception that the bid prices shall include all royalties or costs arising from the use of such design, device, or materials in any way involved in the work.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**10.0 SIZING**

To ensure a perfect fit, sizing shall be determined by actual measurements taken of the firefighter by a trained measurement specialist, or sizing try-ons, or both. Sizing measurements shall be taken according to a schedule and location(s) mutually agreed between the manufacturer and the department.

Garments shall be available in custom sizing as follows: coat chest in 2-inch (5.1 cm) increments, coat sleeve in 0.5-inch (1.3 cm) increments, coat back length in 1-inch (2.5 cm) increments, pant waist in 2-inch (5.1 cm) increments and pant inseam in 1-inch (2.5 cm) increments. A full range of women’s sizing, on women’s patterns, must also be available. Each sleeve and inseam length shall provide 100% gradation from shoulder to wrist, and from hip to ankle, to provide proper fit for individual arm and leg lengths. Pattern tailoring to custom-fit neck, bicep, hip/seat and thigh circumferences must also be provided, when needed, at no additional charge. Neither Small-Medium-Large-Extra Large sizing nor women’s garments cut to men’s patterning are considered acceptable, since proper fit facilitates mobility and minimizes stress.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**11.0 SELF-BINDING**

Liner and moisture barrier shall be stitched together and turned, then topstitched, to create a self-binding edge. The extra bulk of separate binding material is specifically prohibited.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**12.0 THREAD**

All thread used in structural seams shall be Nomex® of minimum Tex size T-70. Light colored garments and trim areas shall feature yellow thread. Black and dark garments shall feature black thread. Tan- or bronze-colored garments shall feature tan thread.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

## **13.0 STITCH METHODS**

### **13.1 MAJOR A & B SEAMS**

Except for the collar Major A seam, which is single-needle lock stitched three times, all Major A & B seams (as defined by NFPA 1971) shall be double stitched, double fold throughout all three layers (outer shell, moisture barrier and thermal liner), and shall be made with Nomex® thread, minimum Tex size T-90. Stitch and seam type requirements:

Stitch Type 401 Double lockstitch, as defined by ASTM D 6193-97 and  
Modified Seam Type LSc-2 Double fold seam, modified only to ensure that both stitch lines penetrate all layers of cloth at joining, otherwise as defined by ASTM D 6193-97.

Also, all moisture barrier seams shall be tape-sealed to meet all requirements of the NFPA 1971 Liquid Penetration Resistance Test.

Does Your Bid Comply with All Aspects of This Section?

For Outer Shell: Yes \_\_\_\_\_ No \_\_\_\_\_

For Thermal Lining: Yes \_\_\_\_\_ No \_\_\_\_\_

For Moisture Barrier: Yes \_\_\_\_\_ No \_\_\_\_\_

### **13.2 MINOR SEAMS**

Most Minor seams, such as storm shields and mated hems, shall also be stitched with the specified Nomex thread. Detailed stitch and seam type requirements are listed below:

- Stitch Type 301 Lockstitch as defined by ASTM D 6193-97 and Seam Type SSae-2 As defined by ASTM D 6193-97,

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **13.3 POCKETS**

Flat garment pockets shall be stitched with the specified Nomex® thread. Detailed stitch and seam type requirements are listed below.

- Stitch Type 301 Lockstitch as defined by ASTM D 6193-97 and Seam Type LSd-2 As defined by ASTM D 6193-97.
- 3-Dimensional pocketing shall feature these same construction details, but the reinforced single stitch Seam Type LSd-1 may be substituted for LSd-2. Detailed seam type requirements are listed below:
- Stitch Type 301 Lockstitch as defined by ASTM D 6193-97 and Seam Type LSd-1 As defined by ASTM D 6193-97.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **13.4 TRIM AND DANGER LABELS**

Trim and DANGER labels shall be stitched with the specified Nomex® thread. Detailed stitch and seam type requirements are listed below:

- Stitch Type 301 Lockstitch as defined by ASTM D 6193-97 and Seam Type SSbd-1 As defined by ASTM D 6193-97.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**13.5 SINGLE LAYER HEMMING AND FINISHING**

Single layer hemming and finishing shall be stitched with the specified Nomex® thread. Detailed stitch and seam type requirements are listed below.

- Stitch Type 301 Lockstitch as defined by ASTM D 6193-97 and Seam Type EFb-1 As defined by ASTM D 6193-97.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**14.0 POCKETS**

When exterior pockets are specified, the following requirements shall apply to all such custom option specified exterior pockets:

- All pockets and flaps shall be reinforced at the top corners with bar tack stitching.
- All pockets shall be reinforced with an extra layer of NFPA-certified outer shell, moisture barrier, or other NFPA-certified reinforcement material for extra durability. The exact location of the reinforcements shall be identified in the custom options section(s).
- All pockets shall have a means to drain water and shall have a means of closure.
- All pocket closures shall be made either with hook and loop fastener tape a minimum of 1.5 inches (3.8 cm) wide, with a flap, or with snaps. The specific placement of the closure system shall be outlined in the custom options sections.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**15.0 TAILORED GRADING OF GARMENT LININGS**

All garment layers and Cold Weather Accessory Linings shall be graduated in size to fit within in each other in the overall composite without causing bunching or binding when the garment is worn.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**16.0 POINTS OF STRESS**

All points of stress shall be reinforced with sturdy bar tacks. Rivets are not acceptable because of their potential for rust and electrical or heat conduction.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_



## **17.0 ASSET TRACKING SERVICES**

Upon request, the manufacturer shall be capable of providing a web-based software to track care, cleaning and maintenance of PPE. The tracking software will include Inventory Assist and the Hot Spot Locator to help you analyze gaps in your inventory and pinpoint recurring repair problems. Records will be secured in a cloud-based environment with 24/7 access.

This tracking program shall meet or exceed all record-keeping requirements of NFPA 1851, Standard on Selection, Care and Maintenance of Structural Fire Fighting Protective Ensembles, Latest Edition. Manufacturer shall have the ability to import records for gear purchased from them, upon request, providing all details required to meet NFPA 1851, and assist with training to assign all gear while importing.

Labels on each separable part of the garment shall include a standard style interleaved 2 of 5 barcode containing (at a minimum) an individualized serial number for asset tracking purposes.

The manufacturer shall be capable of providing training to department personnel who are involved in the daily use of this tracking program, as well as a built-in interactive tutorial.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

## **18.0 REPAIRS AND ALTERATION SUPPORT**

The manufacturer shall furnish, free of charge, reasonable quantities of NFPA 1971-certified thread, materials and other supplies to allow the department to manage its own ongoing internal maintenance efforts. Also, the manufacturer shall provide on call at no charge, during normal business hours, a liaison for the repair department to assist the Fire Department on a telephone consultation basis, on all maintenance or repair questions that might arise. Additionally, the manufacturer shall agree to expedite, on its own cost-only basis, all repairs that must be performed at the manufacturer's plant, rather than in department, over the life of the contract.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

## **19.0 HIGH TEMPERATURES THERMAL INSULATING MATERIALS REQUIREMENT**

Because thermally stable materials are essential to maximizing protective performance in firefighters' PPE, and because NFPA only states "minimum" performance requirements, all thermal liner or thermal enhancing materials used in the garments shall also meet the following criteria after the 500-degree F oven test:

- 1) Material shall remain intact and flexible
- 2) No portion of the material shall crack, crumble or flake

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

## **20.0 BREATHABILITY REQUIREMENT**

Excluding where required by NFPA standard, necessary for functionality, or specifically called out in the custom option sections, all materials fabrics and reinforcements used in the construction of the garments shall be breathable and all moisture barrier material must be as specified in the Materials Section.

The breathability requirement includes but is not limited to: collar, chinstrap, storm shield, fly, water wells, front coat facings, and reinforcement cushioning where applicable.

Areas where non-breathability is allowed (absent Custom Option specifications): trim or other items placed externally on the arms that might need extra material to pass NFPA required Stored Energy Testing, hook and loop fastening, hardware or hardware backing, and pocket linings where used exterior to the outer shell.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**21.0 CONDUCTIVE AND COMPRESSIVE HEAT RESISTANCE (CCHR)**

Using breathable materials as outlined in the section titled Breathable Materials, there shall be: A minimum area of 4” x 4” (10.2 cm x 10.2 cm) at the shoulders and elbows that provide a minimum of 25 CCHR at 2 psi. with a minimum 6” x 6” (15.2 cm x 15.2 cm) area at the knees that provide 25 CCHR at 8 psi.

In all three of these compression areas at least a portion of the protective area shall be made from high temperature fiber-based materials sewn to the thermal liner on the inside of the liner toward the moisture barrier.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**22.0 SEAM PROTECTION AT CUFFS**

At the coat and pant cuff Major A seams, the reflective trim shall stop just before the folding of the full fold seam and for additional abrasion protection be covered by a sewn-on strip of polymer coated Kevlar material laid on top of the Major A seam and covering each end of the trim.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**23.0 APPLICABLE DOCUMENTS**

The following standards in their active versions on the date of invitation for bid shall form a part of this specification to the extent specified herein.

<b><u>STANDARD</u></b>	<b><u>TITLE</u></b>
ASTM D 6193-97	Standard Practice for Stitches and Seams
NFPA 1500, Latest Edition	Standard on Fire Department Occupational Safety and Health Program
NFPA 1851, Latest Edition	Standard on Selection, Care, and Maintenance of Structural Fire Fighting Protective Ensembles
NFPA 1971, Latest Edition	Standard on Protective Ensemble for Structural Fire Fighting

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

To avoid liability and interface problems, coats and pants shall be procured from the same manufacturer.

**24.0 DESIGN CONCEPT (STYLING)**

The standard coat design shall be 6-inches (15.2 cm) longer at the rear hem than at the front hem and provide continuous and unbroken moisture barrier and thermal liner protection from the collar seam to the hem at the bottom of the coat tail. Each coat length shall be determined by each individual’s torso length to provide the coat-to-pant interface as defined by NFPA 1500. Coat design must interface properly with standard waist high bunker pants. To facilitate various body types the front to rear length differential shall be made available in 3-inch (7.5cm), 4-inch (10.0cm), 5-inch (12.5cm and 6-inch (15.0cm) “Tail Drops”.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**25.0 PATTERNING CONCEPT**

Garments shall feature a tailored three-piece body (with one-piece back) and one-piece, set-in sleeve construction throughout the outer shell, moisture barrier and thermal liner layers. One-piece garment body (either all layers or some layers) will not be considered acceptable since they cannot be tailored to hard-to-fit personnel. Similarly, garments with seams in mid-back are not considered acceptable because of backbone irritation that can occur with SCBA use. To facilitate individual tailoring needs, the major A & B seams joining the one-piece back to the right and the left front body panels (outer shell and all interior layers) shall be located at the most lateral position when the coat is laid flat for inspection.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**26.0 PATTERNING REQUIREMENTS**

To assure maximum freedom of movement and reduce kinetic resistance with minimum garment weight and bulk, coat patterning shall include the following features:

- Degree of slope on shoulders shall be no more than 20%.
- Hydraulic Butterfly sleeve patterning having built-in underarm bellow with 85-degree Lift Up Release Action shall be provided to minimize coat hem rise. • Sleeve attachment shall minimize shoulder lift and allow a full 360 degrees freedom of movement.
- Coat hem rise with overhead reach of both arms not to exceed 4-inch (10.2-cm) maximal extension on properly fitted garments.
- Shell-and-liner retraction at the cuff shall not exceed 1 inch (2.5 cm) when both arms are raised overhead. This helps eliminate wrist exposure.
- 10-inch (25.4-cm) chest over-sizing shall be provided.
- Coat sweep measurements must be consistent with the chest over-size at the hem.
- Reach when measured from cuff to cuff, with coat lying flat, and standard-length sleeves extended to each side, shall be provided as detailed below.
- An alteration point at the hem that during manufacture allows the sweep dimension to be adjustable in two-inch (5.0cm) increments.

<u>Chest Size</u>	<u>Standard Reach</u>
40 in (101.6 cm)	66 in (167.6 cm)
42 in (106.7 cm)	67 in (170.2 cm)
44 in (111.8 cm)	68 in (172.7 cm)
46 in (116.8 cm)	68 in (172.7 cm)

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**27.0 DRAG RESCUE DEVICE (DRD)**

Manufacturer shall supply an NFPA required and certified Drag Rescue Device with each coat. Each strap will be properly labeled with the chest size(s) the Rescue Strap is designed to fit.

Rescue Strap shall be designed in a fashion that it functionally provides a dynamic and articulated action and to eliminate excess strapping material hanging down the back when installed between the garment’s liner and outer shell.

The device shall be constructed using two components: a 1.75" (4.45 cm) Kevlar webbing grab handle; and a free-floating loop of Kevlar rope to go around each of the wearer's arms/shoulder.

The grab loop shall extend upward and pass through a tunnel of outer shell and pass out through a reinforced slot in the coat outer shell just below the center rear of the collar seam. The protruding grab loop shall then fold back down and be stored by hook and loop fastener.

The end of the grab loop shall be covered with an outer shell flap sewn below the held in place with hook & loop fastener to reduce the chances of snagging the grab loop by accident.

The Grab Handle shall be constructed of soft and pliable Kevlar webbing meeting the following specifications:

Description 100% Kevlar Double Plain Weave  
Width 1.75" (4.45 dm)  
Thickness 0.064" ± 0.010" (.163 cm ± .0254 cm)  
Tensile 5,000 lbs minimum (22.24 kN)

To facilitate comfort and safety the free-floating loop shall be constructed of soft and pliable Kevlar rope meeting the following specifications:

Description 100% Kevlar Tubular Plain Weave - Natural  
Width .038" (.097 cm)  
Thickness 0.144" ± 0.005" (.366 cm ± .013 cm)  
Tensile 3500 lbs minimum (15.57 kN)

Rescue Strap shall be sewn with Kevlar thread.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

## **28.0 LINER ATTACHMENT**

The completed liner-moisture barrier assembly shall attach by means of five (5) evenly spaced glove snaps to each outer shell front facing to reduce weight, bulk and stiffness. To provide continuous moisture and pathogen protection at the front, the liner shall be positioned so it is sandwiched between the coat front facing and a breathable pathogen shield. The use of zippers or hook and loop fasteners in this area is not allowed due to their added weight, bulk and stiffness.

Liner sleeves shall be attached at the cuff by means of snaps on two (2) sets of Nomex tabbing per liner cuff. The male and female snap parts shall both be located on Nomex tabbing that is sewn to the liner at the cuff. A separate piece of Nomex tabbing shall be sewn to the shell cuff and fashioned as a loop without any snap hardware.

To provide continuous moisture protection and pathogen protection at the neck, the liner shall be positioned so that it is sandwiched between an outer-facing pathogen shield and an inside facing of the specified outer shell material.

Attachment at the neck shall be by means of four (4) glove snaps that penetrate only the layer of the attachment strip facing towards the liner, so that metal contact at a wearer's neckline is completely eliminated.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **29.0 COAT CERTIFICATION LABEL ON LINER**

The coat certification label on the liner shall be affixed to the inside right body panel of the liner in a fashion to provide an inside liner pocket.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **30.0 COAT CERTIFICATION LABEL ON SHELL**

The coat label on the shell shall be affixed in a conspicuous location once the liner is removed.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **31.0 COLLAR**

The collar shall be of layered construction, consisting of a layer of waterproof moisture barrier and a layer of NFPA 1971-certified insulating material, sandwiched between two (2) layers of specified outer shell material. NFPA compliant collars shall be at least 3 inches (7.6 cm) high while CGSB compliant collars shall be at least 4 inches (10.2 cm) high. The design shall incorporate in its patterning a natural contour that will allow proper fit and performance in the standing (upright) or stowed position.

There shall be no vertical or horizontal seams or stitching in the body of the collar. The left outside of the collar shall have a sewn piece of 2-inch x 2-inch (5.0-cm x 5.0-cm) hook fastener tape for chinstrap-to-collar closure. The fastener tape shall be located rear ward far enough to allow for the location of a forward mounted microphone tab if so desired. Each collar shall be graded to individual coat sizes.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **32.0 CHIN STRAP**

The chinstrap shall be of layered construction identical to that of the collar configuration described in the previous paragraphs. Chinstrap shall be of a crescent shaped design with minimum dimensions of: 9 inches (22.5 cm) long across the top corners, 10.5 inches (26 cm) long across the bottom corners, and 3.5 inches (8.75 cm) in vertical height, measured at the center. The leading underside edge of the chinstrap shall have a 4.0-inch-wide (3.8 cm-wide) horizontal strip of loop fastener tape to ensure an adequately adjustable closure and to ensure passage of the Whole Garment Liquid Penetration Test.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **33.0 HANG-UP LOOP**

An 80-pound (36.3 kg) tear strength hang-up loop shall be provided at the interior collar seam. The loop shall be constructed of triple layers of the specified outer shell material, lock-stitched to the coat. Webbing is not acceptable.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **34.0 SLEEVES**

To prevent stove-piping the sleeves shall be individually graded by coat size and sleeve length. For maximum freedom, the sleeve design shall feature extra full cut one-piece set-in sleeves with built-in bellows. To reduce the chances of possible top seam failure in that high thermal exposure area, the sleeve Major seams shall follow the underside of the arm and shall not cross over the outside of the elbow joint. Sleeve seam and sleeve attachment to coat body in all layers shall be 100% double fold and double stitched for maximum.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **35.0 INNER WRISTLET & WATERWELL**

Every coat shall feature a minimum 4.5-inch (11.4-cm) long, double-layer knit inner wristlets protected by a flame-resistant and moisture-resistant inner water well. The inner wristlet shall be sewn to the thermal liner sleeve end (not to the outer shell). The specified moisture barrier shall form an inner water well with an elastic gather sewn to the moisture barrier sleeve end.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **36.0 EXTERNAL WRISTLET**

Every coat shall feature a 2.5-inch (6.4 cm) long knit outer wristlet, which shall be mounted to the end of each outer shell sleeve to prevent liquid and debris movement up the sleeve between the outer shell and the moisture barrier/thermal liner assembly.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **37.0 FRONT CLOSURE PROTECTIVE OVERLAP**

Two-inch-wide (5.1 cm-wide) panels of breathable moisture/ pathogen barrier and specified thermal liner materials shall be provided at coat front closure facings to preclude any type of break in the protective envelope. The entire circumference of a closed coat shall consist of specified shell, moisture barrier and thermal liner materials.

An additional layer of breathable moisture/ pathogen barrier material shall be sewn between the 2-inch-wide (5.1 cm-wide) panels and outer shell coat body for the entire length of coat front in a fashion to prevent liquid entry during the NFPA 1971 Whole Garment Liquid Penetration Test.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **38.0 COMPOSITE MATERIALS**

The specifier has determined the ONLY acceptable combination of materials. Any substitution of materials shall be grounds for immediate disqualification of bid without further consideration.

### **38.1 OUTER SHELL KOMBAT FLEX 7 W/ FREEFAS BRONZE**

### **38.2 THERMAL LINING GLIDE ICE 2 LAYER**

### **38.3 MOISTURE BARRIER CROSSTECH 3L TYPE 4AF**

Does Your Bid Comply with All Aspects of This Section?

For Outer Shell: Yes \_\_\_\_\_ No \_\_\_\_\_

For Thermal Lining: Yes \_\_\_\_\_ No \_\_\_\_\_

For Moisture Barrier: Yes \_\_\_\_\_ No \_\_\_\_\_

### **39.0 COAT CUSTOM OPTIONS TO BE PROVIDED**

Instructions in this custom options section that contradict earlier specifications or statements supersede those earlier specifications or statements as long as the required certifications are not compromised.

- Standard Inspection Port
- Liner detachable
- Trim Double stitched
- 2" Velcro/zipper coat closure
- Liner within 1" of Hem
- Half Hi Bellows pockets- kombat Flex- Bronze with FREEFAS 6.9
- Handwarmers behind bellows pocket- Fleece
- Mic Tab- Kombat Flex- bronze- to be specified upon bid award
- Radio pocket- Kombat Flex- with FREEFAS- Bronze left chest
- Notch flap- right
- Sewn D-ring- Kombat Flex Bronze with FREEFAS on left pocket
  - Place centered on pocket with bottom of D-ring above trim, OK to be under flap
- Sewn D-ring- Kombat Flex- bronze with FREEFAS on right pocket
  - Place centered on pocket with bottom of D-ring above trim, OK to be under flap
- Lanyard flashlight clip- style #2- Flex 7 with FREEFAS- black- right chest
- New York Triple Trim 3"
- Sewn on 3" Scotch lite SFD lettering under DRD device- back of coat
- Sewn on 2" scotch lite lettering "rank of officer" (Lieutenant, Captain, Batt. Chief, Asst. Chief, Chief) just above upper scotch lite trim
- Sewn on 3" scotch lite lettering name panel bottom of coat under bottom scotch lite trim
- Embroidered American Flag sewn on Left Sleeve

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**Delivery must be less than 90 days No Exceptions**

## PERCENTAGE SPECIFICATION COMPLIANCE CALCULATIONS

Total Number "Yes/No" Questions \_\_\_\_\_

Total Number of **Yes** Answers \_\_\_\_\_

Total Number of **No** Answers \_\_\_\_\_

% Specification Compliance:  $(\text{Total yes answers}) \div (\text{total Answers}) \times 100\%$

Percent Compliance \_\_\_\_\_

- Each "No" answer requires a full written explanation.
- Each "Yes/No" question not checked where provided will be considered a "No" Answer.



# Detailed Technical Specifications for Protective Clothing for Structural Firefighting Pro Fit Pant



## Springfield Fire Department

This specification dated May 31, 2023 supersedes, modifies and replaces all previous editions.

## **LEGAL RIGHT TO SPECIFY**

The Fire Department (for the remainder of this section referred to as the “specifier”) chooses to exercise its Legal Right to Specify as determined by the U.S. Supreme Court’s affirmation of the decision handed down in the case of Whitten Corp. vs. Paddock, by the U.S. District Court of Massachusetts, the First Federal District Court, which in effect states:

- 1) That as trained professionals, specifiers make informed judgments on products that they feel best serve their needs. Also, that proprietary specifications (if chosen) DO NOT violate any antitrust laws. Technically, very few brands of material or equipment are exactly alike, and if the specifier wants to limit the specification to one source, he has the right to do so and enforce it.
- 2) Only the specifier has the responsibility and judgment for determining whether a proposed substitution is an “or equal”.
- 3) That from start to finish in the purchasing process, only the specifier can ultimately decide if another desirable product is available in lieu of the specification.
- 4) Finally, that the courts concluded “the burden is on the supplier or manufacturer, who has NOT been specified, to convince the specifier that their product is equal for the purpose of a particular project”.

The specifier has determined that this product specification shall represent the product to which all offerings shall be compared. Due to the fact that firefighting is an ULTRAHAZARDOUS, UNAVOIDABLY DANGEROUS activity, only trained Fire Department personnel with specific knowledge in the area of Personal Protective Equipment shall be allowed to make the final determining decision on the selection of the appropriate product to serve the Fire Department’s needs.

### **1.0 PURPOSE AND SCOPE**

This specification defines the minimum requirements for structural firefighter personal protective equipment (PPE) providing limited protection as defined by NFPA 1971, Standard on Protective Ensemble for Structural Fire Fighting, Latest Edition. In the absence of comment on a particular point, industry standard practice shall be presumed to prevail. Every exception to specifications must be clearly spelled out at the time of bid.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **2.0 UNITS OF MEASURE**

Current NFPA standards applicable to this product specification express values for measurement requirements in SI (metric-based) units, followed by US (inch-pound) approximate equivalents in parentheses. For the convenience of the fire department, this product specification reverses the order and presents the more familiar US approximation first, followed by the SI requirement in parentheses.

### **3.0 CERTIFICATION**

The manufacturer must certify that the garments proposed in its bid meet or exceed all requirements of NFPA 1971. The manufacturer must also list and label this product with Underwriters Laboratories Inc. (UL) or Safety Equipment Institute (SEI), as the third-party certification organization prescribed in NFPA 1971. All certification testing and test preconditioning must have been performed by an ISO 17025-certified laboratory. UL, SEI or a UL Authorized Client Test Data Program laboratory will fulfill this requirement.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

The manufacturer shall be registered to ISO 9001, Quality Management Systems – Requirements, 2000.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**4.0 WARRANTY**

The manufacturer must provide a lifetime warranty against defects in materials and workmanship with the bid package.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**5.0 PRODUCT COUNTRY OF ORIGIN**

For liability reasons, garments must be manufactured in the United States of America or Canada by companies with their assets and incorporation within the United States of America or Canada.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**6.0 LABELING REQUIREMENTS**

Labels shall be permanently and integrally printed onto materials that meet all the requirements for labels of NFPA 1971. The garment shall be clearly labeled to fully identify the material content of all three layers: outer shell, moisture barrier and thermal liner.

In addition, each separable outer shell component shall be labeled in an obvious location including the size, date of manufacturer and an individualized serial number and bar code that matches the corresponding garment liner.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**7.0 CARE INSTRUCTIONS**

The manufacturer shall provide a user information guide for the garments, which complies with user information requirements of NFPA 1971. Topics shall include, but not necessarily be limited to: pre-use information, preparation for use, inspection frequency and details, don/doff, use consistent with NFPA 1500, maintenance and cleaning, and retirement and disposal criteria and considerations.

This document shall be packaged with each garment along with a specification summary sheet describing garment custom options, sizing and production details. This written information shall be in complete compliance with NFPA 1971 requirements, and shall reference same.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**8.0 TRACEABILITY PROGRAM**

The manufacturer shall have in place a computer-maintained traceability program that provides for the assignment of a production control number to each garment. The traceability program must be capable of tracing the garment through production, from the bolts of cloth used in all three layers of the garment composite construction, to the assignment of the garment to the individual firefighter. This production control number shall be visibly located on the garment label and on other protected areas of garment.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

## **9.0 PATENT CONSIDERATIONS**

The Bidder, without exception, shall indemnify and save harmless the Purchaser and its employees from liability of any nature and kind, including cost and expenses for or on account of any copyrighted, patented or un-patented invention, process, or article manufactured or used in the performance of the contract, including its use by the Purchaser. If the Bidder uses any design, device, or materials covered by letters, patent or copyright, it is mutually agreed and understood without exception that the bid prices shall include all royalties or costs arising from the use of such design, device, or materials in any way involved in the work.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

## **10.0 SIZING**

To ensure a perfect fit, sizing shall be determined by actual measurements taken of the firefighter by a trained measurement specialist, or sizing try-ons, or both. Sizing measurements shall be taken according to a schedule and location(s) mutually agreed between the manufacturer and the department.

Garments shall be available in custom sizing as follows: coat chest in 2-inch (5.1 cm) increments, coat sleeve in 0.5-inch (1.3 cm) increments, coat back length in 1-inch (2.5 cm) increments, pant waist in 2-inch (5.1 cm) increments and pant inseam in 1-inch (2.5 cm) increments. A full range of women's sizing, on women's patterns, must also be available. Each sleeve and inseam length shall provide 100% gradation from shoulder to wrist, and from hip to ankle, to provide proper fit for individual arm and leg lengths. Pattern tailoring to custom-fit neck, bicep, hip/seat and thigh circumferences must also be provided, when needed, at no additional charge. Neither Small-Medium-Large-Extra Large sizing nor women's garments cut to men's patterning are considered acceptable, since proper fit facilitates mobility and minimizes stress.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

## **11.0 SELF-BINDING**

Liner and moisture barrier shall be stitched together and turned, then topstitched, to create a self-binding edge. The extra bulk of separate binding material is specifically prohibited.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

## **12.0 THREAD**

All thread used in structural seams shall be Nomex® of minimum Tex size T-70. Light colored garments and trim areas shall feature yellow thread. Black and dark garments shall feature black thread. Tan- or bronze-colored garments shall feature tan thread.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

## **13.0 STITCH METHODS**

### **13.1 MAJOR A & B SEAMS**

Except for the collar Major A seam, which is single-needle lock stitched three times, all Major A & B seams (as defined by NFPA 1971) shall be double stitched, double fold throughout all three layers (outer shell, moisture barrier and thermal liner) and shall be made with Nomex® thread, minimum Tex size T-90. Detailed stitch and seam type requirements are listed below.

Stitch Type 401 Double lockstitch, as defined by ASTM D 6193-97 and Modified Seam Type LSc-2 Double fold seam, modified only to ensure that both stitch lines penetrate all layers of cloth at joining, otherwise as defined by ASTM D 6193-97.

Also, all moisture barrier seams shall be tape-sealed to meet all requirements of the NFPA 1971 Liquid Penetration Resistance Test.

Does Your Bid Comply with All Aspects of This Section?

For Outer Shell: Yes \_\_\_\_\_ No \_\_\_\_\_

For Thermal Lining: Yes \_\_\_\_\_ No \_\_\_\_\_

For Moisture Barrier: Yes \_\_\_\_\_ No \_\_\_\_\_

### **13.2 MINOR SEAMS**

Most Minor seams, such as storm shields and mated hems, shall also be stitched with the specified Nomex thread. Detailed stitch and seam type requirements are listed below.

- Stitch Type 301 Lockstitch as defined by ASTM D 6193-97 and Seam Type SSae-2 As defined by ASTM D 6193-97, shown (a) before and (b) after required turning.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **13.3 POCKETS**

Flat garment pockets shall be stitched with the specified Nomex® thread. Detailed stitch and seam type requirements are listed below.

- Stitch Type 301 Lockstitch as defined by ASTM D 6193-97 and Seam Type LSd-2 As defined by ASTM D 6193-97.
- 3-Dimensional pocketing shall feature these same construction details, but the reinforced single stitch Seam Type LSd-1 may be substituted for LSd-2. Detailed seam type requirements are listed below.
- Stitch Type 301 Lockstitch as defined by ASTM D 6193-97 and Seam Type LSd-1 As defined by ASTM D 6193-97.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **13.4 TRIM AND DANGER LABELS**

Trim and DANGER labels shall be stitched with the specified Nomex® thread. Detailed stitch and seam type requirements are listed below.

- Stitch Type 301 Lockstitch as defined by ASTM D 6193-97 and Seam Type SSbd-1 As defined by ASTM D 6193-97.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **13.5 SINGLE LAYER HEMMING AND FINISHING**

Single layer hemming and finishing shall be stitched with the specified Nomex® thread. Detailed stitch and seam type requirements are listed below.

Stitch Type 301 Lockstitch as defined by ASTM D 6193-97 and Seam Type EFb-1 As defined by ASTM D 6193-97.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **14.0 POCKETS**

When exterior pockets are specified, the following requirements shall apply to all such custom option specified exterior pockets:

- All pockets and flaps shall be reinforced at the top corners with bar tack stitching.
- All pockets shall be reinforced with an extra layer of NFPA-certified outer shell, moisture barrier, or other NFPA-certified reinforcement material for extra durability. The exact location of the reinforcements shall be identified in the custom options section(s).
- All pockets shall have a means to drain water and shall have a means of closure.
- All pocket closures shall be made either with hook and loop fastener tape a minimum of 1.5 inches (3.8 cm) wide, with a flap, or with snaps. The specific placement of the closure system shall be outlined in the custom options sections.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **15.0 TAILORED GRADING OF GARMENT LININGS**

All garment layers and Cold Weather Accessory Linings shall be graduated in size to fit within in each other in the overall composite without causing bunching or binding when the garment is worn.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **16.0 POINTS OF STRESS**

All points of stress shall be reinforced with sturdy bar tacks. Rivets are not acceptable because of their potential for rust and electrical or heat conduction.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

### **17.0 ASSET TRACKING SERVICES**

Upon request, the manufacturer shall be capable of providing a web-based software to track care, cleaning and maintenance of PPE. The tracking software will include Inventory Assist and the Hot Spot Locator to help you analyze gaps in your inventory and pinpoint recurring repair problems. Records will be secured in a cloud-based environment with 24/7 access.

This tracking program shall meet or exceed all record-keeping requirements of NFPA 1851, Standard on Selection, Care and Maintenance of Structural Fire Fighting Protective Ensembles, Latest Edition. Manufacturer shall have the ability to import records for gear purchased from them, upon request, providing all details required to meet NFPA 1851, and assist with training to assign all gear while importing.

Labels on each separable part of the garment shall include a standard style interleaved 2 of 5 barcode containing (at a minimum) an individualized serial number for asset tracking purposes.

The manufacturer shall be capable of providing training to department personnel who are involved in the daily use of this tracking program, as well as a built-in interactive tutorial.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**18.0 REPAIRS AND ALTERATION SUPPORT**

The manufacturer shall furnish, free of charge, reasonable quantities of NFPA 1971-certified thread, materials and other supplies to allow the department to manage its own ongoing internal maintenance efforts. Also, the manufacturer shall provide on call at no charge, during normal business hours, a liaison for the repair department to assist the Fire Department on a telephone consultation basis, on all maintenance or repair questions that might arise. Additionally, the manufacturer shall agree to expedite, on its own cost-only basis, all repairs that must be performed at the manufacturer’s plant, rather than in department, over the life of the contract.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**19.0 HIGH TEMPERATURES THERMAL INSULATING MATERIALS REQUIREMENT**

Because thermally stable materials are essential to maximizing protective performance in firefighters’ PPE, and because NFPA only states “minimum” performance requirements, all thermal liner or thermal enhancing materials used in the garments shall also meet the following criteria after the 500-degree F oven test:

- 1) Material shall remain intact and flexible
- 2) No portion of the material shall crack, crumble or flake

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**20.0 BREATHABILITY REQUIREMENT**

Excluding where required by NFPA standard, necessary for functionality, or specifically called out in the custom option sections, all materials fabrics and reinforcements used in the construction of the garments shall be breathable and all moisture barrier material must be as specified in the Materials Section.

The breathability requirement includes but is not limited to: collar, chinstrap, storm shield, fly, water wells, front coat facings, and reinforcement cushioning where applicable.

Areas where non-breathability is allowed (absent Custom Option specifications): trim or other items placed externally on the arms that might need extra material to pass NFPA required Stored Energy Testing, hook and loop fastening, hardware or hardware backing, and pocket linings where used exterior to the outer shell.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**21.0 CONDUCTIVE AND COMPRESSIVE HEAT RESISTANCE (CCHR)**

Using breathable materials as outlined in the section titled Breathable Materials, there shall be: A minimum area of 4" x 4" (10.2 cm x 10.2 cm) at the shoulders and elbows that provide a minimum of 25 CCHR at 2 psi. with a minimum 6" x 6" (15.2 cm x 15.2 cm) area at the knees that provide 25 CCHR at 8 psi.

In all three of these compression areas at least a portion of the protective area shall be made from high temperature fiber-based materials sewn to the thermal liner on the inside of the liner toward the moisture barrier.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**22.0 SEAM PROTECTION AT CUFFS**

At the coat and pant cuff Major A seams, the reflective trim shall stop just before the folding of the full fold seam and for additional abrasion protection be covered by a sewn-on strip of polymer coated Kevlar material laid on top of the Major A seam and covering each end of the trim.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**23.0 APPLICABLE DOCUMENTS**

The following standards in their active versions on the date of invitation for bid shall form a part of this specification to the extent specified herein.

<u>STANDARD</u>	<u>TITLE</u>
ASTM D 6193-97	Standard Practice for Stitches and Seams
NFPA 1500, Latest Edition	Standard on Fire Department Occupational Safety and Health Program
NFPA 1851, Latest Edition	Standard on Selection, Care, and Maintenance of Structural Fire Fighting Protective Ensembles
NFPA 1971, Latest Edition	Standard on Protective Ensemble for Structural Fire Fighting

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

To avoid liability and interface problems, coats and pants shall be procured from the same manufacturer.

**24.0 DESIGN CONCEPT (STYLING)**

The pant shall be of a traditional waist-high design to facilitate full torso ventilation of front, rear and sides of trunk for maximum body cooling effect to help minimize firefighter heat stress. For this reason, other than waist-high pants shall not be considered acceptable or "equal," since additional trunk wrapping traps heat and moisture, increasing heat stress buildup while also creating mechanical resistance when covering the natural torso flexion point of the waist.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_



**25.0 PATTERNING CONCEPT**

Garments shall feature a tailored four-piece body plus a one-piece, over-sized crotch diamond pattern in the outer shell, moisture barrier and thermal liner.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**26.0 PATTERNING REQUIREMENTS**

To assure maximum freedom of movement and reduced kinetic resistance with minimum garment weight and bulk, the pants patterning shall:

- Incorporate hydraulic, swivel action leg-to-torso interfaces.
- Incorporate an oversized diamond-shaped crotch insert, graded per size, for maximum action stride, optimum stepping reach and no “in-crotch” seaming.
- In the outer seam hip area, in all three layers shall, incorporate convex seam technology to provide for generous seat expansion when squatting and crawling without creating unsightly bagginess.
- That the diamond extends from just above the left knee to just above the right knee, and be centered equally from front to rear. Width of diamond at top of crotch shall be approximately proportionally graded to waist size and inseam length.
- Ensure that pants rest in normal body line balance of 22 inches (55.9 cm) center distance at the cuff for 42 waist, 30 inseam pants.
- Provide for an alteration point at the hips so that during manufacture the hip dimension can be adjustable in two-inch (5.0cm) increments

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**27.0 SUSPENDER ATTACHMENT**

8 snap style suspender loops shall be positioned on the internal waist facing. Suspender loops shall be mounted through top of waistband with triple later outer shell material, thermal and moisture barrier.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**28.0 LINER ATTACHMENT**

The moisture barrier and thermal liner assembly shall be attached to the outer shell at the waistband with seven (7) evenly-spaced glove snaps. Liners shall be attached at the cuff by means of snaps on two (2) sets Hypolan coated Kevlar tabbing per liner cuff. The male and female snap parts shall both be located on Hypalon coated Kevlar tabbing that is sewn to the liner at the cuff. A separate piece of Hypalon coated Kevlar tabbing shall be sewn to the shell cuff.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**29.0 PANT CERTIFICATION LABEL ON LINER**

The pant certification label on the liner shall be affixed to the inner left hip area of the liner.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**30.0 PANT CERTIFICATION LABEL ON SHELL**

The pant label on the shell shall be affixed to the facing at the fly.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**31.0 FLY FRONT**

The outer shell fly shall be lock stitched to the left side of the front opening and shall be in proportion to waist size and crotch rise in both length and width. Fly inner lining shall extend at least 2 inches (5.1 cm) to the left of the outer shell fly attachment seam and shall be constructed of certified breathable moisture barrier and thermal liner. The right front pant opening shall have an internal facing extending at least 2 inches (5.1 cm) to the right and constructed of specified fabric. In combination with the liner, the system shall offer 360-degree protection without gaps during movement of the outer shell moisture barrier and thermal liner. Closure shall be by means of a minimum 1.5-inch-wide (3.8-cm-wide) hook and loop fastener, and all construction techniques used shall provide liquid penetration protection under the NFPA 1971 Whole Garment Liquid Penetration Test. The fly shall be graded to the waist size of garments and crotch rise.

Does Your Bid Comply with All Aspects of This Section? Yes \_\_\_\_\_ No \_\_\_\_\_

**32.0 COMPOSITE MATERIALS**

The specifier has determined the ONLY acceptable combination of materials. Any substitution of materials shall be grounds for immediate disqualification of bid without further consideration.

**32.1 OUTER SHELL KOMBAT FLEX 7 BRONZE W/ FREEFAS**

**32.2 THERMAL LINING GLIDE ICE 2 LAYER**

**32.3 MOISTURE BARRIER TYPE 4A CROSSTECH 3L**

Does Your Bid Comply with All Aspects of This Section?

For Outer Shell: Yes \_\_\_\_\_ No \_\_\_\_\_

For Thermal Lining: Yes \_\_\_\_\_ No \_\_\_\_\_

For Moisture Barrier: Yes \_\_\_\_\_ No \_\_\_\_\_

**33.0 PANT CUSTOM OPTIONS TO BE PROVIDED**

Instructions in this custom options section that contradict earlier specifications or statements supersede those earlier specifications or statements if the required certifications are not compromised.

- Standard inspection port liner
- Liner Detachable
- Trim double stitched
- New York Triple Trim
- Standard L/R Narrow Fly- 2" Velcro w/reverse hook-on tab
- Standard half angled cuffs- Arashield- black
- Pant cuffs- Arashield Black
- BiFlex Heat Channel Knees- Advance- soft w/ FREEFAS Black
- Both center sections in BiFlex knee to be Arashield- Black

- Standard Take-up straps- 2 postmans- KF- w/FREEFAS- Bronze
- X-large Bellows pockets- Kombat Flex w/ FREEFAS Bronze
- Standard 3 strips Velcro on flap/full Velcro on pocket
- EZ Grip Flaps- Arashield- Black
- Standard full Kevlar lined
  - Place inside right bellows pocket at bottom
  - On pant portion
  - Divide into 3 equal compartments
- Tool divider
  - 4" high
  - Place in right bellows pocket
  - On the other tool divider at bottom
  - Divide into 3 equal compartments
- Standard snap style suspender attachment
- Basic H-back suspenders w/Snap attach & quick adjust install suspender padding

**Delivery must be less than 90 Days No Exceptions.**

**PERCENTAGE SPECIFICATION COMPLIANCE CALCULATIONS**

Total Number "Yes/No" Questions \_\_\_\_\_

Total Number of **Yes** Answers \_\_\_\_\_

Total Number of **No** Answers \_\_\_\_\_

% Specification Compliance:  $(\text{Total yes answers}) \div (\text{total Answers}) \times 100\%$

Percent Compliance \_\_\_\_\_

- Each "No" answer requires a full written explanation.
- Each "Yes/No" question not checked where provided will be considered a "No" Answer.

# IRAN DIVESTMENT ACT NOTICE

Tenn. Code Ann. § 12-12-106 requires the chief procurement officer to publish, using credible information freely available to the public, a list of persons it determines engage in investment activities in Iran, as described in § 12-12-105.

For these purposes, the State intends to use the attached list of “Entities determined to be non-responsive bidders/offerers pursuant to the New York State Iran Divestment Act of 2012.”

While inclusion on this list would make a person ineligible to contract with the state of Tennessee, if a person ceases its engagement in investment activities in Iran, it may be removed from the list.

If you feel as though you have been erroneously included on this list please contact the Central Procurement Office at [CPO.Website@tn.gov](mailto:CPO.Website@tn.gov).

List Date: May 4, 2022

Source: <https://www.ogs.ny.gov/iran-divestment-act-2012>

1. Ak Makina, Ltd.
2. Amona
3. Bank Markazi Iran  
(Central Bank of Iran)
4. Bank Mellat
5. Bank Melli Iran
6. Bank Saderat Iran
7. Bank Sepah
8. Bank Tejarat
9. China Precision Machinery  
Import- Export Corporation  
(CPMIEC)
10. ChinaOil (China National United  
Oil Corporation)
11. China National Offshore Oil  
Corporation (CNOOC)
12. China National Petroleum  
Corporation (CNPC)
13. Indian Oil Corporation
14. Kingdream PLC
15. Naftiran Intertrade Co. (NICO)
16. National Iranian Tanker Co.  
(NITC)
17. Oil and Natural Gas Corporation  
(ONGC)
18. Oil India, Ltd.
19. Persia International Bank
20. Petroleos de Venezuela  
(PDVSA Petróleo, SA)
21. PetroChina Co., Ltd.
22. Petronet LNG, Ltd.
23. Sameh Afzar Tajak Co. (SATCO)
24. Shandong FIN CNC Machine  
Co., Ltd.
25. Sinohydro Co., Ltd.
26. Sinopec Corp. (China  
Petroleum & Chemical  
Corporation)
27. SKS Ventures
28. SK Energy Co., Ltd.
29. Som Petrol AS
30. Unipet (China International  
United Petroleum & Chemicals  
Co., Ltd.)
31. Zhuhai Zhenrong Co.

# IRAN DIVESTMENT ACT

“By the submission of this bid, each bidder and each person signing on behalf of any bidder certifies, and in the case of a joint bid each thereto certifies as to its own organization, under penalty of perjury, that to the best of its knowledge and belief that each bidder is not a person included within the list created pursuant to § 12-12-106.”

Signature: \_\_\_\_\_

Date: \_\_\_\_\_

Title: \_\_\_\_\_