# Section 3.00 - Specifications USD 250 Parking Lot Sealing and Striping Project 2023

### **Description of Work:**

Provide two applications of Coal Tar Pavement Sealer over existing asphalt surface with third coat applied to all entrance ways.

### **Site Conditions:**

- 1. Apply coating when pavement temperature is at least fifty-five (55) degrees F and air temperature is the same and rising.
- 2. Apply coating during dry weather and when rain is not anticipated.

#### **Preparation:**

- 1. Spray all vegetation in cracks with Roundup Quick Pro Dry Instant Kill where applicable prior to job date.
- 2. Clean all cracks with compressed air, wire wheel routing and hand work to ensure all loose debris is removed.
- 3. Inject all cracks 3/16" or larger with Nuvo CS Type C crack sealant (does not include asphalt and concrete joints).
- 4. Prime oil spots. Heat and scrape excess oil off pavement and apply Tarloc MPC Oil Spot Primer to promote adhesion of sealer.
- 5. Clean entire asphalt surface and remove all debris from job site and discard.

#### **Application:**

- 1. Allow each coat to cure sufficiently to take traffic between coats.
- 2. Allow final coat to dry overnight under good drying conditions before allowing traffic.

#### Striping:

- 1. All striping of lines and any other marking on pavement will be re-applied unless otherwise directed by owner.
- 2. Sherwin Williams brand paint will be applied by approved commercial striping equipment at the manufacturer's suggested application rate. All paints used meet or exceed Federal Specification TTP115E or TTP1952B.

#### **Protection:**

- 1. All barricades will be supplied and set up prior to commencement of work and removed from job site after completion of project.
- 2. Owner will be responsible for having parking area cleared of vehicles. If towing services are required to perform work, towing charges will be at owner's expense.

# Section 3.00 - Specifications USD 250 Parking Lot Sealing and Striping Project 2023

## Warranty:

Pro-Tect Coal Tar Pavement Sealer: Performance of the coating against flaking or chipping for a period of one year.

**Bid Specifications:** 

Please bid each building location separately. If there is a discount for receiving all three bids, please indicate this information when bidding the project.