SPECIFICATIONS

Item	Spec/Description
Teacher Chair	Mesh Mid-Back task chair with height adjustable arms and a Grade 3 Fabric
Teacher Desk	Single & double Pedestal, Top with privacy panel and casters 60" x 30" Laminate Top with T Mold edge. Provide upgrade charge for permatuff edge.
Para Pro Desk	Single Pedestal Rectangle Top with privacy panel and casters 48" x 30" Laminate Top with T Mold edge. Provide upgrade charge for permatuff edge.
Classroom Book Case	Mobile 2 Shelf Metal Bookcase, 1 adj shelf, 36" Wide
Kidney Table	42 x 72 Student Activity Table with T-Mold Edge, height adjustable legs and casters. Provide upgrade charge for permatuff edge.
30" x 54" Activity Table	30 x 54 Student Shape Table with T-Mold Edge, height adjustable legs and casters. Rectangular shape must nestle with other shapes. Provide upgrade charge for permatuff edge.
24" x 48" Activity Table	24 x 48 Student Activity Table with T-Mold Edge and casters. Provide upgrade charge for permatuff edge.
Science Table	30 x 60 Table with Chemsurf Laminate and Height Adjustable Legs
Half-Round Table	30 x 54 Student Shape Table with T-Mold Edge, height adjustable legs and casters. Half Round shape must nestle with other shapes. Provide upgrade charge for permatuff edge.
Training Table	60" x 24" Flip and Nest Table with Locking Casters and height adjustable legs.
Computer Chair	Heavy duty and static free, high-density polypropylene material injection molded into a one-piece shell unit with 17 heavy duty reinforcing structural ribs. The shell is attached to the frame with steel rivets underneath the seat, which offers no exposed hardware on the surface Legs formed of 18-gauge, 1 1/8" full-tube steel. Each leg set (front and back) made of one tube running side to side of the seat mounted to 14ga steel brackets. Includes casters.
Computer Stool	Polypropylene shell on five star base with foot ring, adjustable height 20" – 28"
Student Desk	Trapezoid Shape - Work surface to be made of 5/8" solid plastic. Top size: 20" x 32". The solid plastic top is standard with an ergo edge. 12 gauge frame structure MIG welded to 1" 16 gauge steel legs and cross-brace forming an unitized frame design. The nickel chrome plated leg inserts are made of 16 gauge steel.

SPECIFICATIONS

Rectangle Shape- Work surface to be made of 5/8" solid plastic. Top size: 20" x 32". The solid plastic top is standard
with an ergo edge. 12 gauge frame structure MIG welded to 1" 16 gauge steel legs and cross-brace forming an unitized frame design. The nickel chrome plated leg inserts are made of 16 gauge steel. Wheelchair accessible
Heavy duty and static free, high-density polypropylene material injection molded into a one-piece shell unit with 17 heavy duty reinforcing structural ribs. The shell is attached to the frame with steel rivets underneath the seat, which offers no exposed hardware on the surface Legs formed of 18-gauge, 1 1/8" full-tube steel. Each leg set (front and back) made of one tube running side to side of the seat mounted to 14ga steel brackets.
Heavy duty and static free, high-density polypropylene material injection molded into a one-piece shell unit with 17 heavy duty reinforcing structural ribs. The shell is attached to the frame with steel rivets underneath the seat, which offers no exposed hardware on the surface Legs formed of 18-gauge, 1 1/8" full-tube steel. Each leg set (front and back) made of one tube running side to side of the seat mounted to 14ga steel brackets.
Heavy duty and static free, high-density polypropylene material injection molded into a one-piece shell unit with 17 heavy duty reinforcing structural ribs. The shell is attached to the frame with steel rivets underneath the seat, which offers no exposed hardware on the surface Legs formed of 18-gauge, 1 1/8" full-tube steel. Each leg set (front and back) made of one tube running side to side of the seat mounted to 14ga steel brackets.
Heavy duty and static free, high-density polypropylene material injection molded into a one-piece shell with waterfall edge. Molded in a Ribless back design. The shell is attached to the frame with steel rivets underneath the seat, which offers no exposed hardware on the surface. Legs are formed of 1-1/8" 14-gauge tubular steel. The legs are welded to two 14-gauge steel brackets with a continuous weld at all four connection areas. Brackets run front to back on the chair. No additional bracing is needed between the legs for support.
Features a 7/8" frame with 16-gauge square tubing, 14-gauge rear seat brace, Band-pitch style with a seat back angle of 97 degrees, Polypropylene contoured seat, Non-marring polyethylene glides.
30" x 72" x 27", P-lam tops, Accessible from all 4 sides
Easy adjustment- 28"x19.675" Wx27"-41.10"H
Mobile stool-
Recycle of furniture being replaced

SPECIFICATIONS

Item	Spec/Description
Alternate 1	Complete School Recycle
Alternate 2	Per Classroom recycle