



TYPICAL SECTION

NOTES:

1. WHERE PRACTICAL, LIMITS OF 12 FOOT WIDE OVERLAY SHALL CORRESPOND WITH TRAVEL LANES AS DIRECTED BY THE PROJECT OFFICER.
2. WHEN THE DISTANCE FROM THE EDGE OF EXISTING PAVEMENT TO THE EDGE OF THE PAVEMENT RESTORATION IS 3' OR LESS, THE ADDITIONAL PAVEMENT SHALL BE REMOVED AND REPLACED BACK TO THE EDGE.
3. THICKNESS OF BASE MAY BE REDUCED TO 3" WHEN PATCH IS BEING MADE IN PAVEMENTS OF SURFACE TREATED GRAVEL, AND AS DIRECTED BY THE PROJECT OFFICER.
4. WHEN WIDENING OR PATCHING A STREET WITH ASPHALT, A NEAT, CLEAN JOINT OF AT LEAST ONE (1) INCH IN DEPTH BETWEEN OLD AND NEW PAVEMENT SHALL BE PROVIDED FOR TOPPING SO AS TO ELIMINATE THE NEED FOR FEATHERING OF THE OVERLAY.
5. FOR TRENCH AND BEDDING DETAILS, SEE DRAWING No. M-3.0.

**MODIFIED PAVEMENT PATCHING
FOR UTILITY CUTS**



ARLINGTON COUNTY, VIRGINIA
DEPARTMENT OF ENVIRONMENTAL SERVICES

ISSUED	8/12/2019
DRAWING NO. M-6.1 (MOD.)	