



MATERIAL LEGEND

	NEW CONCRETE PAVEMENT PER CITY OF OAKLAND STANDARD DETAIL S-1
	PLANTING AREA, SEE LANDSCAPE PLANS FOR FINISHED GRADES
	DETECTABLE WARNING SURFACE, SEE DETAIL 9, SHEET C6.00
	NEW CONCRETE PAVEMENT, SLD FOR PAVEMENT SECTION AND SCORING (6" LIGHTWEIGHT LAVAROCK BACKFILL)
	NEW CONCRETE PAVEMENT, SLD FOR PAVEMENT SECTION AND SCORING (12" LIGHTWEIGHT LAVAROCK BACKFILL)
	NEW CONCRETE PAVEMENT, SLD FOR PAVEMENT SECTION AND SCORING, SSD FOR BACKFILL SECTION
	CONCRETE INTERLOCKING PAVERS (H-20 RATED AND ADA COMPLIANT), SEE DETAIL 2, SHEET C7.01
	FOOTING / GRADE BEAM BELOW BUILDING SLAB FOR TOP OF FOOTING AND GRADE BEAM ELEVATIONS, SEE SHEET S2.01
	CONCRETE WALL (SEE SHEET S4.30)

GRADING QUANTITIES

CUT: 4,560 CUBIC YARDS
FILL: 620 CUBIC YARDS
NET: 3,940 CUBIC YARDS <EXPORT>

1. THE EARTHWORK QUANTITIES ABOVE HAVE BEEN ADJUSTED TO ACCOUNT FOR:
A. EXISTING EXTERIOR SLABS 4" CONCRETE / 4" AB
B. INTERIOR SLAB 8" CONCRETE / 4" AB

2. THE EARTHWORK QUANTITIES ABOVE HAVE NOT BEEN ADJUSTED TO ACCOUNT FOR:
A. FOOTINGS, MATSLAB, COLUMNS, AND GRADE BEAMS
B. DEEP SOIL MIX SPOLS
C. TRENCH SPOILS
D. CLEARING AND GRUBBING
E. REMOVAL OF EXISTING PAVEMENT SECTIONS OR UNACCEPTABLE SOILS
F. BULKING OR SHRINKAGE
G. CONSTRUCTION METHODS

3. THE EARTHWORK QUANTITIES ABOVE ARE APPROXIMATE ONLY.

NOTE:
1. CONTRACTOR SHALL SUBMIT SHOP DRAWINGS FOR ALL SHORING AS NECESSARY FOR PAD GRADING.
2. SEE LANDSCAPE DRAWINGS FOR FINISHED GRADES OUTSIDE OF BUILDING FOOTPRINT.

