



1 REFLECTED CEILING PLAN - LEVEL 2
1/8" = 1'-0"

RCP FINISH LEGEND

	ACT-1 2x2 ACT CEILING FOR DETAILS SEE A8.31		GYP-X PAINTED GYP FOR DETAILS SEE A8.32
	ACT-2 4x4 CONCEALED ACT CEILING FOR DETAILS SEE A8.31		APC-1 ACOUSTIC PLASTER CEILING FOR DETAILS SEE A8.32
	ACT-3 2x4 SHAPED ACT CEILING FOR DETAILS SEE A8.31		
	ACT-4 2x8 CONCEALED ACT CEILING FOR DETAILS SEE A8.31		

- WINDOW SHADES, ROLLER, MOTORIZED, AUTOMATIC
- WINDOW SHADES, ROLLER, MANUAL
- WINDOW SHADES, ROLLER, MOTORIZED, REMOTE SWITCHED
- BLACKOUT WINDOW SHADES, ROLLER, MANUAL

- ARCHITECTURAL REVEAL TYPE 1 - CLG MTD RECESSED
- ARCHITECTURAL REVEAL TYPE 2 - CLG MTD EXPOSED
- ARCHITECTURAL REVEAL TYPE 3 - WALL MTD

- PENDANT LIGHT FIXTURES, SED
- RECESSED LIGHT FIXTURE, SED
- RECESSED CAN LIGHT, SED
- FIRE SPRINKLER, SFPD
- INSULATED METAL PANEL

KEYNOTE LEGEND	
Key Value	Keynote Text
23 34 00 C3	23 34 00 10-FT DIA HVLS CEILING FAN, SMD

GENERAL NOTES

1. SEE ROOM FINISH SCHEDULE FOR ADDITIONAL INFORMATION.
2. SEE ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.
3. SEE MECHANICAL DRAWINGS FOR ADDITIONAL INFORMATION.
4. WHERE OWSJ PENETRATES GWB - CUT GWB TIGHT TO JOISTS. MUD, TAPE & SEAL. PAINT TO MATCH ADJACENT WALL.
5. PAINT ALL EXPOSED OWSJ, METAL ROOF DECK, STRUCTURAL STEEL AND FRAMING, PIPES, DUCTS, CONDUIT AND ALL OTHER EXPOSED ITEMS TYP.
6. ACOUSTIC TILE SHALL BE CENTERED IN ROOM UON.
7. ALL GYP BO CEILINGS ARE SUSPENDED UON.
8. APPLY INTUMESCENT FIREPROOFING TO ALL EXPOSED COLUMNS AND BEAMS, TYP. SPRAY PRIMARY STRUCTURAL STEEL MEMBERS HIDDEN FROM VIEW WITH CEMENTITIOUS FIREPROOFING.