





A2.1

ADD. ALTERNATE #1 -

A2.1

DOOR GENERAL NOTES:

- A. PROVIDE DOOR CLOSERS FOR ALL EXTERIOR DOORS. CLOSERS TO ALLOW FOR 135° DOOR POSITION B. ALL EXTERIOR DOORS SHALL HAVE WEATHER SEALS AND ALUMINUM THRESHOLD U.N.O.
- C. ALL DOOR HARDWARE TO BE ADA COMPLIANT.

REVISIONS PROJECT NO.

KEYNOTE LEGEND

3 ADD. ALTERNATE #1 - REPLACE BRICK PAVERS FOLLOWING INSTALLATION OF NEW STOOP. TOOTH IN PAVERS AS NECESSARY TO PRESERVE EXISTING PATTERNS.

5 FINISH NEWLY EXPOSED ENDS OF MODIFIED BENCH TO MATCH EXISTING SURFACE.

STAIRS. SPLASHBLOCK AND LEADER TO BE LOCATED TO LIMIT VISIBILITY.

ALL PAINT & PAINT FINISHES TO MATCH EXISTING. SUBMIT SAMPLES & PRODUCT DATA

FOR APPROVAL. ALLOW TREATED LUMBER TO DRY OUT PRIOR TO FINISHING

4 PATCH EXISTING DECK WHERE BOARDS HAVE BEEN REMOVED AT TRUNCATED COLUMN. FINISH

7 MODIFY EXISTING GRADE AS REQUIRED TO PROVIDE 4'-6" X 4'-6" LEVEL SURFACE EVEN WITH

10 PROVIDE NEW LEADER TO RE-ROUTE EXISTING DOWNSPOUT TO SPLASHBLOCK UNDER NEW

11 PAINT ENTIRE WALL AND INTERIOR DOORS/WINDOWS. COORDINATE COLOR SELECTION WITH

12 ADD. ALTERNATE #1 - ALIGN EDGE OF RISER WITH EDGE OF EXISTING BRICK PAVER ACCENT

BAND. IF EXISTING GRADE DOES NOT ALLOW FOR THIS ARRANGEMENT, NOTIFY ARCHITECT.

9 ADD. ALTERNATE #1 - PAINT ENTIRE WALL. COORDINATE COLOR SELECTION WITH OWNER.

2 REMOVABLE ACCESS PANEL.

TO MATCH EXISTING SURFACE.

BOTTOM SURFACE OF FIRST RISER.

6 ADD. ALTERNATE #1 - RELOCATED DUPLEX OUTLET.

8 EXISTING ELECTRICAL EQUIPMENT. PAINT TO MATCH BRICK.

DESCRIPTION

1 ADD. ALTERNATE #1 - INFILL WALL TO MATCH EXISTING. USING SALVAGED BRICK REMOVED FROM NEW OPENINGS, TOOTH IN BRICK TO REDUCE VISIBILITY OF PATCHING.

16174

MARCH 23, 2016 DRAWN: CHECKED

SHEET TITLE:

FLOOR PLAN

SHEET NO:

1/4" = 1'-0"

FLOOR PLAN