



INVITATION TO BID  
HANAHAN PUBLIC SERVICES DEPARTMENT  
BATTING CAGES CONCRETE SLAB  
FOR THE CITY OF HANAHAN, SC

**COH#-112216**

The City of Hanahan, SC is seeking bids from qualified contractors for the installation of two (2) concrete slabs for batting cages at the Hanahan Athletic Complex. Approximate area for concrete installation will be 26' x 72'+/- each. A site visit must be scheduled to inspect the area and review the scope of the project.

Bids will be received by the City of Hanahan, **UNTIL 12:00 P.M. – Thursday, December 15, 2016**. Submittals are to be mailed or hand-delivered to:

City of Hanahan Recreation & Parks  
1255 Yeamans Hall Rd.  
Hanahan, SC 29410  
Attn. **Batting Cages**

**For information please contact:**

Randy Moneymaker, Recreation and Parks Director  
3100 Mabeline Rd.  
Hanahan, SC 29410  
(843) 266-0723  
(843) 266-0725 Fax  
[rmoneymaker@cityofhanahan.com](mailto:rmoneymaker@cityofhanahan.com)



## SCOPE OF WORK

### **Specifications:**

**Two (2) each 26' x 72' +/- 4-inch concrete slab.**

1. Work done under this item shall consist of the construction of concrete pads for athletic batting cages. It shall consist of excavating and filling, for fine grading and compaction of subgrade, and all backfilling necessary to complete the work and cleaning up of the work.
2. The subgrade for the slab shall be formed by excavating to the required depth, and shaped to the proper cross section, and shall be thoroughly compacted by rolling or tamping before placing any concrete to 95 % compaction.
3. Contraction joints shall be provided uniformly to separate the slab, and shall be cut in a straight line to a depth equal to at least one-third (1/3) of the total slab thickness. The joint shall be not less than one-eighth inch (1/8"), nor more than one-fourth inch (1/4") in width.
4. After the freshly-poured concrete has been brought to the establishing grade, it shall be floated with a wooden float to produce a surface free from irregularities. The final surface shall be obtained by troweling with a steel trowel or hand float and brushing lightly with a light weight brush in a transverse direction to produce a uniform gritty surface of the proper texture. All edges and joints shall be rounded to one-fourth inch (1/4").
  - **A SITE VISIT IS MANDATORY TO REVIEW THE SCOPE AND TO DETERMINE ALL NEEDED MATERIALS TO COMPLETE THE PROJECT.**
  - **A SITE VISIT CAN BE SCHEDULED BY CONTACTING THE HANAHAN PUBLIC SERVICE DEPARTMENT AT (843) 266-0723.**